

Carrier-sense multiple access with collision avoidance (CSMA/CA)

in computer networking, is a network multiple access method in which carrier sensing is used, but nodes attempt to avoid collisions by beginning transmission only after the channel is sensed to be "idle". When they do transmit, nodes transmit their packet data in its entirety.

It is particularly important for wireless networks, where the collision detection of the alternative CSMA/CD is not possible due to wireless transmitters desensing their receivers during packet transmission.

CSMA/CA is a protocol that operates in the Data Link Layer (Layer 2) of the OSI model.

DETAILS:

CD

Collision avoidance is used to improve the performance of the CSMA method by attempting to divide the channel somewhat equally among all transmitting nodes within the collision domain.

Carrier Sense: prior to transmitting, a node first listens to the shared medium (such as listening for wireless signals in a wireless network) to determine whether another node is transmitting or not. Note that the hidden node problem means another node may be transmitting which goes undetected at this stage.

Collision Avoidance: if another node was heard, we wait for a period of time (usually random) for the node to stop transmitting before listening again for a free

communications channel.

✓ Request to Send/Clear to Send (RTS/CTS) may optionally be used at this point to mediate access to the shared medium.

This goes some way to alleviating the problem of hidden nodes because, for instance, in a wireless network, the Access Point only issues a Clear to Send to one node at a time. However, wireless 802.11 implementations do not typically implement RTS/CTS for all transmissions; they may turn it off completely, or at least not use it for small packets (the overhead of RTS, CTS and transmission is too great for small data transfers).

Transmission: if the medium was identified as being clear or the node received a CTS to explicitly indicate it can send, it sends the frame in its entirety.

Unlike CSMA/CD, it is very challenging for a wireless node to listen at the same time

as it transmits (its transmission will dwarf any attempt to listen). Continuing the wireless example, the node awaits receipt of an acknowledgement packet from the Access Point to indicate the packet was received and checksummed correctly. If such acknowledgement does not arrive in a timely manner, it assumes the packet collided with some other transmission, causing the node to enter a period of binary exponential backoff prior to attempting to re-transmit.

Although CSMA/CA has been used in a variety of wired communication systems, it is particularly beneficial in a wireless LAN due to a common problem of multiple stations being able to see the Access Point, but not each other. This is due to differences in transmit power, and receive sensitivity, as well as distance, and location with respect to the AP. [5] This will

cause a station to not be able to 'hear' another station's broadcast. This is the so-called 'hidden node', or 'hidden station' problem. Devices utilizing 802.11 based standards can enjoy the benefits of collision avoidance (RTS / CTS handshake, also Point coordination function), although they do not do so by default. By default they use a Carrier sensing mechanism called 'exponential backoff', or (Distributed coordination function) that relies upon a station attempting to 'listen' for another station's broadcast before sending. CA, or PCF relies upon the AP (or the 'receiver' for Ad hoc networks) granting a station the exclusive right to transmit for a given period of time after requesting it (Request to Send / Clear to Send).[6]

CSMA-CA requires a determination of whether a channel is 'idle', even when

incompatible standards and overlapping transmission frequencies are used. Per the standards, for 802.11/Wi-Fi transmitters on the same channel, transmitters must take turns to transmit if they can detect each other even 3 dB above the noise floor (the thermal noise floor is around -101 dBm for 20 MHz channels).[7] On the other hand, transmitters will ignore transmitters with incompatible standards or on overlapping channels if the received signal strength from them is below a threshold P_{th} which, for non Wi-Fi 6 systems, is between -76 and -80 dBm.