

LOCAL SEARCH ALGORITHMS

CHAPTER 4, SECTIONS 3–4

Outline

- ◇ Hill-climbing
- ◇ Simulated annealing
- ◇ Genetic algorithms (briefly)
- ◇ Local search in continuous spaces (very briefly)

Iterative improvement algorithms

In many optimization problems, **path** is irrelevant;
the **goal state** itself is the solution


Then **state space** = set of “**complete**” configurations;
find **optimal** configuration, e.g., TSP
or, find configuration satisfying constraints, e.g., timetable

In such cases, can use **iterative improvement algorithms**;
keep a single “**current**” state, try to improve it

Constant space, suitable for online as well as offline search

Example: Travelling Salesperson Problem

Start with any complete tour, perform pairwise exchanges




Variants of this approach get within 1% of optimal very quickly with thousands of cities



Example: n -queens

Put n queens on an $n \times n$ board with no two queens on the same row, column, or diagonal



Move a queen to reduce number of conflicts



$h = 5$




$h = 2$



$h = 0$

Almost always solves n -queens problems almost instantaneously for very large n , e.g., $n = 1\text{million}$



Hill-climbing (or gradient ascent/descent)


“Like climbing Everest in thick fog with amnesia”

```
function HILL-CLIMBING(problem) returns a state that is a local maximum
  inputs: problem, a problem
  local variables:  $\left[ \begin{array}{l} \textit{current}, \text{ a node} \\ \textit{neighbor}, \text{ a node} \end{array} \right.$ 

  current  $\leftarrow$  MAKE-NODE(INITIAL-STATE[problem])
  loop do
    neighbor  $\leftarrow$  a highest-valued successor of current
    if VALUE[neighbor]  $\leq$  VALUE[current] then return STATE[current]
    current  $\leftarrow$  neighbor
  end
```


Hill-climbing contd.

Useful to consider **state space landscape**



Random-restart hill climbing overcomes local maxima—trivially complete

Random sideways moves 😊 escape from shoulders 😞 loop on flat maxima



Simulated annealing

Idea: escape local maxima by allowing some “bad” moves
but gradually decrease their size and frequency

function SIMULATED-ANNEALING(*problem*, *schedule*) **returns** a solution state

inputs: [*problem*, a problem

schedule, a mapping from time to “temperature”

local variables: [*current*, a node

next, a node

T, a “temperature” controlling prob. of downward steps

current ← MAKE-NODE(INITIAL-STATE[*problem*])

for *t* ← 1 **to** ∞ **do**

T ← *schedule*[*t*]

if *T* = 0 **then return** *current*

next ← a randomly selected successor of *current*

ΔE ← VALUE[*next*] − VALUE[*current*]

if $\Delta E \geq 0$ **then** *current* ← *next*

else *current* ← *next* only with probability $e^{\Delta E/T}$

Properties of simulated annealing

At fixed “temperature” T , state occupation probability reaches Boltzman distribution

✓ $p(x) = \alpha e^{\frac{E(x)}{kT}}$

T decreased slowly enough \implies always reach best state x^*

because $e^{\frac{E(x^*)}{kT}} / e^{\frac{E(x)}{kT}} = e^{\frac{E(x^*) - E(x)}{kT}} \gg 1$ for small T

Is this necessarily an interesting guarantee??

Devised by Metropolis et al., 1953, for physical process modelling

Widely used in VLSI layout, airline scheduling, etc.



Local beam search

Idea: keep k states instead of 1; choose top k of all their successors

Not the same as k searches run in parallel!

Searches that find good states recruit other searches to join them

[Problem: quite often, all k states end up on same local hill


[Idea: choose k successors randomly, biased towards good ones

Observe the close analogy to natural selection!



Genetic algorithms


= stochastic local beam search + generate successors from **pairs** of states



Genetic algorithms contd.

GAs require states encoded as strings (GPs use programs)

Crossover helps **iff substrings are meaningful components**



GAs \neq evolution: e.g., real genes encode replication machinery!


Continuous state spaces

Suppose we want to site three airports in Romania:

- 6-D state space defined by $(x_1, y_1), (x_2, y_2), (x_3, y_3)$
- objective function $f(x_1, y_1, x_2, y_2, x_3, y_3) =$
sum of squared distances from each city to nearest airport

Discretization methods turn continuous space into discrete space, e.g., empirical gradient considers $\pm\delta$ change in each coordinate

Gradient methods compute


$$\nabla f = \left(\frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial y_1}, \frac{\partial f}{\partial x_2}, \frac{\partial f}{\partial y_2}, \frac{\partial f}{\partial x_3}, \frac{\partial f}{\partial y_3} \right)$$

to increase/reduce f , e.g., by $\mathbf{x} \leftarrow \mathbf{x} + \alpha \nabla f(\mathbf{x})$

Sometimes can solve for $\nabla f(\mathbf{x}) = 0$ exactly (e.g., with one city).

Newton–Raphson (1664, 1690) iterates $\mathbf{x} \leftarrow \mathbf{x} - \mathbf{H}_f^{-1}(\mathbf{x}) \nabla f(\mathbf{x})$

to solve $\nabla f(\mathbf{x}) = 0$, where $\mathbf{H}_{ij} = \partial^2 f / \partial x_i \partial x_j$