```
entry:
  %retval = alloca i8, align 1
  %zStream.addr = alloca %struct._IO_FILE*, align 8
  %stream.addr = alloca %struct._IO_FILE*, align 8
  %bzf = alloca i8*, align 8
  %bzerr = alloca i32, align 4
  %bzerr_dummy = alloca i32, align 4
  %ret = alloca i32, align 4
  %nread = alloca i32, align 4
  %streamNo = alloca i32, align 4
  %i = alloca i32, align 4
  %obuf = alloca [5000 x i8], align 16
  %unused = alloca [5000 x i8], align 16
  %nUnused = alloca i32, align 4
  %unusedTmp = alloca i8*, align 8
  store %struct._IO_FILE* %zStream, %struct._IO_FILE** %zStream.addr, align 8
  call void @llvm.dbg.declare(metadata %struct._IO_FILE** %zStream.addr,
  ... metadata !264, metadata !DIExpression()), !dbg !265
  store %struct._IO_FILE* %stream, %struct._IO_FILE** %stream.addr, align 8
  call void @llvm.dbg.declare(metadata %struct._IO_FILE** %stream.addr,
  ... metadata !266, metadata !DIExpression()), !dbg !267
  call void @llvm.dbg.declare(metadata i8** %bzf, metadata !268, metadata
  ... !DIExpression()), !dbg !271
  store i8* null, i8** %bzf, align 8, !dbg !271
  call void @llvm.dbg.declare(metadata i32* %bzerr, metadata !272, metadata
  ... !DIExpression()), !dbg !273
  call void @llvm.dbg.declare(metadata i32* %bzerr_dummy, metadata !274,
  ... metadata !DIExpression()), !dbg !275
  call void @llvm.dbg.declare(metadata i32* %ret, metadata !276, metadata
  ... !DIExpression()), !dbg !277
  call void @llvm.dbg.declare(metadata i32* %nread, metadata !278, metadata
  ... !DIExpression()), !dbg !279
  call void @llvm.dbg.declare(metadata i32* %streamNo, metadata !280, metadata
  ... !DIExpression()), !dbg !281
  call void @llvm.dbg.declare(metadata i32* %i, metadata !282, metadata
  ... !DIExpression()), !dbg !283
  call void @llvm.dbg.declare(metadata [5000 x i8]* %obuf, metadata !284,
  ... metadata !DIExpression()), !dbg !286
  call void @llvm.dbg.declare(metadata [5000 x i8]* %unused, metadata !287,
  ... metadata !DIExpression()), !dbg !288
  call void @llvm.dbg.declare(metadata i32* %nUnused, metadata !289, metadata
  ... !DIExpression()), !dbg !290
  call void @llvm.dbg.declare(metadata i8** %unusedTmp, metadata !291,
  ... metadata !DIExpression()), !dbg !292
  store i32 0, i32* %nUnused, align 4, !dbg !293
  store i32 0, i32* %streamNo, align 4, !dbg !294
  %0 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !295
  %call = call i32 @ferror(%struct._IO_FILE* noundef %0) #10, !dbg !297
  %tobool = icmp ne i32 %call, 0, !dbg !297
  br i1 %tobool, label %if.then, label %if.end, !dbg !298
T | F

if.then:
  br label %errhandler_io, !dbg !299

if.end:
  %1 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8, !dbg
  ... !300
  %call1 = call i32 @ferror(%struct._IO_FILE* noundef %1) #10, !dbg !302
  %tobool2 = icmp ne i32 %call1, 0, !dbg !302
  br i1 %tobool2, label %if.then3, label %if.end4, !dbg !303
T | F

if.then3:
  br label %errhandler_io, !dbg !304

if.end4:
  br label %while.body, !dbg !305

while.body:
  %2 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8, !dbg
  ... !306
  %3 = load i32, i32* @verbosity, align 4, !dbg !308
  %4 = load i8, i8* @smallMode, align 1, !dbg !309
  %conv = zext i8 %4 to i32, !dbg !310
  %arraydecay = getelementptr inbounds [5000 x i8], [5000 x i8]* %unused, i64
  ... 0, i64 0, !dbg !311
  %5 = load i32, i32* %nUnused, align 4, !dbg !312
  %call5 = call i8* @BZ2_bzReadOpen(i32* noundef %bzerr, %struct._IO_FILE*
  ... noundef %2, i32 noundef %3, i32 noundef %conv, i8* noundef %arraydecay, i32
  ... noundef %5), !dbg !313
  store i8* %call5, i8** %bzf, align 8, !dbg !314
  %6 = load i8*, i8** %bzf, align 8, !dbg !315
  %cmp = icmp eq i8* %6, null, !dbg !317
  br i1 %cmp, label %if.then9, label %lor.lhs.false, !dbg !318
T | F

lor.lhs.false:
  %7 = load i32, i32* %bzerr, align 4, !dbg !319
  %cmp7 = icmp ne i32 %7, 0, !dbg !320
  br i1 %cmp7, label %if.then9, label %if.end10, !dbg !321
T | F

if.then9:
  br label %errhandler, !dbg !322

if.end10:
  %8 = load i32, i32* %streamNo, align 4, !dbg !323
  %inc = add nsw i32 %8, 1, !dbg !323
  store i32 %inc, i32* %streamNo, align 4, !dbg !323
  br label %while.cond11, !dbg !324

while.cond11:
  %9 = load i32, i32* %bzerr, align 4, !dbg !325
  %cmp12 = icmp eq i32 %9, 0, !dbg !326
  br i1 %cmp12, label %while.body14, label %while.end, !dbg !324
T | F

while.end:
  %18 = load i32, i32* %bzerr, align 4, !dbg !359
  %cmp37 = icmp ne i32 %18, 4, !dbg !361
  br i1 %cmp37, label %if.then39, label %if.end40, !dbg !362
T | F

if.then39:
  br label %errhandler, !dbg !363

if.end40:
  %19 = load i8*, i8** %bzf, align 8, !dbg !364
  call void @BZ2_bzReadGetUnused(i32* noundef %bzerr, i8* noundef %19, i8**
  ... noundef %unusedTmp, i32* noundef %nUnused), !dbg !365
  %20 = load i32, i32* %bzerr, align 4, !dbg !366
  %cmp41 = icmp ne i32 %20, 0, !dbg !368
  br i1 %cmp41, label %if.then43, label %if.end44, !dbg !369
T | F

if.then43:
  call void @panic(i8* noundef getelementptr inbounds ([27 x i8], [27 x i8]*
  ... @.str.129, i64 0, i64 0)) #11, !dbg !370
  unreachable, !dbg !370

if.end44:
  store i32 0, i32* %i, align 4, !dbg !371
  br label %for.cond, !dbg !373

while.body14:
  %10 = load i8*, i8** %bzf, align 8, !dbg !327
  %arraydecay15 = getelementptr inbounds [5000 x i8], [5000 x i8]* %obuf, i64
  ... 0, i64 0, !dbg !329
  %call16 = call i32 @BZ2_bzRead(i32* noundef %bzerr, i8* noundef %10, i8*
  ... noundef %arraydecay15, i32 noundef 6000), !dbg !330
  store i32 %call16, i32* %nread, align 4, !dbg !331
  %11 = load i32, i32* %bzerr, align 4, !dbg !332
  %cmp17 = icmp eq i32 %11, -5, !dbg !334
  br i1 %cmp17, label %if.then19, label %if.end20, !dbg !335
T | F

if.then19:
  br label %trycat, !dbg !336

if.end20:
  %12 = load i32, i32* %bzerr, align 4, !dbg !337
  %cmp21 = icmp eq i32 %12, 0, !dbg !339
  br i1 %cmp21, label %land.lhs.true, label %lor.lhs.false23, !dbg !340
T | F

for.cond:
  %21 = load i32, i32* %i, align 4, !dbg !374
  %22 = load i32, i32* %nUnused, align 4, !dbg !376
  %cmp45 = icmp slt i32 %21, %22, !dbg !377
  br i1 %cmp45, label %for.body, label %for.end, !dbg !378
T | F

for.body:
  %23 = load i8*, i8** %unusedTmp, align 8, !dbg !379
  %24 = load i32, i32* %i, align 4, !dbg !380
  %idxprom = sext i32 %24 to i64, !dbg !379
  %arrayidx = getelementptr inbounds i8, i8* %23, i64 %idxprom, !dbg !379
  %25 = load i8, i8* %arrayidx, align 1, !dbg !379
  %26 = load i32, i32* %i, align 4, !dbg !381
  %idxprom47 = sext i32 %26 to i64, !dbg !382
  %arrayidx48 = getelementptr inbounds [5000 x i8], [5000 x i8]* %unused, i64
  ... 0, i64 %idxprom47, !dbg !382
  store i8 %25, i8* %arrayidx48, align 1, !dbg !383
  br label %for.inc, !dbg !382

for.inc:
  %27 = load i32, i32* %i, align 4, !dbg !384
  %inc49 = add nsw i32 %27, 1, !dbg !384
  store i32 %inc49, i32* %i, align 4, !dbg !384
  br label %for.cond, !dbg !385, !llvm.loop !386

for.end:
  %28 = load i8*, i8** %bzf, align 8, !dbg !388
  call void @BZ2_bzReadClose(i32* noundef %bzerr, i8* noundef %28), !dbg !389
  %29 = load i32, i32* %bzerr, align 4, !dbg !390
  %cmp50 = icmp ne i32 %29, 0, !dbg !392
  br i1 %cmp50, label %if.then52, label %if.end53, !dbg !393
T | F

if.then52:
  call void @panic(i8* noundef getelementptr inbounds ([27 x i8], [27 x i8]*
  ... @.str.129, i64 0, i64 0)) #11, !dbg !394
  unreachable, !dbg !394

if.end53:
  %30 = load i32, i32* %nUnused, align 4, !dbg !395
  %cmp54 = icmp eq i32 %30, 0, !dbg !397
  br i1 %cmp54, label %land.lhs.true56, label %if.end61, !dbg !398
T | F

land.lhs.true56:
  %31 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !399
  %call57 = call zeroext i8 @myfeof(%struct._IO_FILE* noundef %31), !dbg !400
  %conv58 = zext i8 %call57 to i32, !dbg !400
  %tobool59 = icmp ne i32 %conv58, 0, !dbg !400
  br i1 %tobool59, label %if.then60, label %if.end61, !dbg !401
T | F

if.then60:
  br label %while.end62, !dbg !402

if.end61:
  br label %while.body, !dbg !305, !llvm.loop !403

trycat:
  call void @llvm.dbg.label(metadata !457), !dbg !458
  %4 = load i8, i8* @forceOverwrite, align 1, !dbg !459
  %tobool95 = icmp ne i8 %4, 0, !dbg !459
  br i1 %tobool95, label %if.then96, label %if.end121, !dbg !461
T | F

if.then96:
  %45 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !462
  call void @rewind(%struct._IO_FILE* noundef %45), !dbg !464
  br label %while.body97, !dbg !465

if.end121:
  br label %errhandler, !dbg !459

lor.lhs.false23:
  %13 = load i32, i32* %bzerr, align 4, !dbg !341
  %cmp24 = icmp eq i32 %13, 4, !dbg !342
  br i1 %cmp24, label %land.lhs.true, label %if.end32, !dbg !343
T | F

land.lhs.true:
  %14 = load i32, i32* %nread, align 4, !dbg !344
  %cmp26 = icmp sgt i32 %14, 0, !dbg !345
  br i1 %cmp26, label %if.then28, label %if.end32, !dbg !346
T | F

if.then28:
  %arraydecay29 = getelementptr inbounds [5000 x i8], [5000 x i8]* %obuf, i64
  ... 0, i64 0, !dbg !347
  %15 = load i32, i32* %nread, align 4, !dbg !348
  %conv30 = sext i32 %15 to i64, !dbg !348
  %16 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !349
  %call31 = call i64 @fwrite(i8* noundef %arraydecay29, i64 noundef 1, i64
  ... noundef %conv30, %struct._IO_FILE* noundef %16), !dbg !350
  br label %if.end32, !dbg !350

if.end32:
  %17 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !351
  %call33 = call i32 @ferror(%struct._IO_FILE* noundef %17) #10, !dbg !353
  %tobool34 = icmp ne i32 %call33, 0, !dbg !353
  br i1 %tobool34, label %if.then35, label %if.end36, !dbg !354
T | F

errhandler:
  call void @llvm.dbg.label(metadata !497), !dbg !498
  %53 = load i8*, i8** %bzf, align 8, !dbg !499
  call void @BZ2_bzReadClose(i32* noundef %bzerr_dummy, i8* noundef %53), !dbg
  ... !500
  %54 = load i32, i32* %bzerr, align 4, !dbg !501
  switch i32 %54, label %sw.default [
    i32 -9, label %sw.bb
    i32 -6, label %sw.bb122
    i32 -4, label %sw.bb123
    i32 -3, label %sw.bb124
    i32 -7, label %sw.bb125
    i32 -5, label %sw.bb126
  ], !dbg !502
def | -9 | -6 | -4 | -3 | -7 | -5

sw.default:
  call void @panic(i8* noundef getelementptr inbounds ([28 x i8], [28 x i8]*
  ... @.str.132, i64 0, i64 0)) #11, !dbg !539
  unreachable, !dbg !539

sw.bb:
  call void @configError() #11, !dbg !503
  unreachable, !dbg !503

sw.bb123:
  call void @crcError() #11, !dbg !508
  unreachable, !dbg !508

sw.bb124:
  call void @outOfMemory() #11, !dbg !509
  unreachable, !dbg !509

sw.bb125:
  call void @compressedStreamEOF() #11, !dbg !510
  unreachable, !dbg !510

while.body97:
  %46 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !466
  %call98 = call zeroext i8 @myfeof(%struct._IO_FILE* noundef %46), !dbg !469
  %tobool99 = icmp ne i8 %call98, 0, !dbg !469
  br i1 %tobool99, label %if.then100, label %if.end101, !dbg !470
T | F

if.then100:
  br label %while.end120, !dbg !471

if.end101:
  %arraydecay102 = getelementptr inbounds [5000 x i8], [5000 x i8]* %obuf, i64
  ... 0, i64 0, !dbg !472
  %47 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !473
  %call103 = call i64 @fread(i8* noundef %arraydecay102, i64 noundef 1, i64
  ... noundef 5000, %struct._IO_FILE* noundef %47), !dbg !474
  %conv104 = trunc i64 %call103 to i32, !dbg !474
  store i32 %conv104, i32* %nread, align 4, !dbg !475
  %48 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !476
  %call105 = call i32 @ferror(%struct._IO_FILE* noundef %48) #10, !dbg !478
  %tobool106 = icmp ne i32 %call105, 0, !dbg !478
  br i1 %tobool106, label %if.then107, label %if.end108, !dbg !479
T | F

if.then107:
  br label %errhandler, !dbg !480

if.end108:
  %49 = load i32, i32* %nread, align 4, !dbg !481
  %cmp109 = icmp sgt i32 %49, 0, !dbg !483
  br i1 %cmp109, label %if.then111, label %if.end115, !dbg !484
T | F

if.then111:
  %arraydecay112 = getelementptr inbounds [5000 x i8], [5000 x i8]* %obuf, i64
  ... 0, i64 0, !dbg !485
  %50 = load i32, i32* %nread, align 4, !dbg !486
  %conv113 = sext i32 %50 to i64, !dbg !486
  %51 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !487
  %call114 = call i64 @fwrite(i8* noundef %arraydecay112, i64 noundef 1, i64
  ... noundef %conv113, %struct._IO_FILE* noundef %51), !dbg !488
  br label %if.end115, !dbg !488

if.end115:
  %52 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !489
  %call116 = call i32 @ferror(%struct._IO_FILE* noundef %52) #10, !dbg !491
  %tobool117 = icmp ne i32 %call116, 0, !dbg !491
  br i1 %tobool117, label %if.then118, label %if.end119, !dbg !492
T | F

if.then118:
  br label %errhandler, !dbg !493

if.end119:
  br label %while.body97, !dbg !465, !llvm.loop !494

while.end120:
  br label %closeok, !dbg !496

if.end36:
  br label %while.cond11, !dbg !324, !llvm.loop !356

while.end62:
  br label %closeok, !dbg !305

closeok:
  call void @llvm.dbg.label(metadata !405), !dbg !406
  %32 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !407
  %call63 = call i32 @ferror(%struct._IO_FILE* noundef %32) #10, !dbg !409
  %tobool64 = icmp ne i32 %call63, 0, !dbg !409
  br i1 %tobool64, label %if.then65, label %if.end66, !dbg !410
T | F

if.then65:
  br label %errhandler_io, !dbg !411

if.end66:
  %33 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !412
  %call67 = call i32 @fclose(%struct._IO_FILE* noundef %33), !dbg !413
  store i32 %call67, i32* %ret, align 4, !dbg !414
  %34 = load i32, i32* %ret, align 4, !dbg !415
  %cmp68 = icmp eq i32 %34, -1, !dbg !417
  br i1 %cmp68, label %if.then70, label %if.end71, !dbg !418
T | F

if.then70:
  br label %errhandler, !dbg !419

if.end71:
  %35 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !420
  %call72 = call i32 @ferror(%struct._IO_FILE* noundef %35) #10, !dbg !422
  %tobool73 = icmp ne i32 %call72, 0, !dbg !422
  br i1 %tobool73, label %if.then74, label %if.end75, !dbg !423
T | F

if.then74:
  br label %errhandler, !dbg !424

if.end75:
  %36 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !425
  %call76 = call i32 @fflush(%struct._IO_FILE* noundef %36), !dbg !426
  store i32 %call76, i32* %ret, align 4, !dbg !427
  %37 = load i32, i32* %ret, align 4, !dbg !428
  %cmp77 = icmp ne i32 %37, 0, !dbg !430
  br i1 %cmp77, label %if.then79, label %if.end80, !dbg !431
T | F

if.then79:
  br label %errhandler_io, !dbg !432

if.end80:
  %38 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !433
  %39 = load %struct._IO_FILE*, %struct._IO_FILE** @stdout, align 8, !dbg !435
  %cmp81 = icmp ne %struct._IO_FILE* %38, %39, !dbg !436
  br i1 %cmp81, label %if.then83, label %if.end89, !dbg !437
T | F

if.then83:
  %40 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !438
  %call84 = call i32 @fclose(%struct._IO_FILE* noundef %40), !dbg !440
  store i32 %call84, i32* %ret, align 4, !dbg !441
  store %struct._IO_FILE* null, %struct._IO_FILE** @outputHandleJustInCase,
  ... align 8, !dbg !442
  %41 = load i32, i32* %ret, align 4, !dbg !443
  %cmp85 = icmp eq i32 %41, -1, !dbg !445
  br i1 %cmp85, label %if.then87, label %if.end88, !dbg !446
T | F

if.then87:
  br label %errhandler_io, !dbg !447

if.end88:
  br label %if.end89, !dbg !448

if.end89:
  store %struct._IO_FILE* null, %struct._IO_FILE** @outputHandleJustInCase,
  ... align 8, !dbg !449
  %42 = load i32, i32* @verbosity, align 4, !dbg !450
  %cmp90 = icmp sge i32 %42, 2, !dbg !452
  br i1 %cmp90, label %if.then92, label %if.end94, !dbg !453
T | F

if.then92:
  %43 = load %struct._IO_FILE*, %struct._IO_FILE** @stderr, align 8, !dbg !454
  %call93 = call i32 (%struct._IO_FILE*, i8*, ...) @fprintf(%struct._IO_FILE*
  ... noundef %43, i8* noundef getelementptr inbounds ([6 x i8], [6 x i8]*
  ... @.str.130, i64 0, i64 0)), !dbg !455
  br label %if.end94, !dbg !455

if.end94:
  store i8 1, i8* %retval, align 1, !dbg !456
  br label %return, !dbg !456

sw.bb122:
  br label %errhandler_io, !dbg !503

if.then35:
  br label %errhandler_io, !dbg !355

sw.bb126:
  %55 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !511
  %56 = load %struct._IO_FILE*, %struct._IO_FILE** @stdin, align 8, !dbg !513
  %cmp127 = icmp ne %struct._IO_FILE* %55, %56, !dbg !514
  br i1 %cmp127, label %if.then129, label %if.end131, !dbg !515
T | F

if.then129:
  %57 = load %struct._IO_FILE*, %struct._IO_FILE** %zStream.addr, align 8,
  ... !dbg !516
  %call130 = call i32 @fclose(%struct._IO_FILE* noundef %57), !dbg !517
  br label %if.end131, !dbg !517

if.end131:
  %58 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !518
  %59 = load %struct._IO_FILE*, %struct._IO_FILE** @stdout, align 8, !dbg !520
  %cmp132 = icmp ne %struct._IO_FILE* %58, %59, !dbg !521
  br i1 %cmp132, label %if.then134, label %if.end136, !dbg !522
T | F

if.then134:
  %60 = load %struct._IO_FILE*, %struct._IO_FILE** %stream.addr, align 8, !dbg
  ... !523
  %call135 = call i32 @fclose(%struct._IO_FILE* noundef %60), !dbg !524
  br label %if.end136, !dbg !524

if.end136:
  %61 = load i32, i32* %streamNo, align 4, !dbg !525
  %cmp137 = icmp eq i32 %61, 1, !dbg !527
  br i1 %cmp137, label %if.then139, label %if.else, !dbg !528
T | F

if.then139:
  store i8 0, i8* %retval, align 1, !dbg !529
  br label %return, !dbg !529

if.else:
  %62 = load i8, i8* @noisy, align 1, !dbg !531
  %tobool140 = icmp ne i8 %62, 0, !dbg !531
  br i1 %tobool140, label %if.then141, label %if.end143, !dbg !534
T | F

if.then141:
  %63 = load %struct._IO_FILE*, %struct._IO_FILE** @stderr, align 8, !dbg !535
  %64 = load i8*, i8** @progName, align 8, !dbg !536
  %call142 = call i32 (%struct._IO_FILE*, i8*, ...) @fprintf(%struct._IO_FILE*
  ... noundef %63, i8* noundef getelementptr inbounds ([45 x i8], [45 x i8]*
  ... @.str.131, i64 0, i64 0), i8* noundef %64, i8* noundef getelementptr inbounds
  ... ([1034 x i8], [1034 x i8]* @inName, i64 0, i64 0)), !dbg !537
  br label %if.end143, !dbg !537

if.end143:
  store i8 1, i8* %retval, align 1, !dbg !538
  br label %return, !dbg !538

errhandler_io:
  call void @llvm.dbg.label(metadata !505), !dbg !506
  call void @ioError() #11, !dbg !507
  unreachable, !dbg !507

return:
  %65 = load i8, i8* %retval, align 1, !dbg !540
  ret i8 %65, !dbg !540
```

CFG for 'uncompressStream' function