

Unsupervised Steering Vectors from Learned Classifiers: A Summary

Keira Wiechecki
WAKARU · KAW504@NYU.EDU

Lamb Wakefield
FLOCK CAPITAL · LAMB@FLOCK.HOLDINGS

Jade Zaslavsky
WAKARU · JADEOFNAMELESS@GMAIL

vmfunc
FLOCK CAPITAL · CELESTE@LINUX.COM

October 29, 2026

Checking a model for a hidden goal, or for a concept that no one has thought to name, means finding the model's internal variables without labeling them first. This summary presents a method built for that task and states plainly where it stands. The method describes a network's internal state compactly enough for the network to run on. But editing that description steers the network no more specifically than editing arbitrary categories of the same state would. Past the first round, the variables found by the method also differ from one training run to the next. Until both of these change, the variables cannot be named or relied on.

What the method does

The method, which we call an *Ontologizer*, rewrites a neural network's internal representation at one point as a short list of discrete choices. It then rebuilds the representation from those choices. The method is made of small classifiers. Each classifier sorts every input into one of k categories, and each category stores one vector. The input is rebuilt by adding up the vectors of the categories that it was sorted into. The models described here have 5 rounds of 32 classifiers, with 32 categories each. So an input is described by 160 choices (800 bits), plus one number per round that sets the size of that round's contribution. Nothing is labeled: classifiers and vectors are learned only by asking the rebuilt representation to match the original.

Because a classifier's categories are mutually exclusive, changing one classifier's choice for an input, from category j to category j', swaps one stored vector for another. This swap is the steering move that the method is built around. It moves

the representation from j to j' along one axis found by the method. The result is always another valid description, so the edited representation stays within the range of states that occur in normal operation.

We study two representations. The main one is the internal state of GPT-2 small after its first eight blocks [1], on web text. The rebuilt state can be put back into the running model, so we can measure how much of the model's behavior survives. The second is SONAR sentence embeddings [2]. SONAR gives one fixed-length vector per text, here the opening of a web document (SONAR is built for sentences). The vector can be decoded back into a short paraphrase, which makes a steered embedding readable.

What it is for

Watching what a model does cannot settle what it is trying to do: a model can behave differently when it believes it is being trained [3]. Settling the question means reading the model's internal state, including concepts that have never been named.

To steer a model is to change its internal state so that it behaves differently in a chosen way. A standard method is a *steering vector*. Average the representations of examples that have a property, subtract the average of examples without it, and add the difference to new inputs [4]. A single contrasting pair of prompts can be enough [5]. This often works, though not for every property. And someone who already suspects that the property exists must supply contrasting examples of it. Supervised steering, and the linear probe that detects a property in the same way, can therefore confirm a suspected concept but cannot find an unsuspected one.

Sparse autoencoders (SAEs) find features without labels: each input is described by a few active features out of thousands [6, 7]. But each feature is an isolated direction that is either on or off, with no stated alternatives. A feature can stay off on inputs that have its property, because a more specific feature has taken over its direction [8]. A silent feature is therefore weak evidence that the property is absent. Features also split as the dictionary grows [9], and adding a feature direction can push the representation anywhere. On a recent steering benchmark, prompting, fine-tuning and the averaged difference each beat SAE features [10].

The methods that win are contrasts between alternatives. They contrast a property with its absence, or one value of a *variable* (a property with several possible values, such as a text's topic) with another. The goal is steering vectors that need no labels but keep that shape. Each would be a move between named alternatives, found together with the contrast that it moves along. Steering can then test the method, but only against a baseline. Suppose that a swap moves the model's behavior the way that the categories predict. This shows that the variable matters to the model only if the swap does better than swaps between arbitrary categories of the same state. On both representations, it does not yet do better (see

below).

What it assumes, and why that is acceptable

1. **A representation is mostly a sum of a few categorical choices, plus a remainder that is described by later rounds.** Much of language is categorical: which token, which syntactic role, which topic. Describing a remainder in successive rounds is also how residual vector quantization works in compression [11]. On GPT-2, 800 bits per token rebuild the held-out state well. Put back into the model, the rebuilt state recovers 97.5% of the next-token loss that replacing the state with its average would cost.


2. **The classifiers act as roughly independent factors.** Independence is what lets a few small choices cover many combinations. On GPT-2, two classifiers' choices share 0.27 bits of information in the first round and 0.02 bits by the third. Each choice carries about 5 bits.

3. **The network still works when it runs on the description.** If it did not, editing the description would mean nothing. Beyond the 97.5% recovery, swapping one classifier's choice changes GPT-2's next-token distribution by only 0.001–0.06 nats.

4. **The categories can be named.** Partly true. On GPT-2, we show a judge model a description of a first-round category. The judge then distinguishes the category's most typical members from distractors with a score of 0.91, where 0.5 is chance. The score falls to 0.65 for randomly chosen members and 0.55 for members near the category's edge. In the fourth and fifth rounds, the judge is at or near chance even on the most typical members. In the first round, 29–31 of the 32 classifiers track which token is present. There, a rule that uses only the current token's identity beats the judge on single categories. It scores 0.75 vs. 0.69 when each classifier writes to its own block of coordinates, and 0.74 vs. 0.71 when every classifier writes to all of them (*direct vectors*). On sentence embeddings, the strongest classifier sorts by topic and genre (crime news, legislation, encyclopedic description, and so on).

5. **The categories are a property of the data, not of the training run.** This has *not* held. Two runs from different random starts reconstruct equally well, but on both representations only the first round's classifiers recur; later rounds differ from run to run.

How it works, intuitively



Think of describing a token by answering a fixed list of multiple-choice questions, where both the questions and the answers are learned. In the first round, each of 32 classifiers assigns the token to one of its categories, all in parallel. The chosen vectors are summed and scaled to the size of what they explain. The next round receives only what the first round left unexplained, and describes that remainder; there are five rounds in all. Training uses hard choices in the forward pass and soft ones when computing gradients (a straight-through estimator). In compression terms, the design is a residual quantizer in which each round adds up vectors chosen from several sets [11, 12]. (Product quantization [13] is the case in which each set covers its own coordinates.) Here the quantizer is used not for compression but so that every choice can be read and swapped. The same kind of quantizer has been used to turn SONAR embeddings into discrete codes for a language model that writes in them [14].

How it compares with existing methods

Against supervised steering — the comparison that matters. Three tests so far, none of them yet the decisive one.

- *Swaps are specific, but so are arbitrary categories (GPT-2).* Swapping a token's category from j to j' moves the model's output toward the typical output of j'. Among 31 alternatives, j' ranks 3.5–6 on average, and still 5–8 at four times the step. A random step of the same size ranks 14–18 (one classifier

each in the first, third and fifth rounds). But arbitrary categories steer just as specifically in every round (mean rank 0.21–1.69 across the five rounds, against 0.56–1.37 for learned categories, on 8 classifiers per round). We made them by sorting each state by which of 32 random directions it points along most, so nothing in them is learned. Specificity shows that the state can be steered along any way of dividing it, not that the method's categories mean anything.

- *Language (sentence embeddings).* Forcing one of the method's categories moved decoded text toward a target language 0.64 times as far as the supervised difference-of-means vector did, and 4 times as far as a linear-probe direction. All methods, supervised included, damaged unrelated content about as much as a random step of the same size.

- *Reaching its own categories (sentence embeddings).* For each category, we fitted the two standard supervised vectors (difference of means and a linear probe) to the method's own choices. This baseline is generous, because it is fitted to the answer. Every direction got the same step. The soft version's own direction reached its category on 75% of inputs, against 46–47% for the supervised vectors. The hard multi-round version's own direction reached only 37%, against 91–94%: its categories are reachable, but its own direction does not point at them. Arbitrary categories are just as reachable. On an untrained 5-round model, the supervised vectors reach 75% and 94% of its random categories (and the classifiers' own gradients reach 61–85%), while disturbing a third as many other classifiers (22% vs. 66%). On 380 random-direction classifiers of 32 categories, swapping category averages reaches 78%. The supervised or projection directions reach 87–100%, while disturbing 30–32%.

The decisive test has not been run. It would steer toward externally defined concepts, as in AxBench [10]. Supervised vectors fitted to those concepts' labels, SAE features and the method's swaps would each run at their best tuned strength. The same judge would score each of them for the concept, for staying on task and for fluency.

Against SAEs on steering. On sentence embeddings, each model is steered with its own step size. A feature of a standard SAE (32 active per input) takes effect on 46–50% of inputs, and the multi-round method on 8–19%. Both disturb other features or classifiers about as much as a random step. A one-round version of the method takes effect on 41% while disturbing 1.4% of its other classifiers, against 18% for a random step. On GPT-2, only removal has been compared. Setting one classifier to its average choice everywhere costs 0.02–0.075 nats, and removing one SAE feature where it is active costs 0.055.

Against SAEs on reconstruction (a precondition, not the goal). Steering through a description only means something if the model runs on it.

GPT-2 small, after 8 blocks, held out	per-token code	unexplained variance	loss recovered
Ontologizer, 32 categories (10M)	800 bits + 5 numbers	0.217	97.0%
Ontologizer, 32 categories (40M)	800 bits + 5 numbers	0.195	97.6%
Ontologizer, 32 categories, concat.	800 bits + 5 numbers	0.186	97.5%
Ontologizer, 64 categories, concat.	960 bits + 5 numbers	0.164	97.9%
SAE, 32 active features	32 indices + 32 numbers	0.189	96.2%
SAE, 128 active features	128 indices + 128 numbers	0.116	98.6%

The 800-bit description recovers more of the model's loss than the 32-feature SAE. That holds on the same 10M-token training cache (97.0% vs. 96.2%) and after one pass over 40M tokens (97.5–97.6%). Its errors must then fall in directions that matter less to the model's output. But if the SAE's 32 numbers are rounded to about 5 bits each (556–588 total bits), the SAE leads on unexplained variance per bit. In the concatenated-head model (concat. in the table), each classifier writes to its own block of coordinates. Giving each of its rounds a separate output projection, instead of one shared across all five, cuts unexplained variance from 0.186 to 0.169 (97.3% to 97.7% loss recovered). It also cuts the coupling between classifiers that hold the same position in different rounds from 97% to 6%. On sentence embeddings, 1900 bits of choices and the per-round sizes leave 15% of the variance unexplained, and 16% with the sizes fixed. A standard SAE can be held to the same 1900 bits: about 1200 bits to specify which 160 features are active, and the rest for their 160 numbers. It then leaves at least 24% unexplained, however those numbers are rounded. But consider an SAE trained with a weaker sparsity penalty, with its numbers rounded coarsely and each feature's activity coded by how often it fires. At 1900 bits, it leaves 13% unexplained. Its features fire unevenly, which makes the list of active ones cheap to send. The method's categories are used evenly, so there is nothing to save.

What we can claim

On both representations, the method describes the network's state with a small set of discrete choices. It does so about as accurately as a sparse autoencoder that also sends continuous numbers: more accurately than the standard kind at the same number of bits, though not than every kind. On GPT-2, the model runs on that description with little loss. Swapping one choice moves the model's output specifically toward the new category, though swapping between arbitrary categories does too. Some categories can be named. On GPT-2, a first-round category can be named from its most typical members (0.91, where 0.5 is chance). But a rule based on token identity beats the judge on single first-round categories (0.74–0.75 vs. 0.69–0.71). Combining two first-round categories adds 0.10 when each classifier has its own block (0.69 to 0.78, mostly from token identity), and 0.01 with direct vectors (0.71 to 0.72). On sentence embeddings, a classifier that sorts by

topic and genre recurs in every run. Three questions remain open: whether the categories are in general easier to interpret than SAE features, whether they steer better than arbitrary categories, and whether swapping them steers better than supervised vectors toward concepts that a user cares about.

What does not work yet

- **The classifiers past the first round are not reproducible.** This is the main open problem, not a detail. On both representations, two runs reconstruct equally well but agree on almost none of these classifiers. Reconstruction quality therefore cannot reveal the failure. A classifier that differs on every run cannot be named, and an audit could not rely on it. A goal defined in terms of it would no longer refer to the same thing once the model is retrained.
- **Categories are named from their extremes.** Descriptions fit a category's most typical members, not its ordinary ones. This is a known failure of automated description when only the strongest examples are shown [15]. The deeper rounds cannot yet be named at all, though changing them does change the model's output.
- **Swaps do not yet beat arbitrary categories.** On both GPT-2 and sentence embeddings, swaps between categories made from random directions, or from an untrained model, are as specific as swaps between learned categories. That leaves reconstruction as the only case for the deeper rounds.
- **Steering through the input is not targeted.** On sentence embeddings, pushing an input toward one category changes other classifiers' choices about as much as a random push of the same size. Swaps made on the description itself do not have this problem.

Next

Reproducibility comes first: making the classifiers reproducible, or identifying the ones that are. Theory shows that reconstructing individual inputs cannot, on its own, identify discrete or continuous factors. Identifying them requires structural constraints matched to the data, or paired views such as adjacent sentences [16, 17, 18, 19, 20, 21, 22, 23, 24]. On 44.1M consecutive sentence embeddings, a linear predictor from one sentence explains only about 10% of the next sentence's variance (unexplained variance 0.896). Adjacent sentences point in similar directions (cosine discrimination 0.923), yet existing classifiers switch categories on 92.2–98.1% of adjacent pairs. Directly penalizing category changes across adjacent sentences collapses the penalized classifiers to 0.04–0.09 bits. That points instead to a bound

on conditional entropy that switches off once a classifier rarely changes category between adjacent sentences.

The method then needs the AxBench-style test: steering toward externally defined concepts [10]. Difference-of-means vectors from labeled examples, SAE features and the method's swaps would each run at their best tuned strength. A judge would score each of them for the concept, for staying on task and for fluency, and detection would be compared against a linear probe. Initial runs toward that evaluation are underway on Gemma 3 1B and Gemma 4 A4B. They use mean-squared error with a small uniformity penalty, and a separate output projection for each round.

References

[1] Alec Radford et al. *Language Models are Unsupervised Multitask Learners*. Tech. rep. OpenAI, 2019.

[2] Paul-Ambroise Duquenne, Holger Schwenk, and Benoît Sagot. *SONAR: Sentence-Level Multimodal and Language-Agnostic Representations*. 2023. arXiv: 2308.11466 [cs.CL]. URL: https://arxiv.org/abs/2308.11466.

[3] Ryan Greenblatt et al. *Alignment Faking in Large Language Models*. 2024. arXiv: 2412.14093 [cs.AI]. URL: https://arxiv.org/abs/2412.14093.

[4] Nina Rimsky et al. "Steering Llama 2 via Contrastive Activation Addition". In: *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Bangkok, Thailand: Association for Computational Linguistics, 2024, pp. 15504–15522. DOI: 10.18653/v1/2024.acl-long.828. URL: https://aclanthology.org/2024.acl-long.828/.

[5] Alexander Matt Turner et al. *Steering Language Models With Activation Engineering*. 2024. arXiv: 2308.10248 [cs.CL]. URL: https://arxiv.org/abs/2308.10248.

[6] Trenton Bricken et al. "Towards Monosemanticity: Decomposing Language Models With Dictionary Learning". In: *Transformer Circuits Thread* (2023). URL: https://transformer-circuits.pub/2023/monosemantic-features/index.html.

[7] Leo Gao et al. *Scaling and evaluating sparse autoencoders*. 2024. arXiv: 2406.04093 [cs.LG]. URL: https://arxiv.org/abs/2406.04093.

[8] David Chanin et al. "A is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders". In: *Advances in Neural Information Processing Systems*. Vol. 38. 2025, pp. 91489–91526. arXiv: 2409.14507 [cs.CL]. URL: https://arxiv.org/abs/2409.14507.

[9] Bart Bussmann et al. "Learning Multi-Level Features with Matryoshka Sparse Autoencoders". In: *Proceedings of the 42nd International Conference on Machine Learning*. Vol. 267. Proceedings of Machine Learning Research. PMLR, 2025, pp. 6077–6101. arXiv: 2503.17547 [cs.LG]. URL: https://arxiv.org/abs/2503.17547.

[10] Zhengxuan Wu et al. "AxBench: Steering LLMs? Even Simple Baselines Outperform Sparse Autoencoders". In: *Proceedings of the 42nd International Conference on Machine Learning*. Vol. 267. Proceedings of Machine Learning Research. PMLR, 2025, pp. 67035–67080. arXiv: 2501.17148 [cs.CL]. URL: https://arxiv.org/abs/2501.17148.

[11] Neil Zeghidour et al. *SoundStream: An End-to-End Neural Audio Codec*. 2021. arXiv: 2107.03312 [cs.SD]. URL: https://arxiv.org/abs/2107.03312.

[12] Artem Babenko and Victor Lempitsky. "Additive Quantization for Extreme Vector Compression". In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. 2014, pp. 931–938. URL: https://openaccess.thecvf.com/content_cvpr_2014/html/Babenko_Additive_Quantization_for_2014_CVPR_paper.html.

[13] Hervé Jégou, Matthijs Douze, and Cordelia Schmid. "Product Quantization for Nearest Neighbor Search". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 33.1 (2011), pp. 117–128.

[14] LCM team et al. *Large Concept Models: Language Modeling in a Sentence Representation Space*. 2024. arXiv: 2412.08821 [cs.CL]. URL: https://arxiv.org/abs/2412.08821.

[15] Gonçalo Paulo et al. "Automatically Interpreting Millions of Features in Large Language Models". In: *Proceedings of the 42nd International Conference on Machine Learning*. Vol. 267. Proceedings of Machine Learning Research. PMLR, 2025. arXiv: 2410.13928 [cs.LG]. URL: https://arxiv.org/abs/2410.13928.

[16] Francesco Locatello et al. "Challenging Common Assumptions in the Unsupervised Learning of Disentangled Representations". In: *Proceedings of the 36th International Conference on Machine Learning*. Vol. 97. Proceedings of Machine Learning Research. PMLR, 2019, pp. 4114–4124. arXiv: 1811.12359 [cs.LG]. URL: https://proceedings.mlr.press/v97/locatello19a.html.

[17] Christopher J. Hillar and Friedrich T. Sommer. *When Can Dictionary Learning Uniquely Recover Sparse Data from Subsamples?* 2015. arXiv: 1106.3616 [q-bio.NC]. URL: https://arxiv.org/abs/1106.3616.

[18] Elizabeth S. Allman, Catherine Matias, and John A. Rhodes. "Identifiability of Parameters in Latent Structure Models with Many Observed Variables". In: *The Annals of Statistics* 37.6A (2009), pp. 3099–3132. DOI: 10.1214/09-AOS689. arXiv: 0809.5032 [math.ST]. URL: https://arxiv.org/abs/0809.5032.

[19] Sunny Duan et al. "Unsupervised Model Selection for Variational Disentangled Representation Learning". In: *International Conference on Learning Representations*. 2020. arXiv: 1905.12614 [cs.LG]. URL: https://arxiv.org/abs/1905.12614.

[20] Aapo Hyvärinen and Hiroshi Morioka. "Nonlinear ICA of Temporally Dependent Stationary Sources". In: *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*. Vol. 54. Proceedings of Machine Learning Research. PMLR, 2017. URL: https://proceedings.mlr.press/v54/hyvarinen17a.html.

[21] David Klindt et al. "Towards Nonlinear Disentanglement in Natural Data with Temporal Sparse Coding". In: *International Conference on Learning Representations*. 2021. arXiv: 2007.10930 [stat.ML]. URL: https://arxiv.org/abs/2007.10930.

[22] Francesco Locatello et al. "Weakly-Supervised Disentanglement Without Compromises". In: *Proceedings of the 37th International Conference on Machine Learning*. Vol. 119. Proceedings of Machine Learning Research. PMLR, 2020. arXiv: 2002.02886 [cs.LG]. URL: https://arxiv.org/abs/2002.02886.

[23] Ilyes Khemakhem et al. "Variational Autoencoders and Nonlinear ICA: A Unifying Framework". In: *Proceedings of the 23rd International Conference on Artificial Intelligence and Statistics*. Vol. 108. Proceedings of Machine Learning Research. PMLR, 2020. arXiv: 1907.04809 [stat.ML]. URL: https://arxiv.org/abs/1907.04809.

[24] Roland S. Zimmermann et al. "Contrastive Learning Inverts the Data Generating Process". In: *Proceedings of the 38th International Conference on Machine Learning*. Vol. 139. Proceedings of Machine Learning Research. PMLR, 2021. arXiv: 2102.08850 [cs.LG]. URL: https://arxiv.org/abs/2102.08850.