

Hi-Hose Nursery Irrigation System

The Hi-Hose Watering System is a simple, efficient way to remove the drudgery of dragging a hose over paths and around plants. It also prevents dirt from contaminating your plants.

<i>Required Material</i>	Hi-Hose length		
	50 ft (15 m)	75 ft (23 m)	100 ft (30 m) ***
	Quantity needed		
Cable	55 ft (17 m)	80 ft (24 m)	105 ft (32 m)+ 5 ft (2.5 m) for a center support
Hose	65 ft (20 m)	90 ft (27 m)	2×65 ft (20 m)
Steel coils (or any anti-kink devices)	7	11	14
S-hook	7	11	14
Zip ties	14	22	28
Pulleys	7	11	14
Cable clamps	4	6	9
Turnbuckle	1	1	1 heavy duty

*** The 100 ft (30 m) hose requires a center support to prevent the cable from drooping. A 5 ft (2.5 m) piece of wire can be used, by looping it around the support structure and the cable. Note that the water supply can be at either end of the hose or you can use a splitter at the center.

Instructions

1. Stretch the cable from one end of the greenhouse to the other.
2. Use 2-3 feet (1 m) of wire to attach the turnbuckle to one side of the greenhouse structure.
 - a. The wire is passed around a sturdy part of the greenhouse and is then attached to itself using cable clamps
 - b. The other end goes through the turnbuckle and is then attached to itself using a cable clamp.
 - c. Make sure the turnbuckle is completely unscrewed.
3. Attach the cable to the turnbuckle, using another cable clamp.
4. Slide all the pulleys onto the cable.
5. Attach the cable to the other end of the greenhouse with a cable clamps. The cable must be as tight as possible.
6. Go back to the other end of the greenhouse and tighten the cable with the turnbuckle.
7. Stretch the hose out under the cable, making sure it is not twisted.
8. Position the steel coils (or any anti-kink devices) at regular intervals on the hose.
9. Using S-hooks, hang the hose onto the swivel pulleys.
 - a. The S hooks should be in the middle of the coil.
 - b. The hose may need half a twist between each coil to hang nicely.
10. Once you are satisfied with the size of the loops and how the hose is hanging, secure the coils using zip ties, leaving enough room for the hose to freely rotate inside the springs.