


Feasibility report

Archetype

24 kWh/day - Genset → PV+Battery



Power | Storage | Off-grid - Photovoltaic

Executive summary

This report was prepared using the RETScreen Clean Energy Management Software. The key findings and recommendations of this analysis are presented below:

System summary

	Technology	Capacity kW	Energy delivered kWh	Fraction of load delivered %
Power				
Base load	Photovoltaic	7.6	8,414	92.2%
	Total	7.6	8,414	92.2%
Equipment	Unit	Capacity		
Inverter	kW	5		
Battery	kWh	23.04		
Fuels	Unit	Consumption		
Base case				
Diesel (#2 oil)	L	6,778		

The main results are as follows:


Cash flow - Cumulative



Disclaimer: This report is distributed for informational purposes only and does not necessarily reflect the views of the Government of Canada nor constitute an endorsement of any commercial product or person. Neither Canada nor its ministers, officers, employees or agents make any warranty in respect to this report or assumes any liability arising out of this report.


Location | Climate data

Location



	Unit	Climate data location	Facility location
Name		Australia - Queensland - Cloncurry A	Australia
Latitude	°N	-20.7	-20.7
Longitude	°E	140.5	140.5
Climate zone		1B - Very hot - Dry	1B - Very hot - Dry
Elevation	m	190	188


Climate data



Heating design temperature	9.2								
Cooling design temperature	39.7								
Earth temperature amplitude	19.6								
Month	Air temperature	Relative humidity	Precipitation	Daily solar radiation - horizontal	Atmospheric pressure	Wind speed	Earth temperature	Heating degree-days	Cooling degree-days
	°C	%	mm	kWh/m²/d	kPa	m/s	°C	°C-d	°C-d
January	31.3	48.5%	128.65	6.86	98.4	4.1	32.3	0	660
February	30.2	54.0%	106.96	6.47	98.5	4.1	31.0	0	566
March	28.7	47.5%	63.55	6.11	98.7	4.6	29.1	0	580
April	26.1	41.5%	16.50	5.97	99.1	4.1	26.9	0	483
May	21.9	42.0%	12.71	4.92	99.3	4.6	22.6	0	369
June	19.0	43.5%	10.50	4.69	99.5	3.6	18.9	0	270
July	18.0	39.5%	6.51	4.89	99.5	3.6	18.3	0	248
August	20.0	33.0%	2.79	5.64	99.5	3.6	21.1	0	310
September	23.9	28.0%	4.50	6.50	99.3	4.1	26.3	0	417
October	28.0	28.5%	20.46	7.08	99.0	4.1	30.7	0	558
November	30.3	29.5%	43.50	7.42	98.8	4.1	32.9	0	609
December	31.1	37.0%	82.77	7.00	98.5	4.1	33.6	0	654
Annual	25.7	39.3%	499.40	6.13	99.0	4.1	26.9	0	5,724

Benchmark

Energy production cost - Off-grid - Range (AUD/kWh)




Benchmark: 1.19 AUD/kWh

System summary


	Technology	Capacity kW	Energy delivered kWh	Fraction of load delivered %
Power				
Base load	Photovoltaic	7.6	8,414	92.2%
	Total	7.6	8,414	92.2%
Equipment	Unit	Capacity		
Inverter	kW	5		
Battery	kWh	23.04		
Fuels	Unit	Consumption		
Base case				
Diesel (#2 oil)	L	6,778		

GHG emissions

GHG emissions



GHG equivalence



GHG emissions		
Base case	18.2	tCO ₂
Proposed case	0	tCO ₂
Gross annual GHG emission reduction	18.2	tCO ₂

Financial viability

Financial parameters

General			
Inflation rate	%		2%
Discount rate	%		9%
Reinvestment rate	%		9%
Project life	yr		20
Finance			
Debt ratio	%		70%
Debt	AUD		15,689
Equity	AUD		6,724
Debt interest rate	%		7%
Debt term	yr		15
Debt payments	AUD/yr		1,723

Costs | Savings | Revenue


Initial costs			
Power system	100%	AUD	22,413
Total initial costs	100%	AUD	22,413
Yearly cash flows - Year 1			
Annual costs and debt payments			
O&M		AUD	287
Debt payments - 15 yrs		AUD	1,723
Total annual costs		AUD	2,010
Annual savings and revenue			
Fuel cost - base case		AUD	11,134
GHG reduction savings		AUD	0
Total annual savings and revenue		AUD	11,134
Net yearly cash flow - Year 1		AUD	9,124
Periodic costs (credits)			
Generator replacement - 2 yrs		AUD	-10,000
Proposed case battery replacement - 6 yrs		AUD	28,020
Proposed case inverter replacement - 13 yrs		AUD	2,000

Financial viability

Pre-tax IRR - equity	%	180%
Pre-tax MIRR - equity	%	19.9%
Pre-tax IRR - assets	%	56.2%
Pre-tax MIRR - assets	%	16.3%
Simple payback	yr	2.1
Equity payback	yr	0.72
Net Present Value (NPV)	AUD	106,522
Annual life cycle savings	AUD/yr	11,669
Benefit-Cost (B-C) ratio		16.8
Debt service coverage		6.4
GHG reduction cost	AUD/tCO ₂	-629
Energy production cost	AUD/kWh	0.959

Cash flow

Annual



Cumulative




Yearly cash flows


Year #	Pre-tax AUD	Cumulative AUD
0	-6,724	-6,724
1	9,341	2,617
2	19,966	22,583
3	9,788	32,371
4	20,842	53,213
5	10,253	63,466
6	-9,801	53,665
7	10,737	64,402
8	22,702	87,104
9	11,240	98,344
10	23,689	122,033
11	11,764	133,797
12	-10,820	122,977
13	9,721	132,699
14	25,784	158,483
15	12,875	171,358
16	28,618	199,976
17	15,188	215,163
18	-10,245	204,919
19	15,801	220,720
20	30,977	251,697

Risk

Impact



Distribution



Perform analysis on	Net Present Value (NPV)				
Number of combinations	500				
Random seed	No				
Parameter	Unit	Value	Range (+/-)	Minimum	Maximum
Initial costs	AUD	22,413	25%	16,810	28,017
O&M	AUD	287	25%	216	359
Fuel cost - base case	AUD	11,134	25%	8,350	13,917
Debt ratio	%	70.0%	25%	52.5%	87.5%
Debt interest rate	%	7.00%	25%	5.25%	8.75%
Debt term	yr	15	25%	11	19
Median				AUD	107,156
Level of risk				%	10%
Minimum within level of confidence				AUD	91,163
Maximum within level of confidence				AUD	122,795

Analysis type

Feasibility

