EVALUATION DASHBOARD LAB

From evaluation records to stakeholder decisions

Walid Barakat | i@work | 8 October 2026

Tableau solution route with an offline browser preview and optional judge-agreement extension.

Goal

Explain where evaluation quality varies across categories and candidate versions, and let a manager inspect the results through clear filters. Technical preparation and audit evidence stay in the notebook and documentation.

Data choice

Option B: 9,000 synthetic evaluation rows covering five categories, four generic candidates and 90 days. The fixed window is 10 July to 7 October 2026. There are 2,250 distinct examples, each evaluated for all four candidates. Seed 42 makes the data reproducible.

Default metric	Simulated result
Average rubric score	55.26 / 100
Scores at or above illustrative target 80	15.50%
Weakest / strongest category	Reasoning / instruction following
Judge agreement within 10 points	61.96%
Average judge score gap	9.03 points

Readiness and limits

Prepared and checked: CSVs, native workbook files, HTML preview, Python notebook, labelled preview images, reflection, README and submission guide. Local data, JavaScript logic and Tableau XML/packaging checks passed.

Before submission: open and verify the workbooks in Tableau, test native filters, save genuine dashboard screenshots, and upload the dedicated lab repository to GitHub. No native screenshot or published repository is claimed.

All scores and candidate differences are simulated. They do not establish commercial model quality, measured savings or performance of the EU tender agent.

1. Main dashboard preview



Figure 1. Preview render generated from the exact dashboard chart code. This is not a screenshot from Tableau Desktop.

Reading the view

The histogram shows how many evaluations fall in each score band. The category box view shows the middle half of scores, median and minimum/maximum. The sorted bars expose improvement priorities. The candidate grid checks whether a weakness is common across versions.

Use model, category and date controls in the HTML file. Clicking a category chart applies a filter, and a candidate cell selects both candidate and category. Reset restores the full set. CSV export downloads only the selected rows.

Native Tableau uses a category-by-score-range heatmap for the distribution sheet; the HTML preview uses a box plot. Both complement the separate ranked comparison.

2. Data preparation and chart solution

Steps 1-3: prepare data

Generate records using the included script, keep raw and clean CSVs, verify numeric scores and canonical dates, and document Option B in data_source.md. No rows were removed: the generator produces valid complete records. Keep genuine 0 and 100 values.

Validation	Evidence
9,000 unique evaluation IDs; no missing critical values	docs/data_quality_report.json
Five categories, four candidates, 90 dates	450 rows per category/candidate combination
Raw score and judge ranges	All score fields remain within 0-100
Repeatability and error cases	10 Python tests, including missing scores, invalid dates and duplicate IDs

Steps 4-7: connect and create charts

Native Tableau worksheet	Fields / aggregation
Score Distribution	score_range; SUM(Row Count)
Scores by Category	category x score_range; SUM(Row Count) on colour and label
Category Comparison	category vs AVG(score), descending order
Candidate Comparison	category x model_version; AVG(score)
Summary cards	AVG(score), SUM(Row Count), AVG(meets_target)

Counts are row counts, not summed evaluation IDs. Average quality is a row-weighted mean. Score ranges are lower-inclusive and upper-exclusive, except 90-100 includes 100. Target rate is the mean of a 0/1 indicator for score at least 80.

Steps 8-10: communication and interaction

Use model/category/date filters across every chart and card. Keep score definitions, record counts, clear titles and the synthetic-data label visible. Use category cross-filtering and concise next-action language. Generation assumptions, data checks and statistical details belong in the notebook.

The native comparison reference line averages displayed category means. It equals the row-weighted mean in this balanced sample; the preview always uses the selected-row mean. Check this distinction when replacing the sample with uneven real data.

3. Optional judge-agreement solution



Figure 2. Judge dashboard preview render, not a native Tableau screenshot. Every selected rating pair is plotted.

Interpretation

Agreement means an absolute score gap of 10 points or less. The mean agreement is 61.96%, mean gap is 9.03 points, and 3,424 cases exceed the tolerance. Agreement is not proof of correct ratings: two judges can share a mistake.

The bars show which categories have more consistent ratings. The gap histogram shows disagreement sizes. The scatter makes rating differences visible. In the preview, the diagonal is equality and dashed lines represent the 10-point tolerance. The native workbook also includes an association trend line.

Compute agreement from the exported rounded judge scores. A difference of exactly 10 counts as agreement even though its histogram bin starts at 10. Review large gaps against a human-approved rubric before drawing conclusions.

4. Verification and requirements status

Requirement	Current status / next evidence
Clean evaluation data and source note	Delivered and validated; synthetic Option B disclosed
At least three charts and filters	Native XML prepared; preview chart logic tested
Stakeholder-friendly communication	Titles, scale, sample count, synthetic label and interpretation included
Final native dashboard file	Main and optional TWBX delivered; actual Tableau opening/filter checks pending
Dashboard screenshot	Labelled preview renders supplied; real Tableau screenshots pending
Reflection and README	Delivered; personalise the suggested reflection after Tableau checks
GitHub-only submission	Dedicated-folder package prepared; repository upload and actual URL pending

Evidence completed

Ten Python tests passed. Twelve JavaScript logic checks passed, including combined filters, chart clicks, reset, empty results, CSV export and judge agreement. JavaScript ran with DOM test doubles and a canvas renderer, so browser end-to-end behaviour is not claimed. The notebook contains eight executed Python cells, run through a local cell runner rather than a Jupyter kernel.

Two TWB sources and two packaged TWBX files passed structural checks using Tableau's official 2026.2 schema, workbook-reference checks, ZIP integrity and embedded-CSV checks. The published schema imports two namespaces without locations; validation supplies namespace declarations for those imports without changing the main workbook structure.

Why native verification is still necessary

Tableau states that schema validation does not guarantee that a workbook opens in the product. Tableau Desktop was unavailable here. The package therefore distinguishes prepared files from confirmed native rendering and includes a manual rebuild recipe if the generated workbook needs correction.

Known interaction counts

All data: 9,000. Candidate A: 2,250. Reasoning: 1,800. Candidate A plus reasoning: 450. The same selection on 7 October only: 5. Every card and chart should follow these selections, and reset should return to 9,000.

5. Submission, reflection and sources

Finish and submit

1. Open the main TWBX in Tableau Desktop 2026.2 or later and verify the CSV connection.
2. Apply all filters to all relevant worksheets, enable category cross-filtering, and check the known counts.
3. Re-save the verified workbook and capture dashboard_screenshot.png from Tableau.
4. Repeat for the optional judge dashboard and capture judge_agreement_screenshot.png.
5. Review the reflection, update status evidence, upload only this lab to a dedicated GitHub repository and submit its actual URL.

Suggested reflection

I designed the dashboard around a manager's questions: where scores are weak, whether the pattern changes by candidate, and which examples deserve review. Clear definitions, sample counts and simple filters support those decisions. I kept code and validation details outside the communication layer.

The generated data limit what I can conclude. A real follow-up would use held-out evaluations from my EU tender agent, the same examples across candidates, and a documented human-reviewed rubric. I would inspect low-score reasoning examples, make one targeted change and track quality, cost and review time before claiming business impact.

Package map

README.md maps every deliverable. The notebook documents calculations. data/ contains CSVs and summaries. scripts/ regenerates data and dashboards. tests/ contains local checks. docs/ holds the Tableau guide, requirement matrix, interpretation and GitHub instructions. Preview images are labelled and kept separate from required native screenshots.

Primary references

Assignment: Uploaded LAB | Evaluation Dashboard Lab(1).pdf: steps 1-11, deliverables and optional extension

Tableau packaged workbooks: Local data inside TWBX
https://help.tableau.com/current/pro/desktop/en-us/save_savework_packagedworkbooks.htm

Tableau filters: Interactive controls and worksheet scope
https://help.tableau.com/current/pro/desktop/en-us/filtering.htm

Tableau filter actions: Selection-based dashboard filtering
https://help.tableau.com/current/pro/desktop/en-us/actions_filter.htm

Official Tableau document schemas: 2026.2 structure and limits of syntactic validation
https://github.com/tableau/tableau-document-schemas

All numerical findings were calculated from the included synthetic CSVs. No unsupported score, real-vendor ranking, fabricated GitHub URL or measured business saving is used.