References

- Bergeron, Janick. Writing Testbenches Using SystemVerilog. Norwell, MA: Springer, 2006
- Bergeron, Janick, Cerny, Eduard, Hunter, Alan, and Nightingale, Andrew. Verification Methodology Manual for System Verilog. Norwell, MA: Springer, 2006
- Cohen, Ben, Venkataramanan, Srinivasan, and Kumari, Ajeetha. SystemVerilog Assertions Handbook for Formal and Dynamic Verification: VhdlCohen Publishing 2005
- Cummings, Cliff. Nonblocking Assignments in Verilog Synthesis, Coding Styles That Kill! Synopsys User Group, San Jose, CA, 2000
- Cummings, Cliff, Salz, Arturo. SystemVerilog Event Regions, Race Avoidance & Guidelines, Synopsys User Group, Boston, CA, 2006
- Denning, Peter. *The Locality Principle*, Communications of the ACM, 48(7), July 2005, pp. 19–24
- Haque, Faisal, Michelson, Jonathan. The Art of Verification with SystemVerilog Assertions. Verification Central 2006
- IEEE IEEE Standard for SystemVerilog Unified Hardware Design, Specification, and Verification Language. New York: IEEE 2009 (a.k.a. SystemVerilog Language Reference Manual, or LRM.)
- IEEE IEEE Standard Verilog Hardware Design, Description Language. New York: IEEE 2001 Rich, Dave Are SystemVerilog Program Blocks Needed? http://blogs.men-tor.com/verificationhorizons/blog/2009/05/07/programblocks/ 2009
- Sutherland, Stuart. Integrating SystemC Models with Verilog and SystemVerilog Using the SystemVerilog Direct Programing Interface. Synopsys User Group Europe, 2004
- Sutherland, Stuart, Davidmann, Simon, Flake, Peter, and Moorby, Phil. System-Verilog for Design: A Guide to Using SystemVerilog for Hardware Design and Modeling. Norwell, MA: Springer, 2006
- Sutherland, Stuart, Mills, Don. Verilog and SystemVerilog Gotchas. Norwell, MA: Springer, 2007 Synopsys, Inc., Hybrid RTL Formal Verification Ensures Early Detection of Corner-Case Bugs, http://synopsys.com/products/magellan/magellan_wp.html, 2003
- van der Schoot, Hans, and Bergeron, Janick *Transaction-Level Functional Coverage in SystemVerilog*. San Jose, CA: DVCon, February 2006
- Vijayaraghavan, Srikanth, and Ramanathan, Meyyappan. A Practical Guide for SystemVerilog Assertions. Norwell, MA: Springer, 2005
- Wachowski Andy, and Wachowski Larry. *The Matrix*. Hollywood, CA: Warner Brothers Studios, 1999

| !, 179 | \$value\$plusargs, 311, 390-391, 452 |
|---|--|
| , 69 | \$warning, 117 |
| ## cycle delay, 108, 204, 375 | %0t, 27 |
| \$, 37, 343–344 | %p, 29–30, 41, 309 |
| \$bits, 305 | %t, 82 |
| \$cast, 55, 60, 284, 286, 291, 305 | ++, 69 |
| \$clog2, 28 | +=, 69–70 |
| \$dist_exponential, 195 | +ntb_random_seed, 224, 390 |
| \$dist_normal, 195 | ::, 54, 142, 144, 250 |
| \$dist_poisson, 195 | <<, 55 |
| \$dist_uniform, 195 | <->, 186, 190 |
| \$error, 117 | -=, 69 |
| \$exit, 110–111 | ->, 184, 188–189, 192 |
| \$fatal, 117 | ->, 190 |
| \$fclose, 70 | >>, 55–57, 161 |
| \$feof, 40, 70 | ?: operator, 32, 43 |
| \$finish, 110–111, 426 | [\$], 37 |
| \$fopen, 40, 70 | [], 35 |
| \$fscanf, 40, 70–71 | ^=, 69, 74, 76 |
| \$get_coverage, 359 | FILE, 174 |
| \$info, 117 | LINE, 174 |
| \$isunknown, 27, 118 | `define, 49 |
| \$monitor, 372 | 'include, 53, 93 |
| \$psprintf, 62 | 'SV_RAND_CHECK, 174 |
| \$random, 195, 217 | |
| \$realtime, 82–83 | Numerics |
| \$root, 115 | |
| \$sformat, 62 | 2-state types, 27, 416, 420, 423, 426 |
| \$sformatf, 62 | 4-state types, 27, 424–426 |
| \$size, 30, 35, 41 | |
| \$strobe, 372 | A |
| \$system, 452 | Abstract class, 295-296, 298-299, 311, |
| \$test\$plusargs, 390–391 | 314, 315 |
| \$time, 27, 82–83 | Accellera, viii |
| \$timeformat, 27, 82–83 | Accessor methods, 162 |
| \$typename, 305, 310 | Active region, 101-103, 106, 112 |
| \$unit, 114, 417, 449 | Agent, 17, 163 |
| \$urandom, 195, 202, 251 | AHB, 128 |
| \$urandom_range, 41, 194, 195, 202, 215 | Always block, 230 |
| - - | |

| Always block in programs, 111 | Bus Functional Model (BFM), 13 |
|---|---|
| and method, 41 | Bidirectional constraint, see Constraint |
| Anonymous enumerated type, 57 | bidirectional |
| API see Application Programming | Bidirectional signal, 108 |
| Interface (API) | Binsof, 351, 353 |
| Application Programming Interface (API), ix | Bit data type, 27, 421, 432 |
| Arguments | Bit streaming <i>see</i> Streaming operator |
| default value, 75–76 | Blueprint pattern, 279 |
| sticky, 73 | BNF see Backus-Naur Form (BNF) |
| task and function, 72 | |
| | Backus-Naur Form (BNF), 213 |
| type, 73 | Bounded mailbox, 256–257 |
| Array | Break, 70 |
| assignment, 37 | Bval, 424, 426 |
| associative, 38–42, 47 | Byte data type, 27, 418, 430 |
| compare, 32 | |
| constraint, 203 | ~ |
| copy, 32 | C |
| dynamic, 35–36, 38, 46, 47 | calc_csm method, 275–276, 287 |
| fixed-size, 28, 36, 38, 46, 47 | Callback |
| handle, 155 | coverage, 335 |
| literal, 29, 35, 37, 40 | creation, 298 |
| locator methods, 42 | inject distrubance, 297 |
| methods, 41 | scoreboard, 300 |
| multi-dimensional, 28, 30-31, 36, 436 | usage, 299 |
| open, 435–436 | Case, 71 |
| packed, 33–34 | Cast, 54, 60, 63, 71 |
| queue, 36, 38, 46, 47 | function return value, 71 |
| reduction methods, 41 | Cerny, Eduard, 455 |
| slice, 32 | Chandle data type, 419, 421–423, 430 |
| unpacked, 29, 34 | Char, 419 |
| Assertion | Checker, 17, 163 |
| concurrent, 118 | Class, 132, 134 |
| coverage, 328 | Class constructor, 136 |
| immediate, 116–117, 286 | Class scope resolution operator, 144, 250 |
| in an interface, 379 | Clock generator, 111–112 |
| Assignment pattern, 29 | Clocking block, 98–99, 103, 108, 109, 123, |
| Associative array, 38–42, 47, 50 | 124, 365 |
| at_least option, 331, 357 | Cohen, Ben, 455 |
| ATM router, 119–121, 123–125 | Command layer, 17 |
| Atomic stimulus generation, 211 | Comment |
| auto_bin_max, 339–340, 347, 355 | |
| | covergroup, 356 |
| Automatic, 74, 80–81, 103, 137, 138, 141, 237 | Comment option, 333, 356 |
| in threads, 236 | Compilation unit, 113 |
| Aval, 426, 428 | Composition, 273, 288, 290, 292 |
| | Compound assignment, 69–70, 74 |
| n. | Concatenation |
| B | bits, 56 |
| Backdoor load, 115 | string, 61 |
| Base class, 276–277 | Concurrent assertion, 118 |
| BaseTr class, 295, 304–305 | Conditional operator, 32, 43 |
| Beginend, 72, 230 | Config class, 266 |
| optional in tasks and functions, 72 | Configuration database, 308 |
| Bergeron, Janick, xiii, 4, 387, 455 | Const, 76 |
| BFM see Bus Functional Model (BFM) | Const type, 61, 74, 114, 176 |

| Constrained, 7 | wire, 26 |
|---|---|
| Constraint | Deallocation, 139 |
| array, 203 | DDR see Double data rate (DDR) |
| bidirectional, 184, 188 | Decrement, 69 |
| block, 173 | Default clocking block, 108 |
| dist, 178-179, 196, 359 | Default coverage value, 343, 345, 350–351 |
| implication, 188 | Default statement, 98 |
| in extended class, 284 | Default value, 75–76 |
| inside, 176, 179, 183, 202, 203 | Delete method, 35, 37, 39, 48 |
| solvebefore, 190-191, 359, 396 | Derived class, 277 |
| constraint_mode, 191-193, 280 | Design pattern, 314 |
| Constructor, 136–137, 277, 295 | Design Under Test (DUT), 3, 88 |
| Consumer, 244 | Direct Programming Interface (DPI), 415–454 |
| Containment, 149 | Disable, 231, 240–243 |
| Context, 444 | Disable fork, 241–242 |
| Continue, 70 | Disable label, 242–243 |
| Сору | Display method, 141-142, 275, 276, 285 |
| deep, 159 | Dist constraint, 178, 179, 196, 359 |
| method, 159–160, 280, 293, 294 | dowhile, 39, 59, 70, 174 |
| object, 156, 293 | Domain, 338–339 |
| shallow, 158 | Double data rate (DDR) clock, 98 |
| Coverage event, 335 | Double data type, 418–419 |
| Covergroup | Double precision floating point, 28 |
| comment, 356 | Downcasting, 284 |
| embedded, 334 | DPI see Direct Programming Interface (DPI) |
| generic, 354–355 | DPI-C, 416, 423 |
| option, 355 | Driver, 17, 163 |
| sample, 331, 335–337 | Driver class, 375, 379 |
| trigger, 335 | DUT see Design Under Test (DUT) |
| Coverpoint, 330, 334, 337, 340, 343, 351, | Dynamic array, 35–36, 38, 46, 47 |
| 353, 358 | Dynamic cast, see \$cast |
| Cross coverage, 348–354 | Dynamic threads, 235 |
| Cross module reference, 114, 370, 376 | |
| cross_num_print_missing option, 357 | |
| CRT see constrained-random test (CRT) | E |
| Constrained-Random Test (CRT), 4, 7–8, 169, | e Reuse Methodology (eRM), viii |
| 196, 323 | Embedded covergroup, 334 |
| Cummings, Cliff, xiii, 100, 102, 455 | Enum, 57–60 |
| Cyclic random, 173 | Enumerated types, see enum |
| | Enumerated values, 58 |
| | Enumeration, 57 |
| D | Environment, 18, 163 |
| Data type | Environment class, 163 |
| bit, 26–27 | Equivalence operator, 186, 190 |
| byte, 26–27 | eRM see e Reuse Methodology (eRM) |
| chandle, 419, 421–423, 430 | Event, 244–249, 264 |
| int, 27 | Event triggered, 244–249, 261 |
| integer, 25 | Exists, 40, 48 |
| logic, 26 | Expression width, 62 |
| longint, 27 | Extended class, 276–277 |
| real, 25 | Extern, see External routine declaration |
| reg, 25–26 | External constraint, 199–200 |
| shortint, 27 | External routine declaration, 142–143, |
| time, 25 | 266, 296 |
| | |

| | _ |
|---|--|
| F | I |
| Fabs routine, 417 | IEEE 1800, see LRM |
| File I/O, 70 | If constraint, 185–186 |
| File_exists method, 417 | Iff, 118, 344 |
| Final block, 110 | Ignore_bins, 346–347, 351 |
| Find_first method, 43 | Illegal_bins, 347 |
| Find_index method, 43–45 | Immediate assertion, 116–117, 286 |
| Find_last method, 43 | Implication, 184 |
| Find_last_index method, 43 | Implication operator, 184, 190 |
| First, 39 | Implicit port connection, 112 |
| First method, 39, 47, 59–60 | Import, 53, 418–419 |
| Fixed-size array, 28, 35, 38, 46, 47 | Incl.h, 418 |
| Float data type, 418 | Increment, 69 |
| for loop, 30, 39, 59, 69, 197 | Inheritance, 274, 288 |
| Force design signals, 115 | Initial, 29 |
| foreach constraint, 203, 207–209, 396 | Initialization in declaration, 80 |
| foreach loop, 30–31, 35, 37, 40 | In-line constraint, 199 |
| Forkjoin, 230–231 | Inout |
| Forkjoin_any, 230, 233 | argument type, 73 |
| Forkjoin_none, 230, 232, 234, 235, 237, | port type, 126 |
| 238 | Input |
| | 1 |
| Four-state types, <i>see</i> 4-state types Function, 71 | argument type, 73 |
| | port type, 126 |
| arguments, 72 | Insert queue, 37 |
| Functional coverage, 18, 455 | Inside, 71, 176, 180 |
| using callbacks, 301 | Inside constraint, 176, 179, 183, 202, 203 |
| Functional layer, 17 | Instance, 136 |
| | Instantiation, 136 |
| | Int data type, 27, 418, 419, 430 |
| G | Integer data type, 25, 27, 51 |
| Garbage collection, 139–140 | Interface, 91, 97, 113, 369 |
| Generator, 18, 163 | connecting to port, 93 |
| Generator class, 234, 248, 250, 255, 279, 281, | procedural code, 379 |
| 304, 305 | virtual, 363–364, 366, 368, 370, 379 |
| Get method, 251–254, 261, 263, 265 | Interprocess, 2 |
| get_coverage, 359 | Interprocess communication (IPC), 229, |
| get_inst_coverage, 359 | 244, 264 |
| Getc method, 61–62 | Intersect, 351, 353 |
| Goal option, 358 | io_printf, 422, 436 |
| | IPC see Interprocess Communication (IPC) |
| | Iterator argument, 43 |
| H | |
| Handle, 134–135, 139 | |
| array, 155 | L |
| Haque, Faisal, 455 | Language Reference Manual (LRM), vii-viii, |
| Hardware Description Language (HDL), 2, 83 | 47, 76, 100, 102, 109, 175, 200, |
| Hardware Verification Language (HVL), viii, | 229, 333, 352, 363 |
| 2, 13 | Last method, 59 |
| HDL see Hardware Description Language | Local, 162, 302, 303, 308 |
| (HDL) | Logic, 49, 91 |
| Histogram, 180 | Logic data type, 26, 27, 97, 419, 430 |
| Hook, 280, 297 | Long long int, 437 |
| HVL see Hardware Verification Language | Longint data type, 26, 418, 419, 430 |
| (HVL) | LRM see Language Reference Manual (LRM) |
| (11, 12) | 21.1.1 See Language Reference Manage (ERM) |

| M | auto_bin_max, 339, 340, 347, 355 |
|---|--|
| Macro, 48 | comment, 333, 356 |
| Macromodule, 114 | cross_num_print_missing, 357 |
| Magellan, 455 | goal, 358 |
| Mailbox, 252, 257, 262–264 | per_instance, 356, 359 |
| bounded, 256, 257 | weight, 351–353, 355 |
| unbounded, 256 | Output |
| Makes Jack a dull boy | argument type, 73 |
| Malloc, 136, 422 | port type, 126 |
| Max method, 42 | OVM, see Open Verification Methodology |
| Method, 134, 277 | (OVM) |
| virtual, 286-288, 293, 294 | |
| Min method, 42 | |
| Modport, 94, 123 | P |
| Module, 133 | Pack |
| Monitor, 17, 163 | method, 160, 161, 438-439 |
| Multi-dimensional array, 28, 30–31, 36, 436 | operation, 55 |
| | Package, 49, 53, 61, 114, 133, 146, 200 |
| | Packed array, 33–34 |
| N | Packed structure, 52 |
| Name function, 182 | Parameter, 49, 61, 114 |
| Name method, 57 | Parameterized |
| New | class, 302 |
| constructor, 136–137 | interface, 377 |
| copying objects, 156 | mailbox, 253 |
| New function, 137 | module, 377 |
| New[] operator, 35, 138 | virtual interface, 377–379 |
| Next method, 39, 48, 59 | Parent class, 277 |
| Nonblocking assignment, 92, 98, 100, | Peek method, 253 |
| 101, 106 | Per_instance option, 356, 359 |
| Null, 136, 139, 140, 198 | Perl hash array, 39 |
| Num method, 39, 255 | Physical interfaces, 363 |
| | PLI, 415, 422 |
| | Plyant, Tim |
| 0 | a good guy |
| Object, 134, 135 | Polymorphism, 287–288 |
| copy, 156, 293 | Pop_back method, 37 |
| deallocation, 139 | Pop_front method, 37 |
| Object-Oriented Programming | Port |
| (OOP), vii, 131, 132, 273 | connecting to interface, 93 |
| analogy badge, 139 | Post_randomize, 193–195, 210, 212 |
| analogy car, 132 | Post-decrement, 69 |
| analogy house, 135 | Post-increment, 69 |
| terminology, 134, 277 | Postponed region, 102–105 Pre_randomize, 193–195, 202 |
| Observed region, 102 OOP, see Object-Oriented | Pre-decrement, 69 |
| Programming (OOP) | Pre-increment, 69 |
| Open array, 434 | Prev method, 47, 59 |
| Open array, see array open | Primitive, 114 |
| Open Verification Methodology | Print class, 306 |
| (OVM), viii, 4, 309 | Pseudo-random number generator |
| OpenVera, viii | (PRNG), 175, 217, 219 |
| Option, 352 | Process, 229 |
| at_least, 331, 357 | Producer, 244 |
| ,,, | |

| D 1 (d 141 | D (1) |
|--|---|
| Product method, 41 | Routine arguments, 72 |
| Program, 80, 103, 114, 133, 146, 238, | Run method, 279, 281–282 |
| 267–268 | RVM, 4 |
| Program blocks | |
| single vs. multiple, 103 | |
| Property, 136, 277 | S |
| Protected, 308 | S_vpi_vecval, 424 |
| Prototype, 134, 277, 295 | Sample method, 331, 335–337 |
| Proxy class, 314–315 | Scenario generation, 211–212 |
| PRNG see Pseudo-random number | Scenario layer, 18 |
| generator(PRNG) | Scheduling region, 101 |
| Public, 162 | Scheduling regions, 102 |
| Pure | Scope operator, 54, 142 |
| imported method, 440–441 | Scoreboard, 18, 45–46, 163, 297, |
| virtual method, 295–296, 299, 311 | 300–301 |
| virtual methods, 315 | using callbacks, 297 |
| Push_back method, 43, 299 | seed, see Random seed |
| Push_front, 37 | Semaphore, 250–252, 264 |
| Push_front method, 37, 299 | Shortint data type, 29, 418, 430 |
| Put method, 251, 253, 254, 257–258, 261, | Shortreal data type, 418, 430 |
| 263, 265 | Shuffle method, 45 |
| Putc method, 62 | Signal layer, 17 |
| | Signature, 288 |
| | Signed data types, 27 |
| Q | Sine function, 441 |
| Queue, 36, 38, 46–47 | Singleton class, 306, 308, 315 |
| literal, 37–38 | Size function, 203 |
| | Size method, 35, 39 |
| | Solvebefore, see Constraint solvebefore |
| R | Sort method, 45 |
| Ramanathan, Meyyappan, 455 | Sparse matrix, 38 |
| Rand, 173 | Specialization, 303, 305 |
| Rand_mode, 191, 197 | Start method, 344 |
| Randc, 173, 182, 203, 208, 281 | Stat method, 417 |
| Randcase, 215–216 | State variables, 198 |
| Random seed, 11–12, 170, 175, 217, | Static, 29 |
| 219, 224 | cast, 54 |
| Random stability, 217, 219 | class, 306, 311 |
| Randomize function, 173, 176 | method, 145, 311 |
| Randomize() with, 192–193, 199 | storage, 80 |
| Randomize(null), 198 | variable, 143–146, 311 |
| Reactive region, 102–103, 106 | Stop method, 344 |
| Real data type, 25, 27, 175, | Streaming operator, 55–56, 160–161 |
| 418, 430 | String concatenation, 61 |
| Realtime data type, 82–83 | String data type, 61–62, 419, 430 |
| Ref | Stringify, 174, 317 |
| argument type, 76, 418–419 | Struct, 50–53, 57 |
| port type, 126 | Subclass, 277 |
| Reg data type, 25–26 | Substr method, 62 |
| Regions | Sum, 55 |
| scheduling, 101, 102 | Sum method, 41, 43–44, 204–207, 396 |
| Return, 78 | Superclass, 277 |
| Reverse method, 45 | Sutherland, Stuart, 385 |
| Rich, Dave, 455 | SV_PACKED_DATA_NELEMS, 424 |
| 200, 2010, 100 | 51.1011115_D11111_1 (DDD1110, 12-1 |

| SV_RAND_CHECK, 174, 286 | Toupper method, 61–62 |
|-------------------------------------|---|
| SVA, 118, 328, 338 | Transactor, 163–164 |
| SvBit, 419-420, 422, 427-428 | Transition coverage, 345–346 |
| SvBitVecVal, 419-420, 423, 426, 435 | Tri data type, 26 |
| SvDimension, 435 | Triggered, 246 |
| Svdpi.h, 418, 420, 422, 435 | Triggered method, 244–249, 261 |
| SvGetArrayElemPtr1, 437 | Try_get method, 251, 255 |
| SvGetArrayPtr, 434, 435 | Try_put method, 253 |
| SvGetArrElemPtr, 435 | Two-state types, see 2-State types |
| SvGetArrElemPtr1, 435 | Type conversion, 54 |
| SvGetArrElemPtr2, 435–436 | Type_option, 352 |
| SvGetArrElemPtr3, 435 | Typedef, 48–49 |
| SvGetNameFromScope, 450 | array, 50, 79 |
| SvGetScope, 450 | associative array index, 50 |
| SvGetScopeFromName, 450 | class, 152 |
| SvHigh, 435–436 | enum, 58 |
| SvIncrement, 435 | struct, 51–52, 57 |
| SvLeft, 435–436 | union, 52 |
| SvLogic, 418, 426 | virtual interface, 375 |
| SvLogicVecVal, 419, 424–426, 435 | |
| SvLow, 435–436 | |
| SVM, 314 | U |
| SvOpenArrayHandle, 434, 435 | Uint user-defined type, 49, 206 |
| SvRight, 435–436 | Unbounded mailbox, 256 |
| SvScope, 450 | Union, 51–52 |
| -Svseed, 224 | Unique method, 42 |
| SvSetScope, 450 | Universal Verification Methodology (UVM), |
| SvSize, 435 | viii, 4–5, 20, 160, 212, 279, 299, |
| SvSizeOfArray, 435 | 305, 309, 314, 336 |
| Synchronous drive, 106 | Unpack |
| System(), 452 | method, 160–161, 438–439 |
| SystemC, 415 | operation, 55 |
| SystemVerilog, see LRM | Unpacked array, 29, 33–34 |
| SystemVerilog Assertion, see SVA | Unsigned, 27, 49, 195, 201, 208 |
| SystemVerilog Methodology, 314 | Unsized array, see array open |
| | User defined type, see typedef |
| | UVM see Universal Verification Methodology |
| T | (UVM) |
| Task, 71 | |
| Arguments, 72 | |
| Template, see Parameterized class | V |
| Test class, 311 | Van der Schoot, Hans, 455 |
| Test layer, 18 | Vc_hdrs.h, 418 |
| The Matrix, 1 | Verification IP, see VIP |
| This, 148–149 | Verification Methodology Manual for |
| Thread, 229, 232–236, 238–240 | SystemVerilog, see VMM |
| Time data type, 25, 27, 82 | Verification Procedural Interface, |
| Time literals, 82 | see VPI |
| Time step, 102 | Verilog-1995, vii-viii, 25, 28, 32, 72-73, 80, |
| Timeprecision, 82 | 119, 195, 363, 377 |
| Timescale, 81–83, 114 | Verilog-2001, vii–viii, 26, 28, 32, 33, 61, 62, |
| Timeunit, 82 | 70, 72, 80, 89, 93 |
| TLM analysis port, 302 | Veriuser.h, 422 |
| Tolower method, 61 | Vijayaraghavan, Srikanth, 455 |
| | |

| VIP, 14 | W |
|---|-----------------------------------|
| Virtual | Wait, 231, 235, 241, 245–250, 268 |
| class, see Abstract classinterface, 309, | Wait fork, 238-239, 248 |
| 363–379 | Weight option, 351–353, |
| memory, 287 | 355 |
| method, 279, 286-288, 293-295 | Wildcard, 346, 354 |
| VMM, viii, 4-5, 17, 20, 97, 212-213, 279, | Wire data type, 26, 97 |
| 299, 307, 314, 328, 371 | With, 42–44 |
| Void | Wrap_up method, 282 |
| data type, 71, 419, 430 | |
| function, 71, 195 | |
| VPI, 415, 424, 426 | X |
| Vpi_control, 426 | XMR, 370–371, 376 |
| VpiFinish, 426 | Xor method, 41 |