Portfolio maintenance guide - condensed edition

Practical source and control reference
29 October 2026

Use this guide to find a feature, understand its owner, make a bounded change, and check how that change is saved. Paths are relative to C:/Dropbox/Resume Website unless stated otherwise.

Contents

Start here 2

The basic update routine 2

Where things live 2

Shared interface and settings 2

Start page 3

About cube and its six faces 3

Videos and shared player 4

Graphics shelf and tabletops 4

Games page 4

Music page 4

Docs desk and library 5

Sticky notes and saving 5

Preview, recovery and future maintenance 5

Start here

This is the complete short guide to the current site's major systems. It explains the first place to make a change and how to save it. The detailed chapters expand these instructions. The working site is still evolving; do not interpret an older handoff's test counts or screenshots as current acceptance.

Project folder: `C:/Dropbox/Resume Website`. Local preview: http://127.0.0.1:8878/. The public website is separate. Saving a local file, exporting settings or clicking Save to project does not publish it.

The basic update routine

1. Identify the page and feature below. Try its existing Settings or Constructor control before editing code.
2. Back up private drawings/layouts through that feature's own export. A settings archive is not necessarily a content backup.
3. For code, find the active HTML entry and follow its imports. Keep the existing public path and persistent IDs.
4. Change one feature at a time. Preview it in a separate tab, preserving any tab with unsaved work.
5. Check the feature, keyboard operation, sound permission and Reduced motion as applicable. Save/export the intended data layer.
6. Publish only through a separately reviewed release workflow. This guide does not authorize a deployment.

Where things live

- `_0-start` through `_6-docs`: page-specific source and local feature assets. Root `index.html` opens Start.
- `_7-shared-scripts`: shared interface, settings, input, media, panel assembly, storage and annotations.
- `debug`: the normal Settings/Constructor shell as well as diagnostics. Do not remove it from release just because of its name.
- `assets`: shared models, images, SVG, audio, documents, vendor code, annotations and selected-work art. Page-owned assets can also live beside their page.
- `games`: embedded game projects. `_4-games` is the arcade cabinet; Graphics' freeform boards are a third distinct system.
- `source-files`: editable originals and preparation recipes. Runtime exports are not always suitable editing masters.
- `Videos`, `Renders`, `music`, `midi`, `soundfonts`: local copies of externally hosted media families. Some required inputs are ignored by Git.
- `tools`: preview, import, export, conversion, packaging and validation commands. Some generators write several runtime files.
- `data`: catalogs/manifests. `docs`: the current reference and these editable guide chapters. `_8-tools-and-notes`: workflows, coordination rules and dated handoffs.
- `output` and `outputs`: retained evidence and deliverables. `tmp`: local intermediates. Do not delete them as a group without a retention review.

Shared interface and settings

Open the gear for Settings. General owns Audio, Scene appearance, Header, Focused media, Accessibility, Transform resets and Points of interest. Page/face contexts hold specialist controls. Constructor is an authoring mode with additional controls where implemented. Debug is the separate left drawer.

Task lookup Script index Next

Left-click a section heading to fold one section. Right-click a heading to toggle its context's sections. Introductory text should sit outside redundant outer folds. Some contexts use private transfer formats; use their own export/import rather than copying form values.

For a new shared setting, update `_7-shared-scripts/core/settings-schema.js`, its UI binding and the actual feature subscriber. `core/settings.js` stores state; `core/settings-controls.js` binds controls; `debug/panel-shell.js` builds common tabs. A schema default affects fresh/default state; an existing browser preference can override it. Do not reset all storage just to see a new default.

For header/nav links, edit `_7-shared-scripts/header.html`. `core/header.js`, `template.css` and `colors.css` handle behavior and appearance. Marked HTML/header/import-map regions are generated by `tools/prepare-site-html.mjs`; update the source, generate in a coordinated window, then check the output. Do not hand-edit only one generated copy.

For Page summary text and points of interest, inspect `core/page-summary.js` and the page's `registerPageSummaryPoints` callback. Use real page actions instead of simulated keyboard events. Selected work and resume/contact content spans `core/selected-work.js`, header markup and `_0-start/start/project-overlays.js`.

Shared mouse transforms/reset behavior belongs to `shared-glb-mouse-controls.js`; page adapters still own exceptions. `core/panel-viewport.js` accounts for Settings/Debug space. `core/presentation-ui.js` controls focused-media UI movement/layering. Preserve usable Back/gear controls.

Start page

Active entry: `index.html -> _0-start/start-page.js`. Supporting modules are under `_0-start/start/` and styles in `start-page.css`.

To change welcome text or native markup, find the visible phrase in `index.html`. To change controller/setup behavior, follow the corresponding handler in `start-page.js` and its helper. Change featured-project definitions and launchers together so text and model controls open the same project. Calibration clips are separate from featured work; do not replace the wrong media.

Verify controller/text switching, remembered setup, denied sound, project Back/close and fallback entry. Do not require the 3D controller to succeed before native controls work.

About cube and its six faces

Active entry: `_1-about/about.html -> about.js`; `faces/index.js` registers faces. Page summary jumps to a face. Settings has Cube and individual face contexts. Fish's compatible internal ID remains `about`; Oddio is `odd`; the Cube settings context uses `faces`.

- Fish: `faces/about/face.js`, `fish-face.js`, picture-library modules and local artwork. Use Fish Settings/Constructor for implemented mode, appearance and motion controls. Keep Fish and picture-ring/gallery modes distinct.
- Refs: `faces/refs/face.js`, cabinet/door/editor modules and its README. Separate cabinet geometry, artwork sources and saved layouts when changing them.
- Skills: `faces/skills/face.js` and neighboring `BeanBag*` modules. Visuals, supply, throwing and sounds have separate owners; shared panel construction is in `panel-assembly`.
- Clock: `faces/clock/face.js`, `controls.js` and hand/winding/gear modules. Preserve mechanical references and live contrast behavior.
- Oddio: `faces/odd/face-runtime.js`, `deck.mjs`, `cloth-rig.js`, `pod-config.mjs`, `addon-layout-editor.js`. Constructor already moves permitted side panels and assigns supported actions to the two four-button panels. The 3D

controls and accessible 2D deck share an engine. Extend their action bridge rather than creating duplicate transport state.

- Notes: `faces/notes/face.js` integrates the workspace in `_1-about/notes/notes-face.js`. Tools, layers, model, history, library/export and gear modules live under `notes/`. Drawings require their own content save/export; shared preferences are a separate layer.

For a face edit, preserve the host attach/update/suspend/resume/dispose contract. The host owns borrowed cube resources. Shared face layout/backing/travel changes require coordination with face owners. About's text fallback is in the HTML, `about.css` and `fallback-carousel.js`; it must navigate independently when the 3D module fails.

Videos and shared player

Active entry: `_2-videos/videos.html -> videos.js`. Tablet focus is in `tablet-focus.js`; transport integration is in `videos-video-adapter.js`. Source captions and instructions live in `_2-videos/captions/`.

Settings -> Videos includes existing focus/sync/viewport preferences and thumbnail explainer text. To change collections or files, trace `videos.js`, `media-catalog.js` and the asset resolver. Some playback pairs a silent video with a separate soundtrack; update both and preserve sync offsets. A preview file is not always the final player source.

Shared controls span `shared-video-controls.js`, `video-player-controls.js` and `media/`. Rate sets can be page-specific. Verify play/pause, seek, volume, rate, pitch, consent and Back/Escape. Intro termination and its service worker are separate lifecycle concerns; do not casually connect loading errors to completion.

Graphics shelf and tabletops

Active entry: `_3-graphics/graphics.js -> shelf/graphics-preview.mjs`. Consult `shelf/README.md` for the established scene and input model.

Use Page summary/item selection for books, the two games and the easel. Settings -> Graphics controls book surfaces, shelf rotation and video navigation; its Games context handles tabletop character settings. Replace book art through the appropriate grade asset/generation workflow, preserving filenames, manifests and resolution tiers.

For page turns/layout, inspect shelf book modules and `page-controls.mjs`. For boxes, inspect game modules and `game-view-controls.mjs`. Freeform boards use `tabletop.html`, `tabletop.mjs` and support modules; they are not the arcade exports. The easel movie belongs to `easel-video.mjs`. Verify pick alignment, grid/spread return, put-away and source art resolution after a change.

Games page

Active entry: `_4-games/games.html -> games.js`. Cabinet layout and input/audio helpers are alongside it. The actual embedded projects are under root `games/`.

Change cabinet menus, reels and camera behavior in the page owner. Change a game's content/rules in its actual authoring/export workflow. Treat generated game files as a package; do not move only an HTML entry away from its dependencies. Verify game input/focus, sound bridge, Back and both reel soundtracks.

Music page

Active 3D entry: `_5-music/music.html` dynamically imports `music-piano-controls.v2.js`. `music.js` is supporting page code; older similarly named piano controllers are not the active 3D entry. `music-2d.html` is a separate piano/recorder route, not disposable duplication.

Use More for the instrument lists; Settings -> Music exposes the current gain, highlight, screen and icon-distribution controls. Instruments start at `instruments/catalog.js` and its loaders/backends. Track layout, timing, seek state and recorded volume have named helper modules alongside the active controller.

To update a song, find its track record, audio candidates, MIDI and video references together. Recorded media supplies soundtrack audio; MIDI drives notes/keys and timing. Do not repair recorded-track volume by changing only synthesized-note gain. Follow `_8-tools-and-notes/music-midi-workflow.md` and `source-files/music-midi/` for current preparation recipes.

Verify from a user gesture with sound allowed, then denied/muted; seek while playing and paused; check sustain/keys/notes, rate changes and return to the piano. Preserve each track's tempo map and calibration.

Docs desk and library

Active entry: `_6-docs/docs.html -> docs-3d.js`. The document collection is `documents.json`; its editor and validator are in `library/editor.js` and `library/schema.js`.

To add/edit a PDF, image or presentation, open Docs Constructor and use Document, Source and cover, and Paper format and placement. Choose the appropriate type, set title/description/source and adjust size/position. Browser edits are drafts. On the local review site, use Save to project to write the reviewed manifest; local uploads use the loopback authoring server. Export the collection for a portable manifest backup. A manifest is not a copy of every uploaded binary.

Inline PowerPoint playback uses a permitted Microsoft embed/link; an uploaded PPTX is preserved as an original-file link rather than converted into that animated viewer. The current Document type also supports bounded local uploads of other office/text originals; consult `_6-docs/README.md` for formats and limits. Check hosted presentation permissions signed out. Desk geometry is `_6-docs/assets/desk.glb`, generated by `tools/export-docs-desk.py`. Its original and editable extracted blend are documented in `assets/README-desk.md` and `source-files/docs-desk-and-cabinet/README.md`.

Drawer interaction is in `desk-drawers.js`. Preserve the four Drawer node names and parent-local offset metadata when exporting a replacement. Texture detail depends on correct UV scale as well as image size. Current web color maps are capped at 1024px and supporting maps at 512px; avoid substituting the large authoring blend for the web GLB.

Sticky notes and saving

General Constructor edits note text/appearance and exports/imports the note bundle. Shared owners are in `_7-shared-scripts/sticky-notes/`; each page supplies scene attachment behavior. Check current adapter availability before assuming every surface can be authored.

Published content is `assets/annotations/sticky-notes.json`. Browser drafts can override that whole bundle locally, while visitor read history is separate. A local edit does not publish. Export, review and deliberately update the project bundle. Stable surface IDs and anchor conventions are part of saved content; geometry replacement may require migration. Verify placement without accidental model actions, read/hide/show, reload and import/export.

Preview, recovery and future maintenance

Run the existing `npm run review` from the repository root for local authoring preview. An already running server may be shared with other chats; do not kill it casually. Use `package.json` and `tools/VALIDATION.md` for maintained commands. Some tools generate source or package output rather than just inspect it.

Task lookup Script index Next

For missing models, inspect the browser's first error and network path. Bare `three` errors point to import-map/module loading; missing local assets may be separate ignored inputs; valid files can still fail CORS or media decoding. For silent sound, inspect consent/mute/volume and the actual audio owner before changing files. Do not clear user storage as a generic fix.

Folder moves are deferred. Before a migration requiring quiet time, notify the human, coordinate active owners, map old/new paths and preserve public URLs, saved IDs, generators and packaging references. No uncertain file is approved for deletion merely because it lacks a direct import.

Remaining manual work: verify current UI paths and recipes in the browser; expand settings/asset indexes and screenshots; refresh chapters after ongoing page work. Separate site acceptance, architecture/refactor, keyboard/mobile/model and release phases remain in the maintained project plans.