Chapter 8 - Where to change things

Task-to-script lookup | 29 October 2026

A practical lookup for maintaining the site. Find the task in the contents, use the UI when it already supplies the control, and use the named source anchors when changing implementation. All paths start at `C:/Dropbox/Resume Website/`.

Each code anchor was checked against the local source while generating this edition. Line numbers are snapshot hints; search for the named function or literal when lines move. A function nested inside another function is a source location, not necessarily an API you can call externally.

These are source-verified references, not a claim that every browser workflow has passed acceptance. UI names describe current source; Constructor availability can depend on page, active face and review context. Export private content before testing changes.

Companion chapters 1-7 explain saving, shared settings, faces, content, media, assets and troubleshooting. This lookup adds specific implementation anchors; it is not an exhaustive catalog of every internal function.

Find a task

Shared settings and site interface 4

- Add a saved setting or change its default/range . . . 4
- Move a setting into another tab or Constructor . . . 4
- Change section collapse behavior or remove a redundant wrapper . . . 5
- Change focused-media UI hiding and movement . . . 5
- Change reset speed/easing or centering beside side panels . . . 6
- Change Page summary text, destinations or travel speed . . . 6
- Change header behavior or the keyboard help guide . . . 7

Start and shared project launchers 7

- Change a featured project and how it opens . . . 7

About cube and six faces 8

- Change face focus or the cube's framing . . . 8
- Fish: change frame, hover layout or deployed pose . . . 8
- Fish gallery: change picture preparation or stored imagery . . . 9
- Refs: change cabinet controls, door geometry or picture storage . . . 9
- Skills: change beanbag throwing or appearance . . . 10
- Clock: change gear finish, hands or winding math . . . 10
- Oddio: move an entire physical add-on panel . . . 11
- Oddio: rearrange four buttons or change their shape . . . 12
- Oddio: connect an existing 2D action to a 3D button . . . 12
- Oddio: change folding speeds, colors or tape effects . . . 13
- Notes: change toolbar tools or side-panel layout . . . 13
- Notes: change layers or editable-file export . . . 14

Graphics books, boxes and easel 14

- Move grid books, resize a reader or change page arrows . . . 14

Change board-game box rotation or focus framing . . . 15
Reduce book surface relief or change its material style . . . 15
Video players and arcade cabinet 16
Change player controls, seek targets or hover previews . . . 16
Change Videos tablet focus or transport integration . . . 16
Change arcade menu, launched game or reel audio . . . 17
Music piano, instruments and recorded tracks 17
Change instrument slots, group choices or the More picker . . . 17
Change instrument loading feedback or gain . . . 18
Change song icons and their distribution . . . 18
Change recorded-track files, MIDI timing or playback volume . . . 19
Change Music video focus and panel sizing . . . 19
Docs content and desk 20
Add a document or change its source/title . . . 20
Move desk papers or change paper dimensions . . . 20
Change desk drawers or the web export . . . 21
Sticky notes and maintaining the reference 21
Change sticky-note UI, text bundles or read behavior . . . 21
Change how a note sticks to a 3D surface . . . 22
Maintaining this lookup 23

Shared settings and site interface

Add a saved setting or change its default/range

Find in UI	Gear -> General or the relevant page/face tab. Constructor contains authoring controls registered by the feature.

Code anchors	`_7-shared-scripts/core/settings-schema.js`
	Find: `export const SETTINGS_FIELDS`
	Canonical field paths, persistence keys, parsers and defaults. (snapshot line 64)
	
	`_7-shared-scripts/core/settings-controls.js`
	Find: `export function mountSettingsControls`
	Connects data-setting controls to the store. (snapshot line 6)
	
	`_7-shared-scripts/core/settings.js`
	Find: `function patch(input)`
	Applies and persists validated changes; inspect subscribe for consumers. (snapshot line 85)

Change / preserve	Add the schema field, bind a UI control and subscribe the actual feature. Change range validation and the UI range together. A new default does not override a saved browser value.
Verify	Change the control, inspect its actual feature, reload, then check a clean/default context without clearing unrelated content. Test any old saved value that needs migration.

Move a setting into another tab or Constructor

Find in UI	Gear -> tabs; Constructor mode switches the available contexts.
Code anchors	`debug/panel-shell.js` Find: `function registerContext(id, label, element)` Registers an ordinary Settings context. (snapshot line 358) `debug/panel-shell.js` Find: `function registerConstructorContext(id, label, element` Registers the authoring context. (snapshot line 338) `debug/panel-shell.js` Find: `function registerContextControls(id, element)` Registers controls pinned to a context. (snapshot line 373)
Change / preserve	Move the owning element/registration, preserving its data-setting paths and disposer. Page modules and face modules often construct their own controls; the shell does not own all markup.
Verify	Open ordinary Settings and Constructor on the intended page. Check context selection, pinned controls, persistence and cleanup after navigation.

Change section collapse behavior or remove a redundant wrapper

Find in UI	Section headings in Settings and Constructor; genuine child groups should remain independently collapsible.

Code anchors	`_7-shared-scripts/panel-assembly/CollapsibleSections.mjs`
	Find: `export function mountCollapsibleSections`
	Shared heading/details enhancement, state and grouping. (snapshot line 9)
	
	`_6-docs/library/editor.js`
	Find: `<h2 data-section-static>`
	Example of a static introduction above real collapsible groups. (snapshot line 14)

Change / preserve	Use the shared helper instead of a new bespoke accordion. Mark non-collapsible introduction headings data-section-static. Preserve stable section IDs/scopes. Follow settings-menu-gestures.md; do not add visible advertising for hidden transfer gestures.
Verify	Collapse one and all sections; expand again, reload and check nested groups. Confirm no unwanted parent fold swallows the entire panel.

Change focused-media UI hiding and movement

Find in UI	Gear -> General -> Focused media: Hide site UI, Animate UI, left/right hide choices and movement timings.

Code anchors	`debug/settings-focused-media.js`
	Find: `export const focusedMediaMarkup`
	Control labels, grouping and data-setting fields. (snapshot line 2)
	
	`debug/settings-focused-media.js`
	Find: `export function mountFocusedMediaControls`
	Disabled/linked controls and Reduced motion override. (snapshot line 25)
	
	`_7-shared-scripts/core/presentation-ui.js`
	Find: `export function createPresentationUiMotion`
	Measured edge offsets, animation and restoration. (snapshot line 7)

Saved setting	`interaction.focusUiMoveAway`, `focusUiAnimate`, `focusUiHideHeader`, `focusUiHideNavbar`, `focusUiHideGear`, `focusUiHideTopRight`, `focusUiOutSpeedMs`, `focusUiInSpeedMs`, `focusUiSeparateInSpeed` (all under interaction).
Change / preserve	Trace the linked-speed checkbox read/write semantics rather than guessing from its internal name. Preserve access to Back and intentional Settings/Debug overlays. Effective Reduced motion overrides animation without overwriting its saved choice.
Verify	Focus/exit media on affected pages, interrupt an animation, open both side panels, resize, and test Reduced motion on/off. Confirm no invisible UI still intercepts player input.

Change reset speed/easing or centering beside side panels

Find in UI	General -> Transform resets; each page's Center on viewport option where exposed.

Code anchors	`_7-shared-scripts/shared-glb-mouse-controls.js`
	Find: `export function transformResetDuration`
	Shared reset timing preference mapping. (snapshot line 8)
	
	`_7-shared-scripts/core/transform-easing.js`
	Find: `export function resolveTransformResetEasing`
	Resolves the chosen reset curve. (snapshot line 23)
	
	`_7-shared-scripts/core/panel-viewport.js`
	Find: `export function panelViewport`
	Measures the usable viewport with Settings and Debug. (snapshot line 3)

Saved setting	`interaction.panResetSpeed`, `interaction.rotationResetSpeed`, `interaction.panResetEasing`, `interaction.rotationResetEasing`; page-specific `<page>.centerOnViewport`.
Change / preserve	Follow the page adapter for its canonical pose. Do not replace the default pose with the current pan. About retains its upright-face exception. Use shared measured space rather than hardcoded panel widths.
Verify	Pan and rotate, reset each independently, interrupt a reset, open either/both panels, and compare normal versus Reduced motion. Check CSS3D hit alignment as well as the model.

Change Page summary text, destinations or travel speed

Find in UI	Page summary next to the name/title; General -> Points of interest for navigation motion.

Code anchors	`_7-shared-scripts/core/page-summary.js`
	Find: `const pages =`
	Shared page summary copy and fallback destinations. (snapshot line 6)
	
	`_7-shared-scripts/core/page-summary.js`
	Find: `export function registerPageSummaryPoints`
	Page owner registers actual callbacks/destinations. (snapshot line 36)
	
	`debug/settings-poi.js`
	Find: `export function mountPoiSettings`
	Navigation animation/speed controls; getPoiMotion supplies effective timing. (snapshot line 6)

Saved setting	`interaction.poiAnimate`, `interaction.poiSpeed`.
Change / preserve	Edit the brief summary here, but update callback-driven points in the page controller that registers them. Preserve readiness guards and disposal; use actual actions rather than synthetic key presses.
Verify	Use every changed destination from a fresh page and from another focused state. Test Back/Escape and Reduced motion. Ensure the list includes the actual content, not only static fallback labels.

Change header behavior or the keyboard help guide

Find in UI	General -> Header; Shortcuts opens the page/state-specific help dialog.

Code anchors	`_7-shared-scripts/core/header.js`
	Find: `export function enhanceHeader`
	Shared header enhancement; markup/style owners include header.html, template.css and colors.css. (snapshot line 44)
	
	`_7-shared-scripts/core/page-shortcuts.js`
	Find: `export function createShortcutGuide`
	Help dialog construction and key rendering. (snapshot line 210)
	
	`_7-shared-scripts/core/page-shortcuts.js`
	Find: `const PAGE_SHORTCUTS`
	Page/state shortcut inventory; actual event handlers are separate. (snapshot line 5)

Change / preserve	A help entry does not implement a shortcut. Update its real handler too. Shared header/import-map regions are generated: inspect tools/prepare-site-html.mjs and coordinate all destinations before regeneration.
Verify	Check modern/legacy header choices, portrait/nav stacking, focus visibility, dialog keyboard use and text-field exclusions. Verify the advertised action is implemented in that state.

Start and shared project launchers

Change a featured project and how it opens

Find in UI	Start selected-work presentation; shared selected-work launchers and preview overlays.

Code anchors	`_0-start/start/project-overlays.js`
	Find: `export function mountStartProjectOverlays`
	Owns embedded project overlay setup and return behavior. (snapshot line 21)
	
	`_7-shared-scripts/core/selected-work.js`
	Find: `export function mountSelectedWork`
	Shared selected-work interface; inspect the selected project ID and launcher here. (snapshot line 6)

Change / preserve	Change the project's label, artwork, stable ID and real launcher coherently. Root index.html and _0-start/start-page.js own the welcome/native and 3D Start routes. An overlay can reuse another page without navigation.
Verify	Launch the project from Start and its normal page, close it and confirm focus and underlying scene/media resume correctly. Check consent and playback for media projects.

About cube and six faces

Change face focus or the cube's framing

Find in UI	About -> Page summary -> a face; Cube settings control shared shell/face behavior.

Code anchors	`_1-about/about.js`
	Find: `function focusFace(`
	Shared camera/cube face focus. (snapshot line 205)
	
	`_1-about/about.js`
	Find: `function frameBesideSettings(`
	Host framing around side panels. (snapshot line 490)
	
	`_1-about/faces/index.js`
	Find: `export function createFaceRegistry`
	Face registration entry point. (snapshot line 18)

Change / preserve	Change the host for shared focus, not a face's local artwork. Keep compatible IDs: Fish uses about, Oddio uses odd; Cube settings use faces. Preserve attach/update/suspend/resume/dispose and borrowed-resource ownership.
Verify	Visit all six faces, rotate/reset, open either side panel and navigate away/back. Check reduced motion and clearance after any physical change.

Fish: change frame, hover layout or deployed pose

Find in UI	Fish face -> its Settings/Constructor controls. Fish and picture-gallery/ring modes are distinct.
Code anchors	`_1-about/faces/about/fish-face.js` Find: `function setFrameOptions(` Commits normalized frame options and geometry/layout updates. (snapshot line 332) `_1-about/faces/about/fish-face.js` Find: `function setHoverOptions(` Commits hover configuration. (snapshot line 256) `_1-about/faces/about/fish-face.js` Find: `function setPose(` Applies the physical pose; inspect deployment flow before changing it. (snapshot line 649)
Change / preserve	Use existing controls first. For code changes follow normalization, saved values and constructor synchronization together. Keep authored mount coordinates and shared contrast response intact.
Verify	Open/close, switch modes and return, inspect oblique views, compare stowed/deployed clearance and verify saved settings and live contrast.

Fish gallery: change picture preparation or stored imagery

Find in UI	Fish's picture/gallery authoring controls; project artwork and browser-imported pictures have different storage.
Code anchors	`_1-about/faces/about/picture-library.mjs` Find: `export function createPictureLibrary` Browser picture-library entry point. (snapshot line 92) `_1-about/faces/about/picture-library.mjs` Find: `async function prepareImage(` Image preparation; inspect stored blobs and entry metadata together. (snapshot line 70)
Change / preserve	Preserve normalized entries and caption metadata. Project artwork also has its own local catalog/assets and packaging tool; importing a browser blob does not update that project catalog.
Verify	Import, display and reopen a disposable picture; check captions/aspect/order, content export and reload. A preference-only archive may not contain the image bytes.

Refs: change cabinet controls, door geometry or picture storage

Find in UI	Refs face -> its Settings/Constructor and editor controls.

Code anchors	`_1-about/faces/refs/controls.js`
	Find: `export function createRefsControls`
	Control markup, display/apply logic and control handlers. (snapshot line 102)
	
	`_1-about/faces/refs/doors.js`
	Find: `export function createRefsDoors`
	Physical door construction/configuration. (snapshot line 132)
	
	`_1-about/faces/refs/picture-source.js`
	Find: `export async function saveRefsOriginal`
	Original picture persistence rather than merely the preview texture. (snapshot line 44)

Change / preserve	For layout dragging start at createRefsEditor in editor.js; for doors use the construction owner. Preserve picture IDs, originals/previews and history boundaries. Read the local README before cabinet restructuring.
Verify	Open/close doors, edit/undo a layout and export/reopen it. Check source art survives, not only the visible preview. Inspect backing and neighboring-face clearance.

Skills: change beanbag throwing or appearance

Find in UI	Skills face -> beanbag interaction and its face-owned controls.

Code anchors	`_1-about/faces/skills/BeanBagThrower.mjs`
	Find: `export function createBeanBagThrower`
	Throw/interaction mechanism and pose-dependent behavior. (snapshot line 27)
	
	`_1-about/faces/skills/BeanBagVisuals.mjs`
	Find: `export function createBeanBagVisuals`
	Reusable visual geometry/material resources. (snapshot line 16)
	
	`_1-about/faces/skills/face.js`
	Find: `function applySettings(`
	Face integration of shared settings. (snapshot line 17)

Change / preserve	Supply/container/sound have separate BeanBag modules. Shared panel construction is in _7-shared-scripts/panel-assembly/. Follow the existing update/disposal owner rather than adding a second render loop.
Verify	Pick up, throw, return and exhaust/replenish where supported. Check suspension, sound permission, live contrast and host geometry after navigation.

Clock: change gear finish, hands or winding math

Find in UI	Clock -> its material/mechanism controls.

Code anchors	`_1-about/faces/clock/controls.js`
	Find: `function setFinish(`
	Commits the selected finish through the controls. (snapshot line 36)
	
	`_1-about/faces/clock/gear-appearance.js`
	Find: `export function createGearAppearance`
	Material appearance owner and generated surface resources. (snapshot line 14)
	
	`_1-about/faces/clock/winding.js`
	Find: `export function handAngles(`
	Time-to-hand angle calculation; offsetForWinding handles winding offsets. (snapshot line 16)

Change / preserve	Hand construction starts at createClockHands in hands.js. Keep mechanism JSON/node contracts and shared magnetic-drive references. Materials must respond to site contrast, including loaded saved values.
Verify	Compare ordinary clock motion and winding; change finish/contrast live, suspend/resume and inspect deployed/retracted geometry. Do not infer mechanical clearance from correct timekeeping.

Oddio: move an entire physical add-on panel

Find in UI	Constructor -> Oddio -> Side-panel placement; choose the add-on and its permitted side/host/gap/vertical position.

Code anchors	`_1-about/faces/odd/addon-layout-editor.js`
	Find: `export function createAddonLayoutEditor`
	Authoring diagram and fields; proposal/finish handle preview and commit. (snapshot line 7)
	
	`_1-about/faces/odd/addon-layout.mjs`
	Find: `export function constrainAddon`
	Constrains a requested position. (snapshot line 77)
	
	`_1-about/faces/odd/addon-layout.mjs`
	Find: `export function resolveAddonLayout`
	Resolves complete layout; ADDON_SPECS and MAIN_PANELS define bounds. (snapshot line 90)

Saved setting	`about.odd.addonTransportSide/Host/Gap/Y`, corresponding Shuttle/Meter/TrackMeters fields; layoutSnapCtrl/Shift/Both.
Change / preserve	These controls move the whole assembly. To change permitted dimensions/hosts, inspect ADDON_SPECS and envelope constraints; do not merely remove clamping. Preserve arm/tape clearance and preview cancellation.
Verify	Drag and type a placement, cancel, commit and reload. Check flips and front/oblique views with all other add-ons present.

Oddio: rearrange four buttons or change their shape

Find in UI	Constructor -> Oddio -> Four-button panel. Existing editor swaps slots/actions and controls icon, color, image and flips.

Code anchors	`_1-about/faces/odd/pod-config.mjs`
	Find: `export const POD_DEFAULTS`
	Default slot actions; assignPodAction and swapPodSlots preserve assignment rules. (snapshot line 4)
	
	`_1-about/faces/odd/pod-editor.js`
	Find: `const CENTERS=`
	Authoring diagram positions; BUTTONS supplies button paths. (snapshot line 8)
	
	`_1-about/faces/odd/shuttle-controls.js`
	Find: `const CENTERS=`
	Physical button geometry/icon/input placement; inspect buttonShape and applyShape too. (snapshot line 9)

Saved setting	`about.odd.podTransportConfig`, `about.odd.podShuttleConfig`; addonTransportFlipX/Y and addonShuttleFlipX/Y.
Change / preserve	Use assignment UI for rearranging existing slots. A geometry/layout edit must keep diagram, visible mesh, icon and proxy hit target aligned. A fifth slot requires schema/normalizer/editor/geometry changes: changing the drawing alone is insufficient.
Verify	Activate every slot after swaps/flips, compare diagram to model and verify saved import/export. Confirm the supported action remains unique when assignment swaps another slot.

Oddio: connect an existing 2D action to a 3D button

Find in UI	Accessible Oddio console supplies the 2D action; a physical panel can expose supported action IDs.

Code anchors	`_1-about/faces/odd/face-runtime.js`
	Find: `function perform(action)`
	Physical action dispatcher, including special mappings and deck-button forwarding. (snapshot line 79)
	
	`_1-about/faces/odd/deck.mjs`
	Find: `export function createSoundDeck`
	Accessible controls, handlers and shared engine. (snapshot line 17)
	
	`_1-about/faces/odd/pod-config.mjs`
	Find: `export const POD_ACTIONS`
	Assignable action inventory; schema validation has a matching allowlist. (snapshot line 2)

Change / preserve	Find the 2D data-action and actual handler. Decide one-shot/held/toggle/value semantics. For a new assignment update POD_ACTIONS/POD_ICONS and the podConfig validator in settings-schema.js. Route through the existing deck/engine; keep permission, busy and selection guards.
Verify	Compare the 2D and 3D result, enabled/pressed states, undo/redo and suspension. Held winding must release on cancellation. Microphone/file access needs a real gesture/device test.

Oddio: change folding speeds, colors or tape effects

Find in UI	Oddio Settings: Armatures, Woven voices & enamel controls and related face-owned sections; accessible console contains audio effect controls.

Code anchors	`_1-about/faces/odd/oddio-settings.js`
	Find: `export function createOddioSettings`
	Face-owned ordinary/Constructor controls and shared-store registration. (snapshot line 10)
	
	`_1-about/faces/odd/face-runtime.js`
	Find: `rig.update(dt,`
	Feeds physical tape state from the shared engine each host tick. (snapshot line 109)
	
	`_1-about/faces/odd/deck.mjs`
	Find: `createAudioEngine(`
	Connects accessible UI to audio-engine.mjs; effects have their own audio owner. (snapshot line 77)

Saved setting	`about.odd.armSpeed`, `foldSpeed`, `separateSpeeds`, `sewingAnimations`, `color1` through `color4`, `highlightColor`.
Change / preserve	Keep visual state derived from the deck engine. Do not duplicate playhead or audio state to change an animation. Cloth-rig/arm-motion own physical mechanisms; live audio effects belong to the engine/effects path.
Verify	Play, pause, reverse, seek and edit a clip; compare cloth and audio. Check linked/separate timing, Reduced motion, contrast and return after suspension.

Notes: change toolbar tools or side-panel layout

Find in UI	Notes face -> drawing workspace, tool strip and layers/art panels.

Code anchors	`_1-about/notes/notes-face.js`
	Find: `function layoutStyle(`
	Workspace panel style/layout helper; frameLayout and readPanelMargin supply related sizing. (snapshot line 151)
	
	`_1-about/notes/notes-face.js`
	Find: `function showTools(`
	Controls tool-panel presentation. (snapshot line 267)
	
	`_1-about/notes/drawing-editor.js`
	Find: `export function createDrawingEditor`
	Tool UI and drawing-editor behavior. (snapshot line 28)

Change / preserve	Separate panel CSS/layout changes from drawing input/tool logic. Preserve input ownership while drawing, the layers boundary and saved tool state. Do not reload an edited tab without exporting the current drawing.
Verify	Open tools, select several tools, draw/select/drag, resize, and open Settings/Debug. Verify panels clear required navigation and tools stay usable without accidental cube rotation.

Notes: change layers or editable-file export

Find in UI	Notes -> Layers; drawing library/save/export controls for editable content.

Code anchors	`_1-about/notes/drawing-layers.js`
	Find: `export function createLayersPanel`
	Layer tree UI, rename and drag/drop integration. (snapshot line 5)
	
	`_1-about/notes/drawing-library.js`
	Find: `export function validateDrawing`
	Editable drawing format validation. (snapshot line 11)
	
	`_1-about/notes/drawing-library.js`
	Find: `export function createDownloadManager`
	Download ownership/lifetime; drawingFile describes the editable wrapper. (snapshot line 141)

Change / preserve	Route layer edits through the existing document/history actions. Distinguish editable drawing data, library contents, preferences and raster output. A PNG is not an editable backup.
Verify	Create groups/layers, hide/lock/reorder, undo/redo, export and reopen editable content. Check anchors and group structure as well as visible appearance.

Graphics books, boxes and easel

Move grid books, resize a reader or change page arrows

Find in UI	Graphics -> select coursebooks -> grid/spread and page navigation controls.

Code anchors	`_3-graphics/shelf/book-layout.mjs`
	Find: `export function gridPoses(`
	Grid object poses; gridView computes its camera framing. (snapshot line 25)
	
	`_3-graphics/shelf/book-layout.mjs`
	Find: `export function focusPoses(`
	Focused-book arrangement; tightView/readerFrame handle related fitting. (snapshot line 61)
	
	`_3-graphics/shelf/page-controls.mjs`
	Find: `export function pageControlPlacements(`
	Physical navigation placement; overviewPageControlPlacements handles overview. (snapshot line 18)

Change / preserve	Change object placement and fit together, accounting for aspect and header safe area. Navigation meshes should stay in scene space when the user rotates the scene. Artwork/tier generation is a separate change.
Verify	Grid and spread, focused and overview, tall/wide viewports, neighboring books, outside-click put-away and arrow hit areas after rotation.

Change board-game box rotation or focus framing

Find in UI	Graphics -> Global Conquest/Manor Mayhem -> box inspection/open/pack-up.

Code anchors	`_3-graphics/shelf/game-view-controls.mjs`
	Find: `export function installGameViewControls`
	Inspection drag/camera interaction. (snapshot line 5)
	
	`_3-graphics/shelf/graphics-preview.mjs`
	Find: `function frameGameArtwork(`
	Fits game artwork for closed/open states. (snapshot line 218)
	
	`_3-graphics/shelf/graphics-preview.mjs`
	Find: `function choose(`
	Item selection/state transition; putAway restores shelf state. (snapshot line 296)

Change / preserve	Follow the item state and authored animation frame, not only the generic camera. Board tabletop scenes are separate from arcade games. Preserve nearest-visible picking and sticky-note ownership locks.
Verify	Rotate all directions, open/close, inspect board, pack away and select another item. Compare both games and resize while focused.

Reduce book surface relief or change its material style

Find in UI	Gear -> Graphics -> page surface controls.

Code anchors	`_7-shared-scripts/core/settings-schema.js`
	Find: `'graphics.pageSurfaceType'`
	Surface type default and allowed options. (snapshot line 73)
	
	`_7-shared-scripts/core/settings-schema.js`
	Find: `'graphics.pageSurfaceStrength'`
	Relief strength, with adjacent scale and ink controls. (snapshot line 74)
	
	`_3-graphics/shelf/graphics-preview.mjs`
	Find: `function applyScene(`
	Scene-level appearance settings entry point; follow imported material owner. (snapshot line 330)

Saved setting	`graphics.pageSurfaceType`, `pageSurfaceStrength`, `pageSurfaceScale`, `pageSurfaceInk`.
Change / preserve	Try the existing material controls before replacing coursebook artwork. Trace the consuming material module before changing shader implementation; the schema defines storage, not the rendering effect itself.
Verify	Inspect text and artwork close up and at grid distance under several views; check contrast and persistence. Avoid trading a material problem for larger images.

Video players and arcade cabinet

Change player controls, seek targets or hover previews

Find in UI	On-screen video player controls across Videos, Games, Music, Graphics and embedded Start projects.

Code anchors	`_7-shared-scripts/media/controls-view.js`
	Find: `function getLayout(cw, ch)`
	Control rectangles and display proportions. (snapshot line 272)
	
	`_7-shared-scripts/media/controls-input.js`
	Find: `export function createControlsInput`
	Pointer mapping and hit inspection; seekHitPadding is an input option. (snapshot line 3)
	
	`_7-shared-scripts/media/controls-view.js`
	Find: `function drawHoverPreview(`
	Timeline preview rendering; setCameraGestureActive suppresses it during camera gestures. (snapshot line 544)

Change / preserve	Update visible geometry and effective hit bounds together. Keep capability checks for players with fewer actions. Suppress previews during pan/rotate and do not let seeking fall through to play/pause.
Verify	Use small and large players; drag seek/volume/sync, hover the timeline, pan/rotate over controls and test Back/Escape. Compare every page using the shared renderer.

Change Videos tablet focus or transport integration

Find in UI	Videos -> category preview -> focused playback; player Back/focus controls.

Code anchors	`_2-videos/tablet-focus.js`
	Find: `export function createTabletFocus`
	Tablet focus controller with snapshot, fit, projection and restoration. (snapshot line 6)
	
	`_2-videos/tablet-focus.js`
	Find: `function setFocus(`
	Changes focused state. (snapshot line 109)
	
	`_2-videos/videos-video-adapter.js`
	Find: `export function createVideosVideoAdapter`
	Page-to-shared-player adapter. (snapshot line 3)

Change / preserve	Keep full-canvas dimensions and projection offset distinct. Inspect the actual screen mesh bounds before changing fit. Shared media URLs begin in media-catalog.js but page adapters determine which source plays.
Verify	Enter/exit focus from rotated/panned views, resize, use Back/Escape and Reduced motion. Check soundtrack sync as well as the visual video.

Change arcade menu, launched game or reel audio

Find in UI	Games cabinet -> menu, five games and two video reels.
Code anchors	`_4-games/games.js` Find: `function setupMenu(` Cabinet menu setup; follow its actual IDs and launch handlers. (snapshot line 1122) `_4-games/games.js` Find: `function updateCssGameObject(` CSS3D embedded-game placement relative to the model. (snapshot line 1378) `_4-games/games.js` Find: `function setSharedVolume(` Shared player volume path for cabinet media. (snapshot line 1601)
Change / preserve	Cabinet presentation belongs here; a game's rules/content belong to its root games/ export and authoring package. Keep CSS3D and WebGL bounds aligned. Paired video/soundtrack controls must reach the actual audio owner.
Verify	Launch/exit each changed game, restore cabinet input, play both reels and test sound/seek/Back. Check mouse targets after rotating/resizing the cabinet.

Music piano, instruments and recorded tracks

Change instrument slots, group choices or the More picker

Find in UI	Music instrument group tabs, existing sound slots and More picker; two-instrument mode has separate panels.

Code anchors	`_5-music/instruments/catalog.js`
	Find: `const INSTRUMENT_CONFIG =`
	Instrument records, IDs, labels and source/backend configuration. (snapshot line 41)
	
	`_5-music/instruments/catalog.js`
	Find: `const INSTRUMENT_TABS =`
	Instrument group inventory. (snapshot line 69)
	
	`_5-music/music-piano-controls.v2.js`
	Find: `function openCategoryPicker(`
	More picker opening; updateCategoryPickerColumns handles its columns. (snapshot line 3252)

Change / preserve	The active 3D controller is music-piano-controls.v2.js. Preserve IDs, backend/source and group mapping. Do not mistake old similarly named controllers or the separate 2D recorder for the active owner.
Verify	Select every changed slot/group, sample low/mid/high notes with the picker open, switch one/two-instrument modes, reload and check saved choices.

Change instrument loading feedback or gain

Find in UI	Music piano readiness, note feedback; Music master gain and any instrument-level controls.
Code anchors	`_5-music/music-piano-controls.v2.js` Find: `async function loadInstrument(id)` Instrument-load coordination and failure handling. (snapshot line 5531) `_5-music/music-piano-controls.v2.js` Find: `function showMusicInstrumentNotice(` Music feedback presentation. (snapshot line 532) `_5-music/music-piano-controls.v2.js` Find: `function setInstrumentAutoGain(` Per-instrument gain calibration path. (snapshot line 812)
Saved setting	`music.masterGain`; instrument mix/readiness has additional controller-owned state.
Change / preserve	Keep loading/ready/error distinct. Notify on an attempted note that cannot play, not on every successful note. Soften sample/backend gain in the actual instrument route, while preserving release/sustain and global mute.
Verify	Slow/failed load, rapidly switch instruments, play repeated/overlapping notes and sustain. Listen to low and high notes; a successful network request does not prove acceptable sound.

Change song icons and their distribution

Find in UI	Gear -> Music -> Track icons: common size, horizontal distance and vertical offset.

Code anchors	`_5-music/music-track-icon-layout.mjs`
	Find: `export function layoutMusicTrackIcons`
	Fixed available area, margins and overview icon circles. (snapshot line 20)
	
	`_5-music/music-track-icon-layout.mjs`
	Find: `export function layoutSelectedMusicTrackIcons`
	Selected icon transition while keeping source indices stable. (snapshot line 4)
	
	`_5-music/music-piano-controls.v2.js`
	Find: `function renderTopPadGrid(`
	Tablet drawing and integration of computed positions. (snapshot line 4575)

Saved setting	`music.trackIconSize`, `music.trackIconSpacing`, `music.trackIconVerticalOffset`.
Change / preserve	Use existing controls for normal adjustments. The layout supports different track counts; do not assume every state is a three-icon triangle. Retain common visual/hit circles and strict title/song-name margins.
Verify	Select every song after changing spacing, switch modes, resize and inspect both labels and hit targets. Confirm hidden icons cannot activate another track.

Change recorded-track files, MIDI timing or playback volume

Find in UI	Music -> song selection; recorded playback with falling notes and video; common volume/sync controls.

Code anchors	`_5-music/music-piano-controls.v2.js`
	Find: `const TRACKS =`
	Per-track audio/MIDI/video records. (snapshot line 5773)
	
	`_5-music/music-piano-controls.v2.js`
	Find: `async function selectTrack(`
	Track selection/loading flow; loadTrackAudio chooses audio candidates. (snapshot line 8981)
	
	`_5-music/music-recorded-volume.mjs`
	Find: `export function createRecordedTrackVolumeRoute`
	Recorded-source gain connection and live settings update. (snapshot line 1)

Change / preserve	Recorded audio supplies the soundtrack; MIDI drives notes/keys. Do not fix soundtrack volume by changing only instrument master gain. Timing/seek helpers include music-track-timing.mjs and midi-seek-state.mjs; follow music-midi-workflow.md before preparing replacements.
Verify	Seek during playback and pause, including sustained notes; inspect start/middle/end sync, volume, mute and zero level. Confirm chosen screen/instrument mode persists through seeking.

Change Music video focus and panel sizing

Find in UI	Music tablet -> video playback, focus/fullscreen-style controls and Back/Escape.

Code anchors	`_5-music/music-piano-controls.v2.js`
	Find: `function startTopPadZoom(`
	Music-specific focus transition; inspect projected video bounds and restoration. (snapshot line 1365)
	
	`_5-music/music-screen-layout.mjs`
	Find: `export function musicPlayerRect(`
	Player content rectangle. (snapshot line 34)
	
	`_5-music/music-screen-layout.mjs`
	Find: `export function layoutMusicVideoZones(`
	Video zones and instrument slide layout inputs. (snapshot line 42)

Change / preserve	Fit the actual playing video area, not the whole tablet/piano or an already magnified rectangle. Keep camera/projection and drawing/hit rectangles distinct. Music does not share every Videos focus assumption.
Verify	Start from home and a user-transformed view; focus/exit, resize and press Escape. Ensure Back, seek, volume and sync remain visible and usable.

Docs content and desk

Add a document or change its source/title

Find in UI	Constructor -> Docs -> Document; Source and cover; Paper format and placement.

Code anchors	`_6-docs/library/editor.js`
	Find: `export function mountDocsEditor`
	Editor fields, type handling and Save to project/export actions. (snapshot line 11)
	
	`_6-docs/library/editor.js`
	Find: `function persistDraft(`
	Browser draft persistence. (snapshot line 121)
	
	`_6-docs/library/schema.js`
	Find: `export function validateLibrary`
	Collection validation; presentationUrl normalizes supported presentation sources. (snapshot line 21)

Change / preserve	Use documents.json as project collection data. PDF/image uploads and Save to project use the local authoring server; a browser draft is not a published update. Presentations use supported hosted Microsoft URLs/embeds; direct PPTX conversion is separate.
Verify	Save/export, reopen in another review tab and inspect the real document, not just its cover. Test external presentation permissions signed out. Back up uploaded binaries alongside the manifest.

Move desk papers or change paper dimensions

Find in UI	Docs Constructor -> Paper format and placement: format, width/height, scale, Desk X/Z and rotation.
Code anchors	`_6-docs/library/editor.js` Find: `function suggestPosition(` Placement suggestions within tabletop/lamp bounds. (snapshot line 55) `_6-docs/library/editor.js` Find: `function footprint(` Physical document footprint calculation. (snapshot line 50) `_6-docs/library/editor.js` Find: `function updateSuggestedPosition(` Updates automatic placement without blindly replacing explicit positioning. (snapshot line 102)
Change / preserve	Dimensions/Desk X/Z use metres; rotation uses degrees. Keep placement data separate from the desk model transform. Changing the desk scale without adapting its paper layout can misalign every document.
Verify	Compare portrait/landscape/widescreen formats, overlaps, lamp clearance, click targets and reload. Confirm the saved dimensions match the intended physical proportions.

Change desk drawers or the web export

Find in UI	Docs -> click drawer/hardware; accessible drawer controls. Desk material export is an offline asset task.
Code anchors	`_6-docs/desk-drawers.js` Find: `export function createDeskDrawers` Drawer collection, accessible controls and integration. (snapshot line 8) `_6-docs/desk-drawers.js` Find: `function toggle(entry)` Open/close transition; update samples it on the owned loop. (snapshot line 64) `_6-docs/desk-drawers.js` Find: `const DURATION =` Current base duration; exported parent-local offset metadata controls travel. (snapshot line 6)
Change / preserve	Preserve Drawer_TL/TR/BL/BR nodes and docsDrawerOffset when exporting _6-docs/assets/desk.glb. tools/export-docs-desk.py owns the web material/export recipe. Source blend and web GLB are distinct. Desk work remains stopped unless separately resumed.
Verify	Open/close all four drawers and reverse mid-motion; test Reduced motion, document occlusion and sticky placement input locks. Re-import the exported GLB to inspect actual textures and transforms.

Sticky notes and maintaining the reference

Change sticky-note UI, text bundles or read behavior

Find in UI	General Constructor -> Sticky notes; page note icon handles visibility/read entry points.

Code anchors	`_7-shared-scripts/sticky-notes/index.js`
	Find: `export async function mountStickyNotes`
	Shared authoring/read interface and state. (snapshot line 34)
	
	`_7-shared-scripts/sticky-notes/index.js`
	Find: `function startPlacement(`
	Placement-mode entry; open/shut/animateDialog own reading presentation. (snapshot line 418)
	
	`_7-shared-scripts/sticky-notes/data.js`
	Find: `const MAX_TEXT =`
	Content limits and validation; anchors are validated separately. (snapshot line 5)

Change / preserve	Project bundle is assets/annotations/sticky-notes.json. Browser drafts and visitor dismissal/read history are distinct. Export/import content through the actual owner; changing a local draft does not publish it.
Verify	Place/read/close, hide/show and reveal dismissed notes, reload, export/import and compare text/color/rotation/anchors. Test a fresh visitor separately from the authoring browser.

Change how a note sticks to a 3D surface

Find in UI	Sticky placement/repositioning on supported page surfaces.
Code anchors	`_7-shared-scripts/sticky-notes/scene-adapter.js` Find: `export function createSceneStickyAdapter` Shared scene adapter and raycasting. (snapshot line 119) `_7-shared-scripts/sticky-notes/scene-adapter.js` Find: `function anchorAt(` Creates a surface anchor from a hit, with clearance logic. (snapshot line 180) `_7-shared-scripts/sticky-notes/scene-adapter.js` Find: `function ownInput(` Suspends scene interaction while placing/editing. (snapshot line 242)
Change / preserve	Pages can supply specialized adapters; registerStickySceneAdapter connects them. Preserve surface IDs, triangle/barycentric or supported plane conventions. A model replacement can invalidate saved anchors and require migration.
Verify	Place near edges/curves, rotate the object, edit/reposition and cancel. Confirm placement never triggers the underlying GLB action and saved notes return to the same surface after reload.

Maintaining this lookup

Editable task records are in `docs/user-guide/08-task-to-script-reference.json`. Add a task under its page/group with a UI route, exact file/literal anchors, change boundaries and a meaningful verification check. Prefer named declarations/configuration keys over a line number alone.

Rebuild from the repository root: `python tools/build-user-guide.py docs/user-guide/08-task-to-script-reference.json`. Use the installed/bundled Python if the Windows Store alias intercepts python. ReportLab and pypdf are required; Poppler renders the result for visual review.

The builder rejects missing files and missing literal anchors. That catches some stale references; it cannot prove a function is still the active owner or that the UI route still exists. Recheck imports/call sites and the browser workflow when a feature changes. Snapshot line numbers are recalculated each build.

Cross-PDF navigation is in each footer; Chapter 9 supplies the derived alphabetical script/function index with links back to these task pages. Keep all PDFs together. Use `python tools/build-user-guide.py --all` after changing tasks so the index and destination pages are rebuilt together. Browser acceptance, more screenshots and broader field/asset coverage remain. Continue adding high-value tasks instead of cataloging every private helper.

Separate deferred work: deliberate folder migration/obsolete-file review, controller architecture and animation standardization, plus mobile/device acceptance. Coordinate file reservations before edits and request the agreed quiet window before moves. No publication or desk continuation is authorized by this documentation pass.