

BASELINE AI WORKFORCE OS

Production Verification Checklist

Mission Control supervises · Baseline OS coordinates · Hermes / OpenClaw / Claude Code execute

Document: ops-production-verification-checklist.pdf

Source: docs/operations/PRODUCTION_VERIFICATION_CHECKLIST.md

Generated: 2026-05-29

Run immediately after the first successful App Platform deployment. Every check is one command. Every check has an expected output. Don't post the launch link until every box is green.

Time budget: 15 minutes.

Set this once at the top of your terminal:

```
export MC_HOST="mission.baselineautomations.com"
export AUTH_USER="admin"
export AUTH_PASS="<the production password>"
```

✓ Tier 1 — Foundation (must pass)

T1.1 — DNS resolves to DO

```
dig +short "$MC_HOST"
# Expect: <something>.ondigitalocean.app OR the DO static IP
```

- [] Resolves to a *.ondigitalocean.app host

T1.2 — TLS cert is valid

```
echo | openssl s_client -servername "$MC_HOST" -connect "$MC_HOST:443" 2>/dev/null \
| openssl x509 -noout -subject -dates -issuer
# Expect: Let's Encrypt issuer, notAfter > 60 days from now
```

- [] Cert issued by Let's Encrypt, not expired

T1.3 — Health endpoint reports healthy

```
curl -fsS "https://$MC_HOST/api/status?action=health" | python3 -m json.tool
# Expect: "status": "healthy", "checks": [...all healthy or warning, none critical]
```

- [] status is healthy
- [] Database check is healthy
- [] Process Memory is not critical

T1.4 — HSTS + secure-cookie headers

```
curl -sI "https://$MC_HOST/" | grep -iE 'strict-transport|set-cookie|content-security'
# Expect:
#   Strict-Transport-Security: max-age=31536000; includeSubDomains
#   Content-Security-Policy: ...
```

- ☐ HSTS header present
- ☐ CSP header present

✓ Tier 2 — Auth & login

T2.1 — Login round-trip

```
rm -f /tmp/c.txt
curl -s -c /tmp/c.txt -X POST "https://$MC_HOST/api/auth/login" \
  -H 'Content-Type: application/json' \
  -d '{"username":"$AUTH_USER","password":"$AUTH_PASS"}' \
  -w '\nHTTP %{http_code}\n'
# Expect: HTTP 200, Set-Cookie with Secure; SameSite=Strict
```

- ☐ HTTP 200
- ☐ Cookie is `Secure` and `SameSite=Strict`

T2.2 — Session works

```
curl -s -b /tmp/c.txt "https://$MC_HOST/api/auth/me" | python3 -m json.tool
# Expect: "user": { "username": "admin", "role": "admin", ... }
```

- ☐ Returns an admin user

T2.3 — Bad password is rejected

```
curl -s -X POST "https://$MC_HOST/api/auth/login" \
  -H 'Content-Type: application/json' \
  -d '{"username":"$AUTH_USER","password":"wrong"}' \
  -w '\nHTTP %{http_code}\n'
# Expect: HTTP 401, generic error (no user enumeration)
```

- ☐ HTTP 401

✓ Tier 3 — Demo share + watermark

T3.1 — Mint a signed demo link as the operator

```
TOKEN=$(curl -s -b /tmp/c.txt -X POST "https://$MC_HOST/api/demo-share" \
  -H 'Content-Type: application/json' \
  -d '{"vertical":"cpa","ttlDays":1,"prospect":"Acme & Co.","hours":8,"tour":true,"watermark":true}' \
  | python3 -c "import sys,json;print(json.load(sys.stdin)['token'])")
echo "Token (first 40 chars): ${TOKEN:0:40}..."
```

- [] Token is a 3-part HMAC string (header.payload.sig)

T3.2 — Redeem URL hands out a guest cookie

```
curl -s -i "https://$MC_HOST/api/demo-share/redeem?token=$TOKEN" | head -20
# Expect: HTTP 302 → /app?demo=cpa, Set-Cookie: mc_demo_guest=...; HttpOnly; Secure; SameSite=Lax
```

- [] Redirects to /app?demo=cpa
- [] mc_demo_guest cookie set, Secure, HttpOnly

T3.3 — Invalid token redirects to expired page

```
curl -s -o /dev/null -w '%{http_code} %{redirect_url}\n' "https://$MC_HOST/api/demo-share/redeem?token=invalid.invalid.invalid"
# Expect: 302 https://.../demo/expired?reason=bad-signature
```

- [] Redirects to /demo/expired?reason=...

T3.4 — Visually verify watermark interpolation (incognito)

Open `https://<the redeem URL from T3.1>` in a clean incognito window.

- [] No /login redirect
- [] Guided Demo opens automatically
- [] Watermark reads DEMO WORKSPACE FOR ACME & CO. · BASELINE OS · NO LIVE CUSTOMER DATA

✓ Tier 4 — Memory & narratives

T4.1 — All 9 verticals load via signed link

```
for V in pm gc home-services real-estate mortgage cpa law-firm marketing-agency ai-agency; do
  RES=$(curl -s -b /tmp/c.txt -X POST "https://$MC_HOST/api/demo-share" \
    -H 'Content-Type: application/json' -d "{\"vertical\":\"$V\",\"ttlDays\":1}")
  printf "%-20s %s\n" "$V" "$(echo "$RES" | python3 -c 'import sys,json;d=json.load(sys.stdin);print("OK" if d.get("ok") else "FAIL: "+str(d))')")
done
# Expect: every line ends with OK
```

- ☐ 9/9 verticals mint successfully

T4.2 — Memory citations render on at least one vertical

Open one redeem URL in a fresh incognito session and confirm at least one AI employee card shows an Obsidian or Notion citation under "Memory:".

- ☐ At least one memory citation visible

✓ Tier 5 — Runtime contract (Hermes / OpenClaw / Claude Code)

T5.1 — Run the harness against production

```
./scripts/runtime-validate.sh \
  --base-url "https://$MC_HOST" \
  --auth-user "$AUTH_USER" --auth-pass "$AUTH_PASS" \
  --runtime hermes
# Expect, in order:
# PASS login as admin
# PASS register agent → id=<n>
# PASS heartbeat 200
# PASS task transitions ...
# PASS billing idempotent (1st=200, 2nd=200|409)
# PASS telemetry session:start / session:end
# PASS cleanup agent <n>
```

Repeat for `openclaw` and `claude`.

- ☐ Hermes: every stage PASS
- ☐ OpenClaw: every stage PASS
- ☐ Claude Code: every stage PASS

Capture the output to `docs/operations/proofs/runtime-validation-prod-<date>.txt`.

T5.2 — Runtime Validation panel mirrors reality

Browser → `https://$MC_HOST/app/runtime-validation` (logged in).

- [] At least one runtime band is `healthy` after T5.1

✓ Tier 6 — Billing (only if Stripe live)

If `STRIPE_SECRET_KEY` is `sk_test_...`, skip this tier.

T6.1 — Webhook endpoint accepts a signed event

```
# In the Stripe Dashboard → Webhooks → Your endpoint → "Send test webhook"
# Pick: checkout.session.completed
# Expect: 200 response from MC
```

- [] Stripe shows `200` for the test event

T6.2 — Real \$1 purchase posts a credit

Walk through Billing → buy the smallest pack (\$1 in production). Verify:

- [] Stripe shows `succeeded`
 - [] Mission Control Billing panel shows the credited tokens
 - [] Sending the same webhook again does NOT credit twice
-

✓ Tier 7 — Flight Deck

T7.1 — Desktop shell connects to production

Local dev machine with Rust + Node installed:

```
cd desktop && yarn install && cd .. && pnpm desktop:dev
# In the Flight Deck window:
# 1. Click "Production" mode card
# 2. Connection pill turns green ("Connected")
# 3. Click "Open Mission Control"
# 4. Webview navigates to MC, login page renders
```

- [] Connection pill turns green on Production mode
- [] Mission Control opens inside the desktop window
- [] Login flow completes inside the desktop window

T7.2 — Allowlist rejects an off-list URL

In the Custom Mission Control URL field, paste `https://attacker.example.com`, click Save & use.

- [] Pill shows URL NOT ALLOWLISTED
- [] No navigation occurs

✓ Tier 8 — Marketplace & Workforce

T8.1 — Marketplace catalog returns bundles + skills + employees

```
curl -s -b /tmp/c.txt "https://$MC_HOST/api/marketplace/catalog" \
  | python3 -c "import sys,json;d=json.load(sys.stdin);print(f'bundles={len(d.get(\"bundles\",[]))} skills=
{len(d.get(\"skills\",[]))} employees={len(d.get(\"employees\",[]))}')"
# Expect: bundles>=7 skills>=8 employees>=8
```

- [] Catalog returns ≥ 7 bundles, ≥ 8 skills, ≥ 8 employees

T8.2 — Workforce Dashboard renders

Browser → `https://$MC_HOST/app/workforce`.

- [] 4 outcome KPI cards
- [] 8 departments
- [] 10 AI employees
- [] 10 vertical templates (incl. cigar-retail)
- [] 10 skill packs

✓ Tier 9 — Onboarding readiness

T9.1 — `/docs` and `/onboarding` reachable

```
for p in /docs /onboarding /app/help /app/docs; do
  printf '%-20s %s\n' "$p" "$(curl -s -o /dev/null -w '%{http_code}' "https://$MC_HOST$p")"
done
# Expect: every path returns 200
```

- [] `/docs` returns 200
- [] `/onboarding` returns 200
- [] `/app/help` returns 200
- [] `/app/docs` returns 200

T9.2 — In-app help checklist API responds

```
curl -s -b /tmp/c.txt "https://$MC_HOST/api/help/checklist" | python3 -m json.tool | head
# Expect: a checklist with items + statuses
```

- ☐ Help checklist returns structured JSON

✓ Tier 10 — Definition of Done (the seven-checkbox gate)

Open `https://$MC_HOST/` in an incognito window — no cookies, no saved sessions — and verify the full prospect journey:

1. ☐ Land on the marketing site (Hero says "AI Workforce OS")
2. ☐ Click `Book a Demo` → reaches login or the booking surface
3. ☐ Receive a signed demo link (mint via `/app/share` and email to your own throwaway address; click the link from the inbox)
4. ☐ Watch the guided demo end-to-end without re-auth
5. ☐ See AI employees with memory citations
6. ☐ See ROI counters (hours saved, value created)
7. ☐ CTA to "Start a Pilot" leads to the pilot onboarding surface

If every box is green, post the launch link.

If any one is red, capture the failure (curl output / screenshot) and:

- Tier 1–4 red → rollback per `docs/operations/DIGITALOCEAN_EXECUTION.md § 7`
- Tier 5 red → fix the runtime config first, then retry
- Tier 6 red → re-create the Stripe webhook, retry
- Tier 7 red → rebuild Flight Deck with the production host in the allowlist
- Tier 8–9 red → file a PO issue, deploy is not launch-blocking