Impact Area Alignment

- Decarbonization
- ☑ Quality of Life
- Ecological Conservation and Restoration

Indoor Environmental Quality Credit

ACCESSIBILITY AND INCLUSION

EQc3

1–2 points

INTENT

To support the diverse needs of occupants and increase widespread usability of the building to foster an individual and collective sense of belonging.

REQUIREMENTS

Achievement Pathways	Points
Commercial Interiors	1–2
Accessibility and Inclusion Strategies	1–2

Comply with Local Accessibility Codes

Support access for those with physical disabilities by locating in a building that meets all locally applicable accessibility codes identified in the *IPp2: Human Impact Assessment*.

If there is no locally applicable code, the base building must include the following strategies:

- Accessible routes or regularly used exterior building entrances must have ramps to accommodate elevation changes.
- All doors meant for human passage from the main exterior building entrance to the project entrance have a minimum clear width of 32 inches (0.86 meters).
- Reception desks, security counters, and service counters within the project boundary all have a front-approach, wheelchair-accessible section.

AND

Include at least five (1 point) or 10 (2 points) of the following accessibility and inclusion strategies that go beyond the locally applicable accessibility code and are most relevant to the project:

Accessibility for Physical Diversity

- Provide wave-to-open or vertical hand/foot-press door operators at all regularly used building entrances.
- Design meeting spaces to accommodate mobility devices for at least 10% of occupants.

- Incorporate accessible and inclusive equipment and activities in fitness facilities. Ensure an open and accessible route to and around the equipment.
- Where inaccessible routes are provided (e.g., stairs), provide an alternate accessible route that starts and terminates at the same location.

Accessibility for Safety and Aging

- Provide nonslip flooring.
- Fix area rugs to the floor below and provide transition strips at all edges.
- Provide a visual indication or a railing at all full-height glazing, except in private residences.
- Provide audible and visual alerts for emergency alerts.
- Provide closed risers (visually and physically) in all stairs.
- Use visual contrast between walls and floors, walls and doors, and walls and casework.
- Provide visual, tactile, contrasting, or photoluminescent warnings at floor level changes.

Accessibility for Social Health

- Provide lactation rooms or pods.
- Provide at least one fully accessible, all-gender, single-user restroom OR one multiuser all-gender restroom on each floor of the building.
- Include at least one adult changing station or table in a designated, accessible restroom or family restroom, or in one men's and one women's restroom.
- Provide signage in all languages spoken by more than 5% of the local population.
- Support neurodivergent users by achieving *EQc2: Occupant Experience,* Option 1. Biophilic Environments, Path 1, Integrated Biophilic Design.

Accessibility for Navigation

- Provide wayfinding signage that clearly indicates exits, entrances, and major functions in the project.
- Provide nontext diagrams and symbols on signage.
- Provide Braille, visual and auditory cues, and/or continuous linear indicators on paths of travel.
- Use pattern and color blocking to identify key access spaces.
- Provide haptic/tactile maps for wayfinding.