


Recap-1

The Compilers' Front End

Front End of Compilers



PART I: Regex $\rightarrow$ NFA $\rightarrow$ (Min) DFA

Regular Expression (Regex)

- Regex describes a language
- Primitive regex
 - $\emptyset, \epsilon, a$
- Given two regex: r_1, r_2 , the following are regex
 - $r_1|r_2$
 - r_1r_2
 - r_1^*
 - (r_1)
- **Example:** $(a|b)^*c$

Language by Regex

- The language represented by regex are defined below
- Primitive regex
 - $L(\emptyset) = \emptyset$; $L(\epsilon) = \{\epsilon\}$; $L(a) = \{a\}$
- Given two regex: r_1, r_2 , the following are regex
 - $L(r_1|r_2) = L(r_1) \cup L(r_2)$
 - $L(r_1r_2) = L(r_1)L(r_2)$
 - $L(r_1^*) = (L(r_1))^*$
 - $L((r_1)) = L(r_1)$


Regex to NFA (DFA)

- Primitive regex

- $L(\emptyset) = \emptyset$; $L(\epsilon) = \{\epsilon\}$; $L(a) = \{a\}$


- Given two regex: r_1, r_2 , the following are regex

- $L(r_1|r_2) = L(r_1) \cup L(r_2)$
- $L(r_1r_2) = L(r_1)L(r_2)$
- $L(r_1^*) = (L(r_1))^*$
- $L((r_1)) = L(r_1)$



Example



- Build the NFA for the regex: $(a|b)^*c$
- $L((a|b)^*c) = (L(a|b))^*L(c) = (L(a) \cup L(b))^*L(c)$



From NFA to DFA



- **Subset Construction**
- A subset of NFA states is a DFA state

From NFA to DFA



DFA Minimization

- Minimizing DFA can improve the efficiency of computation



Step 1	$\{q_0, q_1, q_5\}, \{q_2, q_3, q_4\}$	Distinguish final and non-final states
Step 2	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	$\delta(q_0, a/b)$ and $\delta(q_1, a/b)$ are in the same set, but $\delta(q_5, a/b)$ not
Step 3	$\{q_0, q_1\}, \{q_5\}, \{q_2, q_3, q_4\}$	The result does not change and the algorithm completes

PART II: CFG and Parsing

Context Free Grammar (CFG)

- A context-free grammar is a tuple $G = (N, T, S, P)$
 - N : a finite set of non-terminals
 - T : a finite set of terminals, such that $N \cap T = \emptyset$
 - $S \in N$: start non-terminals
 - P : production rules in the form of $A \rightarrow a$, where $A \in N$ and $a \in (N \cup T)^*$

assignment $\rightarrow$ identifier = expression
expression $\rightarrow$ term + term
term $\rightarrow$ identifier
term $\rightarrow$ identifier * number

assignment $\rightarrow$ identifier = expression
expression $\rightarrow$ term + term
term $\rightarrow$ identifier
| identifier * number

Exercises

$S \rightarrow aSb \mid \epsilon$ is the grammar for $a^n b^n$

- Write a context-free grammar for the following languages
 - 0^*1^*

Exercises

$S \rightarrow aSb \mid \epsilon$ is the grammar for $a^n b^n$

- Write a context-free grammar for the following languages
 - $0^n 1^{2n}$

Exercises

$S \rightarrow aSb \mid \epsilon$ is the grammar for $a^n b^n$

- Write a context-free grammar for the following languages
 - $L = \{ w \mid w \text{ is a string of balanced parentheses} \}$

Exercises

$S \rightarrow aSb \mid \epsilon$ is the grammar for $a^n b^n$

- Write a context-free grammar for the following languages
 - $a^i b^j c^k$ where $i = j$ or $j = k$

Exercises

$S \rightarrow aSb \mid \epsilon$ is the grammar for $a^n b^n$

- Write a context-free grammar for the following languages
 - $a^i b^j c^k$ where $i \neq j$ or $j \neq k$

Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
- **Problem 1: A left-recursive grammar can cause infinite loops**
 - when expanding a non-terminal, we may find itself and expand it again
- **Problem 2: Backtracking may be necessary**
 - when one derivation does not work, we may try others

Eliminating Left-Recursion

- A grammar is left-recursive if it has a non-terminal A such that there is a derivation $A \Rightarrow^+ A\alpha$
- **Example:** $A \rightarrow A\alpha \mid \beta$ is left-recursive, can be transformed into

$$\begin{array}{l} A \rightarrow \beta A' \\ A' \rightarrow \alpha A' \mid \epsilon \end{array}$$

$$A \rightarrow A\alpha_1 \mid A\alpha_2 \mid \cdots \mid A\alpha_m \mid \beta_1 \mid \beta_2 \mid \cdots \mid \beta_n$$

$$\begin{array}{l} A \rightarrow \beta_1 A' \mid \beta_2 A' \mid \cdots \mid \beta_n A' \\ A' \rightarrow \alpha_1 A' \mid \alpha_2 A' \mid \cdots \mid \alpha_m A' \mid \epsilon \end{array}$$

Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
-  **Problem 1:** A **left-recursive** grammar can cause **infinite loops**
 - when expanding a non-terminal, we may find itself and expand it again
- **Problem 2:** Backtracking may be necessary
 - when one derivation does not work, we may try others

Predictive Parsing

- Predictive parsers are recursive descent parser w/o backtracking
- LL(1)
 - L: scanning input from left to right
 - L: leftmost derivation
 - 1: Using one input symbol of lookahead at each step
- LL(1) grammar (Not ambiguous! Not left-recursive!)
 - **Rich enough** to cover most programming constructs

Predictive Parsing

• Predictive Parsing

• LL(1)

• L: S

• L: E

• 1: T

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
E	$E \rightarrow TE'$			$E \rightarrow TE'$		
E'		$E' \rightarrow +TE'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
T	$T \rightarrow FT'$			$T \rightarrow FT'$		
T'		$T' \rightarrow \epsilon$	$T' \rightarrow *FT'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
F	$F \rightarrow \text{id}$			$F \rightarrow (E)$		

backtracking

• LL(1) grammar (Not ambiguous! Not left-recursive!)

- **Rich enough** to cover most programming constructs
- To build the predictive table, let's define **FIRST(α)**; **FOLLOW(α)**

First() and Follow()

- $\text{FIRST}(\alpha)$:
 - A set of terminals that α may start with
- $\text{FOLLOW}(\alpha)$:
 - A set of terminals that can appear immediately to the right of α

First()

- **Example:** $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FIRST}(a) = \{a\}$
- $\text{FIRST}(b) = \{b\}$
- $\text{FIRST}(c) = \{c\}$
- $\text{FIRST}(S) = \{c\}$
- $\text{FIRST}(A) = \{a\}$

Follow()

- FOLLOW(α):
 - A set of terminals that can appear immediately to the right of α
 - $\$ \in \text{FOLLOW}(S)$, where $\$$ is string's end marker, S the start non-terminal

Follow()

- **Example:** $S \rightarrow c A b; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) = \{b\}$
- **Example:** $S \rightarrow c A A; A \rightarrow a b \mid a$
- $\text{FOLLOW}(S) = \{\$ \}$
- $\text{FOLLOW}(A) \supseteq \text{FIRST}(A) \setminus \{\epsilon\} = \{a\}$
- $\text{FOLLOW}(A) \supseteq \text{FOLLOW}(S) = \{\$ \}$

Predictive Parsing Table

- To build a parsing table $M[A, a]$, for each $A \rightarrow \alpha$
 - $\forall a \in \text{FIRST}(\alpha): M[A, a] = A \rightarrow \alpha$
 - $\epsilon \in \text{FIRST}(\alpha) \Rightarrow \forall b \in \text{FOLLOW}(A): M[A, b] = A \rightarrow \alpha$

E	$\rightarrow$	$T E'$
E'	$\rightarrow$	$+ T E' \mid \epsilon$
T	$\rightarrow$	$F T'$
T'	$\rightarrow$	$* F T' \mid \epsilon$
F	$\rightarrow$	$(E) \mid \text{id}$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	(	)	\$
E	$E \rightarrow T E'$			$E \rightarrow T E'$		
E'		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
T	$T \rightarrow F T'$			$T \rightarrow F T'$		
T'		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
F	$F \rightarrow \text{id}$			$F \rightarrow (E)$		

- Choose the production rule as per the table; empty means error

Building a Parser in Practice

- Each non-terminal has a procedure or function for parsing
- => Recursive-Descent Parser
-  **Problem 1: A left-recursive grammar can cause infinite loops**
 - when expanding a non-terminal, we may find itself and expand it again
-  **Problem 2: Backtracking may be necessary**
 - when one derivation does not work, we may try others

PART III: IR Generation

Three-Address Code

- `do i = i + 1; while (a[i + 2] < v);`

```
L:  t1 = i + 1
    i = t1
    t2 = i + 2
    t3 = a [ t2 ]
    if t3 < v goto L
```

Symbolic Labels

```
100:  t1 = i + 1
101:  i = t1
102:  t2 = i + 2
103:  t3 = a [ t2 ]
104:  if t3 < v goto 100
```

Numeric Labels

- Implementation methods: *quadruples*, *triples*, etc.

Static Single-Assignment

- **Feature 1:** Every variable has only one definition
- **Feature 2:** Using ϕ to merge definitions from multi paths
- $\Rightarrow$ Direct def-use chains

```
if ( flag ) x = -1; else x = 1;
y = x * a;
```



```
if ( flag ) x1 = -1; else x2 = 1;
x3 =  $\phi$  (x1, x2);
y = x3 * a
```

Dominance Relations


- **A dom B**
 - if all paths from Entry to B goes through A
- **A post-dom B**
 - if all paths from B to Exit goes through A
- **Strict** (post-)dominance – A (post-)dom B but $A \neq B$
- **Immediate** dominance – A strict-dom B, but there's no C, such that A strict-dom C, C strict-dom B

Dominator Tree


- Almost linear time to build a dominator tree.

- Node: Block
- Edge: Immediate dom relation

- Why is it a tree?




Flow Graph



Dominator Tree

Dominance Frontier

- $DF(B) = \{ \dots \}$ for the block B
 - The immediate successors of the blocks dominated by B
 - Not strictly dominated by B



Dominance Frontier

- $DF(B) = \{ \dots \}$ for the block B
 - The immediate successors of the blocks dominated by B
 - Not strictly dominated by B
- $DF(\mathbb{B}) = \{ \dots \}$ for a set of blocks $\mathbb{B}$
 - $DF(\mathbb{B}) = \bigcup_{B \in \mathbb{B}} DF(B)$

Iterated Dominance Frontier

- Iterated DF of a block set $\mathbb{B}$
 - $DF_1 = DF(\mathbb{B}); \mathbb{B} = \mathbb{B} \cup DF_1$
 - $DF_2 = DF(\mathbb{B}); \mathbb{B} = \mathbb{B} \cup DF_2$
 -
 - until fixed point! (i.e., $DF_n = DF_{n-1}$)