

12 详细设计

刘钦

知识点

- 详细设计的输入输出
- 面向对象设计的思想
- 面向对象设计的过程 (P29)
- 类之间的关系 (P34)
- 信息专家模式 (P40)
- 辅助类 (P51)
- 创建者模式 (P58-P60)
- 控制器模式 (P67, P71-P72)
- 控制风格 (P77)
- 详细设计的集成测试 (P107-P110)

预习测试

- 面向对象方法下详细设计的过程是什么？
- 现在要写一个Sink dot com游戏，其中棋盘，dot com各应该由哪个类来创建？

主要内容


- 详细设计基础
- 面向对象详细设计
- 为类间协作开发集成测试用例
- 详细设计文档描述和评审

主要内容

- 详细设计基础
 - 什么是详细设计
 - 详细设计的出发点
 - 详细设计的上下文
- 面向对象详细设计
- 为类间协作开发集成测试用例
- 详细设计文档描述和评审

What is Detail Design?

- Mid-level design to a specific module
- And low-level design to objects/classes of the specific module



What is Detail Design?

- Software Architecture defined the specification of a module
- Detail Design implements the module with **detail design mechanism**
 - Mid-Level: (sub-moduled) ->OO -> Specification of classes
 - Low-Level: DS. + ALG. ->Implementation of the class
- Detail Design requires a designer to consider the aesthetic, functional, and many other aspects of the module
 - Quality attributes in Detail Design
 - **Modification , Maintenance, Performance ...**

详细设计的输入

1. 需求规格说明

功能性需求：

要在两座山之间建一座桥


非功能性需求：


使得汽车可以以 100 千米每小时的的速度在 5 分钟之内从一座山到达另一座山

2. 体系结构设计

风格：斜拉桥风格（桥墩、桥身和悬索）

原型：斜拉桥模型






从需求、体系结构设计到详细设计

思考...


- RE的工作?
 - 哪些会影响详细设计?
- 软件体系结构的工作?
 - 哪些会影响详细设计?

Where from Detail Design Starts ?

- Context
 - **Specification** of modules
 - Export/import interfaces
- **Responsibility** assignment :
 - Some responsibilities are from **RE**(SRS)
 - Typically use cases, domain models, sequence diagrams, state diagrams
 - Some others are from implementation **decisions**



输入：需求 - 分析类图




输入：需求-系统顺序图

输入： 软件体系结构： 构件之间的接口

```
// 被 Presentation 层调用的接口
public interface SalesBLSERVICE {
    public CommodityVO getCommodityByID(int id);
    public MemberVO getMember();
    public CommodityPromotionVO getCommodityPromotionByID(int
        commodityID);
    public boolean addMember(int id);
    public boolean addCommodity(int id, int quantity);
    public int getTotal(int mode);
    public int getChange(int payment);
    public void endSales();

    // 调用 DataService 层的接口
    public interface SalesDataService extends Remote {
        public void init()throws RemoteException;
        public void finish()throws RemoteException;
        public void insert(SalesPO po)throws RemoteException;
        public void delete(SalesPO po)throws RemoteException;
        public void update(SalesPO po)throws RemoteException;
        public SalesPO find(int id)throws RemoteException;
        public ArrayList<PO> finds(String field, int value)throws
RemoteException;
    }
}
```



输出： 详细设计的输出

主要内容

- 详细设计基础
- 面向对象详细设计
 - 面向对象设计的思想
 - 职责
 - 协作
 - 面向对象详细设计的过程
 - 设计模型建立
 - 通过职责建立静态设计模型
 - 通过协作建立动态设计模型
 - 设计模型重构（第13-16章）
- 为类间协作开发集成测试用例
- 详细设计文档描述和评审

面向对象设计的思想： 职责

Responsibilities

- A responsibility is an obligation to perform a **task** (an operational responsibility) or to maintain some **data** (a data responsibility).
- Operational responsibilities are usually fulfilled by operations.
- Data responsibilities are usually fulfilled by attributes.
- Class collaborations may be involved.

Responsibility-Driven Decomposition

- Responsibilities may be stated at different levels of abstraction.
- Responsibilities can be decomposed.
- High-level responsibilities can be assigned to high-level components.
- Responsibility decomposition can be the basis for decomposing components.
- Responsibilities reflect both operational and data obligations, so responsibility-driven decomposition can be different from functional decomposition.

Responsibility Heuristics

- Assigning responsibilities well helps achieve high cohesion and low coupling.
- Make sure module responsibilities do not overlap.
- Place operations and data in a module only if they help to fulfill the module's responsibilities.

Delegation

- Delegation is a tactic wherein one module (the delegator) entrusts another module (the delegate) with a responsibility.

面向对象设计的思想： 协作

What's Collaboration?

- "The objects within a program must **collaborate**; otherwise, the program would consist of only one big object that does everything."
- -- Rebecca Wirfs-Brock, et. al., 《Designing Object-Oriented Software》 , Prentice Hall, 1990

What's Collaboration?

- "Equally important [as inheritance] is the invention of societies of objects that responsibly collaborate with one another. ... These societies form what I call the **mechanisms** of a system, and thus represent **strategic architectural decisions** because they transcend individual classes."
- -- [The C++ Journal, Vol. 2, NO. 1 1992, "Interview with Grady Booch"]

What's Collaboration?

- An application can be broken down into a set of many different behaviors.
- Each such behavior is implemented by a distinct collaboration between the objects of the application.
- Every collaboration, no matter how small or large, always implements a behavior of the application

What's Collaboration?

- Imagine an object-oriented application as a network of objects connected by relationships.
- Collaborations are the patterns of **messages** that play through that network in pursuit of a particular behavior
- The collaboration is distributed across the network of objects, and so does not exist in any one place

The needs of collaboration design

- It's the application behaviors, after all, that we are trying to achieve.
- If the collaborations which implement them are not properly designed, then the application will be inaccurate or brittle

面向对象详细设计的过程

面向对象设计的过程


- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

面向对象设计的过程

- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

抽象对象的职责

- 类表达了对对象族的本质特征的抽象
- 构建的蓝图
- 职责
 - 数据职责
 - 行为职责




单一类图

面向对象设计的过程

- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

关系类型	关 系	关系短语	解 释	多 重 性	UML 表示法
Object Level	普通关联	A has a B	某个对象会长期持有另一个对象的引用。关联的两个对象彼此间没有任何强制性的约束	A: 0..* B: 0..*	
	聚合	A owns B	它暗含着一种集合所属关系。被聚合的对象还可以再被别的对象关联，所以被聚合对象是可以共享的	A: 0..1 B: 0..* 集合可以为空	
	组合	B is a part of A	它既要求包含对象对被包含对象的拥有，又要求包含对象与被包含对象的生命期相同。被包含对象还可以再被别的对象关联，所以被包含对象是可以共享的。然而绝不存在两个包含对象对同一个被包含对象的共享	A: 0..1 B: 1..1 整体存在，部分一定存在	
Class Level	继承	B is A	继承是一种非常强的关系。子类会将父类所有的接口和实现都继承回来。但是，也可以覆盖父类的实现	无	
	实现	B implements A	类实现接口，必须实现接口中的所有方法	无	

类之间的关系



类图

UML和模式应用



Craig Larman

GRASP Patterns

- General Responsibility Assignment Software Patterns
- Not 'design patterns', rather **fundamental principles** of object design
- Focus on one of the most important aspects of object design: assigning responsibilities to classes

GRASP Patterns

- Low Coupling
- High Cohesion
- Information Expert
- Creator
- Controller

Rule of thumb


- When there are alternative design choices take a closer look at the cohesion and coupling implications of the alternatives and possibly at the **future evolution** pressures on the alternatives. Choose an alternative with good **cohesion, coupling and stability**.

Information Expert

- Problem:
 - What is the most basic principle by which responsibilities are assigned in object-oriented design?
- Solution:
 - Assign a responsibility to the class that has the information necessary to fulfill the responsibility.


Information Expert : Example

- Who is responsible for knowing the grand total of a sale in a typical Point of Sale application?




Information Expert : Example

- Need all SalesLineItem instances and their subtotals.
- Only Sale knows this, so **Sale is the information expert.**
- Hence



Information Expert : Example

- But subtotals are needed for each line item(multiply quantity by price).
- By Expert, **SalesLineItem** is expert, knows quantity and has association with ProductSpecification which knows price.



Information Expert : Example

- Hence responsibilities assign to the 3 classes.

Class	Responsibility
Sale	knows sale total
SalesLineItem	knows line item subtotal
ProductSpecification	knows product price

Information Expert

- Maintain encapsulation of information
- Promotes low coupling
- Promotes highly cohesive classes

Case Study: 智能热水器

- 智能控制水温
 - 周末水温高
 - 夜晚水温低
 - 生病等特殊情况水温高
 - 度假水温低

概念模型

- Class:
 - WaterHeaterController
 - mode
 - lowTemp
 - highTemp
 - weekendDays
 - Clock
- Interface:
 - ThermostatDevice

WaterHeaterController和Clock怎么交互?

- 轮询
- 通知

怎么知道当前时间是改升温还是降温？

- Controller自己保存特殊时间并计算（比较当前时间和特殊时间）
 - Bad：多个职责。
- 由SpecialTime类保存特殊时间；Controller调用getSpecialTime（）得到特殊时间，再计算
 - Bad：数据职责与行为职责的分离
- 由SpecialTime类保存特殊时间，并提供isSpecialTime（）；Controller调用方法
 - Good：单一职责


面向对象设计的过程

- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

辅助类

- 接口类
- 记录类(数据类)
- 启动类
- 控制器类
- 实现数据类型的类
- 容器类

添加辅助类后的设计模型



面向对象设计的过程


- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

抽象对象之间的协作

- 1. 从小到大,将对象的小职责聚合形成大职责;
- 2. 从大到小,将大职责分配给各个小对象。
- 这两种方法,一般是同时运用的,共同来完成对协作的抽象。


顺序图

- 可以用顺序图表示对象之间的协作。顺序图是交互图的一种,它表达了对象之间如何通过消息的传递来完成比较大的职责。



状态图

- 除了顺序图,我们还可以通过状态图来表达软件的动态模型。UML 状态图(State Diagram)
- 主要用于描述一个复杂对象在其生存期间的动态行为,表现为一个对象所经历的状态序列,引起状态转移的事件(Event),以及因状态转移而伴随的动作(Action)。一般可以用状态机 对一个对象的生命周期建模,UML 状态图用于显示状态机(State Machine Diagram),重点 在于描述 UML 状态图的控制流。而协作是:用复杂对象的状态图中的 Event 体现出对象之 间消息的传递;用 Action 体现消息引发的对象状态的改变(行为)。



面向对象设计的过程

- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

Creator

- Problem:
 - Who is responsible for creating a new instance of some class?
- Solution:
 - Determine which class should create instances of a class based on the relationship between potential creator classes and the class to be instantiated.

Creator

- Q: Who has responsibility to create an object?
- A: By creator, assign class B responsibility of creating instance of class A if
 - B aggregates A objects
 - B contains A objects
 - B records instances of A objects
 - B closely uses A objects
 - B has the initializing data for creating A objects
 - where there is a choice, prefer B aggregates or contains A objects


表 12-4 对象创建者

优 先	场 景	创 建 地 点	创 建 时 机	备 注
高 ↑ ↓ 低	唯一属于某个整体的密不可分的一部分（组合关系）	整体对象的属性定义和构造方法	整体对象的创建	例如，销售的业务逻辑对象由销售页面对象创建
	被某一对象记录和管理（单向被关联）	关联对象的方法	业务方法的执行中对象的生命周期起始点	例如，连接池管理对象需要负责创建连接池对象
	创建所需的数据被某个对象所持有	持有数据的对象的业务方法	业务方法的执行中	也可以考虑在此持有数据对象不了解创建时机时，由别的对象创建，由它来初始化
	被某个整体包含（聚合关系）	整体对象的业务方法（非构造方法）	业务方法的执行中	如果某个对象有多个关联，优先选择聚合关联的整体对象。如果某个对象有多个聚合关联的整体对象，则考查整体对象的高内聚和低耦合来决定由谁创建
	其他			通过高内聚和低耦合来决定由谁创建

对象创建者


Creator : Example

- Who is responsible for creating SalesLineItem objects?
- Look for a class that aggregates or contains SalesLineItem objects.




Creator : Example

- Creator pattern suggests Sale.
- Collaboration diagram is



Creator

- Promotes low coupling by making instances of a class responsible for creating objects they need to reference
- By creating the objects themselves, they avoid being dependent on another class to create the object for them



Who creates the Squares/Piece/Player?

Piece的创建

- Player?
- Board?
- 两者的区别是什么?

面向对象设计的过程


- 设计模型建立
 - 通过职责建立静态设计模型
 - 抽象类的职责
 - 抽象类之间的关系
 - 添加辅助类
 - 通过协作建立动态设计模型
 - 抽象对象之间协作
 - 明确对象的创建
 - 选择合适的控制风格
- 设计模型重构
 - 根据模块化的思想进行重构，目标为高内聚、低耦合
 - 根据信息隐藏的思想进行重构，目标为隐藏职责与变更
 - 利用设计模式重构

Controller

- Problem:
 - How to assign responsibility for handling a system event?
- Solution:
 - If a program receive events from external sources other than its graphical interface, add an event class to **decouple** the event source(s) from the objects that actually handle the events.


Controller : Example

- System events in Buy Items use case
 - enterItem()
 - endSale()
 - makePayment()
- Who has the responsibility for enterItem()?



Bad design

- presentation layer coupled to problem domain



Good design


- presentation layer decoupled from problem domain

Controller pattern

- Assign the responsibility for handling a system event message to a class representing one of these choices:
 - 1. The business or overall organization (a façade controller).
 - 2. The overall "system" (a façade controller).
 - 3. An animate thing in the domain that would perform the work (a role controller).
 - 4. An artificial class (Pure Fabrication) representing the use (a use case controller).

Controller : Example


- By controller, we have 4 choices
 - the overall system **Post**
 - the overall business **Store**
 - someone in the real world who is active in the task **Cashier**
 - an artificial handler of all system **events of a use case** **BuyItemsHandler**



The choice of which one to use will be influenced by other factors such as cohesion and coupling

Controller

- Using a controller object keeps external event sources and internal event handlers independent of each other' type and behavior
- The controller objects can become highly coupled and incohesive with more responsibilities



Who is the controller of playGame operation?

Collaboration of a system behavior

- The way that the logic of a system behavior is distributed among objects(components) network.
- Dispersed—Logics of a system behavior is spread widely through the objects network
- Centralized—One extra controller record all logics of a system behavior

Centralized Collaboration Design

- Controllers
 - Objects that **make decisions** and **direct the actions** of others are controllers.
 - They always collaborate with others for two reasons:
 - to gather the information in order to make decisions
 - and to call on others to act.
 - Their focus typically is on decision making and not on performing subsequent actions.
 - Their ultimate responsibility is often passed to others that have more specific responsibilities for part of a larger task that the controller manages

Collaboration (Control) Styles

- A control style is a way that all system behavior is distributed among objects(components) network.
- **Dispersed**—All system behavior is spread widely through the objects network
- **Centralized**—A few controller record logics of all system behaviors
- **Delegated**—Decision making is distributed through the object networks with a few controllers making the main decisions





图 12-13 控制风格


控制风格

Centralized Control

- Easy to find where decisions are made
- Easy to see how decisions are made and to alter the decision-making process
- Controllers may become bloated—large, complex, and hard to understand, maintain, test, etc.
- Controller may treat other components as data repositories
 - Increases coupling
 - Destroys information hiding




Centralized Control Form




Less-Centralized Control Form


Figure 6-9. The MessageBuilder listens for events and delegates work to others.



Centralized Control



Less-Centralized Control



Delegate Control

Control Heuristics - Centralized Controller


- Avoid interaction designs where most messages originate from a single component.
- Keep components small.
- Make sure operational responsibilities are not all assigned to just a few components.
- Make sure operational responsibilities are consistent with data responsibilities.

Dispersed Control Style

- Characterized by having many components holding little data and having few responsibilities.
- It is hard to understand the flow of control.
- Components are unable to do much on their own, increasing coupling.
- It is hard to hide information.
- Cohesion is usually poor.
- Few modularity principles can be satisfied.

Control Heuristics - Dispersed Controller

- Avoid interactions that require each component to send many messages.



案例-基于委托式控制风格的业务逻辑层的设计

综合案例


- Monopoly (大富翁游戏)



课堂练习

游戏中，玩家通过界面发起行为，例如点击按钮掷骰子，掷骰子的行为进入业务逻辑后应该由哪个类负责执行？


- A.MonopolyGame
- B.Board
- C.Main方法所在类
- D.新建Controller
- E.Player



课堂练习

现在需要根据方块名称name寻找相应的Square，这个职责应该由哪个类执行？


- A.Player
- B.Board与Square
- C.Square
- D.Board
- E.MonopolyGame



课堂练习


游戏采用回合制，每个回合按顺序逐一给各玩家执行权。回合及顺序控制职责应该由哪个类执行？
()

- A.Player
- B.新建Controller
- C.MonopolyGame
- D.Main方法所在



课堂练习

- 考虑到游戏的完整性，需要提供中断保存游戏、装载游戏存盘等功能，应该由哪些类负责？
- A.为所有需要持久化数据的类都建立一个对应的io类
- B.新建controller
- C.MonopolyGame
- D.为所有需要持久化数据的类都增加一个持久化方法
- E.Main方法所在类




课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

这一个执行过程中第（1）步应该怎样分配职责？

- A.新建Controller
- B.MonopolyGame
- C.Player
- D.Die




课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

这一个执行过程中第（2）步应该怎样分配职责？

- A.MonopolyGame
- B.Player
- C.Piece
- D.Square
- E.Player与Piece




课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

这一个执行过程中第（3）步应该怎样分配职责？

- A.新建Controller
- B.MonopolyGame
- C.Player
- D.Board
- E.Square




课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

这一个执行过程中第（4）步应该怎样分配职责？

- A.Player与Piece联合
- B.Piece
- C.MonopolyGame
- D.Player



课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

假设4个步骤的职责都应该分配给了具体类

整个执行过程应该由谁来调度？

A.Player


B.Die

C.Square

D.Board

E.MonopolyGame

F.Piece




课堂练习

玩家每次执行过程是：

- (1) 计算一个随机数；
- (2) 找到玩家现在的位置；
- (3) 根据随机数和现在的位置确定新的位置方块Square；
- (4) 将玩家移动到新的Square。

画出顺序图



大作业订单模块的实现

```
@Service
public class OrderServiceImpl implements OrderService {

    @Autowired
    OrderRepository orderRepository;

    @Autowired
    SecurityUtil securityUtil;

    @Autowired
    StoreRepository storeRepository;

    @Autowired
    ProductRepository productRepository;

    @Autowired
    CouponRepository couponRepository;

    @Autowired
    CouponGroupRepository couponGroupRepository;

    @Autowired
    AlipayTools alipayTools;
```

画出下来支付功能的顺序图

@Override

```
public String pay(Integer orderId,Integer couponId) {
    User user=securityUtil.getCurrentUser();
    Order order = orderRepository.findById(orderId).orElse(null);
    if(order == null){
        throw BlueWhaleException.orderNotExists();
    }
    if(order.getStatus() != OrderStatusEnum.UNPAID){
        throw BlueWhaleException.orderStatusError();
    }
    String tradeName=String.valueOf(order.getId()).concat("-");
    if (couponId!=0){
        Coupon coupon = couponRepository.findById(couponId).get();
        CouponGroup couponGroup=couponGroupRepository.findById(coupon.getGroupId()).get();
        Product product=productRepository.findById(order.getProductId()).get();
        if (coupon.getUsed() || !coupon.getUserId().equals(user.getId()) ||
            couponGroup.getStoreId()>0 && !couponGroup.getStoreId().equals(product.getStoreId())){
            throw BlueWhaleException.couponNotAllowed();
        }
        tradeName=tradeName.concat(String.valueOf(coupon.getId()));
    }else {
        tradeName=tradeName.concat("$");
    }
    String name=productRepository.findById(order.getProductId()).get().getName();
    return alipayTools.pay(tradeName,name,calculate(orderId,couponId));
}
```

课堂练习

为了丰富的游戏体验，地图有很多种不同类型的Square，玩家移动到某个Square之后会触发不同的行为，有程序员给出了如下的伪代码实现方案：

```
Square: : landOn (Player) {
```

```
    switch (this.Type) {
```

```
        case Tax:
```

```
            收税;
```

```
            break;
```

```
        case Income:
```

```
            增加收入;
```

```
            break;
```

```
        case Pay: 罚款;
```

```
            break;
```

```
        .....
```

```
        case
```

```
        default: 没有行为;
```

```
    }
```

```
}
```

你认为该方案?

A.没有问题

B.有问题，应该建立抽象的Controller解决switch case语句

C.有问题，应该建立行为继承树，使用多态代替switch case语句


D.有问题，应该使用工厂模式处理switch case语句

Outline

- 详细设计基础
- 面向对象详细设计
- 为类间协作开发集成测试用例
- 详细设计文档描述和评审

详细设计的集成测试

- 类间协作的集成测试
 - 重点针对复杂逻辑（交互比较多）
 - 自顶向下或者自底向上的集成
- Mock Object
 - 不是stub
- 测试用例



powered by astah*

类间协作的集成测试

```
public class MockCommodity extends Commodity{  
    double price;  
    public MockCommodity ( double p){  
        price=p;  
    }  
    public getPrice ( ){  
        return price;  
    }  
}
```

MockObject

类似于Stub，但是更简单

```
public class TotalIntegrationTester {  
    @Test  
    public void testTotal () {  
        MockCommodity commodity1 = new MockCommodity (50);  
        MockCommodity commodity2 = new MockCommodity (40);  
        SalesLineItem salesLineItem1 =  
            new SalesLineItem (commodity1, 2);  
        SalesLineItem salesLineItem2  
            = new SalesLineItem (commodity2, 3);  
  
        Sales sale=new Sales();  
        sale.addSalesLineItem(salesLineItem1);  
        sale.addSalesLineItem(salesLineItem2);  
  
        assertEquals (220, sale.total () );  
    }  
}
```

集成测试代码

主要内容

- 详细设计基础
- 面向对象详细设计
- 为类间协作开发集成测试用例
- 结构化详细设计
- 详细设计文档描述和评审

1引言

1.1编制目的

表明文档的读者，以及文档主题。

1.2词汇表

文档中用到的缩写、专业词汇等。

1.3参考资料

相关参考文献。

2 中层设计

2.1 xxx模块的静态结构和动态行为

2.1.1 xxx模块局部模块的职责

通过逻辑视角、结构视角、依赖视角描述其相应的职责。

2.1.2 xxx模块局部模块的接口规范

各子层的供接口和需接口的规范。

2.1.3 xxx模块的行为

用例执行时，对象之间的消息传递和状态的转移。通常用顺序图、通讯图、状态表示。

2.1.4 xxx模块的实现注解

具体实现时注意点。比如构造方法、枚举、常量、静态方法的说明

2.1.5 业务逻辑模块的设计原理

详细设计验证

- 评审
- 度量
 - 模块化度量
- 测试
 - 协作测试

一、基本

- 1) 设计方案自身是否一致?
- 2) 设计制品的详细程度是否合适?
- 3) 设计是否包含了各个视角?
- 4) 多个视角之间是否一致?

二、设计考量

- 5) 设计是否采用了标准技术,而不是晦涩难懂的技术?
- 6) 设计是否强调简洁性重于灵活性?
- 7) 设计是否尽可能简单?
- 8) 设计是否精干? 每个部分都是必需的?
- 9) 如果维护时需求发生变更,需要修改的地方是否支持修改? 是否支持未来的扩展?
- 10) 设计是否支持重用?
- 11) 设计是否具有低复杂性?
- 12) 设计是否是可理解的? 是否没有超越普通人的智力范围?

三、过程考量

- 13) 设计是否覆盖了所有的需求?
- 14) 设计中设计的功能对应需求的哪些部分?
- 15) 是否足够遵循软件体系结构设计的决策?
- 16) 设计的详细程度对后继开发人员是否足够?

详细设计的评审

Q&A