

QML project

Ludovico Venturi

2024-02-08

# Table of contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Barren Plateaus . . . . .	2
1.1.1	Barren Plateaus on QCNs . . . . .	2
	<b>References</b>	<b>3</b>

# Chapter 1

## Introduction

### 1.1 Barren Plateaus

- Random circuits are often proposed as initial guesses for exploring the space of quantum states
- The exponential dimension of Hilbert space and the gradient estimation complexity ... on more than a few qubits
- For a wide class of PQCs, the probability that the gradient along any reasonable direction is non-zero to some fixed precision is exponentially small as a function of the number of qubits<sup>1</sup>

#### 1.1.1 Barren Plateaus on QCNNs

- The variance of the gradient vanishes no faster than polynomially<sup>2</sup> so QCNNs do not exhibit *barren plateaus*.
- It is guaranteed that randomly initialized QCNNs are trainable, unlike many other QNN architectures.

# References

1. McClean, J. R., Boixo, S., Smelyanskiy, V. N., Babbush, R. & Neven, H. [Barren plateaus in quantum neural network training landscapes](#). *Nat. Commun.* **9**, 1–6 (2018).
2. Pesah, A. *et al.* [Absence of Barren Plateaus in Quantum Convolutional Neural Networks](#). *Phys. Rev. X* **11**, 041011 (2021).