

# Investor KPI Assistant — Runbook

Anonymous run instructions. Keep three processes open. Closing a terminal stops that process and, on Windows, deactivates the virtualenv. Installed packages remain on disk.

## Prerequisites

| Tool                          | Why                                    |
|-------------------------------|----------------------------------------|
| Git                           | Obtain the source                      |
| Python 3.12+                  | Backend, MCP, seed, tests              |
| Node.js 18+ and npm           | React / Vite UI                        |
| Docker Desktop or Postgres 16 | kpi/kpi/kpi on port 5432               |
| OpenAI API key                | Live chat only; not required for tests |

## One-time setup (PowerShell, repo root)

```
docker compose up -d postgres
python -m venv backend\.venv
backend\.venv\Scripts\Activate.ps1
pip install -r backend\requirements.txt
copy .env.example .env
# set OPENAI_API_KEY in .env, then:
cd backend
python -m app.seed
```

If scripts are disabled: Set-ExecutionPolicy -Scope Process -ExecutionPolicy Bypass. Seed success: Imported 2000 KPI records. Wrong command: python -m seed. Correct: python -m app.seed from backend\.

## Every session (three terminals)

```
backend\.venv\Scripts\Activate.ps1
cd backend && python -m app.mcp_server --transport http
cd backend && python -m app.main
cd frontend && npm run dev
Browser: http://127.0.0.1:5173/
```

## macOS / Linux

```
python3 -m venv backend/.venv
source backend/.venv/bin/activate
pip install -r backend/requirements.txt
cp .env.example .env && cd backend && python -m app.seed
```

## Troubleshooting

| Symptom                    | Fix                               |
|----------------------------|-----------------------------------|
| No module named seed       | cd backend; python -m app.seed    |
| No module named app        | Current directory must be backend |
| No module named sqlalchemy | Activate backend\.venv            |

|                              |                                         |
|------------------------------|-----------------------------------------|
| Postgres connection refused  | docker compose up -d postgres           |
| ERR_CONNECTION_REFUSED :5173 | Start npm run dev; use 127.0.0.1        |
| LLM key missing              | Set OPENAI_API_KEY and restart app.main |
| MCP unavailable              | Start app.mcp_server on :8001           |

## Tests and demo client

```
cd backend
python -m pytest -q
python -m app.demo_mcp_client
python -m app.demo_mcp_client --in-process
```

## External MCP

HTTP URL: <http://127.0.0.1:8001/mcp>. stdio command: the venv python with args `-m app.mcp_server --transport stdio` and `cwd=backend`. Optional local speed: `MCP_IN_PROCESS=true` on the chat API only.

## Latency

Tool calls are milliseconds. Sequential OpenAI rounds are seconds. Ask with ticker + KPI to skip catalog lookup. Keep `OPENAI_MODEL=gpt-4o-mini`.