

# Package ‘SigBridgeR’

January 20, 2026

**Title** Integrative Toolkit for Linking Phenotypes to Cell Subpopulations via scRNA-seq and Bulk Data

**Version** 3.2.0

**Description** Identifies phenotype-associated cell subpopulations by integrating phenotypic data (e.g., survival, drug sensitivity), bulk gene expression, and single-cell RNA-seq (scRNA-seq) profiles. It employs multiple algorithms to reliably connect cellular features with clinical or functional phenotypes, offering a unified pipeline for multi-modal analysis that uncovers biologically and clinically relevant cell states in heterogeneous datasets.

**License** GPL (>= 3)

**Encoding** UTF-8

**URL** <https://github.com/WangLabCSU/SigBridgeR>

**BugReports** <https://github.com/WangLabCSU/SigBridgeR/issues>

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.3

**Imports** chk,  
cli,  
data.table,  
DEGAS (>= 1.0.0),  
dplyr,  
edgeR,  
IDConverter (>= 0.3.5),  
LPSGL (>= 0.0.0.9000),  
Matrix,  
methods,  
PIPET (>= 0.1.2),  
processx,  
purrr,  
rlang,  
scAB (>= 1.0.1),  
Scissor (>= 2.0.0),  
scPAS (>= 0.2.0),  
ScPP (>= 0.0.0.9000),  
Seurat (>= 5.0.0),  
SeuratObject (>= 5.0.0),  
SigBridgeRUtils (>= 0.1.0)

**Depends** R (>= 4.1.0)

**Remotes** bioc::edgeR,  
github::Exceret/ALRA,  
github::Exceret/DEGAS,  
github::Exceret/LPSGL,  
github::Exceret/PIPET,  
github::Exceret/scAB,  
github::Exceret/Scissor,  
github::Exceret/scPAS,  
github::Exceret/ScPP,  
github::WangLabCSU/SigBridgeRUtils,  
github::ShixiangWang/IDConverter,  
github::yonicd/tidycheckUsage

**Suggests** ALRA,  
anndata,  
carrier,  
cheapr,  
codetools,  
furrr,  
future,  
future.mirai,  
ggforce,  
ggplot2,  
ggupset,  
ggVennDiagram,  
glue,  
here,  
KernSmooth,  
knitr,  
lintr,  
matrixStats,  
matrixTests,  
org.Hs.eg.db,  
patchwork,  
preprocessCore,  
randomcoloR,  
RColorBrewer,  
reticulate,  
rmarkdown,  
scCustomize,  
sparseMatrixStats,  
testthat (>= 3.0.0),  
tibble,  
tictoc,  
tidycheckUsage,  
tidyr,  
WGCNA,  
zeallot

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**Config/testthat/parallel** true

## Contents

|                                |           |
|--------------------------------|-----------|
| AddMetaFeature . . . . .       | 3         |
| AddMisc . . . . .              | 4         |
| aggregate-dups . . . . .       | 5         |
| BulkPreProcess . . . . .       | 7         |
| DoDEGAS . . . . .              | 10        |
| DoLP_SGL . . . . .             | 13        |
| DoPIPET . . . . .              | 15        |
| DoscAB . . . . .               | 17        |
| DoScissor . . . . .            | 18        |
| DoscPAS . . . . .              | 21        |
| DoscPP . . . . .               | 23        |
| FindRobustElbow . . . . .      | 25        |
| getFuncOption . . . . .        | 26        |
| ListPyEnv . . . . .            | 27        |
| LoadRefData . . . . .          | 28        |
| MergeResult . . . . .          | 29        |
| Pattern2Colname . . . . .      | 30        |
| QCFilter . . . . .             | 31        |
| QCPatternDetect . . . . .      | 32        |
| RegisterScreenMethod . . . . . | 33        |
| SCPreProcess . . . . .         | 35        |
| Screen . . . . .               | 38        |
| ScreenFractionPlot . . . . .   | 42        |
| ScreenStrategy . . . . .       | 44        |
| ScreenUpset . . . . .          | 45        |
| setFuncOption . . . . .        | 47        |
| SetupPyEnv . . . . .           | 48        |
| SymbolConvert . . . . .        | 49        |
| ValidateScreenFunc . . . . .   | 50        |
| <b>Index</b>                   | <b>51</b> |

---

|                |                                                                         |
|----------------|-------------------------------------------------------------------------|
| AddMetaFeature | <i>Add Gene-Level Metadata to Seurat Object (Vectorized, ...-based)</i> |
|----------------|-------------------------------------------------------------------------|

---

## Description

Add multiple feature-level metadata (vectors or 2D tables) to a Seurat object. Handles vectors (length-checked), matrices, data.frames, data.tables, etc. Columns/variables with duplicated names are suffixed (e.g., "type\_1"). Gene alignment is auto-detected: rows or cols must match nrow(seurat\_obj).

**Usage**

```
AddMetaFeature(seurat_obj, ..., assay = "RNA")
```

**Arguments**

|            |                                                                                                                                                                                                                                             |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| seurat_obj | A Seurat object.                                                                                                                                                                                                                            |
| ...        | One or more metadata inputs: <ul style="list-style-type: none"> <li>• Named/unnamed vectors (length = ngenes)</li> <li>• 2D objects (matrix, data.frame, data.table, etc.) where one dimension (rows or cols) has size = ngenes.</li> </ul> |
| assay      | Assay name (default: "RNA", fallback to first).                                                                                                                                                                                             |

**Value**

Modified seurat\_obj (invisibly).

---

|         |                                                       |
|---------|-------------------------------------------------------|
| AddMisc | <i>Safely Add Miscellaneous Data to Seurat Object</i> |
|---------|-------------------------------------------------------|

---

**Description**

Adds arbitrary data to the @misc slot of a Seurat object with automatic key conflict resolution. If the key already exists, automatically appends a numeric suffix to ensure unique key naming (e.g., "mykey\_1", "mykey\_2").

**Usage**

```
AddMisc(seurat_obj, ..., cover = TRUE)
```

**Arguments**

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| seurat_obj | A Seurat object to modify                                                 |
| ...        | key-value pairs to add to the @misc slot.                                 |
| cover      | Logical indicating whether to overwrite existing data. If (default TRUE). |

**Value**

The modified Seurat object with added @misc data. The original object structure is preserved with no other modifications.

**Key Generation Rules**

1. If key doesn't exist: uses as-is
2. If key exists: appends the next available number (e.g., "key\_1", "key\_2")
3. If numbered keys exist (e.g., "key\_2"): increments the highest number

## Examples

```
## Not run:
# Basic usage
seurat_obj <- AddMisc(seurat_obj, "QC_stats" = qc_df)

# Auto-incrementing example
seurat_obj <- AddMisc(seurat_obj, markers = markers1)
seurat_obj <- AddMisc(seurat_obj, markers = markers2, cover=FALSE)
# Stores as "markers" and "markers_1"

## End(Not run)
```

---

 aggregate-dups

---

*Aggregate Rows or Columns with Duplicate Names*


---

## Description

These functions collapse duplicated row names (e.g., gene symbols) or column names (e.g., sample IDs) in matrix-like objects by aggregating values using configurable methods. They support:

**Rows** [AggregateDupRows](#): merges rows sharing the same row name.

**Columns** [AggregateDupCols](#): merges columns sharing the same column name.

**Both** [AggregateDups](#): convenience wrapper applying row-then-column aggregation.

Designed for expression matrices, count tables, or any numeric data where feature/sample duplication occurs. Handles `matrix`, `data.frame`, and S4 `Matrix` classes (e.g. `dgCMatrix`) robustly.

Convenience wrapper that first aggregates duplicated rows, then duplicated columns. Useful for cleaning matrices where both feature and sample duplication may occur.

## Usage

```
AggregateDupRows(
  x,
  method = c("max", "sum", "mean", "median", "first"),
  verbose = TRUE,
  ...
)

AggregateDupCols(
  x,
  method = c("max", "sum", "mean", "median", "first"),
  verbose = TRUE,
  ...
)

AggregateDups(
```

```

x,
method = c("max", "sum", "mean", "median", "first"),
row_method = NULL,
col_method = NULL,
verbose = TRUE,
...
)

```

### Arguments

|                         |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| <code>x</code>          | A numeric matrix-like object (see Details).                       |
| <code>method</code>     | Character scalar. Aggregation method (see Methods below).         |
| <code>verbose</code>    | Whether to print messages                                         |
| <code>...</code>        | No usage                                                          |
| <code>row_method</code> | Aggregation method for rows. Defaults to <code>method</code> .    |
| <code>col_method</code> | Aggregation method for columns. Defaults to <code>method</code> . |

### Value

An aggregated object of the same effective type as `x`, with unique row/column names.

### Methods

Supported methods (applied column-wise for rows, row-wise for columns):

"max" Maximum value per group (default).  
 "sum" Sum of values per group.  
 "mean" Arithmetic mean (uses `na.rm = TRUE`).  
 "median" Median value.  
 "first" First occurrence in original order.

### Input Types and Return Types

| Input class             | Output class (unless noted)                                        |
|-------------------------|--------------------------------------------------------------------|
| <code>matrix</code>     | <code>matrix</code>                                                |
| <code>data.frame</code> | <code>data.frame</code>                                            |
| S4 Matrix               | <code>matrix</code> (dense) — S4 attributes dropped for generality |

Row/column order in output follows *first occurrence* of each unique name in `rownames(x)` / `colnames(x)`.

## Examples

```
# Full deduplication in one step
mat <- matrix(1:16, nrow = 4,
              dimnames = list(c("TP53", "TP53", "BRCA1", "ACTB"),
                             c("S1", "S1", "S2", "S3")))
AggregateDups(mat, method = "sum")
#>      S1 S2 S3
#> TP53   5  7  9
#> BRCA1   3  7 11
#> ACTB   4  8 12
```

---

BulkPreProcess

*Bulk RNA-seq Data Preprocessing and Quality Control Function*


---

## Description

This function performs comprehensive preprocessing and quality control analysis for bulk RNA-seq data, including data validation, filtering, batch effect detection, principal component analysis, and visualization.

## Usage

```
BulkPreProcess(
  data,
  sample_info = NULL,
  gene_symbol_conversion = FALSE,
  check = TRUE,
  min_count_threshold = 10L,
  min_gene_expressed = 3L,
  min_total_reads = 1000000L,
  min_genes_detected = 10000L,
  min_correlation = 0.8,
  n_top_genes = 500L,
  show_plot_results = TRUE,
  ...
)
```

## Arguments

|                          |                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>        | Expression matrix with genes as rows and samples as columns, or a list containing <code>count_matrix</code> and <code>sample_info</code>                                                                                                                                                                                                                                                                   |
| <code>sample_info</code> | Sample information data frame (optional), ignored if <code>data</code> is a list. A qualified <code>sample_info</code> should contain both <code>sample</code> and <code>condition</code> columns (case-sensitive), and there are no specific requirements for the data type stored in the <code>condition</code> column. <code>batch</code> column is optional, which is used for batch effect detection. |

|                        |                                                                                                                                                                                                                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| gene_symbol_conversion | Whether to convert Ensembles version IDs and TCGA version IDs to genes with IDConverter, default: FALSE                                                                                                                                                                                                                       |
| check                  | Whether to perform detailed quality checks, default: TRUE                                                                                                                                                                                                                                                                     |
| min_count_threshold    | Minimum count threshold for gene filtering. Only values greater than this threshold are considered to represent valid gene expression. Default: 10L                                                                                                                                                                           |
| min_gene_expressed     | Minimum number of samples a gene must be expressed in, default: 3L                                                                                                                                                                                                                                                            |
| min_total_reads        | Minimum total reads per sample, default: 1e6L                                                                                                                                                                                                                                                                                 |
| min_genes_detected     | Minimum number of genes detected per sample, default: 10000                                                                                                                                                                                                                                                                   |
| min_correlation        | Minimum correlation threshold between samples, default: 0.8                                                                                                                                                                                                                                                                   |
| n_top_genes            | Number of top variable genes for PCA analysis, default: 500                                                                                                                                                                                                                                                                   |
| show_plot_results      | Whether to generate visualization plots, default: TRUE                                                                                                                                                                                                                                                                        |
| ...                    | Additional arguments. Currently supports: <ul style="list-style-type: none"> <li>• verbose: Logical indicating whether to print progress messages. Defaults to TRUE.</li> <li>• seed: For reproducibility, default is 123L</li> <li>• method: Method for duplicates aggregation, see <a href="#">AggregateDups</a></li> </ul> |

## Details

The function performs the following operations:

1. Data validation and format conversion
2. Basic statistics calculation (missing values, read depth, gene detection)
3. Optional detailed quality checks including:
  - Sample correlation analysis
  - Principal Component Analysis (PCA)
  - Outlier detection using Mahalanobis distance
  - Batch effect detection using ANOVA
4. Data filtering based on count thresholds and quality metrics
5. Optional gene symbol conversion
6. Visualization generation (PCA plots)

## Value

Filtered count matrix



## Quality Metrics

The function calculates and reports several quality metrics:

**Data Integrity** Number of missing values

**Gene Count** Total number of genes after filtering

**Sample Read Depth** Total reads per sample

**Gene Detection Rate** Number of genes detected per sample

**Sample Correlation** Pearson correlation between samples

**PCA Variance** Variance explained by first two principal components

**Batch Effects** Proportion of genes significantly affected by batch

## Sample Information Format

The sample\_info data frame should contain:

**sample** Character vector of unique sample identifiers

**condition** Character vector of experimental conditions

**batch** Optional character vector of batch identifiers

## Filtering Criteria

Genes are retained if:

- They have counts  $\geq$  min\_count\_threshold in  $\geq$  min\_gene\_expressed samples

Samples are retained if:

- Total reads  $\geq$  min\_total\_reads
- Detected genes  $\geq$  min\_genes\_detected
- Mean correlation  $\geq$  min\_correlation (if check=TRUE)

## See Also

[cpm](#) for counts per million calculation, [prcomp](#) for PCA analysis, [cor](#) for correlation analysis, [SymbolConvert](#) for gene symbol conversion

DoDEGAS

*Run DEGAS Analysis for Single-Cell and Bulk RNA-seq Data Integration***Description**

This function performs DEGAS to integrate single-cell and bulk RNA-seq data, identifying phenotype-associated cells using a bootstrap aggregated multi-task learning approach.

**Usage**

```
DoDEGAS(
  select_fraction = 0.05,
  min_thresh = 0.4,
  matched_bulk,
  sc_data,
  phenotype = NULL,
  sc_data.pheno_colname = NULL,
  label_type = "DEGAS",
  phenotype_class = c("binary", "continuous", "survival"),
  tmp_dir = "tmp",
  env_params = list(),
  degas_params = list(),
  normality_test_method = c("jarque-bera", "d'agostino", "kolmogorov-smirnov"),
  ...
)
```

**Arguments**

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>select_fraction</code>       | The top percentage of selected cells will be considered as Positive cells, without considering how much larger the possible correlation coefficient of the observation group is compared to that of the control group. Only used when <code>phenotype_class</code> is "binary" or "survival". (default: 0.05)                                                                                                          |
| <code>min_thresh</code>            | DEGAS will calculate the possible correlation coefficients for each cell related to the phenotype. When the coefficient of the observation group is at least <code>min_thresh</code> larger than that of the control group, it can be considered related to the phenotype and will be marked as Positive. The priority of <code>min_thresh</code> is higher than that of <code>select_fraction</code> . (default: 0.4) |
| <code>matched_bulk</code>          | Bulk RNA-seq data as matrix or data.frame (rows=genes, columns=samples)                                                                                                                                                                                                                                                                                                                                                |
| <code>sc_data</code>               | Single-cell data as Seurat object containing RNA assay                                                                                                                                                                                                                                                                                                                                                                 |
| <code>phenotype</code>             | Bulk-level phenotype data. For classification: binary matrix with one-hot encoding. For survival: matrix with two columns (time and event status). Can be NULL, matrix, data.frame, or vector.                                                                                                                                                                                                                         |
| <code>sc_data.pheno_colname</code> | Column name for single-cell phenotype in metadata (if available), default: NULL                                                                                                                                                                                                                                                                                                                                        |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label_type            | Label type for DEGAS results (default: "DEGAS")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| phenotype_class       | Type of phenotype: "binary" (classification), "continuous", or "survival"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| tmp_dir               | Temporary directory for intermediate files (default: "tmp")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| env_params            | List of environment parameters for Python setup including: <ul style="list-style-type: none"> <li>• env.name: environment name (default: "r-reticulate-degas")</li> <li>• env.type: environment type "conda", "environment", or "venv" (default: "environment")</li> <li>• env.method: environment setup method "system", "conda" (default: "system")</li> <li>• env.file: path to environment file (default: system.file("conda/DEGAS_environment.yml", package = "SigBridgeR"))</li> <li>• env.python_version: Python version (default: "3.9.15")</li> <li>• env.packages: named vector of Python packages and versions (default: c("tensorflow" = "2.4.1", "protobuf" = "3.20", "numpy" = "any"))</li> <li>• env.recreate: whether to recreate environment (default: FALSE)</li> <li>• env.use_conda_forge: whether to use conda-forge channel (conda only, default: TRUE)</li> <li>• env.verbose: verbose output (default: FALSE)</li> </ul>                                                                                                                                                                                                                     |
| degas_params          | List of DEGAS algorithm parameters including: <ul style="list-style-type: none"> <li>• DEGAS.model_type: model type ("BlankClass", "ClassBlank", "ClassClass", "ClassCox", "BlankCox")</li> <li>• DEGAS.architecture: "Standard" (feed forward) or "DenseNet" (dense net), default: "DenseNet"</li> <li>• DEGAS.ff_depth: number of layers in model (<math>\geq 1</math>, default: 3)</li> <li>• DEGAS.pyloc: path to Python executable (default: NULL, automatic detection)</li> <li>• DEGAS.bag_depth: bootstrap aggregation depth (<math>\geq 1</math>, default: 5)</li> <li>• DEGAS.train_steps: training steps (default: 2000)</li> <li>• DEGAS.scbatch_sz: single-cell batch size (default: 200)</li> <li>• DEGAS.patbatch_sz: patient batch size (default: 50)</li> <li>• DEGAS.hidden_feats: hidden features (default: 50)</li> <li>• DEGAS.do_prc: dropout percentage (default: 0.5)</li> <li>• DEGAS.lambda1: regularization parameter 1 (default: 3.0)</li> <li>• DEGAS.lambda2: regularization parameter 2 (default: 3.0)</li> <li>• DEGAS.lambda3: regularization parameter 3 (default: 3.0)</li> <li>• DEGAS.seed: random seed (default: 2)</li> </ul> |
| normality_test_method | Method for normality testing: "jarque-bera", "d'agostino", or "kolmogorov-smirnov"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| ...                   | Additional arguments. Currently supports: <ul style="list-style-type: none"> <li>• verbose: Logical indicating whether to print progress messages. Defaults to TRUE.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

## Details

The function performs the following steps:

1. Validates input data and parameters
2. Sets up Python environment with required dependencies
3. Trains bootstrap aggregated DEGAS model using `runCCMTLBag`
4. Generates cell-level predictions using `predClassBag`
5. Applies statistical testing to identify phenotype-associated cells
6. Labels cells as "Positive" or "Other" based on selection criteria

Model type is automatically determined:

- BlankClass: only bulk phenotype specified (`scLab = NULL`)
- ClassBlank: only single-cell phenotype specified (`patLab = NULL`)
- ClassClass: both single-cell and bulk phenotypes specified
- ClassCox: single-cell phenotype + bulk survival data
- BlankCox: only bulk survival data specified

## Value

A list containing:

- `scRNA_data`: Seurat object with DEGAS labels added to metadata
- `model`: The model trained using the input data, and it can be used for cell classification prediction.
- `DEGAS_prediction`: Data table with DEGAS predictions containing:
  - Predicted label probabilities for each cell
  - Cell labels ("Positive"/"Other") based on selection criteria
  - Difference scores for binary phenotypes
  - Cell identifiers

## References

Johnson TS, Yu CY, Huang Z, Xu S, Wang T, Dong C, et al. Diagnostic Evidence GAuge of Single cells (DEGAS): a flexible deep transfer learning framework for prioritizing cells in relation to disease. *Genome Med.* 2022 Feb 1;14(1):11.

## See Also

Other screen\_method: [DoLP\\_SGL\(\)](#), [DoPIPET\(\)](#), [DoScissor\(\)](#), [DoscAB\(\)](#), [DoscPAS\(\)](#), [DoscPP\(\)](#)

Other DEGAS: [DEGASEnvSet\(\)](#), [DEGASFindPy\(\)](#), [DEGASModelDetect\(\)](#), [DEGASParamSet\(\)](#)

**Examples**

```
## Not run:
# Binary classification example
result <- DoDEGAS(
  select_fraction = 0.05, # `select_fraction` only used in binary and survival phenotyping
  matched_bulk = bulk_matrix,
  sc_data = seurat_obj,
  phenotype = bulk_phenotype,
  phenotype_class = "binary"
)

# Survival analysis example
result <- DoDEGAS(
  select_fraction = 0.05, # `select_fraction` only used in binary and survival phenotyping
  matched_bulk = bulk_matrix,
  sc_data = seurat_obj,
  phenotype = survival_data,
  phenotype_class = "survival"
)

## End(Not run)
```

DoLP\_SGL

*Perform LP-SGL Screening Analysis***Description**

Identifies phenotype-associated cell subpopulations using Lasso-Penalized Sparse Group Lasso (LP-SGL) with Leiden community detection. This method integrates bulk and single-cell RNA-seq data to identify cell subpopulations associated with phenotypic outcomes.

**Usage**

```
DoLP_SGL(
  matched_bulk,
  sc_data,
  phenotype,
  label_type = "LP_SGL",
  family = c("logit", "cox", "linear"),
  resolution = 0.6,
  alpha = 0.5,
  nfold = 5,
  dge_analysis = list(run = FALSE, logFC_threshold = 1, pval_threshold = 0.05),
  ...
)
```

**Arguments**

|                           |                                                                                                                                                                                                                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>matched_bulk</code> | Bulk expression matrix (features $\times$ samples)                                                                                                                                                                                                                                                                              |
| <code>sc_data</code>      | Single-cell RNA-seq data (Seurat object)                                                                                                                                                                                                                                                                                        |
| <code>phenotype</code>    | Binary phenotype vector for bulk samples                                                                                                                                                                                                                                                                                        |
| <code>label_type</code>   | Character specifying phenotype label type (default: "LP_SGL")                                                                                                                                                                                                                                                                   |
| <code>family</code>       | Type of regression model: "logit" (logistic), "cox" (Cox), or "linear" (linear regression)                                                                                                                                                                                                                                      |
| <code>resolution</code>   | Resolution parameter for Leiden clustering (default: 0.6)                                                                                                                                                                                                                                                                       |
| <code>alpha</code>        | Alpha parameter for SGL balancing L1 and L2 penalties (default: 0.5)                                                                                                                                                                                                                                                            |
| <code>nfold</code>        | Number of folds for cross-validation (default: 5)                                                                                                                                                                                                                                                                               |
| <code>dge_analysis</code> | List controlling differential expression analysis: <ul style="list-style-type: none"> <li>• <code>run</code>: Whether to run DEG analysis (default: FALSE)</li> <li>• <code>logFC_threshold</code>: Log fold change threshold (default: 1)</li> <li>• <code>pval_threshold</code>: P-value threshold (default: 0.05)</li> </ul> |
| <code>...</code>          | Additional arguments passed to preprocessing functions, e.g.: <ul style="list-style-type: none"> <li>• <code>verbose</code>: Whether to print progress messages (default: TRUE)</li> <li>• <code>seed</code>: Random seed for reproducibility (default: 123L)</li> </ul>                                                        |

**Value**

A list containing:

|                         |                                                               |
|-------------------------|---------------------------------------------------------------|
| <code>scRNA_data</code> | Seurat object with LP-SGL results integrated                  |
| <code>sgl_fit</code>    | Fitted SGL model object                                       |
| <code>cvfit</code>      | Cross-validation results                                      |
| <code>dge_res</code>    | Differential expression results if requested (NULL otherwise) |

**References**

Li J, Zhang H, Mu B, Zuo H, Zhou K. Identifying phenotype-associated subpopulations through LP\_SGL. *Briefings in Bioinformatics*. 2023 Nov 22;25(1):bbad424.

**See Also**

Other screen\_method: [DoDEGAS\(\)](#), [DoPIPET\(\)](#), [DoScissor\(\)](#), [DoscAB\(\)](#), [DoscPAS\(\)](#), [DoscPP\(\)](#)

**Examples**

```
## Not run:
# Example using simulated data
set.seed(123)

# Create simulated data
bulk_data <- matrix(rnorm(1000*50), nrow=1000, ncol=50)
sc_data <- matrix(rnorm(1000*500), nrow=1000, ncol=500)
```

```

phenotype <- rep(c(0, 1), each=25)

# Run LP-SGL analysis
results <- DoLP_SGL(
  matched_bulk = bulk_data,
  sc_data = sc_data,
  phenotype = phenotype,
  family = "logit",
  resolution = 0.6,
  dge_analysis = list(run = TRUE, logFC_threshold = 1, pval_threshold = 0.05)
)

# Access results
lpsgl_seurat <- results$scRNA_data
sgl_model <- results$sgl_fit
deg_results <- results$dge_res

## End(Not run)

```

---

DoPIPET

---

*Perform PIPET Screening Analysis*


---

## Description

Predicts cell subpopulations in single-cell data by matching expression profiles to predefined marker gene templates using various distance/similarity metrics. This function implements a template-based classification approach with permutation testing for significance assessment.

## Usage

```

DoPIPET(
  matched_bulk,
  sc_data,
  phenotype,
  phenotype_class = c("binary", "continuous"),
  group = NULL,
  discretize_method = c("kmeans", "median", "custom"),
  cutoff = NULL,
  label_type = "PIPET",
  log2FC = 1L,
  p_adjust = 0.05,
  show_log2FC = TRUE,
  freq_counts = NULL,
  normalize = TRUE,
  scale = TRUE,
  nPerm = 1000L,
  distance = c("cosine", "pearson", "spearman", "kendall", "euclidean", "maximum"),
  ...
)

```

**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| matched_bulk      | Normalized bulk expression matrix (features $\times$ samples). Column names must match phenotype identifiers.                                                                                                                                                                                                                             |
| sc_data           | Seurat object containing single-cell RNA-seq data.                                                                                                                                                                                                                                                                                        |
| phenotype         | Clinical outcome data. Can be: - Vector: named with sample IDs - Data frame: with row names matching bulk columns                                                                                                                                                                                                                         |
| phenotype_class   | Analysis mode: - "binary": Case-control design (e.g., responder/non-responder) - "continuous": Continuous outcome (e.g.,)                                                                                                                                                                                                                 |
| group             | A character, name of one metadata column to group cells by (for example, orig.ident). The default value is NULL. In this case, screening will be performed on each group separately.                                                                                                                                                      |
| discretize_method | c("median", "kmeans", "custom"). Discretization strategy for continuous phenotypes. Note: "median" is mapped internally to "quantile" (2-group quantile split). Default: "median".                                                                                                                                                        |
| cutoff            | Numeric vector of length n_group - 1. Required only when discretize_method = "custom". Defines interior breakpoints on the <i>normalized, log2-transformed scale</i> (i.e., after $\text{scale}(\log_2(x + 1))$ ). Must be sorted in ascending order.                                                                                     |
| label_type        | Character specifying phenotype label type (e.g., "SBS1", "time"), stored in scRNA_data@misc                                                                                                                                                                                                                                               |
| log2FC            | In the DESeq differential expression analysis results, the cutoff value of log2FC. The default value is 1L.                                                                                                                                                                                                                               |
| p_adjust          | In the DESeq differential expression analysis results, the cutoff value of adjust P. The default value is 0.05.                                                                                                                                                                                                                           |
| show_log2FC       | Select whether to show log2 fold changes. The default value is TRUE.                                                                                                                                                                                                                                                                      |
| freq_counts       | An integer, keep genes expressed in more than a certain number of cells. The default value is NULL, which means no filtering.                                                                                                                                                                                                             |
| normalize         | Select whether to perform normalization of count data. The default value is TRUE.                                                                                                                                                                                                                                                         |
| scale             | Select whether to scale and center features in the dataset. The default value is TRUE.                                                                                                                                                                                                                                                    |
| nPerm             | An integer, number of permutations to do. The default value is 1000L.                                                                                                                                                                                                                                                                     |
| distance          | A character, the distance algorithm must be included in "cosine", "pearson", "spearman", "kendall", "euclidean", "maximum". default value is NULL, which means "cosine".                                                                                                                                                                  |
| ...               | Additional arguments to be passed to PIPET.optimized. <ul style="list-style-type: none"> <li>• seed: Random seed for reproducibility</li> <li>• verbose: Whether to show progress messages</li> <li>• parallel: Whether to use parallel processing, default is FALSE. future::plan() must be set before calling this function.</li> </ul> |

**See Also**

Other screen\_method: [DoDEGAS\(\)](#), [DoLP\\_SGL\(\)](#), [DoScissor\(\)](#), [DoscAB\(\)](#), [DoscPAS\(\)](#), [DoscPP\(\)](#)



---

|        |                                        |
|--------|----------------------------------------|
| DoscAB | <i>Perform scAB Screening Analysis</i> |
|--------|----------------------------------------|

---

**Description**

Implements the scAB algorithm to identify phenotype-associated cell subpopulations in single-cell RNA-seq data by integrating matched bulk expression and phenotype information. Uses non-negative matrix factorization (NMF) with dual regularization for phenotype association and cell-cell similarity.

**Usage**

```
DoscAB(
  matched_bulk,
  sc_data,
  phenotype,
  label_type = "scAB",
  phenotype_class = c("binary", "survival"),
  alpha = c(0.005, NULL),
  alpha_2 = c(0.005, NULL),
  maxiter = 2000L,
  tred = 2L,
  ...
)
```

**Arguments**

|                 |                                                                                                                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| matched_bulk    | Normalized bulk expression matrix (genes × samples) where: - Columns match phenotype row names - Genes match features in sc_data                                                                                                                                                                                                     |
| sc_data         | Seurat object containing preprocessed single-cell data:                                                                                                                                                                                                                                                                              |
| phenotype       | Data frame with clinical annotations where: - Rows correspond to matched_bulk columns - For survival: contains time and status columns                                                                                                                                                                                               |
| label_type      | Character specifying phenotype label type (e.g., "SBS1", "time"), stored in scRNA_data@misc                                                                                                                                                                                                                                          |
| phenotype_class | Analysis mode: - "binary": Case-control design (e.g., responder/non-responder)<br>- "survival": Time-to-event analysis data.frame                                                                                                                                                                                                    |
| alpha           | Coefficient of phenotype regularization (default=0.005).                                                                                                                                                                                                                                                                             |
| alpha_2         | Coefficient of cell-cell similarity regularization (default=0.005).                                                                                                                                                                                                                                                                  |
| maxiter         | Maximum number of iterations for NMF (default=2000).                                                                                                                                                                                                                                                                                 |
| tred            | Z-score threshold in finding subsets (default=2).                                                                                                                                                                                                                                                                                    |
| ...             | Additional arguments. Currently supports: <ul style="list-style-type: none"> <li>• verbose: Logical indicating whether to print progress messages. Defaults to TRUE.</li> <li>• seed: For reproducibility, default is 123L</li> <li>• parallel: Logical indicating whether to use parallel processing. Defaults to FALSE.</li> </ul> |

**Value**

A list containing:

**scRNA\_data** Filtered Seurat object with selected cells

**scAB\_result** scAB screening result

**LICENSE**

Licensed under the GNU General Public License version 3 (GPL-3.0). A copy of the license is available at <https://www.gnu.org/licenses/gpl-3.0.en.html>.

**References**

Zhang Q, Jin S, Zou X. scAB detects multiresolution cell states with clinical significance by integrating single-cell genomics and bulk sequencing data. *Nucleic Acids Research*. 2022 Nov 28;50(21):12112–30.

**See Also**

Other screen\_method: [DoDEGAS\(\)](#), [DoLP\\_SGL\(\)](#), [DoPIPET\(\)](#), [DoScissor\(\)](#), [DoscPAS\(\)](#), [DoscPP\(\)](#)

**Examples**

```
## Not run:
# Binary phenotype example
result <- DoscAB(
  matched_bulk = bulk_matrix,
  sc_data = seurat_obj,
  phenotype = clinical_df,
  label_type = "disease_status",
  phenotype_class = "binary",
  alpha = 0.005,
  alpha_2 = 0.005,
  maxiter = 2000,
  tred = 2
)

## End(Not run)
```

**Description**

Identifies phenotype-associated cell subpopulations in single-cell data using regularized regression on matched bulk expression profiles. Scissor integrates bulk and single-cell RNA-seq data to identify cells that are significantly associated with phenotypic outcomes.

**Usage**

```

DoScissor(
  path2load_scissor_cache = NULL,
  path2save_scissor_inputs = "Scissor_inputs.RData",
  matched_bulk,
  sc_data,
  phenotype,
  label_type = "scissor",
  alpha = c(0.05, NULL),
  cutoff = 0.2,
  family = c("gaussian", "binomial", "cox"),
  reliability_test = list(
    run = FALSE, # whether to run reliability test
    n = 10L, # permutation times
    nfold = 10L # cross validation folds
  ),
  cell_evaluation = list(
    run = FALSE, # whether to run cell evaluation
    benchmark_data = "path_to_file.RData", # path to benchmark data
    FDR_cutoff = 0.05,
    bootstrap_n = 100L
  ),
  ...
)

```

**Arguments**

|                                       |                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>path2load_scissor_cache</code>  | Path to precomputed Scissor inputs (RData file). If provided, skips recomputation (default: NULL).                                                                                                                                                                                                                   |
| <code>path2save_scissor_inputs</code> | Path to save intermediate files (default: "Scissor_inputs.RData").                                                                                                                                                                                                                                                   |
| <code>matched_bulk</code>             | Normalized bulk expression matrix (features $\times$ samples). Column names must match phenotype identifiers.                                                                                                                                                                                                        |
| <code>sc_data</code>                  | Seurat object containing single-cell RNA-seq data.                                                                                                                                                                                                                                                                   |
| <code>phenotype</code>                | Clinical outcome data. Can be: - Vector: named with sample IDs - Data frame: with row names matching bulk columns                                                                                                                                                                                                    |
| <code>label_type</code>               | Character specifying phenotype label type (e.g., "SBS1", "time"), stored in <code>scRNA_data@misc</code>                                                                                                                                                                                                             |
| <code>alpha</code>                    | Parameter used to balance the effect of the l1 norm and the network-based penalties. It can be a number or a searching vector. If <code>alpha = NULL</code> , a default searching vector is used. The range of <code>alpha</code> is between 0 and 1. A larger <code>alpha</code> lays more emphasis on the l1 norm. |
| <code>cutoff</code>                   | (default: 0.2). When <code>alpha=NULL</code> , the cutoff is used to determine the optimal <code>alpha</code> . Higher values increase specificity.                                                                                                                                                                  |
| <code>family</code>                   | Model family for outcome type: - "gaussian": Continuous outcomes - "binomial": Binary outcomes (default) - "cox": Survival outcomes                                                                                                                                                                                  |

**reliability\_test**

List controlling reliability testing:

- run: Whether to perform reliability test (default: FALSE)
- n: Permutation times (default: 10L)
- nfold: Cross-validation folds (default: 10L)

**cell\_evaluation**

List controlling cell evaluation:

- run: Whether to perform cell evaluation (default: FALSE)
- benchmark\_data: Path to benchmark data (RData file)
- FDR\_cutoff: FDR threshold for evaluation (default: 0.05)
- bootstrap\_n: Bootstrap iterations (default: 100L)

...

Additional arguments. Currently supports:

- verbose: Logical indicating whether to print progress messages. Defaults to TRUE.
- seed: For reproducibility, default is 123L

**Value**

A list containing:

**scRNA\_data** A Seurat object with screened cells containing metadata:**scissor** "Positive"/"Negative"/"Neutral" classification**label\_type** Outcome label used**scissor\_result** Raw Scissor results**reliability\_result** If reliability\_test=TRUE, contains:**statistic** A value between 0 and 1**p** p-value of the test statistic**AUC\_test\_real** 10 values of AUC for real data**AUC\_test\_back** A list of AUC for background data**cell\_evaluation** If cell\_evaluation=TRUE, contains:**evaluation\_res** A data.frame with some supporting information for each Scissor selected cell**LICENSE**

Licensed under the GNU General Public License version 3 (GPL-3.0). A copy of the license is available at <https://www.gnu.org/licenses/gpl-3.0.en.html>.

**References**

Sun D, Guan X, Moran AE, Wu LY, Qian DZ, Schedin P, et al. Identifying phenotype-associated subpopulations by integrating bulk and single-cell sequencing data. Nat Biotechnol. 2022 Apr;40(4):527–38.

**See Also**Other screen\_method: [DoDEGAS\(\)](#), [DoLP\\_SGL\(\)](#), [DoPIPET\(\)](#), [DoscAB\(\)](#), [DoscPAS\(\)](#), [DoscPP\(\)](#)Other scissor: [DoScissorCellEval\(\)](#), [DoScissorRelTest\(\)](#)

**Examples**

```
## Not run:
# Binary outcome example
res <- DoScissor(
  matched_bulk = bulk_matrix,
  sc_data = seurat_obj,
  phenotype = a_named_vector,
  family = "binomial"
)

## End(Not run)
```

DoscPAS

*Perform scPAS Screening Analysis***Description**

This function performs scPAS screening analysis by integrating bulk and single-cell RNA-seq data. It includes data filtering steps and wraps the core `scPAS::scPAS` function.

**Usage**

```
DoscPAS(
  matched_bulk,
  sc_data,
  phenotype,
  label_type = "scPAS",
  assay = "RNA",
  imputation = FALSE,
  imputation_method = c("KNN", "ALRA"),
  nfeature = 3000L,
  alpha = c(0.01, NULL),
  cutoff = 0.2,
  network_class = c("SC", "bulk"),
  family = c("cox", "gaussian", "binomial"),
  permutation_times = 2000L,
  FDR_threshold = 0.05,
  independent = TRUE,
  ...
)
```

**Arguments**

|                           |                                                           |
|---------------------------|-----------------------------------------------------------|
| <code>matched_bulk</code> | Bulk RNA-seq data (genes x samples)                       |
| <code>sc_data</code>      | Single-cell RNA-seq data (Seurat object and preprocessed) |
| <code>phenotype</code>    | Phenotype data frame with sample annotations              |

|                   |                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label_type        | Character specifying phenotype label type (e.g., "SBS1", "time"), stored in <code>scRNA_data@misc</code> . (default: "scPAS")                                                                                                                                                                                                                                      |
| assay             | Assay to use from <code>sc_data</code> (default: 'RNA')                                                                                                                                                                                                                                                                                                            |
| imputation        | Logical, whether to perform imputation (default: FALSE)                                                                                                                                                                                                                                                                                                            |
| imputation_method | Character. Name of alternative method for imputation. (options: "KNN", "ALRA")                                                                                                                                                                                                                                                                                     |
| nfeature          | Number of features to select (default: 3000, indicating that the top 3000 highly variable genes are selected for model training)                                                                                                                                                                                                                                   |
| alpha             | Numeric. Significance threshold. Parameter used to balance the effect of the l1 norm and the network-based penalties. It can be a number or a searching vector. If <code>alpha = NULL</code> , a default searching vector is used. The range of <code>alpha</code> is in $[0, 1]$ . A larger <code>alpha</code> lays more emphasis on the l1 norm. (default: 0.01) |
| cutoff            | Numeric. Cutoff value for selecting the optimal <code>alpha</code> value when <code>alpha = NULL</code> . (default: 0.2)                                                                                                                                                                                                                                           |
| network_class     | Network class to use (default: 'SC', indicating gene-gene similarity networks derived from single-cell data. The other one is 'bulk'.)                                                                                                                                                                                                                             |
| family            | Model family for analysis (options: "cox", "gaussian", "binomial")                                                                                                                                                                                                                                                                                                 |
| permutation_times | Number of permutations to perform (default: 2000)                                                                                                                                                                                                                                                                                                                  |
| FDR_threshold     | Numeric. FDR value threshold for identifying phenotype-associated cells (default: 0.05)                                                                                                                                                                                                                                                                            |
| independent       | Logical. The background distribution of risk scores is constructed independently of each cell. (default: TRUE)                                                                                                                                                                                                                                                     |
| ...               | Additional arguments. Currently supports: <ul style="list-style-type: none"> <li>• <code>verbose</code>: Logical indicating whether to print progress messages. Defaults to TRUE.</li> <li>• <code>seed</code>: For reproducibility, default is 123L</li> </ul>                                                                                                    |

**Value**

A Seurat object from scPAS analysis

**LICENSE**

Licensed under the GNU General Public License version 3 (GPL-3.0). A copy of the license is available at <https://www.gnu.org/licenses/gpl-3.0.en.html>.

**References**

Xie A, Wang H, Zhao J, Wang Z, Xu J, Xu Y. scPAS: single-cell phenotype-associated subpopulation identifier. *Briefings in Bioinformatics*. 2024 Nov 22;26(1):bbae655.

**See Also**

Other screen\_method: `DoDEGAS()`, `DoLP_SGL()`, `DoPIPET()`, `DoScissor()`, `DoscAB()`, `DoscPP()`

---

|        |                                        |
|--------|----------------------------------------|
| DoscPP | <i>Perform scPP screening analysis</i> |
|--------|----------------------------------------|

---

## Description

This function performs scPP screening on single-cell data using matched bulk data and phenotype information. It supports binary, continuous, and survival phenotype types.

## Usage

```
DoscPP(
  matched_bulk,
  sc_data,
  phenotype,
  label_type = "scPP",
  phenotype_class = c("Binary", "Continuous", "Survival"),
  ref_group = 0,
  Log2FC_cutoff = 0.585,
  estimate_cutoff = 0.2,
  probs = c(0.2, NULL),
  ...
)
```

## Arguments

|                 |                                                                                                                                                                                                                               |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| matched_bulk    | Bulk expression data (genes × samples) where: - Column names must match phenotype row names                                                                                                                                   |
| sc_data         | Seurat object containing preprocessed single-cell data: - Normalized counts in RNA assay                                                                                                                                      |
| phenotype       | Data frame or tibble or named vector with: - Rownames matching matched_bulk columns - For survival: must contain time and status columns                                                                                      |
| label_type      | Character specifying phenotype label type (e.g., "SBS1"), stored in scRNA_data@misc                                                                                                                                           |
| phenotype_class | Analysis type (case-sensitive): - "Binary": Case-control studies (e.g., tumor/normal) - "Continuous": Quantitative traits (e.g., drug response) - "Survival": Time-to-event data (requires time/status columns)               |
| ref_group       | Reference group or baseline for <b>binary</b> comparisons, e.g. "Normal" for Tumor/Normal studies and 0 for 0/1 case-control studies. (default: 0)                                                                            |
| Log2FC_cutoff   | Minimum log2 fold-change for binary markers (default: 0.585)                                                                                                                                                                  |
| estimate_cutoff | Effect size threshold for <b>continuous</b> traits (default: 0.2)                                                                                                                                                             |
| probs           | A numeric value indicating the quantile cutoff for cell classification. This parameter can also be a numeric vector, in which case an optimal threshold will be selected based on the AUC and enrichment score.(default: 0.2) |

... Additional arguments. Currently supports:

- **verbose**: Logical indicating whether to print progress messages. Defaults to TRUE.
- **seed**: For reproducibility, default is 123L

## Value

A list containing:

**scRNA\_data** Seurat object with added metadata:

**ScPP** "Positive"/"Negative"/"Neutral" classification

**gene\_list** List of genes used for screening

## Algorithm Steps

1. Data Validation: Checks sample alignment between bulk and phenotype data
2. Marker Selection: Identifies phenotype-associated genes from bulk data
3. Single-cell Screening: Projects bulk markers onto single-cell data
4. Cell Classification: Categorizes cells based on phenotype association

## Reference

WangX-Lab/ScPP [Internet]. [cited 2025 Aug 31]. Available from: <https://github.com/WangX-Lab/ScPP>

## See Also

Other screen\_method: [DoDEGAS\(\)](#), [DoLP\\_SGL\(\)](#), [DoPIPET\(\)](#), [DoScissor\(\)](#), [DoscAB\(\)](#), [DoscPAS\(\)](#)

## Examples

```
## Not run:
# Binary phenotype analysis
res <- DoscPP(
  matched_bulk = bulk_data,
  sc_data = seurat_obj,
  phenotype = ms_data,
  label_type = "SBS1",
  phenotype_class = "Binary"
)

# Survival analysis
surv_res <- DoscPP(
  sc_data = seurat_obj,
  matched_bulk = bulk_data,
  phenotype = surv_df,
  label_type = "OS_status",
  phenotype_class = "Survival"
)
```



```
## End(Not run)
```

---

|                 |                                                                                     |
|-----------------|-------------------------------------------------------------------------------------|
| FindRobustElbow | <i>Automatically determine optimal PCA dimensions using multiple robust methods</i> |
|-----------------|-------------------------------------------------------------------------------------|

---

## Description

This function combines multiple statistical approaches to automatically determine the optimal number of principal components (PCs) for downstream single-cell analysis. It integrates variance-based heuristics, elbow detection algorithms, and provides comprehensive visualization for result validation.

## Usage

```
FindRobustElbow(
  obj,
  verbose = SigBridgeUtils::getFuncOption("verbose") %||% TRUE,
  ndims = 50L
)
```

## Arguments

|         |                                                                                                                             |
|---------|-----------------------------------------------------------------------------------------------------------------------------|
| obj     | A Seurat object that has PCA computed (after RunPCA)                                                                        |
| verbose | Logical, if TRUE outputs detailed method results and creates visualization plot. If FALSE returns only the final dimension. |
| ndims   | Integer, maximum number of dimensions to consider (default: 50L)                                                            |

## Value

Integer, the recommended number of PCA dimensions for downstream analysis

## See Also

Other single\_cell\_preprocess: [FilterTumorCell\(\)](#), [Pattern2Colname\(\)](#), [QCPatternDetect\(\)](#), [SCPreProcess\(\)](#), [compatible\\_with\\_3.0.2\(\)](#)

## Examples

```
## Not run:
# After running PCA on Seurat object
pbmc <- RunPCA(pbmc, npcs = 50)
optimal_dims <- FindRobustElbow(pbmc, verbose = TRUE)
pbmc <- FindNeighbors(pbmc, dims = 1:optimal_dims)

## End(Not run)
```

getFuncOption

*Configuration Functions for SigBridgeR Package***Description**

These functions provide a centralized configuration system for the SigBridgeR package, allowing users to set and retrieve package-specific options with automatic naming conventions.

setFuncOption sets one or more configuration options for the SigBridgeR package. Options are automatically prefixed with "SigBridgeR." if not already present, ensuring proper namespace isolation.

getFuncOption retrieves configuration options for the SigBridgeR package. The function automatically handles the "SigBridgeR." prefix, allowing users to reference options with or without the explicit prefix.

checkFuncOption validates configuration options for the SigBridgeR package. This function ensures that all options meet type and value requirements before they are set in the global options.

**Usage**

```
getFuncOption(option, default = NULL)
```

**Arguments**

|         |                                                                         |
|---------|-------------------------------------------------------------------------|
| option  | Character string specifying the option name to check                    |
| default | The default value to return if the option is not set. Defaults to NULL. |

**Details**

This function performs the following validations:

**verbose** Must be single logical values (TRUE/FALSE)

**timeout, seed** Must be single integer values

The function is automatically called by setFuncOption to ensure all configuration options are valid before they are set.

**Value**

Invisibly returns NULL. The function is called for its side effects of setting package options.

The value of the specified option if it exists, otherwise the provided default value.

No return value. The function throws an error if the value doesn't meet the required specifications for the given option.

**Available Options**

- **verbose**: A logical value indicating whether to print verbose messages, defaults to TRUE
- **timeout**: An integer specifying the timeout in seconds for parallel processing, defaults to '180L'
- **seed**: An integer specifying the random seed for reproducible results, defaults to '123L'

**Examples**

```
# Set options with automatic prefixing
setFuncOption(verbose = TRUE)

# Retrieve options with automatic prefixing
getFuncOption("verbose")
```

ListPyEnv

*List Available Python Environments***Description**

Discovers and lists available Python environments of various types on the system. This generic function provides a unified interface to find Conda environments and virtual environments (venv) through S3 method dispatch.

Default method that lists all Python environments by combining results from Conda and virtual environment discovery methods.

Discovers Conda environments using multiple detection strategies for maximum reliability. First attempts to use system Conda commands, then falls back to reticulate's built-in Conda interface if Conda command is unavailable or fails. Returns empty data frame if Conda is not available or no environments are found.

Discovers virtual environments by searching common venv locations including user directories ('~/virtualenvs', '~/venvs') and project folders ('./venv', './venv'). Supports custom search paths through the 'venv\_locations' parameter. Returns empty data frame if no virtual environments are found in the specified locations.

**Usage**

```
ListPyEnv(
  env_type = c("all", "conda", "venv", "virtualenv"),
  timeout = 30000,
  venv_locations = c("~/virtualenvs", "~/venvs", "./venv", "./venv"),
  verbose = TRUE,
  ...
)
```

**Arguments**

|                |                                                                                                                                             |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| env_type       | Character string specifying the type of environments to list. One of: "all", "conda", "venv". Defaults to "all".                            |
| timeout        | The maximum timeout time when using system commands, only effective when 'env_type=conda'.                                                  |
| venv_locations | Character vector of directory paths to search for virtual environments. Default includes standard locations and common project directories. |
| verbose        | Logical indicating whether to print verbose output.                                                                                         |
| ...            | For future use.                                                                                                                             |

## Details

The function uses S3 method dispatch to handle different environment types:

- `all`: Combines results from all environment types using `rbind()` - `conda`: Searches for Conda environments using multiple methods: - Primary: `reticulate::conda_list()` for reliable environment detection - Fallback: System `conda info --envs` command for broader compatibility - `venv`: Searches common virtual environment locations including user directories and project folders

Each method includes comprehensive error handling and will return empty results with informative warnings if no environments are found or if errors occur during discovery.

## Value

A data frame with the following columns:

- `name` - Character vector of environment names
- `python` - Character vector of paths to Python executables
- `type` - Character vector indicating environment type (`"conda"` or `"venv"`)

Returns an empty data frame with these columns if no environments are found.

## Examples

```
## Not run:
# List all Python environments
ListPyEnv("all")

# List only Conda environments
ListPyEnv("conda")

# List only virtual environments with custom search paths
ListPyEnv("venv", venv_locations = c("~/my_envs", "./project_env"))

## End(Not run)
```

---

LoadRefData

Download & Load Reference Data

---

## Description

This function checks if the data already exists in a local cache. If not, it downloads the file from the remote repository using multiple sources with fallback.

**Usage**

```
LoadRefData(
  data_type = c("survival", "binary", "continuous"),
  path = NULL,
  timeout = SigBridgeUtils::getFuncOption("timeout"),
  ...
)
```

**Arguments**

|                        |                                                                                                                                                                                            |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data_type</code> | The type of data to download. Must be one of "survival", "binary", or "continuous".                                                                                                        |
| <code>path</code>      | Optional path to save the downloaded file, default: NULL, saving in package.                                                                                                               |
| <code>timeout</code>   | Integer. Connection timeout in seconds (default: 60)                                                                                                                                       |
| <code>...</code>       | Additional arguments. Currently supports: <ul style="list-style-type: none"> <li><code>verbose</code>: Logical indicating whether to print progress messages. Defaults to TRUE.</li> </ul> |

**Value**

The requested datasets, stored in a list.

**Examples**

```
## Not run:
ref_data <- LoadRefData(data_type = c("survival"))

## End(Not run)
```

---

MergeResult

---

Merge Multiple Screening Analysis Results

---

**Description**

Combines results from multiple single-cell screening analyses (Scissor, scPAS, scPP, or scAB) by merging their metadata and miscellaneous information while preserving the original expression data. Performs an inner join on cell barcodes to ensure only cells present in all inputs are retained.

**Usage**

```
MergeResult(..., verbose = SigBridgeUtils::getFuncOption("verbose"))
```

**Arguments**

...                      Input objects to merge. Can be: - Seurat objects - Lists containing scRNA\_data (Seurat objects) - Mixed combinations of the above - The first one will be used as base object for merging, priority given to first one when duplicate columns are found

verbose                Logical, whether to print a message

**Value**

A merged Seurat object containing:

- Expression data from the first input object
- Combined metadata from all input objects
- Miscellaneous information from all input objects
- Only cells present in all input objects (inner join)

**Processing Details**

1. Input Validation: Checks for valid Seurat objects or lists containing Seurat objects
2. Metadata Extraction: Collects metadata from all objects
3. Cell Intersection: Retains only cells present in all datasets
4. Object Merging: Creates new Seurat object with combined metadata
5. Miscellaneous: Adds miscellaneous information to the merged object

**Examples**

```
## Not run:
# Merge mixed analysis types
combined <- MergeResult(scissor_output, scAB_output, scPP_output)

# Merge list-containing objects
merged_list <- MergeResult(list1, list2, seurat_obj)

## End(Not run)
```

---

|                 |                                                          |
|-----------------|----------------------------------------------------------|
| Pattern2Colname | <i>convert regex patterns to column names (internal)</i> |
|-----------------|----------------------------------------------------------|

---

**Description**

An internal utility function that converts regular expression patterns used for quality control in single-cell RNA-seq analysis into standardized column names for Seurat object metadata. This function handles both single patterns and combined patterns with logical OR operators.

**Usage**

```
Pattern2Colname(pat)
```

**Arguments**

**pat** A character string containing a regular expression pattern or multiple patterns combined with | (OR operator).

**Value**

A character string with the standardized column name derived from the input pattern(s). The output follows these conventions: - Lowercase letters only - Special characters removed or replaced with underscores - Common patterns mapped to standardized abbreviations - Combined patterns sorted alphabetically and joined with underscores

**See Also**

Other single\_cell\_preprocess: [FilterTumorCell\(\)](#), [FindRobustElbow\(\)](#), [QCPatternDetect\(\)](#), [SCPreProcess\(\)](#), [compatible\\_with\\_3.0.2\(\)](#)

**Examples**

```
## Not run:
# Internal usage examples
Pattern2Colname("^MT-")           # Returns "mt"
Pattern2Colname("^RP[LS]")        # Returns "rp"
Pattern2Colname("^rt]rna")        # Returns "rt_rna"
Pattern2Colname("MT-|RP[LS]")     # Returns "mt_rp"
Pattern2Colname("HB[AB]?")        # Returns "hb_ab"
Pattern2Colname("Custom_Pattern[0-9]+") # Returns "custom_pattern_0_9"

## End(Not run)
```

---

QCFilter

---

*Filter Seurat object cells by QC metrics*


---

**Description**

Filters cells based on nFeature\_RNA and optional QC metrics (e.g. percent.mt, percent.rp), defined in `seurat_obj@misc$qc_colnames` (See [QCPatternDetect](#)). Only metrics with non-constant, non-all-zero values are used.

**Usage**

```
QCFilter(
  seurat_obj,
  data_filter.thresh = list(nFeature_RNA_thresh = c(200L, 6000L), nCount_RNA_thresh =
    c(500L, 50000L), percent.mt = 20L, percent.rp = 60L),
  verbose = TRUE,
  ...
)
```

**Arguments**

|                    |                                                                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| seurat_obj         | A Seurat object.                                                                                                                                                            |
| data_filter.thresh | A named list with thresholds. Default: <code>list( nFeature_RNA_thresh = c(200L, 6000L), nCount_RNA_thresh = c(500L, 25000L), percent.mt = 20L, percent.rp = 60L )</code> . |
| verbose            | Logical; whether to print progress messages via cli.                                                                                                                        |
| ...                | No use                                                                                                                                                                      |

**Value**

A filtered Seurat object.

---

|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| QCPatternDetect | <i>Calculate Percentage of Features Matching Patterns</i> |
|-----------------|-----------------------------------------------------------|

---

**Description**

This function calculates the percentage of counts coming from features matching specified patterns (e.g., mitochondrial genes, ribosomal genes) and adds them as metadata columns to the Seurat object.

**Usage**

```
QCPatternDetect(
  obj,
  pattern = c("^MT-", "^mt-", "^RP[SL]", "^MT-|^RP[SL]"),
  verbose = TRUE,
  ...
)
```



**Arguments**

|                      |                                                                                                                                                                                                                    |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>obj</code>     | A <code>seurat</code> object.                                                                                                                                                                                      |
| <code>pattern</code> | A character vector or list containing regex patterns to identify mitochondrial genes, ribosomal protein genes, or other unwanted genes, as well as combinations of these genes. Customized patterns are supported. |
| <code>verbose</code> | logical, whether to print progress messages                                                                                                                                                                        |
| <code>...</code>     | Additional arguments passed to <a href="#">PercentageFeatureSet</a>                                                                                                                                                |

**Details**

The function automatically generates friendly column names based on the patterns:

- "mt" for mitochondrial patterns
- "rp" for ribosomal patterns
- "rrna" for ribosomal RNA patterns
- For combined patterns (using `|`), creates names like "mt\_rp"
- For other patterns, creates cleaned lowercase names

**See Also**

Other `single_cell_preprocess`: [FilterTumorCell\(\)](#), [FindRobustElbow\(\)](#), [Pattern2Colname\(\)](#), [SCPreProcess\(\)](#), [compatible\\_with\\_3.0.2\(\)](#)

---

RegisterScreenMethod     *Register a Custom Screening Method for Phenotype-Driven Analysis*

---

**Description**

Registers one or more user-defined screening functions into a shared registry (i.e., `ScreenStrategy`), enabling dynamic dispatch based on phenotype type (binary, survival, or continuous). Each method is stored with metadata including supported phenotypes and an optional parameter remapping function.

This function supports community-driven extension of analysis pipelines—ideal for integrating novel single cell phenotypic screening methods while maintaining compatibility with downstream validation and execution frameworks

**Usage**

```
RegisterScreenMethod(
  ...,
  supported_phenotypes = c("binary", "survival", "continuous"),
  parameter_mapper = NULL,
  registry = ScreenStrategy,
  verbose = getFuncOption("verbose") %||% TRUE
)
```

**Arguments**

|                      |                                                                                                                                                                                                                                                                                                  |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...                  | Named arguments where each value is a <b>function</b> implementing a screening method. The name becomes the method identifier (e.g., Scissor = DoScissor registers DoScissor under the key "Scissor"). Unnamed arguments are auto-named using their expression (e.g., Scissor → name "Scissor"). |
| supported_phenotypes | Character vector specifying which phenotype types the method supports. Must be a subset of c("binary", "survival", "continuous"). Default: all three.                                                                                                                                            |
| parameter_mapper     | A function that transforms the input parameter list before passing it to the executor. Useful for changing parameters from interface function. Receives a named list params and must return a modified list. Default: NULL.                                                                      |
| registry             | An environment used as a method registry (e.g., ScreenStrategy). New methods are stored as registry[["MethodName"]] = metadata list. Default: ScreenStrategy.                                                                                                                                    |
| verbose              | Logical. Whether to print a success message upon registration. Default: TRUE.                                                                                                                                                                                                                    |

**Value**

Invisibly returns TRUE on successful registration.

**Registry Entry Structure**

Each registered method is stored as a list with four elements:

method\_name Character: the method key (e.g., "Scissor")  
 executor Function: the actual screening implementation  
 phenotypes Character vector: supported phenotype classes  
 mapper Function: parameter transformation hook

**Examples**

```
## Not run:
# Example: Register a custom screen method for survival data
DoMyScreen <- function(...) {
  stop("Not implemented")
}

RegisterScreenMethod(
  # Key = function
  MyCox = DoMyScreen,
  # If `continuous` phenotype is not supported
  supported_phenotypes = c("survival", "binary"),
  parameter_mapper = function(params) {
    # If I prefer to use `quiet` instead of `verbose`
    params$quiet <- !params$verbose
    params
  }
)
```

```
## End(Not run)
```

---

SCPreProcess

*Single-Cell RNA-seq Preprocessing Pipeline*


---

## Description

A unified interface for standardized single-cell RNA-seq preprocessing. It accepts raw counts (matrix/data.frame), AnnData (via anndata or anndataR), or existing Seurat objects. The analysis flow is fully customizable via a character string pipeline and a configuration list params.

## Usage

```
SCPreProcess(sc, ...)
```

```
## Default S3 method:
```

```
SCPreProcess(
  sc,
  ...,
  pipeline = "onsvpcetu",
  params = list(o = list(project = "SC_Screen_Proj", min.cells = 400L), n = list(), s =
    list(), v = list(), p = list(), e = list(), c = list(resolution = 0.6), t = list(), u
    = list()),
  quality_control = list(pattern = c("^MT-")),
  data_filter = list(nFeature_RNA_thresh = c(200L, 6000L), nCount_RNA_thresh = c(500L,
    50000L), percent.mt = 20L, percent.rp = 60L),
  column2only_tumor = NULL
)
```

```
## S3 method for class 'R6'
```

```
SCPreProcess(
  sc,
  ...,
  pipeline = "onsvpcetu",
  params = list(o = list(project = "SC_Screen_Proj", min.cells = 400L), n = list(), s =
    list(), v = list(), p = list(), e = list(), c = list(resolution = 0.6), t = list(), u
    = list()),
  quality_control = list(pattern = c("^MT-")),
  data_filter = list(nFeature_RNA_thresh = c(200L, 6000L), nCount_RNA_thresh = c(500L,
    50000L), percent.mt = 20L, percent.rp = 60L),
  column2only_tumor = NULL
)
```

```
## S3 method for class 'Seurat'
```

```
SCPreProcess(sc, column2only_tumor = NULL, ...)
```

**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sc                | <p>Input data. Can be:</p> <ul style="list-style-type: none"> <li>• <b>Matrix/Data frame:</b> Raw count matrix (genes x cells).</li> <li>• <b>AnnData:</b> Python AnnData object (read via anndata or anndataR packages).</li> <li>• <b>Seurat:</b> A Seurat object (automatically validated and repaired if necessary).</li> </ul>                                                                                                                                                                                                                                      |
| ...               | Additional arguments for backward compatibility (mapped to params) or verbose control.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| pipeline          | <p>A character string defining the processing steps and order. Characters map to Seurat functions:</p> <ul style="list-style-type: none"> <li>• 'o': CreateSeuratObject (Must be the first step and cannot be deleted)</li> <li>• 'n': NormalizeData</li> <li>• 's': ScaleData</li> <li>• 'v': FindVariableFeatures</li> <li>• 'p': RunPCA</li> <li>• 'e': FindNeighbors (Because "n" is used)</li> <li>• 'c': FindClusters</li> <li>• 't': RunTSNE</li> <li>• 'u': RunUMAP</li> <li>• 'r': SCTransform (Alternative to n/s/v)</li> </ul> <p>Default is "onsvpcetu".</p> |
| params            | <p>A named list of lists containing arguments for each pipeline step. Keys match the pipeline characters (e.g., params\$n for NormalizeData). Default structure:</p> <pre>list(   o = list(project = "SC_Screen_Proj", min.cells = 400L), # do not pass `counts`   n = list(), # NormalizeData args   s = list(), # ScaleData args   v = list(), # FindVariableFeatures args   c = list(resolution = 0.6),   ... )</pre>                                                                                                                                                 |
| quality_control   | <p>A list containing regex patterns for QC metric calculation. (See <a href="#">QCPatternDetect</a>) Default: list(pattern = "^MT-"). Detected metrics (e.g., percent.mt) are added to meta.data.</p>                                                                                                                                                                                                                                                                                                                                                                    |
| data_filter       | <p>A list of thresholds for cell filtering. Default: nFeature_RNA (200-6000), nCount_RNA (500-50000), percent.mt (&lt;20), percent.rp (&lt;60). Only metrics detected via quality_control are filtered, i.e., nFeature_RNA, nCount_RNA and percent.mt.</p>                                                                                                                                                                                                                                                                                                               |
| column2only_tumor | <p>Optional character. Column name in metadata to filter for tumor cells (matches "Tumor", "Cancer", "Malignant", etc.). If NULL, no filtering is performed.</p>                                                                                                                                                                                                                                                                                                                                                                                                         |

## Details

**Pipeline Strategy:** The function parses the pipeline string and executes corresponding Seurat functions in order. To use SCTransform, simply change the pipeline string (e.g., "orpetu") and provide parameters in params\$r.

**Quality Control & Filtering:** QC metrics are generated based on regex patterns in quality\_control. Cells are then filtered based on thresholds in data\_filter. Column names for filtering are auto-generated (e.g., pattern "^MT-" -> filter "percent.mt"). If confused about the column name, use SigBridgeR::Pattern2Colname().

## Value

A processed Seurat object with reductions, clusters, and QC metrics.

## See Also

Other single\_cell\_preprocess: [FilterTumorCell\(\)](#), [FindRobustElbow\(\)](#), [Pattern2Colname\(\)](#), [QCPatternDetect\(\)](#), [compatible\\_with\\_3.0.2\(\)](#)

## Examples

```
## Not run:
# 1. Standard pipeline (LogNormalize -> Scale -> PCA -> UMAP)
obj <- SCPreProcess(
  sc = counts_matrix,
  pipeline = "onsvpcetu",
  params = list(c = list(resolution = 0.8))
)

# 2. SCTransform pipeline
obj_sct <- SCPreProcess(
  sc = counts_matrix,
  pipeline = "orpcu", # Create -> SCT -> PCA -> Clusters -> UMAP
  quality_control = list(pattern = c("^MT-", "^RP[LS]")),
  params = list(
    r = list(vars.to.regress = "percent.mt")
  )
)

# 3. Start from AnnData with tumor filtering
adata_object <- anndataR::read_h5ad("data.h5ad")
obj_ad <- SCPreProcess(
  sc = adata_object,
  column2only_tumor = "tissue"
)

## End(Not run)
```

Screen

*Single-Cell Data Screening***Description**

Integrates matched bulk expression data and phenotype information to identify phenotype-associated cell populations in single-cell RNA-seq data using one of four computational methods. Ensures consistency between bulk and phenotype data before analysis.

**Usage**

```
Screen(
  matched_bulk,
  sc_data,
  phenotype,
  label_type = NULL,
  phenotype_class = c("binary", "survival", "continuous"),
  screen_method = c("Scissor", "scPP", "scPAS", "scAB", "DEGAS", "LP_SGL", "PIPET"),
  ...
)
```

**Arguments**

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| matched_bulk    | Matrix or data frame of preprocessed bulk RNA-seq expression data (genes x samples). Column names must match names/IDs in phenotype.                                                                                                                                                                                                                                                                                                                                  |
| sc_data         | A matrix/Matrix (genes x cells) or a Seurat object containing scRNA-seq data to be screened.                                                                                                                                                                                                                                                                                                                                                                          |
| phenotype       | Phenotype data, either: - Named vector (names match matched_bulk columns), or - Patient survival Data frame with row names matching matched_bulk columns, colnames named "time" and "status"                                                                                                                                                                                                                                                                          |
| label_type      | Character specifying phenotype label type (e.g., "SBS1", "time")                                                                                                                                                                                                                                                                                                                                                                                                      |
| phenotype_class | Type of phenotypic outcome (must be consistent with input data): - "binary": Binary traits (e.g., case/control) - "continuous": Continuous measurements - "survival": Survival information                                                                                                                                                                                                                                                                            |
| screen_method   | Screening algorithm to use, there are seven options: <ul style="list-style-type: none"> <li>• "Scissor": see also DoScissor()</li> <li>• "scPP": see also DoscPP()</li> <li>• "scPAS": see also DoscPAS()</li> <li>• "scAB": see also DoscAB(), continuous phenotype is not supported</li> <li>• "DEGAS": see also DoDEGAS()</li> <li>• "LP_SGL": see also DoLP_SGL()</li> <li>• "PIPET": see also DoPIPET(), using survival as phenotype is not supported</li> </ul> |
| ...             | Additional method-specific parameters:                                                                                                                                                                                                                                                                                                                                                                                                                                |

**Scissor alpha** (numeric or NULL) Significance threshold. When NULL, alpha will keep increasing iteratively until the corresponding cells are screened out, default 0.05

**cutoff** (numeric) A threshold for terminating the iteration of alpha, only work when alpha is NULL, default 0.2

**path2load\_scissor\_cache** (character) default NULL

**path2save\_scissor\_inputs** (character) A path to save the intermediary data. By using path2load\_scissor\_cache, the intermediary data can be loaded from the specified path. default "Scissor\_inputs.RData"

**reliability\_test** (logical) Whether to perform reliability test, default FALSE

**reliability\_test.nfold** (integer) Cross-validation folds for reliability test, default 10

**reliability\_test.n** (integer) Number of cells to use for reliability test, default 10

**cell\_evaluation** (logical) Whether to perform cell evaluation, default FALSE

**cell\_evaluation.benchmark\_data** .RData Benchmark data for cell evaluation, default NULL

**cell\_evaluation.FDR** (numeric) FDR threshold for cell evaluation, default 0.05

**cell\_evaluation.bootstrap\_n** (integer) Number of bootstrap samples for cell evaluation, default 10

**scPP ref\_group** (integer or character) Reference group or baseline for binary comparisons, e.g. "Normal" for Tumor/Normal studies and 0 for 0/1 case-control studies. default: 0

**Log2FC\_cutoff** (numeric) Minimum log2 fold-change for binary markers, default 0.585

**estimate\_cutoff** (numeric) Effect size threshold for continuous traits, default 0.2

**probs** (numeric) Quantile cutoff for cell classification, default 0.2

**scPAS assay** (character) Assay to use from sc\_data, default "RNA"

**imputation** (logical) Whether to perform imputation, default FALSE

**nfeature** (integer) Number of features to select, default 3000

**alpha** (numeric or NULL) Significance threshold, When NULL, alpha will keep increasing iteratively until the corresponding cells are screened out, default 0.01

**independent** (logical) The background distribution of risk scores is constructed independently of each cell. default: TRUE

**network\_class** (character) Network class to use. default: 'SC', indicating gene-gene similarity networks derived from single-cell data. The other one is 'bulk'.

**permutation\_times** (integer) Number of permutations, default 2000

**FDR\_threshold** (numeric) FDR value threshold for identifying phenotype-associated cells default 0.05

**scAB alpha** (numeric) Coefficient of phenotype regularization ,default 0.005

- alpha\_2** (numeric) Coefficient of cell-cell similarity regularization, default 0.005
- maxiter** (integer) NMF optimization iterations, default 2000
- tred** (integer) Z-score threshold, default 2
- DEGAS sc\_data.pheno\_colname** (character) Phenotype column name in `sc_data`, default "NULL"
- select\_fraction** (numeric) Fraction of cells to select for DEGAS, default 0.05
- tmp\_dir** (character) Temporary directory for DEGAS, default "NULL"
- env\_params** (list) Environment parameters for DEGAS, default "list()"
- degas\_params** (list) DEGAS parameters, default "list()"
- normality\_test\_method** (character) Normality test method for DEGAS, default "jarque-bera"
- LP\_SGL\_resolution** (numeric) Resolution parameter for Leiden clustering, default 0.6
- alpha** (numeric) Alpha parameter for SGL balancing L1 and L2 penalties, default 0.5
- nfold** (integer) Number of folds for cross-validation, default 5
- dge\_analysis** (list) Differential expression analysis settings:
- **run**: (logical) Whether to run DEG analysis, default FALSE
  - **logFC\_threshold**: (numeric) Log fold change threshold, default 1
  - **pval\_threshold**: (numeric) P-value threshold, default 0.05
- PIPET\_group** (character or NULL) Name of a metadata column (e.g., "orig.ident") to stratify cells before screening. When NULL (default), screening is performed globally across all cells.
- discretize\_method** (character) Strategy to binarize continuous phenotypes internally before marker identification. One of:
- "median" (default): Equivalent to 2-quantile split (i.e., median threshold).
  - "kmeans": Two-cluster k-means on the continuous phenotype.
  - "custom": User-defined cutoffs via `cutoff`.
- cutoff** (numeric vector or NULL) Required only if `discretize_method = "custom"`. Specifies interior breakpoints on the *normalized, log2-transformed phenotype scale* (i.e., after `scale(log2(x + 1))`). Must be sorted ascending and of length `n_group - 1`.
- label\_type** (character) Phenotype label type (e.g., "PIPET\_SBS1"), stored in `scRNA_data@misc`. Default: "PIPET".
- log2FC** (numeric) Absolute log2 fold-change cutoff for differential expression marker selection in bulk data (via DESeq2-like analysis). Default: 1.
- p\_adjust** (numeric) Adjusted p-value (FDR) cutoff for marker gene selection. Default: 0.05.
- show\_log2FC** (logical) Whether to annotate markers with signed log2FC direction (e.g., CD3D\_up). Default: TRUE.



**freq\_counts** (integer or NULL) Minimum number of cells a gene must be expressed in to be retained in scRNA-seq data preprocessing. Default: NULL (no filtering).

**normalize** (logical) Whether to apply log-normalization (LogNormalize) to scRNA-seq counts prior to correlation. Default: TRUE.

**scale** (logical) Whether to scale (center + unit-variance) gene expression across cells before computing distances. Default: TRUE.

**nPerm** (integer) Number of label permutations to assess significance of correlation scores. Default: 1000.

**distance** (character) Distance or similarity metric for template matching. Supported: "cosine" (default), "pearson", "spearman", "kendall", "euclidean", "maximum".

**seed** (integer or NULL) Random seed for reproducibility in marker creation and permutation tests. Default: inherits from getFuncOption("seed").

**verbose** (logical) Whether to print progress messages. Default: inherits from getFuncOption("verbose").

**parallel** (logical) Whether to enable parallel permutations (requires `future::plan()` pre-set). Default: FALSE.

## Value

A list containing:

**scRNA\_data** A Seurat object with phenotype-associated cells labelled in `meta.data` column

**Some screen\_result** Important information about the screened result related to the selected method

## Data Matching Requirements

- `matched_bulk` column names and phenotype names/rownames must be identical
- Phenotype values must correspond to bulk samples (not directly to single cells)
- Mismatches will trigger an error before analysis begins, and there is a built-in pre-run check.

## Method Compatibility

| Method  | Supported Phenotypes | Additional Parameters                                                                                                                                                                                  |
|---------|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scissor | All three types      | <code>alpha</code> , <code>cutoff</code> , <code>path2load_scissor_cache</code> , <code>path2save_scissor_inputs</code> , <code>reliability_test</code> , <code>reliability</code>                     |
| scPP    | All three types      | <code>ref_group</code> , <code>Log2FC_cutoff</code> , <code>estimate_cutoff</code> , <code>probs</code>                                                                                                |
| scPAS   | All three types      | <code>n_components</code> , <code>assay</code> , <code>imputation</code> , <code>nfeature</code> , <code>alpha</code> , <code>network_class</code> , <code>permutation_times</code> , <code>FDR</code> |
| scAB    | Binary/Survival      | <code>alpha</code> , <code>alpha_2</code> , <code>maxiter</code> , <code>tred</code>                                                                                                                   |
| DEGAS   | All three types      | <code>sc_data.pheno_colname</code> , <code>select_fraction</code> , <code>tmp_dir</code> , <code>env_params</code> , <code>degas_params</code> , <code>normality_test</code>                           |
| LP_SGL  | All three types      | <code>resolution</code> , <code>alpha</code> , <code>nfold</code> , <code>dge_analysis</code>                                                                                                          |
| PIPET   | Binary/Continuous    | <code>group</code> , <code>discretize_method</code> , <code>cutoff</code> , <code>log2FC</code> , <code>p_adjust</code> , <code>show_log2FC</code> , <code>freq_counts</code> , <code>normalize</code> |

**See Also**

Associated functions:

- [DoScissor](#)
- [DoscPP](#)
- [DoscPAS](#)
- [DoscAB](#)
- [DoDEGAS](#)
- [DoLP\\_SGL](#)
- [DoPIPET](#)

---

|                    |                                                  |
|--------------------|--------------------------------------------------|
| ScreenFractionPlot | <i>Visualization of Cell Screening Fractions</i> |
|--------------------|--------------------------------------------------|

---

**Description**

Generates stacked bar plots showing the proportion of cells classified as Positive/Negative/Neutral by single-cell screening algorithms (Scissor, scPAS, scPP, or scAB) across different sample groups. Supports both single and multiple screen types visualization.

**Usage**

```
ScreenFractionPlot(
  screened_seurat,
  group_by = "Source", # x-axis label
  screen_type = NULL, # default: search all available screens
  show_null = FALSE,
  plot_color = NULL, # stack bar color of each status
  show_plot = FALSE,
  plot_title = "Screen Fraction",
  stack_width = 0.85,
  x_text_angle = 45,
  axis_linewidth = 0.8,
  legend_position = "right",
  x_lab = NULL,
  y_lab = "Fraction of Status",
  ncol = 2, # number of columns for facet wrap
  nrow = NULL, # number of rows for facet wrap
  verbose = SigBridgeRUtils::getFuncOption("verbose"),
  ... # ggplot2 theme arguments
)
```

**Arguments**

|                 |                                                                                                                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| screened_seurat | A Seurat object containing screening results in metadata. Must contain columns corresponding to screen_type.                                                                                     |
| group_by        | Metadata column name for grouping samples (default: "Source").                                                                                                                                   |
| screen_type     | Screening algorithm(s) used. Can be a single value or vector. Must match meta-data column(s) (case-sensitive, e.g., "scissor" for Scissor results).                                              |
| show_null       | Logical whether to show groups with zero cells (default: FALSE).                                                                                                                                 |
| plot_color      | Custom color palette (named vector format): - Required names: "Positive", "Negative", "Neutral" - Default: c("Neutral"="#CECECE", "Other"="#CECECE", "Positive"="#ff3333", "Negative"="#386c9b") |
| show_plot       | Logical to immediately display plot (default: TRUE).                                                                                                                                             |
| plot_title      | Plot title (default: "Screen Fraction"). When multiple screen types, can be a vector of titles or single title (will append screen type).                                                        |
| stack_width     | Bar width (default: 0.85).                                                                                                                                                                       |
| x_text_angle    | X-axis label angle (default: 45).                                                                                                                                                                |
| axis_linewidth  | Axis line thickness (default: 0.8).                                                                                                                                                              |
| legend_position | Legend position (default: "right").                                                                                                                                                              |
| x_lab           | X-axis label (default: NULL).                                                                                                                                                                    |
| y_lab           | Y-axis label (default: "Fraction of Status").                                                                                                                                                    |
| ncol            | Number of columns for facet wrap when multiple screen types (default: 2).                                                                                                                        |
| nrow            | Number of rows for facet wrap when multiple screen types (default: NULL).                                                                                                                        |
| verbose         | Logical, whether to print a message                                                                                                                                                              |
| ...             | Other arguments passed to ggplot2::theme()                                                                                                                                                       |

**Value**

A list containing:

- stats: A data frame (single screen) or list of data frames (multiple screens) with screening statistics including:
  - Grouping variable counts
  - Raw cell counts
  - Percentage fractions
- plot: A ggplot2 object (single screen) or list of ggplot2 objects (multiple screens)
- combined\_plot: A combined plot using patchwork (only for multiple screens)

**Visualization Details**

- Bars are ordered by descending Positive fraction
- Y-axis shows percentage (0-100%)
- Zero-fraction groups are automatically hidden unless show\_null=TRUE
- For multiple screen types, plots can be combined using patchwork

**See Also**

Other visualization\_function: [ScreenUpset\(\)](#)

**Examples**

```
## Not run:
# Single screen type usage
res <- ScreenFractionPlot(
  screened_seurat = scissor_result,
  group_by = "PatientID",
  screen_type = "scissor"
)

# Multiple screen types at once
multi_res <- ScreenFractionPlot(
  screened_seurat = multi_screened_result,
  group_by = "TissueType",
  screen_type = c("scissor", "scPAS", "scPP", "scAB", "DEGAS"),
  ncol = 2
)

## End(Not run)
```

---

ScreenStrategy

---

*Registry of Phenotype-Associated Cell Screening Methods*


---

**Description**

An environment storing methods for screening phenotype-associated cells.

**Usage**

```
ScreenStrategy
```

**Format**

An object of class environment of length 7.

**Details**

Storing structure - named list

- key: method name
- value: list
  - method\_name: method name
  - executor: function implementation of the method
  - phenotypes: The phenotype types supported by this method

- mapper: A function that transforms the parameters passed to the Screen function before forwarding them to the executor; both input and output must be of type list.

---

|             |                                                                                    |
|-------------|------------------------------------------------------------------------------------|
| ScreenUpset | <i>ScreenUpset - Visualize cell type intersections from screened Seurat object</i> |
|-------------|------------------------------------------------------------------------------------|

---

## Description

This function creates an UpSet plot to visualize intersections between different screening methods (e.g., scissor, scAB, scPAS, scPP) in a Seurat object metadata. It calculates all possible combinations of screening types and displays the number of cells positive for each combination.

## Usage

```
ScreenUpset(
  screened_seurat,
  screen_type = NULL,
  show_plot = FALSE,
  n_intersections = 20,
  x_lab = "Screen Set Intersections",
  y_lab = "Number of Cells",
  title = "Cell Counts Across Screen Set Intersections",
  bar_color = "#4E79A7",
  combmatrix_point_color = "black",
  verbose = SigBridgeRUtils::getFuncOption("verbose"),
  ...
)
```

## Arguments

|                        |                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------|
| screened_seurat        | A Seurat object containing screening results in metadata. Must contain columns with screening types marked as "Positive". |
| screen_type            | Character vector of screening types to analyze. Default: NULL, indicating that a self-search pattern will be used.        |
| show_plot              | Whether to show the upset plot. Default: FALSE                                                                            |
| n_intersections        | Number of intersections to display in the plot. Default: 20.                                                              |
| x_lab                  | Label for the x-axis. Default: "Screen Set Intersections".                                                                |
| y_lab                  | Label for the y-axis. Default: "Number of Cells".                                                                         |
| title                  | Plot title. Default: "Cell Counts Across Screen Set Intersections".                                                       |
| bar_color              | Color for the bars in the plot. Default: "#4E79A7".                                                                       |
| combmatrix_point_color | Color for points in the combination matrix. Default: "black".                                                             |

|         |                                                                                                   |
|---------|---------------------------------------------------------------------------------------------------|
| verbose | Logical, whether to print a message                                                               |
| ...     | Additional arguments passed to <code>ggplot2::theme()</code> for customizing the plot appearance. |

## Details

The function performs the following steps:

1. Validates input parameters and checks if specified screening types exist in metadata
2. Generates all possible combinations of screening types (from 1 to the total number of types)
3. Creates a logical matrix of positive cells for efficient computation
4. Calculates cell counts for each intersection using vectorized operations
5. Creates an UpSet plot visualization with customizable appearance

## Value

A list containing two elements:

- `plot`: A ggplot object displaying the UpSet plot
- `stats`: A data frame with intersection statistics including:
  - `intersection`: Name of the intersection
  - `sets`: List of screening types in the intersection
  - `count`: Number of cells positive for all screening types in the intersection

## See Also

Other visualization\_function: [ScreenFractionPlot\(\)](#)

## Examples

```
## Not run:
# Basic usage with default parameters
result <- ScreenUpset(screened_seurat = my_seurat_obj)

# Customize screening types and appearance
result <- ScreenUpset(
  screened_seurat = my_seurat_obj,
  screen_type = c("scissor", "scAB"),
  n_intersections = 15,
  title = "Custom Title",
  bar_color = "darkred"
)

## End(Not run)
```

---

setFuncOption*Configuration Functions for SigBridgeR Package*

---

## Description

These functions provide a centralized configuration system for the SigBridgeR package, allowing users to set and retrieve package-specific options with automatic naming conventions.

setFuncOption sets one or more configuration options for the SigBridgeR package. Options are automatically prefixed with "SigBridgeR." if not already present, ensuring proper namespace isolation.

getFuncOption retrieves configuration options for the SigBridgeR package. The function automatically handles the "SigBridgeR." prefix, allowing users to reference options with or without the explicit prefix.

checkFuncOption validates configuration options for the SigBridgeR package. This function ensures that all options meet type and value requirements before they are set in the global options.

## Usage

```
setFuncOption(...)
```

## Arguments

...                      Named arguments representing option-value pairs. Options can be provided with or without the "SigBridgeR." prefix. If the prefix is missing, it will be automatically added.

## Details

This function performs the following validations:

**verbose** Must be single logical values (TRUE/FALSE)

**timeout, seed** Must be single integer values

The function is automatically called by setFuncOption to ensure all configuration options are valid before they are set.

## Value

Invisibly returns NULL. The function is called for its side effects of setting package options.

The value of the specified option if it exists, otherwise the provided default value.

No return value. The function throws an error if the value doesn't meet the required specifications for the given option.

## Available Options

- **verbose**: A logical value indicating whether to print verbose messages, defaults to TRUE
- **timeout**: An integer specifying the timeout in seconds for parallel processing, defaults to '180L'
- **seed**: An integer specifying the random seed for reproducible results, defaults to '123L'

## Examples

```
# Set options with automatic prefixing
setFuncOption(verbose = TRUE)

# Retrieve options with automatic prefixing
getFuncOption("verbose")
```

---

SetupPyEnv

---

*Create or Use Python Environment with Required Packages*


---

## Description

Sets up a Python environment with specified packages for DEGAS screening methods. This function can create new environments or reuse existing ones, supporting both Conda and venv environment types. It ensures all required dependencies are properly installed and verified.

Default method for unsupported environment types. Throws an informative error with supported environment types.

## Usage

```
SetupPyEnv(env_type = c("conda", "venv"), ...)
```

## Arguments

|          |                                                                                                       |
|----------|-------------------------------------------------------------------------------------------------------|
| env_type | Character string specifying the type of Python environment to create or use. One of: "conda", "venv". |
| ...      | Additional parameters passed to specific environment methods.                                         |

## Details

This function provides a comprehensive solution for Python environment management in R projects, particularly for machine learning workflows requiring TensorFlow. Key features include:

- **Environment Creation**: Automatically creates new environments or reuses existing ones with the same name
- **Package Management**: Installs specified Python packages with version pinning support
- **Verification**: Validates environment setup and package installations
- **Flexible Methods**: Supports different backend methods for environment creation (reticulate vs system calls)

The function uses S3 method dispatch to handle different environment types, allowing for extensible support of additional environment managers in the future.

## Value

A data frame containing verification results for the environment setup, including installation status of all required packages. Invisibly returns the verification results.



See Also

[reticulate::conda\_create()], [reticulate::virtualenv\_create()] for underlying environment creation functions.

Examples

```
## Not run:
# Setup a Conda environment with default parameters
SetupPyEnv("conda")

# Setup a venv environment
SetupPyEnv("venv")

## End(Not run)
```

---

|               |                                                                                              |
|---------------|----------------------------------------------------------------------------------------------|
| SymbolConvert | <i>Convert Ensembles Version IDs &amp; TCGA Version IDs to Genes in Bulk Expression Data</i> |
|---------------|----------------------------------------------------------------------------------------------|

---

Description

Preprocess bulk expression data: convert Ensembles version IDs and TCGA version IDs to genes. NA values are replaced with unknown\_k format (k stands for the position of the NA value in the row).

Usage

```
SymbolConvert(
  data,
  unknown_format = "unknown_{k}",
  genome_build = c("hg38", "hg19", "mm10", "mm9"),
  verbose = SigBridgeUtils::getFuncOption("verbose"),
  ...
)
```

Arguments

|                |                                                                                                                                                                                          |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data           | bulk expression data (matrix or data.frame)                                                                                                                                              |
| unknown_format | A glue pattern containing {k} for replace the NA value during conversion. k must be wrapped in curly braces, stands for the position of the NA value in the row. Default: "unknown_{k}". |
| genome_build   | Genome build of the data. Default: "hg38".                                                                                                                                               |
| verbose        | Whether to print verbose messages. Default: TRUE.                                                                                                                                        |
| ...            | No usage                                                                                                                                                                                 |

---

|                    |                                                      |
|--------------------|------------------------------------------------------|
| ValidateScreenFunc | <i>Validate Custom Screening Function Compliance</i> |
|--------------------|------------------------------------------------------|

---

**Description**

Verifies if a user-provided function meets the interface requirements for the screening pipeline.

**Usage**

```
ValidateScreenFunc(func, ...)
```

**Arguments**

|      |                                                                                  |
|------|----------------------------------------------------------------------------------|
| func | Function to validate. Must accept core parameters and return expected structure. |
| ...  | For future updates                                                               |

**Value**

TRUE if all checks pass, otherwise terminates with diagnostic report

**Examples**

```
## Not run:
# Example compliant function
my_screen <- function(
  sc_data,
  matched_bulk,
  phenotype,
  label_type,
  phenotype_class,
  verbose = FALSE,
  ...
) {
  if (verbose) {
    message("Running custom screen")
  }
  list(
    scRNA_data = sc_data, # Must be Seurat object
    results = data.frame(score = runif(10))
  )
}

ValidateScreenFunc(my_screen)

## End(Not run)
```

# Index

- \* **DEGAS**
  - DoDEGAS, [10](#)
- \* **LP\_SGL**
  - DoLP\_SGL, [13](#)
- \* **PIPET**
  - DoPIPET, [15](#)
- \* **datasets**
  - ScreenStrategy, [44](#)
- \* **duplicate aggregation**
  - aggregate-dups, [5](#)
- \* **scAB**
  - DoscAB, [17](#)
- \* **scPAS**
  - DoscPAS, [21](#)
- \* **scPP**
  - DoscPP, [23](#)
- \* **scissor**
  - DoScissor, [18](#)
- \* **screen\_method**
  - DoDEGAS, [10](#)
  - DoLP\_SGL, [13](#)
  - DoPIPET, [15](#)
  - DoscAB, [17](#)
  - DoScissor, [18](#)
  - DoscPAS, [21](#)
  - DoscPP, [23](#)
- \* **single\_cell\_preprocess**
  - FindRobustElbow, [25](#)
  - Pattern2Colname, [30](#)
  - QCPatternDetect, [32](#)
  - SCPreProcess, [35](#)
- \* **visualization\_function**
  - ScreenFractionPlot, [42](#)
  - ScreenUpset, [45](#)
- AddMetaFeature, [3](#)
- AddMisc, [4](#)
- aggregate-dups, [5](#)
- AggregateDupCols, [5](#)
- AggregateDupCols (aggregate-dups), [5](#)
- AggregateDupRows, [5](#)
- AggregateDupRows (aggregate-dups), [5](#)
- AggregateDups, [5, 8](#)
- AggregateDups (aggregate-dups), [5](#)
- BulkPreProcess, [7](#)
- compatible\_with\_3.0.2, [25, 31, 33, 37](#)
- cor, [9](#)
- cpm, [9](#)
- DEGASEnvSet, [12](#)
- DEGASFindPy, [12](#)
- DEGASModelDetect, [12](#)
- DEGASParamSet, [12](#)
- DoDEGAS, [10, 14, 16, 18, 20, 22, 24, 42](#)
- DoLP\_SGL, [12, 13, 16, 18, 20, 22, 24, 42](#)
- DoPIPET, [12, 14, 15, 18, 20, 22, 24, 42](#)
- DoscAB, [12, 14, 16, 17, 20, 22, 24, 42](#)
- DoScissor, [12, 14, 16, 18, 18, 22, 24, 42](#)
- DoScissorCellEval, [20](#)
- DoScissorRelTest, [20](#)
- DoscPAS, [12, 14, 16, 18, 20, 21, 24, 42](#)
- DoscPP, [12, 14, 16, 18, 20, 22, 23, 42](#)
- FilterTumorCell, [25, 31, 33, 37](#)
- FindRobustElbow, [25, 31, 33, 37](#)
- getFuncOption, [26](#)
- ListPyEnv, [27](#)
- LoadRefData, [28](#)
- MergeResult, [29](#)
- Pattern2Colname, [25, 30, 33, 37](#)
- PercentageFeatureSet, [33](#)
- prcomp, [9](#)
- QCFilter, [31](#)
- QCPatternDetect, [25, 31, 32, 36, 37](#)

RegisterScreenMethod, [33](#)

SCPreProcess, [25](#), [31](#), [33](#), [35](#)

Screen, [38](#)

ScreenFractionPlot, [42](#), [46](#)

ScreenStrategy, [44](#)

ScreenUpset, [44](#), [45](#)

setFuncOption, [47](#)

SetupPyEnv, [48](#)

SymbolConvert, [9](#), [49](#)

ValidateScreenFunc, [50](#)