In [ ]:
```
#Wania Urooj Suleman CMSID:49178
!pip3 install beautifulsoup4
!pip3 install requests
```

In [2]:
```
import sys

import requests
from bs4 import BeautifulSoup
import re
import unicodedata
import pandas as pd
```

In [9]:
```
def date_time(table_cells):
    """
    This function returns the data and time from the HTML  table cell
    Input: the  element of a table data cell extracts extra row
    """
    return [data_time.strip() for data_time in list(table_cells.strings)][0:2]

def booster_version(table_cells):
    """
    This function returns the booster version from the HTML  table cell
    Input: the  element of a table data cell extracts extra row
    """
    out=''.join([booster_version for i,booster_version in enumerate( table_cells.strings) if i%2==0][0:-1])
    return out

def landing_status(table_cells):
    """
    This function returns the landing status from the HTML table cell
    Input: the  element of a table data cell extracts extra row
    """
    out=[i for i in table_cells.strings][0]
    return out
def get_mass(table_cells):
    mass=unicodedata.normalize("NFKD", table_cells.text).strip()
    if mass:
        mass.find("kg")
        new_mass=mass[0:mass.find("kg")+2]
    else:
        new_mass=0
    return new_mass


def extract_column_from_header(row):
    """
    This function returns the landing status from the HTML table cell
    Input: the  element of a table data cell extracts extra row
    """
    if (row.br):
        row.br.extract()
    if row.a:
        row.a.extract()
    if row.sup:
        row.sup.extract()

    colunm_name = ' '.join(row.contents)
    # Filter the digit and empty names
    if not(colunm_name.strip().isdigit()):
        colunm_name = colunm_name.strip()
        return colunm_name
```

In [10]:
```
static_url = "https://en.wikipedia.org/w/index.php?title=List_of_Falcon_9_and_Falcon_Heavy_launches&oldid=1027686922"
response = requests.get(static_url)
soup = BeautifulSoup(response.content, 'html.parser')
soup.title
```

Out[10]:
```
<title>List of Falcon 9 and Falcon Heavy launches - Wikipedia</title>
```

In [11]:
```
html_tables = soup.find_all('table')
first_launch_table = html_tables[2]
print(first_launch_table)
```

```
<table class="wikitable plainrowheaders collapsible" style="width: 100%;">
<tbody><tr>
<th scope="col">Flight No.
</th>
<th scope="col">Date and<br/>time (<a href="/wiki/Coordinated_Universal_Time" title="Coordinated Universal Time">UTC</a>)
</th>
<th scope="col"><a href="/wiki/List_of_Falcon_9_first-stage_boosters" title="List of Falcon 9 first-stage boosters">Version,<br/>Booster</a> <sup class="refer
ence" id="cite_ref-booster_11-0"><a href="#cite_note-booster-11">[b]</a></sup>
</th>
<th scope="col">Launch site
</th>
<th scope="col">Payload<sup class="reference" id="cite_ref-Dragon_12-0"><a href="#cite_note-Dragon-12">[c]</a></sup>
</th>
<th scope="col">Payload mass
</th>
<th scope="col">Orbit
</th>
<th scope="col">Customer
</th>
```

In [12]:
```
column_names = []
flt = first_launch_table.find_all('th')
for row in flt:
    name = extract_column_from_header(row)
    if name is not None and len(name) > 0:
        column_names.append(name)
print(column_names)
```

```
['Flight No.', 'Date and time ( )', 'Launch site', 'Payload', 'Payload mass', 'Orbit', 'Customer', 'Launch outcome']
```

In [13]:
```
launch_dict= dict.fromkeys(column_names)
del launch_dict['Date and time ( )']
launch_dict['Flight No.'] = []
launch_dict['Launch site'] = []
launch_dict['Payload'] = []
launch_dict['Payload mass'] = []
launch_dict['Orbit'] = []
launch_dict['Customer'] = []
launch_dict['Launch outcome'] = []
launch_dict['Version Booster']=[]
launch_dict['Booster landing']=[]
launch_dict['Date']=[]
launch_dict['Time']=[]
extracted_row = 0
for table_number,table in enumerate(soup.find_all('table',"wikitable plainrowheaders collapsible")):
    for rows in table.find_all("tr"):
        if rows.th:
            if rows.th.string:
                flight_number=rows.th.string.strip()
                flag=flight_number.isdigit()
        else:
            flag=False
        row=rows.find_all('td')
        if flag:
            extracted_row += 1
            datatimelist=date_time(row[0])
            date = datatimelist[0].strip(',')
            time = datatimelist[1]
            bv=booster_version(row[1])
            if not(bv):
                bv=row[1].a.string
            print(bv)
            launch_site = row[2].a.string
            payload = row[3].a.string
            payload_mass = get_mass(row[4])
            orbit = row[5].a.string
            customer = row[6].a.string
            launch_outcome = list(row[7].strings)[0]
            booster_landing = landing_status(row[8])
```

```
F9 v1.0B0003.1
F9 v1.0B0004.1
F9 v1.0B0005.1
F9 v1.0B0006.1
F9 v1.0B0007.1
F9 v1.1B1003
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
F9 v1.1
```