

Martin Matrix Array Block

MARTIN MATRIX ARRAY BLOCK

$$[a,b] = a^b$$

chief (a), the first number in the Array.

crew (b), second number in the Array after chief

$$[a,b,c] = a (\uparrow^c) b / [a,b,2] = a \uparrow \uparrow b$$

co-worker (c) third entry in the array after crew, strictly greater than 1.

$$[a,b,c,d] =$$

dung (d) is the fourth entry in the array after co-worker, If the dung and crew is greater than 1, say $[3,2,1,3]$, first reduce crew by 1 then substitute the array by nesting the first array to c, then reduce dung and crew by 1 from outer array, Apply rule 2 first before Rule 4, Then:

$$[3,2,1,3] \rightarrow [3,2,[3,3,3],2] \rightarrow \text{so on}$$

$$[a,b,c,d,e] =$$

customer(e) is the fifth entry in the array after dung, if Customer is greater than 1, then Reduce by 1 and make an inner array replacing Dung, reduce crew in the inner Array By 1, Reduce Coworker in the outer array by 1, $[a,b,c,d,e] \rightarrow [a,b,c-1,[a,b-1,c,d,e],e-1]$, More entries after customer will only be fuel for Customer.

Super Printer $\{n^\circ\}$:

an operator in an array,

$$\text{If } n = 1 \text{ or just } \{^\circ\}: [a,b,c,d,\{^\circ\}] \rightarrow [a,b,c,d,[a,b,c,d-1]]$$

if $n \geq 2$, then create a matrix block with n copy in rows and in collumn:

$$B_0 = (\{[a,b,c,d,[a,b,c,d-1]], [b[a,b,c,d,[a,b,c,d-1]], \{c\}, \{d\}, \dots \text{ n-th Rows Copy}$$

$$\{[a,b,c[a,b,c,d-1]], \{b\}, \{c\}, \{d\}, \dots \text{ n-th Rows Copy}$$

$$\dots \text{ n-th Column Copy}).$$

This means Output of First Row Calculation will be used to add Every Main Array In the Second Row Of Array Blocks, Like $B_0 = (\{a[10]\}, \{a[a,b,c[a,b,c,d]]\})$ It's Both a Because They're different Rows.

This Means First Row Array Block Output is 10, Then $\rightarrow B_0 = (\{a[a+10, b+10, c+10, d+10, [a+10, b+10, d+10]]\})$

Martin Matrix Array Block

Super printer print and added as the next entry, like $[a, \{^\circ\}]$, it'll will be the next entry which is Crew entry, $[a, [a-1]]$.

B_0 is the Main Matrix Block that's able to contain (n) amount of Super Printed Arrays.

example:

$B_0 = (\{a\}, \{b\}) = \{a\}^{\{b\}}$, $(\{a\}, \{b\}, \{c\}) = \{a\} \uparrow \{c\}^{\{b\}}$, and so on Like a normal Main array of n entries.

where $\{a\}$ = Chief Array $\{a\}$, $\{b\}$ = Crew Array $\{b\}$, $\{c\}$ = Co-worker Array $\{c\}$, $\{d\}, \{e\}, \rightarrow$ t-th Array.

$[a, b, c, d]$ = Main Array, Element of Array Block

$(\{a\}, \{b\}, \{c\}, \{d\})$ = Array Blocks, Element of Matrix Block

B_n = Matrix Blocks

$\{\mid\}$ Super Super Printer

Written Inside Super Printer's Parentheses, Like $\{\{^\circ\} \mid\}$, this Means "Copy the Main Array, The Result Of the Calculation Now Make the Super Printer Copy The Main Array Again By The Amount of The Calculation",
Like $[2, 3, \{^\circ\} \mid] = [2, 3, [2, 2]] = 2 \uparrow \uparrow \uparrow \uparrow 3 \rightarrow [2, 3, [2 \uparrow \uparrow \uparrow \uparrow 3^\circ \mid]]$

Doubling it to $\{\mid \mid\}$ Will only Means Use V1 For First Output then add it to Again $\{^\circ \mid\}$, Basically Iterating.

Martin Matrix Array Block

{_} Higher Degree Printer

This Print Matrix Blocks And Creates a Higher Degree Matrix Blocks By the Amount of Main Array/Array Block Calculations Output, higher matrix will, Written at the rightmost Before Super Printer {° }, Like $[2, \{ _ \}] = B_0 = (\{2\}) \rightarrow C_0 = (\{B_0(2), B_1(2)\}) \rightarrow C_0 = (\{B_0(4)\})$.

Matrix Block Operation Is Like Main Array Operation, Where $\{B_0\} = \{B_0\}$, $\{B_0\}$, $\{B_1\} = \{B_0\} \wedge \{B_1\}$, So on until n-th entry of Matrix Block

Adding More {_} Means Going to Higher Degree Matrix Block, Like from B_n Matrix To C_n Matrix, Like $[2, \{ _ \}] \rightarrow D_0 = (\{C_0(\{B_0(2), B_1(1)\}), \{C_1(\{B_0(2), B_1(1)\})\}, \{C_3(\{B_0(2), B_1(1)\})\}, \{C_4(\{B_0(2), B_1(1)\})\})$ Calculate Matrix Block B First, Then The Calculation Value Of B Matrix Blocks Will Be The Copy Amount of Outer Matrix Blocks, Like if B Matrix = 256, and There's 2 HDP {_,}, Copy C Blocks 256 Times, from C_0 To C_255 Inside Matrix Block D_0, Each C Matrix Countains 256 As It's Main Value And Calculate Until you get the X value of C, then $D_0 = (\{X\})$

You Can Add {||} To Higher Degree Printer {_,}, like {_|} Means The Result Of Matrix Block C will Be Used Again as the next Amount of HDP in the main Arrays, Like If $[2, \{ _ | \}] = C_0 = (\{4\}) \rightarrow [2, \{ _ _ \}]$. The Same Way As More {||} In {° }, More {||} In {_,} Will Make Thr Previous Output As The Amount Of {_,}.

Wage {::}

Written Inside Parentheses Of {°} Or {_,}, This Is To Print Super Super Printer {||} Based On The Value Of Chief, Array Chief, or Matrix Chief After first Calculation Value, Like $[3, \{^\circ : \}] = [3, [2]] = 9 = [3, \{9^\circ | ^9, 9 \text{ super super printers}\}]$, Double Wage, Like $[3, \{^\circ :: \}]$ Means The Next Value Of Chief after calculation, Will Be Used By the first {::}, Like $[2, \{^\circ :: \}] = [2, \{4^\circ || | | : \}] \rightarrow \text{Until } V_n \text{ After Iterations} \rightarrow [2, \{V_n^\circ : \}] = [2, \{V_n^\circ | ^{V_n} \text{ Amount of Super Super Printers}\}]$, Super Printer {° } Will Stop Being Used Again After All {||} Or {::} Sequence and Iterations Output Last Value And There's no More Iteration Need to Be Done, Like $[1, \{^\circ || \}] =$ Must Calculate, Iterate Output, Then Use {°} One More Time With The Last Output From Iteration Before Stop Adding {°}, Works The Same With Many {°}'s

Wage Raiser {;}

Basically Amount Of {::} Inside {°} Or {_,} Based On Chief Value After First Calculation.

Martin Matrix Array Block

Promotion {~}

Basically Amount Of {;} Inside {°} Or {□} Based On Chief Value After First Calculation.

Higher Degree Promotion {#}

Basically Amount Of {~} Inside {°} Or {□} Based On Chief Value After First Calculation.

Top Rank Director {*}

Basically Amount Of {#} Inside {°} Or {□} Based On Chief Value After First Calculation.

Martin Matrix Array Block

Rule 1 (1st priority) : Syntax Is Important, Rightmost Will always be Super Printer, Second Rightmost Will Always Be Higher Degree Printer, Writing Main Array In Non Standart Syntax, E.g [operator, a,b,c,d] Or [a,b,c,Operator,d], Like [a,b,c,{°},d] or [{°},a,b,c,d] Are Wrong, Same Way [a,b,c,d,{°}{_}] Is also wrong, entries must have non zero positive integer values

Rule 2 (2nd Priority) : Evaluate Sub arrays/inner arrays first, then outer arrays, then Array Blocks(up to bottom), then Inner Matrix Blocks To Outer Matrix.

Rule 3 (3rd Priority) = Applied before any nesting, any entry from Crew to T-th number, if there exists a number that's =1 And then there's a number right to it = 2, it's labeled as a pair, now the left number is added by the right number, Like [2,2,2,1,2] → [2,2,2,3,1], the Right number is reduced by 1, But If there's a number that = 1, and the number right to it is > 2, Make an Array with Amount of Entry and Value Equal to The Amount of the Right number, then replace the left number with the array, Reduce the right number by 1 after, like [2,2,2,1,3] → [2,2,2,[3,3,3],2] →, scan from Right to Left until there's no 1s or a 1 with number >1 right to it

Rule 4 (4th priority): Use {°|}/{°:}/{°;}/{°~}/{°#}/{°*} First, Then {_}/{_|}/{_:}/{_;}/{_~}/{_#}/{_*}

Rule 5 = [a] = a, [a,b] = a^b, [a,b,c] = a ↑ c b, [a,b,c,d] = [a,b-1[a,b-1,c,d],d-1], [a,b,c,d,e] = [a,b,c-1,[a,b-1,c,d,e],e-1].

Rule 6 : [a,b,c,d....j, 1] = [a,b,c,d....t], Remove 1 At the end of the row

Rule 7 : If Crew is 1 And no Next Number that's >1 Then the answer is Chief