

Conditional Rendering in React JS

What is Conditional Rendering?

Conditional rendering means showing different UI based on conditions.

Example:

- User logged in → show Dashboard
- User not logged in → show Login page

Types of Conditional Rendering

1. `if / else`
2. Ternary Operator
3. Logical AND (&&) , OR , etc

Rendering Lists in React JS

What is List Rendering?

List rendering means displaying multiple items using `.map()`.

Real Life Example

E-commerce websites like Amazon show products using lists.

Code Example

```

function Product() {
  const myproducts = [
    { id: 1, name: "Laptop", price: 120000, color: "Silver" },
    { id: 2, name: "iPhone", price: 250000, color: "Black" },
    { id: 3, name: "Android", price: 80000, color: "Blue" }
  ];
  return (
    <div>
      <h1>Product List</h1>
      {myproducts.map((product) => (
        <div key={product.id} className="productCard">
          <h2 className="title">{product.name}</h2>
          <p>Price: {product.price}</p>
          <p>Color: {product.color}</p>
        </div>
      ))}
    </div>
  );
}

export default Product;

```

External CSS (App.css)

```

/* GLOBAL */
body {
  background: linear-gradient(135deg, #eef2f7, #dbeafe);
  font-family: "Segoe UI", sans-serif;
  margin: 0;
  padding: 0;
}

/* PAGE TITLE */
h1 {
  text-align: center;
  font-size: 34px;
  margin: 30px 0;
  color: #0f172a;
  letter-spacing: 1px;
}

/* CONTAINER */

```

```
div {
  display: flex;
  flex-wrap: wrap;
  justify-content: center;
  gap: 20px;
  padding: 10px;
}

/* PRODUCT CARD */
.productCard {
  background: #ffffff;
  border-radius: 16px;
  padding: 18px;
  width: 260px;
  box-shadow: 0 10px 25px rgba(0, 0, 0, 0.08);
  transition: all 0.3s ease;
  position: relative;
  overflow: hidden;
}

/* TOP COLOR BAR (premium look) */
.productCard::before {
  content: "";
  position: absolute;
  top: 0;
  left: 0;
  height: 4px;
  width: 100%;
  background: linear-gradient(90deg, #3b82f6, #9333ea);
}

/* HOVER EFFECT */
.productCard:hover {
  transform: translateY(-8px) scale(1.02);
  box-shadow: 0 15px 35px rgba(0, 0, 0, 0.15);
}

/* TITLE */
.title {
  font-size: 20px;
  font-weight: 700;
  color: #1d4ed8;
  margin-bottom: 10px;
}
```

```
/* TEXT */
p {
  margin: 6px 0;
  color: #475569;
  font-size: 14px;
}

/* PRICE HIGHLIGHT (extra styling) */
.productCard p:nth-child(3) {
  font-weight: bold;
  color: #16a34a;
}
```

App.jsx

```
import './App.css';
import Product from './Components/Product';

function App(){
  return(
    <>
      <Product/>

    </>
  )
}
export default App;
```

Events in React JS

What are Events?

Events are user actions like click, typing, submit, etc.

Click Event Example

```
function ClickEvent() {  
  
  function handleClick() {  
    alert("Button clicked!");  
  }  
  
  return (  
    <div>  
      <h2>Click Event Example</h2>  
  
      <button onClick={handleClick}>  
        Click Me  
      </button>  
    </div>  
  );  
}  
  
export default ClickEvent;
```

Input Event Example

```
import { useState } from "react";  
  
function InputEvent() {  
  const [text, setText] = useState("");  
  function handleChange(e) {  
    setText(e.target.value);  
  }  
  
  return (  
    <div>  
      <h2>Input Event Example</h2>  
      <input type="text" onChange={handleChange} />  
      <p>You typed: {text}</p>  
    </div>  
  );  
}
```

```
}  
export default InputEvent;
```

Summary

- Conditional rendering controls UI based on conditions
- List rendering uses `.map()` to show multiple items
- External CSS goes in `App.css` and is imported in `React`
- Events handle user interactions like click and input