

Conditional Rendering in React

JS What is Conditional Rendering?

Conditional rendering means showing different UI based on conditions.

Example:

- User logged in → show Dashboard
- User not logged in → show Login page

Types of Conditional Rendering

1. `if / else`
2. Ternary Operator
3. Logical AND (`&&`) , OR , etc

Rendering Lists in React JS

What is List Rendering?

List rendering means displaying multiple items using `.map()`.

Real Life Example

E-commerce websites like Amazon show products using lists.

Code Example

```
function Product() {  
  const myproducts = [  
    { id: 1, name: "Laptop", price: 120000, color: "Silver"  
  }, { id: 2, name: "iPhone", price: 250000, color: "Black"  
  }, { id: 3, name: "Android", price: 80000, color: "Blue" }  
  ];  
  return (  
    <div>  
      <h1>Product List</h1>  
      {myproducts.map((product) => (  
        <div key={product.id}  
          className="productCard"> <h2  
            className="title">{product.name}</h2>  
            <p>Price: {product.price}</p>  
            <p>Color: {product.color}</p>  
          </div>  
        ))}  
      </div>  
    );  
  }  
}  
  
export default Product;
```

External CSS (App.css)

```
/* GLOBAL */  
body {  
  background: linear-gradient(135deg, #eef2f7,  
    #dbeafe); font-family: "Segoe UI", sans-serif;  
  margin: 0;  
  padding: 0;  
}  
  
/* PAGE TITLE */  
h1 {  
  text-align: center;
```

```
font-size: 34px;
margin: 30px 0;
color: #0f172a;
letter-spacing: 1px;
}
```

```
/* CONTAINER */
div {
display: flex;
flex-wrap: wrap;
justify-content: center;
gap: 20px;
padding: 10px;
}
```

```
/* PRODUCT CARD */
.productCard {
background: #ffffff;
border-radius: 16px;
padding: 18px;
width: 260px;
box-shadow: 0 10px 25px rgba(0, 0, 0, 0.08);
transition: all 0.3s ease;
position: relative;
overflow: hidden;
}
```

```
/* TOP COLOR BAR (premium look) */
.productCard::before {
content: "";
position: absolute;
top: 0;
left: 0;
height: 4px;
width: 100%;
background: linear-gradient(90deg, #3b82f6,
#9333ea);
}
```

```
/* HOVER EFFECT */
.productCard:hover {
transform: translateY(-8px) scale(1.02);
box-shadow: 0 15px 35px rgba(0, 0, 0, 0.15);
}
```

```

/* TITLE */
.title {
  font-size: 20px;
  font-weight: 700;
  color: #1d4ed8;
  margin-bottom: 10px;
}
/* TEXT */
p {
  margin: 6px 0;
  color: #475569;
  font-size: 14px;
}

/* PRICE HIGHLIGHT (extra styling) */
.productCard p:nth-child(3) {
  font-weight: bold;
  color: #16a34a;
}

```

App.jsx

```

import './App.css';

import Product from './Components/Product';

function App(){
  return(
    <>
    <Product/>

    </>
  )
}

export default App;

```

Events in React JS

What are Events?

Events are user actions like click, typing, submit, etc.

Click Event Example

```
function ClickEvent() {  
  
  function handleClick() {  
    alert("Button clicked!");  
  }  
  
  return (  
    <div>  
      <h2>Click Event Example</h2>  
  
      <button onClick={handleClick}>  
        Click Me  
      </button>  
    </div>  
  );  
}  
  
export default ClickEvent;
```

Input Event Example

```
import { useState } from "react";  
  
function InputEvent() {  
  const [text, setText] = useState("");  
  function handleChange(e) {  
    setText(e.target.value);  
  }  
  
  return (  

```

```
<div>
  <h2>Input Event Example</h2>
  <input type="text" onChange={handleChange}
  /> <p>You typed: {text}</p>
</div>
);
}
export default InputEvent;
```

Summary

- Conditional rendering controls UI based on conditions •
- List rendering uses .map() to show multiple items •
- External CSS goes in App.css and is imported in React •
- Events handle user interactions like click and input