

Question 1. What happens if you use an undeclared variable?

Multiple: ☐

```
console.log(x); // x not declared
```

1. It creates a global variable ☐
2. It throws an error ☒
3. It becomes null ☐
4. It becomes undefined ☐



Question 2. Which character is NOT allowed in a variable name?

Multiple: ☐

// No code Reference provided

1. _ ☐
2. \$ ☐
3. - ☒
4. A ☐



Question 3. What is the value of y after this code runs: var x = 10; var y = x + 5;

Multiple: ☐

```
var x = 10; var y = x + 5;
```

1. 15 ☒
2. 105 ☐
3. 10+5 ☐
4. NaN ☐



Question 4. Can a variable be reassigned a different type?

Multiple: ☐

```
var a = 5; a = "five";
```

1. No, it's fixed ☐
2. Yes, in strict mode ☐
3. Yes, JavaScript is loosely typed ☒
4. Only with let ☐



Question 5. Which of the following is a legal variable name?

Multiple: ☐

// No code Reference provided

1. 123name ☐
2. user-name ☐
3. \$value ☒
4. my variable ☐



Question 6. Which variable name follows camelCase convention?

Multiple: ☐

// No code Reference provided

1. UserName ☐
2. user_name ☐
3. userName ☒
4. username ☐



Question 7. Which symbol is used for assignment in JavaScript?

Multiple: ☐

```
var x = 5;
```

1. = ☒
2. == ☐
3. === ☐
4. := ☐



Question 8. How do you assign a string to a variable?

Multiple: ☐

// No code Reference provided

1. var a = John; ☐
2. a = "John"; ☐
3. let a = John; ☐
4. var a = "John"; ☒



Question 9. What value does a variable hold before it is assigned?

Multiple: ☐

```
var a;  
console.log(a);
```

1. 0
2. null
3. undefined
4. empty



Question 10. Which keyword is used to declare a variable in JavaScript?

Multiple: ☐

// No code reference provided

1. var
2. int
3. letvar
4. define



Question 11. What is the output of:

Multiple: ☐

```
for (let i = 0; i < 3; i++) {  
  console.log(i);  
}
```

1. 0 1 2
2. 1 2 3
3. 0 1 2 3
4. Error



Question 12. Which part of the for loop updates the loop control variable?

Multiple: ☐

// No code reference provided

1. i=0
2. i < 5
3. i++
4. Loop Body



Question 13. What is a nested loop?

Multiple: ☐

// No code reference provided

1. A loop that runs randomly
2. A loop with a condition
3. A loop inside another loop
4. A loop that stops suddenly



Question 14. What is a common name for the loop control variable?

Multiple: ☐

```
for (let i = 0; i < n; i++)
```

1. index
2. x
3. i
4. loop



Question 15. Which statement correctly sets up a for loop to iterate 5 times?

Multiple: ☐

```
for (i = 0; i < 5; i++)
```

1. for (i = 0; i < 5; i++)
2. for (i = 1; i <= 5; i++)
3. for (i = 0; i <= 4; i++)
4. All of the above



Question 16. What value type is best used for a matchFound flag in loops?

Multiple: ☐

```
var matchFound = false;
```

1. Number
2. Boolean
3. String
4. Array



Question 17. Which property returns the number of elements in an array? Multiple: ☐

// No code Reference provided

1. .total ☐
2. .index ☐
3. .size ☐
4. .length ☒



Question 18. What is the purpose of a for loop in JavaScript? Multiple: ☐

```
for (let i = 0; i < 5; i++) { console.log(i); }
```

1. To declare variables ☐
2. To repeatedly execute a block of code ☒
3. To create arrays ☐
4. To handle events ☐



Question 19. What keyword is used to exit a for loop early? Multiple: ☐

// No code Reference provided

1. return ☐
2. stop ☐
3. break ☒
4. exit ☐



Question 20. What does the loop variable typically start at in a for loop? Multiple: ☐

```
for (let i = 0; i <= 4; i++)
```

1. 1 ☐
2. undefined ☐
3. 0 ☒
4. 10 ☐



Question 21. What is the correct way to test multiple conditions together in JavaScript? Multiple: ☐

// No code Reference provided

1. Using && and || ☒
2. Using for and if ☐
3. Using switch only ☐
4. Using == only ☐



Question 22. What is the primary purpose of comparison operators? Multiple: ☐

// No code Reference provided

1. To assign values ☐
2. To join strings ☐
3. To evaluate conditions ☒
4. To declare variables ☐



Question 23. Which statement checks if a value is either 10 or 20? Multiple: ☐

// No code Reference provided

1. if (val == 10 && 20) ☐
2. if (val == 10 || val == 20) ☒
3. if (val = 10 || 20) ☐
4. if (val === 10 or 20) ☐



Question 24. Which symbol is used for logical AND in JavaScript? Multiple: ☐

// No code Reference provided

1. || ☐
2. && ☒
3. & ☐
4. | ☐



Question 25. In JavaScript, which keyword is used for alternative logic when an if condition fails?

Multiple: ☐

// No code Reference provided

1. else ☒
2. elif ☐
3. otherwise ☐
4. switch ☐



Question 26. What is the output of: if (false || true)?

Multiple: ☐

// No code Reference provided

1. false ☐
2. true ☒
3. undefined ☐
4. error ☐



Question 27. What is the result of '5' === 5 in JavaScript?

Multiple: ☐

// No code Reference provided

1. true ☐
2. false ☒
3. error ☐
4. undefined ☐



Question 28. What happens if the condition in an if statement is false and there is no else block?

Multiple: ☐

// No code Reference provided

1. The script crashes ☐
2. The if block is still executed ☐
3. Nothing happens ☒
4. An error is thrown ☐



Question 29. Which of the following is a strict equality operator?

Multiple: ☐

// No code Reference provided

1. == ☐
2. === ☒
3. = ☐
4. != ☐



Question 30. Which of the following statements correctly checks if a number is not equal to 10?

Multiple: ☐

// No code Reference provided

1. if (num != 10) ☒
2. if (num <> 10) ☐
3. if (num =! 10) ☐
4. if (num !== 10) ☐



Question 31. What is a nested for loop?

Multiple: ☐

// No code Reference provided

1. A loop that breaks early ☐
2. Two loops running together ☐
3. A loop inside another loop ☒
4. A loop using strings ☐



Question 32. What is a for loop used for?

Multiple: ☐

// No code Reference provided

1. To declare variables ☐
2. To execute a block once ☐
3. To repeat a block of code ☒
4. To debug code ☐



Question 33. What value type is best for flags in loops?

Multiple: ☐

// no code reference provided

1. Integer
2. Boolean
3. String
4. Array



Question 34. What is an array?

Multiple: ☐

// no code reference provided

1. A single variable
2. A data type that holds true/false
3. A variable holding multiple values
4. A type of function



Question 35. Which method removes the first element of an array?

Multiple: ☐

// no code reference provided

1. shift()
2. unshift()
3. pop()
4. splice()



Question 36. Which method adds an item to the end of an array?

Multiple: ☐

// no code reference provided

1. unshift()
2. push()
3. pop()
4. shift()




Question 37. What does '&&' represent?

Multiple: ☐

// no code reference provided

1. OR condition
2. AND condition
3. NOT condition
4. XOR condition



Question 38. Which statement executes when a condition is false in an if statement?

Multiple: ☐

// no code reference provided

1. elseif
2. or
3. else
4. break



Question 39. What is nesting in if statements?

Multiple: ☐

// no code reference provided

1. Using if inside if
2. Calling functions
3. Using arrays inside if
4. Using variables inside if



Question 40. What keyword starts an if statement?

Multiple: ☐

Chapter 18

1. when
2. check
3. if
4. for



Question 41. Which operator means 'not equal'?

Multiple: ☐

// No code reference provided

- 1. != ☐
- 2. == ☐
- 3. !== ☒
- 4. <> ☐



Question 42. What does the '++' operator do?

Multiple: ☐

// No code reference provided

- 1. Adds 2 to the variable ☐
- 2. Increments the variable by 1 ☒
- 3. Multiplies the variable by 2 ☐
- 4. No operation ☐



Question 43. How can you control precedence in complex expressions?

Multiple: ☐

// No code reference provided

- 1. Using semicolons ☐
- 2. Using curly braces ☐
- 3. Using parentheses ☒
- 4. Using commas ☐



Question 44. Which operator is used to concatenate text strings?

Multiple: ☐

// No code reference provided

- 1. + ☒
- 2. & ☐
- 3. * ☐
- 4. % ☐



Question 45. What does prompt() do in JavaScript?

Multiple: ☐

// No code reference provided

- 1. Displays a confirmation box ☐
- 2. Asks the user for input ☒
- 3. Shows a warning ☐
- 4. Writes a message to the console ☐



Question 46. Which of the following is a valid way to declare a number variable?

Multiple: ☐

// No code reference provided

- 1. var age = "30"; ☐
- 2. var age = 30; ☒
- 3. num age = 30; ☐
- 4. var age: 30; ☐



Question 47. Which of the following is an illegal variable name?

Multiple: ☐

// No code reference provided

- 1. first_name ☐
- 2. 1stName ☒
- 3. \$name ☐
- 4. userName ☐



Question 48. What does the modulus operator (%) do?

Multiple: ☐

// No code reference provided

- 1. Divides two numbers ☐
- 2. Returns the quotient ☐
- 3. Returns the remainder ☒
- 4. Performs exponentiation ☐



Question 49. What does the alert() function do in JavaScript?

Multiple: ☐

// No code reference provided

1. Logs a message to the console ☐
2. Displays a message box to the user ☒
3. Writes to the document ☐
4. Sends an email ☐



Question 50. Which keyword is used to declare a variable in JavaScript?

Multiple: ☐

// No code reference provided

1. dim ☐
2. var ☒
3. declare ☐
4. letvar ☐



Question 51. Which method removes the first element from an array?

Multiple: ☐

// No code reference provided

1. arr.shift() ☒
2. arr.pop() ☐
3. arr.remove() ☐
4. arr.delete() ☐



Question 52. What will arr.pop() do in JavaScript?

Multiple: ☐

// No code reference provided

1. Removes the last element from an array ☒
2. Adds an element at the end of the array ☐
3. Removes the first element from the array ☐
4. Adds an element at the beginning of the array ☐



Question 53. What is the result of the following code?

Multiple: ☐

```
var x = 10;
var y = 20;
if (x > y) {
  console.log("true");
} else {
  console.log("false");
}
```

1. TRUE ☐
2. FALSE ☒
3. NaN ☐
4. undefined ☐



Question 54. What does the following code output? Multiple: ☐

```
var x = 10;
if (x > 5) {
  console.log("Greater");
} else {
  console.log("Smaller");
}
```

1. Smaller ☐
2. Greater ☒
3. NaN ☐
4. undefined ☐



Question 55. Which keyword is used to test multiple conditions in a single statement?

Multiple: ☐

// No code reference provided

1. else ☐
2. for ☐
3. else if ☒
4. case ☐



Question 56. What is the correct syntax for an if statement in JavaScript?

Multiple: ☐

// No code reference provided

1. if x > 5 then ☐
2. if {x > 5} {} ☒
3. if x > 5 {} ☐
4. if (x > 5): ☐



Question 57. Which statement is used to execute code only if a certain condition is true?

Multiple: ☐

// No code reference provided

1. if
2. switch
3. else
4. case



Question 58. What will be the result of:

Multiple: ☐

```
var arr = [1, 2, 3];  
arr.length;
```

1. 3
2. 2
3. 4
4. undefined



Question 59. How do you remove the last item from an array in JavaScript?

Multiple: ☐

// No code reference provided

1. arr.pop();
2. arr.remove();
3. arr.delete();
4. arr.shift();



Question 60. What will be the output of the following code?

Multiple: ☐

```
var arr = [1, 2, 3];  
alert(arr[1]);
```

1. 1
2. 2
3. 3
4. undefined



Question 61. How do you create an array in JavaScript?

Multiple: ☐

// No code reference provided

1. var arr = [1, 2, 3];
2. var arr = {1, 2, 3};
3. var arr = {1, 2, 3};
4. var arr = 1, 2, 3;



Question 62. How can you add an item to the end of an array in JavaScript?

Multiple: ☐

// No code reference provided

1. arr.push(item);
2. arr.add(item);
3. arr.append(item);
4. arr.insert(item);



Question 63. What will be the output of the following code?

Multiple: ☐

```
for (let i = 0; i < 3; i++) {  
  console.log(i);  
}
```

1. 0 1 2
2. 1 2 3
3. 0 1 2 3
4. 1 2



Question 64. Which loop is used to iterate over a block of code a specified number of times?

Multiple: ☐

// No code reference provided

1. if
2. for
3. while
4. switch



Question 65. What does the % operator do in JavaScript?

Multiple: ☐

// No code reference provided

1. Divides two numbers ☐
2. Returns the remainder of a division operation ☒
3. Adds two numbers ☐
4. Multiplies two numbers ☐



Question 66. Which of the following is correct syntax to subtract numbers in JavaScript?

Multiple: ☐

// No code reference provided

1. 10 minus 5 ☐
2. 10 - 5 ☒
3. subtract(10, 5) ☐
4. 10 subtract 5 ☐



Question 67. Which operator is used for multiplication in JavaScript?

Multiple: ☐

// No code reference provided

1. * ☒
2. x ☐
3. @ ☐
4. *= ☐



Question 68. What will be the result of 10 / 2?

Multiple: ☐

// No code reference provided

1. 5 ☒
2. 2 ☐
3. 20 ☐
4. 1 ☐



Question 69. What will 10 + 5 evaluate to in JavaScript?

Multiple: ☐

// No code reference provided

1. 105 ☐
2. 15 ☒
3. 10 ☐
4. 5 ☐



Question 70. How do you convert a string to a number in JavaScript?

Multiple: ☐

// No code reference provided

1. parseInt("123"); ☒
2. parseString("123"); ☐
3. toNumber("123"); ☐
4. convertToNumber("123"); ☐



Question 71. Which of the following is a valid JavaScript variable name?

Multiple: ☐

// No code reference provided

1. var 2name = "John"; ☐
2. var name-2 = "John"; ☐
3. var _name = "John"; ☒
4. var @name = "John"; ☐



Question 72. JavaScript variable names must:

Multiple: ☐

// No code reference provided

1. Start with a number ☐
2. Start with a letter, underscore (_), or dollar sign (\$) ☒
3. End with a number ☐
4. Be one word without spaces ☐



Question 73. JavaScript variable names:

Multiple: ☐

// No code reference provided

1. Can be any length ☐
2. Cannot contain spaces ☒
3. Must contain at least one number ☐
4. Must contain special characters ☐



Question 74. What is the correct syntax for declaring a variable in JavaScript?

Multiple: ☐

// No code reference provided

1. var name = 30 ☐
2. var name : 30 ☐
3. var name = 30; ☒
4. var 30 = name ☐



Question 75. Which of the following is an illegal variable name in JavaScript?

Multiple: ☐

// No code reference provided

1. var age_1 = 25; ☐
2. var 1age = 25; ☒
3. var _name = "John"; ☐
4. var \$price = 100; ☐



Question 76. How do you assign a number to a variable in JavaScript?

Multiple: ☐

// No code reference provided

1. var age = "30"; ☐
2. var age = 30; ☒
3. var age = 30.0; ☐
4. age = "30"; ☐



Question 77. What will be the output:

Multiple: ☐

```
alert(10 + 20);
```

1. 1020 ☐
2. 30 ☒
3. NaN ☐
4. 10 ☐



Question 78. What is the result of:

Multiple: ☐

```
var number = "10" + 20;
```

1. 30 ☐
2. 1020 ☒
3. NaN ☐
4. 10 ☐



Question 79. Which of the following is a number in JavaScript?

Multiple: ☐

// No code reference provided

1. "Hello" ☐
2. "200" ☐
3. 200 ☒
4. "2.5" ☐



Question 80. What does the following code output:

Multiple: ☐

```
var message = "hello, world!";  
alert(message);
```

1. Hello, World! ☒
2. Hello ☐
3. World ☐
4. Undefined ☐



Question 81. Which of the following is a valid string in JavaScript?

Multiple: ☐

// No code reference provided

1. `var str = Hello;`
2. `var str = 'Hello';`
3. `var str = "Hello";`
4. `var str = `Hello`;`

☐

☒

☐

☐



Question 82. What will happen when you run `alert(100 + 50);`?

Multiple: ☐

// No code reference provided

1. Displays 150
2. Displays 10050
3. Displays NaN
4. Displays an error

☒

☐

☐

☐



Question 83. How do you dismiss the alert box that appears on the screen?

Multiple: ☐

// No code reference provided

1. Click anywhere outside the alert box
2. Click the OK button
3. Press Enter
4. Press the Close button

☐

☒

☐

☐



Question 84. In JavaScript, how do you assign a string to a variable?

Multiple: ☐

// No code reference provided

1. `var name = 100;`
2. `var name = "Mark";`
3. `var name: 'Mark';`
4. `name = 'Mark';`

☐

☒

☐

☐



Question 85. What does the following code output:

Multiple: ☐

```
var message = "Hello, World!";  
alert(message);
```

1. Hello, World!
2. Hello
3. World
4. Undefined

☒

☐

☐

☐



Question 86. The `alert()` function:

Multiple: ☐

// No code reference provided

1. Can accept only numeric values
2. Displays a message and halts the execution of the code
3. Cannot display string values
4. Works only in the development environment

☐

☒

☐

☐



Question 87. Which of the following is a valid way to use the `alert()` function?

Multiple: ☐

// No code reference provided

1. `alert("Hello World!");`
2. `alert{Hello World!}`
3. `alert(Hello World!);`
4. `alert. "Hello World!"`

☒

☐

☐

☐



Question 88. What does the `alert()` function in JavaScript do?

Multiple: ☐

// No code reference provided

1. Outputs to the console
2. Sends a request to the server
3. Displays a message box with a specified message
4. Changes the page content

☐

☐

☒

☐



Question 1. What is the difference between parameters and arguments?

Multiple: ☐

// no code reference provided

1. None ☐
2. Parameters are inside function definition ☒
3. Arguments are defined in function ☐
4. Parameters return values ☐



Question 2. What happens if a global and local variable have the same name?

Multiple: ☐

// no code reference provided

1. Global overrides ☐
2. Local overrides ☒
3. Error ☐
4. Conflict ☐



Question 3. Arguments are supplied when?

Multiple: ☐

// no code reference provided

1. Function is declared ☐
2. Function is defined ☐
3. Function is called ☒
4. Function ends ☐



Question 4. Can you pass variables as arguments to a function?

Multiple: ☐

// no code reference provided

1. Yes ☒
2. No ☐
3. Only numbers ☐
4. Only strings ☐



Question 5. How are parameters separated in a function?

Multiple: ☐

// no code reference provided

1. Semicolons ☐
2. Commas ☒
3. Spaces ☐
4. Undercores ☐



Question 6. Can functions work without parameters?

Multiple: ☐

// no code reference provided

1. Yes ☒
2. No ☐
3. Only with defaults ☐
4. Only with return ☐



Question 7. Modifying a global variable inside a function affects it globally?

Multiple: ☐

// no code reference provided

1. Yes ☒
2. No ☐
3. Only if returned ☐
4. Only if reassigned ☐



Question 8. Can you store a returned value in a variable?

Multiple: ☐

// no code reference provided

1. Yes ☒
2. No ☐
3. Only numbers ☐
4. Only strings ☐



Question 9. Where are global variables declared? Multiple: ☐

// No code reference provided

1. Inside functions
2. Outside all functions
3. Inside loops
4. In return statements



Question 10. What happens if you try to use a local variable outside its function? Multiple: ☐

// No code reference provided

1. Error
2. Undefined
3. null
4. Works normally



Question 11. Can a global variable be accessed inside a function? Multiple: ☐

// No code reference provided

1. Yes
2. No
3. Only if passed
4. Only with return



Question 12. Which scope has higher precedence in a function? Multiple: ☐

// No code reference provided

1. Global
2. Local
3. Loop
4. Block



Question 13. Where is a local variable accessible? Multiple: ☐

// No code reference provided

1. Anywhere
2. Only within its function
3. Only in global scope
4. In other files



Question 14. What keyword is used for declaring a local variable? Multiple: ☐

// No code reference provided

1. var
2. let
3. const
4. All of the above



Question 15. Can two functions have local variables with the same name? Multiple: ☐

// No code reference provided

1. Yes
2. No
3. Only with let
4. Only in strict mode



Question 16. Are local variables independent from other functions? Multiple: ☐

// No code reference provided

1. Yes
2. No
3. Sometimes
4. Only with const



Question 17. Where should the return statement be placed? Multiple: ☐

// No code reference provided

1. Outside the function
2. Anywhere
3. Inside the function
4. After function call



Question 18. What is the term for data passed into a function? Multiple: ☐

// No code reference provided

1. Arguments
2. Returns
3. Conditions
4. Loops



Question 19. What is returned if there is no return statement? Multiple: ☐

// No code reference provided

1. undefined
2. null
3. 0
4. error



Question 20. What is the result of return 5 + 3? Multiple: ☐

// No code reference provided

1. 8
2. 5
3. 3
4. undefined



Question 21. Which keyword is used to define parameters? Multiple: ☐

// No code reference provided

1. param
2. argument
3. inside parentheses
4. define



Question 22. Can a function accept multiple parameters? Multiple: ☐

// No code reference provided

1. Yes
2. No
3. Only if declared as array
4. Only with return



Question 23. What does a function use to send data back? Multiple: ☐

// No code reference provided

1. print
2. console.log
3. return
4. output



Question 24. What does function greet(name) { alert(name); } do when called with greet('Ali')? Multiple: ☐

// No code reference provided

1. Shows 'name'
2. Shows 'Ali'
3. Errors out
4. Returns name



Question 25. How do you pass data to a function? Multiple: ☐

// No code reference provided

1. Using global variables
2. Using parameters
3. Using return
4. Using console.log



Question 26. Where are function parameters defined? Multiple: ☐

// No code reference provided

1. Inside curly braces
2. After function body
3. In parentheses after function name
4. Outside the function



Question 27. What keyword is used to return a value from a function?

Multiple ☐

// No code reference provided

1. break
2. exit
3. return
4. output

☐

☐

☒

☐



Question 28. How do you call a function named greet?

Multiple ☐

// No code reference provided

1. call greet()
2. greet()
3. run greet
4. greet()

☐

☒

☐

☐



Question 29. What is a function that doesn't return a value called?

Multiple ☐

// No code reference provided

1. void
2. method
3. procedure
4. undefined

☒

☐

☐

☐



Question 30. What method changes the minutes of a date?

Multiple ☐

// No code reference provided

1. setMinutes()
2. setmins()
3. setTime()
4. setseconds()

☒

☐

☐

☐



Question 31. What keyword is used to define a function?

Multiple ☐

// No code reference provided

1. def
2. func
3. function
4. define

☐

☐

☒

☐



Question 32. What does setHours(15) do?

Multiple ☐

// No code reference provided

1. Sets hour to 3 AM
2. Sets hour to 3 PM
3. Sets hour to 15 PM
4. Returns current hour

☐

☒

☐

☐



Question 33. How can you create a date for March 5, 2024?

Multiple ☐

// No code reference provided

1. new Date(2024, 2, 5)
2. new Date(2024, 3, 5)
3. new Date('5-3-2024')
4. Date.create(2024, 3, 5)

☒

☐

☐

☐



Question 34. Which of these returns the full year?

Multiple ☐

// No code reference provided

1. getYear()
2. getFullYear()
3. year()
4. Date.getFullYear()

☐

☒

☐

☐



Question 33. How can you create a date for March 5, 2024? Multiple: ☐

// No code reference provided

1. new Date(2024, 2, 5)
2. new Date(2024, 3, 5)
3. new Date('5-3-2024')
4. Date.create(2024, 3, 5)



Question 34. Which of these returns the full year? Multiple: ☐

// No code reference provided

1. getYear()
2. getFullYear()
3. year()
4. Date.getFullYear()



Question 35. What format is accepted by new Date()? Multiple: ☐

// No code reference provided

1. YYYY/MM/DD
2. MM/DD/YYYY
3. ISO 8601
4. All of the above



Question 36. setDate() modifies which part of the date? Multiple: ☐

// No code reference provided

1. Month
2. Year
3. Day of the month
4. Time



Question 37. How do you create a specific date in JavaScript? Multiple: ☐

// No code reference provided

1. new Date('2023-01-01')
2. Date.set('2023')
3. Date.now('2023')
4. setDate('2023')



Question 38. Which method is used to get the time in milliseconds since 1970? Multiple: ☐

// No code reference provided

1. Date.now()
2. getTime()
3. getMilliseconds()
4. now()



Question 39. Which method sets the full year of a date? Multiple: ☐

// No code reference provided

1. setYear()
2. setFullYear()
3. changeYear()
4. updateYear()



Question 40. How do you set the month in a date object? Multiple: ☐

// No code reference provided

1. setMonth()
2. changeMonth()
3. setDate()
4. updateMonth()



Question 41. How can you create a date for March 5, 2024?

Multiple: ☐

// No code reference provided

1. new Date(2024, 2, 5)
2. new Date(2024, 3, 5)
3. new Date("5-3-2024")
4. Date.create(2024, 3, 5)



Question 42. What does new Date() return?

Multiple: ☐

// No code reference provided

1. Current timestamp
2. Current date and time
3. Year only
4. An error



Question 43. Which method gets the current hour?

Multiple: ☐

// No code reference provided

1. getHour()
2. getHours()
3. hour()
4. Date.now()



Question 44. Which method returns the current year?

Multiple: ☐

// No code reference provided

1. getFullYear()
2. getYear()
3. getCurrentYear()
4. year()



Question 45. What does getMonth() return?

Multiple: ☐

// No code reference provided

1. Current month (1-12)
2. Current month (0-11)
3. Month name
4. Number of days in month



Question 46. How do you get the current day of the week?

Multiple: ☐

// No code reference provided

1. getDay()
2. getWeek()
3. getDate()
4. getFullDay()



Question 47. What does getMinutes() return?

Multiple: ☐

// No code reference provided

1. Hour
2. Date
3. Minutes
4. Seconds



Question 48. What is the output of getSeconds()?

Multiple: ☐

// No code reference provided

1. Second of the minute
2. Milliseconds
3. Hours
4. Days



Question 49. Which method returns the day of the month? Multiple: ☐

// No code reference provided

1. `getDay()`
2. `getDate()`
3. `getMonth()`
4. `getFullYear()`

X

✓

X

X



Question 50. Which object is used to work with dates in JavaScript? Multiple: ☐

// No code reference provided

1. `Time`
2. `Clock`
3. `Date`
4. `Calendar`

X

X

✓

X



Question 51. What does `(5.6789).toFixed(2)` return? Multiple: ☐

// No code reference provided

1. `5.67`
2. `5.68`
3. `6`
4. `5.6`

X

✓

X

X



Question 52. What is the return type of `toFixed()`? Multiple: ☐

// No code reference provided

1. `Number`
2. `Integer`
3. `String`
4. `Boolean`

X

X

✓

X



Question 53. How to round a number to no decimals? Multiple: ☐

// No code reference provided

1. `toFixed()`
2. `toFixed(0)`
3. `Math.ceil()`
4. `toString()`

X

✓

X

X



Question 54. What is a possible issue with `toFixed()` on some browsers? Multiple: ☐

// No code reference provided

1. Incorrect string conversion
2. Rounding inaccuracy
3. Too many decimals
4. NaN errors

X

✓

X

X



Question 55. What happens if you `parseInt('abc')`? Multiple: ☐

// No code reference provided

1. `0`
2. `NaN`
3. `undefined`
4. `abc`

X

✓

X

X



Question 56. Which method converts a number to a string? Multiple: ☐

// No code reference provided

1. `toString()`
2. `parseInt()`
3. `Number()`
4. `String.parse()`

✓

X

X

X



Question 55. What happens if you `parseInt('abc')`? Multiple: ☐

// No code reference provided

1. 0
2. NaN
3. undefined
4. abc



Question 56. Which method converts a number to a string? Multiple: ☐

// No code reference provided

1. `toString()`
2. `parseInt()`
3. `Number()`
4. `String.parse()`



Question 57. What is the output of `Number(45.67)`? Multiple: ☐

// No code reference provided

1. `'45.67'`
2. 45
3. 45.67
4. NaN



Question 58. What does `Number('text')` return? Multiple: ☐

// No code reference provided

1. `text`
2. 0
3. NaN
4. undefined



Question 59. How can you convert 123 to the string '123'? Multiple: ☐

// No code reference provided

1. `parseInt(123)`
2. `String(123)`
3. `Number(123)`
4. `123.toString()`



Question 60. What is the result of `(123).toString()`? Multiple: ☐

// No code reference provided

1. 123
2. `'123'`
3. NaN
4. undefined



Question 61. Which method controls decimal places in JavaScript? Multiple: ☐

// No code reference provided

1. `Math.floor()`
2. `Math.ceil()`
3. `toFixed()`
4. `toPrecision()`



Question 62. What does `Math.floor()` do in a dice simulation? Multiple: ☐

// No code reference provided

1. Rounding up
2. Adds decimals
3. Rounds down to nearest integer
4. Returns exact number



Question 63. What is the range of values for `Math.random() * 10`?

Multiple: ☐

// no code reference provided

1. 0 to 1
2. 0 to 9
3. 1 to 10
4. 0 to 10

X

X

X

✓



Question 64. Which method converts a string to an integer?

Multiple: ☐

// no code reference provided

1. `parseInt()`
2. `parseFloat()`
3. `toString()`
4. `Number()`

✓

X

X

X



Question 65. What is the result of `parseInt('42.5')`?

Multiple: ☐

// no code reference provided

1. 42.5
2. 43
3. 42
4. NaN

X

X

✓

X



Question 66. Which method retains decimals in conversion?

Multiple: ☐

// no code reference provided

1. `parseInt()`
2. `Math.floor()`
3. `parseFloat()`
4. `Number.parseInt()`

X

X

✓

X



Question 67. `parseFloat('12.34abc')` returns:

Multiple: ☐

// no code reference provided

1. NaN
2. 12.34
3. 12
4. 0

X

✓

X

X



Question 68. How can you simulate a dice roll using `Math.random()`?

Multiple: ☐

// no code reference provided

1. `Math.random() + 6`
2. `Math.ceil(Math.random())`
3. `Math.floor(Math.random() * 6) + 1`
4. `Math.random() * 100`

X

X

✓

X



Question 69. What type of numbers does `Math.random()` produce?

Multiple: ☐

// no code reference provided

1. Integer
2. String
3. Boolean
4. Floating-point

X

X

X

✓



Question 70. What does `Math.ceil(2.3)` return?

Multiple: ☐

// no code reference provided

1. 2
2. 3
3. 2.3
4. undefined

X

✓

X

X



Question 71. What is the output of Math.floor(4.9)?

Multiple: ☐

// no code reference provided

1. 5
2. 4
3. 4.9
4. undefined



Question 72. Which method always rounds a number down?

Multiple: ☐

// no code reference provided

1. Math.round()
2. Math.ceil()
3. Math.floor()
4. Math.abs()



Question 73. Math.round(1.5) returns:

Multiple: ☐

// no code reference provided

1. 1
2. 2
3. 1.5
4. undefined



Question 74. What does Math.random() return?

Multiple: ☐

// no code reference provided

1. A random integer
2. A number between 0 and 1
3. A boolean
4. A string



Question 75. Which JavaScript method rounds a number to the nearest integer?

Multiple: ☐

// no code reference provided

1. Math.ceil()
2. Math.floor()
3. Math.round()
4. Math.trunc()



Question 76. If cityName = "paris", what is cityName.charAt(0).toUpperCase()?

Multiple: ☐

// no code reference provided

1. p
2. P
3. PARIS
4. paris



Question 77. What is the purpose of combining toUpperCase() with charAt()?

Multiple: ☐

// no code reference provided

1. To reverse a string
2. To replace characters
3. To capitalize the first letter
4. To lowercase the entire string



Question 78. What is the result of "HELLO".toLowerCase()?

Multiple: ☐

// no code reference provided

1. hello
2. HELLO
3. Hello
4. Error



Question 75. Which JavaScript method rounds a number to the nearest integer?

Multiple: ☐

// no code reference provided

1. Math.ceil()
2. Math.floor()
3. Math.round()
4. Math.trunc()

X

X

✓

X



Question 76. If cityName = "paris", what is cityName.charAt(0).toUpperCase()?

Multiple: ☐

// no code reference provided

1. p
2. P
3. PARIS
4. paris

X

✓

X

X



Question 77. What is the purpose of combining toUpperCase() with charAt()?

Multiple: ☐

// no code reference provided

1. To reverse a string
2. To replace characters
3. To capitalize the first letter
4. To lowercase the entire string

X

X

✓

X



Question 78. What is the result of "HELLO".toLowerCase()?

Multiple: ☐

// no code reference provided

1. hello
2. HELLO
3. Hello
4. Error

✓

X

X

X



Question 79. What does indexOf() return if the string is not found?

Multiple: ☐

// no code reference provided

1. 0
2. null
3. undefined
4. -1

X

X

X

✓



Question 80. What is text.indexOf("e") in "JavaScript"?

Multiple: ☐

// no code reference provided

1. 1
2. 2
3. 3
4. 4

✓

X

X

X



Question 81. What can `indexOf()` be used for?

Multiple: ☐

// No code Reference provided

1. Extracting characters
2. Finding the length
3. Finding the position of text
4. Replacing text



Question 82. What is `text.indexOf("e")` in `"JavaScript"`?

Multiple: ☐

// No code Reference provided

1. 1
2. 2
3. 3
4. 4



Question 83. What does `indexOf()` return if the string is not found?

Multiple: ☐

// No code Reference provided

1. 0
2. null
3. undefined
4. -1



Question 84. What does `text.charAt(2)` return for `"Code"`?

Multiple: ☐

// No code Reference provided

1. C
2. o
3. d
4. e



Question 85. If `word = "JavaScript"`, what is `word.slice(0, 4)`?

Multiple: ☐

// No code Reference provided

1. JavaScript
2. Java
3. Script
4. avas



Question 86. If `text = "Hello"`, what does `text.slice(1)` return?

Multiple: ☐

// No code Reference provided

1. Hello
2. ello
3. H
4. Error



Question 87. What method is used to find the index of a substring? Multiple ☐

// no code reference provided

1. find() ☐
2. indexOf() ☒
3. search() ☐
4. slice() ☐



Question 88. What is the result of "Hello World".indexOf("World")? Multiple ☐

// no code reference provided

1. 0 ☐
2. 5 ☐
3. 6 ☒
4. -1 ☐



Question 89. Which method extracts part of a string? Multiple ☐

// no code reference provided

1. charAt() ☐
2. length() ☐
3. slice() ☒
4. toLowerCase() ☐



Question 90. What does someText.length return? Multiple ☐

// no code reference provided

1. Number of spaces ☐
2. Length of text ☒
3. First character ☐
4. Error ☐



Question 91. How can you replace all instances of a word in a string? Multiple ☐

// no code reference provided

1. Use replaceAll() ☐
2. Use a loop ☐
3. Use regex with g flag ☐
4. All of the above ☒



Question 92. How many times does replace() work by default? Multiple ☐

// no code reference provided

1. Unlimited ☐
2. Once ☒
3. Twice ☐
4. Until stopped ☐



Question 93. If text = "hello world", what does text.replace("world", "there") return? Multiple ☐

// no code reference provided

1. hello world ☐
2. hello there ☒
3. there world ☐
4. world hello ☐



Question 94. What does replace() do? Multiple ☐

// no code reference provided

1. Finds a string ☐
2. Deletes characters ☐
3. Replaces a specified value ☒
4. Converts to uppercase ☐



Question 93. If text = "hello world", what does text.replace("world", "there") return?

Multiple ☐

// No code reference provided

1. hello world
2. hello there
3. there world
4. world hello



Question 94. What does replace() do?

Multiple ☐

// No code reference provided

1. Finds a string
2. Deletes characters
3. Replaces a specified value
4. Converts to uppercase



Question 95. What does "cat".replace("c", "b") return?

Multiple ☐

// No code reference provided

1. bat
2. cat
3. boat
4. Error



Question 96. What does "Hello".charAt(0) return?

Multiple ☐

// No code reference provided

1. e
2. H
3. 0
4. l



Question 97. Which method is best to get a character at a given position?

Multiple ☐

// No code reference provided

1. slice()
2. charAt()
3. substring()
4. includes()



Question 98. What is "Code".charAt(4)?

Multiple ☐

// No code reference provided

1. C
2. e
3. undefined
4. Empty string



Question 99. What does "Java".charAt(2) return?

Multiple ☐

// No code reference provided

1. J
2. a
3. v
4. Error



Question 100. What is the index of the first character in a string?

Multiple ☐

// No code reference provided

1. 0
2. 1
3. -1
4. Depends on the string



Question 1. How do you swap two images and set a class using JavaScript?

Multiple ☐

1. By changing the src attribute and className property ☒
2. By changing the innerHTML and className property ☐
3. By changing the textContent and className property ☐
4. By changing the innerText and className property ☐



Question 2. How do you swap two images using JavaScript?

Multiple ☐

1. By changing the src attribute of both images ☐
2. By changing the innerHTML of both images ☒
3. By changing the textContent of both images ☐
4. By changing the innerText of both images ☐



Question 3. How do you change the src attribute of an image element?

Multiple ☐

1. document.getElementById('image').src = 'new image' ☒
2. document.getElementById('image').innerHTML = 'new image' ☐
3. document.getElementById('image').textContent = 'new image' ☐
4. document.getElementById('image').innerText = 'new image' ☐



Question 4. How do you read and set the text of a paragraph element?

Multiple ☐

// No code reference provided

1. innerHTML ☐
2. textContent ☒
3. innerText ☐
4. value ☐



Question 5. How do you set the value of a form field?

Multiple ☐

1. document.getElementById('field').value = 'new value' ☒
2. document.getElementById('field').innerHTML = 'new value' ☐
3. document.getElementById('field').textContent = 'new value' ☐
4. document.getElementById('field').innerText = 'new value' ☐



Question 6. How do you read the value of a form field?

Multiple ☐

// No code reference provided

1. document.getElementById('field').value ☒
2. document.getElementById('field').innerHTML ☐
3. document.getElementById('field').textContent ☐
4. document.getElementById('field').innerText ☐



Question 7. What event is triggered when a form field is changed?

Multiple ☐

// No code reference provided

1. Change ☒
2. Input ☐
3. Focus ☐
4. Blur ☐



Question 8. What event is triggered when the mouse is moved over an element?

Multiple ☐

// No code reference provided

1. Mouseover ☒
2. Mouseout ☐
3. Click ☐
4. DoubleClick ☐



Question 9. What event is triggered when a button is clicked? Multiple: ☐

1. Click
2. Hover
3. Focus
4. Blur



Question 10. What event is triggered when a link is clicked? Multiple: ☐

// no code reference provided

1. Click
2. Hover
3. Focus
4. Blur



Question 11. What is the purpose of commenting code? Multiple: ☐

// no code reference provided

1. To make code run faster
2. To make code more secure
3. To explain what the code does
4. To make code more complex



Question 12. Where is the best place to put a script tag in an HTML document? Multiple: ☐

// no code reference provided

1. in the head
2. in the body
3. At the end of the body
4. Anywhere



Question 13. What is the main difference between a do...while loop and a while loop? Multiple: ☐

// no code reference provided

1. Do...while loops run at least once
2. Do...while loops run indefinitely
3. Do...while loops are faster
4. Do...while loops are slower



Question 14. What is the purpose of a while loop in JavaScript? Multiple: ☐

// no code reference provided

1. To execute a block of code repeatedly while a condition is true
2. To execute a block of code only once
3. To declare variables
4. To define functions



Question 15. false == 0 Multiple: ☐

// no code reference provided

1. TRUE
2. FALSE
3. invalid data types
4. Syntax error



Question 16. what is output Multiple: ☐

```
let num = -1;
if (num)
  console.log("number exists");
else
  console.log("no number");
```

1. Number exists
2. No number
3. Error
4. undefined



Question 17. what is output Multiple: ☐

```
let sum = 0;
for (let i = 1; i <= 10; i++) {
  sum += i;
}
console.log(sum);
```

1. 20
2. 25
3. 35
4. 30



Question 18. How many times will the loop be executed? Multiple: ☐

```
for (let i = 0; i < 5; i++) {
  console.log("loop");
}
```

1. 5
2. 1
3. 0
4. infinite



Question 17. what is output

Multiple 

```
let sum = 0;
for (let i = 1; i < 10; i += 2) {
  sum += i;
}
console.log(sum);
```

1. 20
2. 25
3. 10
4. 30



Question 18. How many times will the loop be executed?

Multiple 

```
for (let i = 0; i < 5; i++) {
  console.log("loop");
}
```

1. 5
2. 1
3. 0
4. infinite



Question 19. what is output

Multiple 

```
let a = 10;
let b = 20;
let result;

if (a > b) {
  if (a > 15) {
    result = 'A is greater';
  } else {
    result = 'A is greater';
  }
} else {
  result = 'B is greater';
}
```

1. A is greater
2. B is greater
3. undefined
4. Error



Question 20. What does document.body return?

Multiple 

// No code reference provided

1. The entire DOM
2. The <head> tag
3. The <body> element
4. All nodes



Question 21. Which of these will remove a child node from the DOM?

Multiple 

// No code reference provided

1. element.removeChild(child)
2. element.removeNode(child)
3. element.removeChild(child)
4. element.deleteNode(child)



Question 22. innerHTML can be used to read and write HTML content of an element.

Multiple 

// No code reference provided

1. TRUE
2. FALSE



Question 23. What does the document.getElementById() method return if no matching element is found?

Multiple 

// No code reference provided

1. undefined
2. null
3. FALSE
4. 0



Question 24. What type of node is a <div> element in the DOM?

Multiple 

// No code reference provided

1. Attribute node
2. Element node
3. Text node
4. Comment node



Question 25. If you call Math.random() multiple times, what can you generally expect?

Multiple ☐

// No code reference provided

1. It always returns the same value ☐
2. It can return the same value multiple times ☒
3. It always returns a different value ☐
4. It will throw an error ☐



Question 26. How to write an IF statement for executing some code if T is NOT equal to 5?

Multiple ☐

// No code reference provided

1. if (t != 5) ☐
2. if (t == 5) ☒
3. if t != 5 ☐
4. if t == 5 ☐



Question 27. When you're writing JS on a webpage, what is the name of the global variable that represents the DOM?

Multiple ☐

// No code reference provided

1. document ☒
2. window ☐
3. DOM ☐
4. doc ☐



Question 28. Every node in the DOM represents what?

Multiple ☐

// No code reference provided

1. a link ☐
2. a section ☐
3. a view ☐
4. an HTML element ☒



Question 29. What sort of data type does the document variable store?

Multiple ☐

// No code reference provided

1. functions ☐
2. object ☒
3. string ☐
4. number ☐



Question 30. Which command creates a new button?

Multiple ☐

// No code reference provided

1. let button = document.new(button); ☐
2. let button = document.createElement(""); ☐
3. let button = document.createElement(button); ☒
4. let button = document.makesElement({button}); ☐



Question 31. Which of these lines of code would replace the content of a webpage with "Prince"?

Multiple ☐

// No code reference provided

1. documentbody.innerHTML = "Khazaaan"; ☒
2. documentbody.html = "Khazaaan"; ☐
3. document.innerHTML = "Khazaaan"; ☐
4. documentbody.html("Khazaaan"); ☐



Question 32. what is output

Multiple ☐

```
function test(a) {  
  return a * 2;  
}  
console.log(test());
```

1. 2 ☐
2. 0 ☐
3. undefined ☐
4. NaN ☒



Question 33. Which event is used when mouse leaves an element?

Multiple ☐

// No code reference provided

1. onhover
2. onmouseover
3. onmouseout
4. ondown



Question 34. Which function sets a style dynamically?

Multiple ☐

// No code reference provided

1. setStyle()
2. element.style.property = value
3. editStyle()
4. cssChange()



Question 35. what is output

Multiple ☐

```
let a;  
console.log(a);
```

1. null
2. 0
3. undefined
4. ""



Question 36. How do you remove an element from the DOM?

Multiple ☐

// No code reference provided

1. element.remove();
2. element.delete();
3. element.destroy();
4. element.clear();



Question 37. How to change an image and its class name simultaneously?

Multiple ☐

// No code reference provided

1. img.src = 'x.jpg'; img.className = 'newClass';
2. img.set('x.jpg', 'newClass')
3. setImageClass('x.jpg')
4. img.addClass('x.jpg')



Question 38. What method swaps an image in JavaScript?

Multiple ☐

// No code reference provided

1. changeImage()
2. element.src = 'newimage.jpg'
3. getImage()
4. setImage()



Question 39. How do you read the value of a text field with

Multiple ☐

// No code reference provided

1. getValue('myinput')
2. document.myinput.value
3. None of them
4. document.getElementById('myinput').value



Question 40. How to change the value of an input field in JavaScript?

Multiple ☐

// No code reference provided

1. text.value = 'Hello'
2. input = 'Hello'
3. document.getElementById('field').value = 'Hello'
4. set('field', 'Hello')



Question 41. How do you read the value of a text field with

Multiple: ☐

// No code Reference provided

1. `getValue("myInput")` ☐
2. `document.myInput.value` ☐
3. None of them ☒
4. `document.getElementById("myInput").value` ☐



Question 42. How to change the value of an input field in JavaScript?

Multiple: ☐

// No code Reference provided

1. `text.value = "Hello"` ☐
2. `input = "Hello"` ☐
3. `document.getElementById("field").value = "Hello"` ☒
4. `set("field", "Hello")` ☐



Question 43. What happens if you forget break in a switch case?

Multiple: ☐

// No code Reference provided

1. Nothing runs ☐
2. Fall-through to the next case ☒
3. Switch ends ☐
4. Syntax error ☐



Question 44. Where should JavaScript scripts be placed for better loading performance?

Multiple: ☐

// No code Reference provided

1. Inside `<head>` ☐
2. Before `<html>` ☐
3. Just before `</body>` ☒
4. Inside CSS ☐



Question 45. What is a global variable?

Multiple: ☐

// No code Reference provided

1. A variable inside a function ☐
2. A variable accessible anywhere in the script ☒
3. A variable in HTML ☐
4. A variable inside a loop ☐



Question 46. What is the purpose of default in switch?

Multiple: ☐

// No code Reference provided

1. To repeat case ☐
2. To run if no match is found ☒
3. To start the switch ☐
4. To stop the code ☐



Question 47. What is the scope of a variable declared inside a function?

Multiple: ☐

// No code Reference provided

1. Global
2. Local
3. Permanent
4. Block

X

✓

X

X



Question 48. what is output

Multiple: ☐

```
function add(a, b) {  
  return a + b;  
}  
console.log(add(2, 3));
```

1. 23
2. 5
3. undefined
4. NaN

X

✓

X

X



Question 49. What is the purpose of a function in JavaScript?

Multiple: ☐

// No code Reference provided

1. To loop through data
2. To define variables
3. To reuse blocks of code
4. To create HTML

X

X

✓

X



Question 50. Which keyword is used to return a value from a function?

Multiple: ☐

// No code Reference provided

1. break
2. return
3. give
4. exit

X

✓

X

X



Question 51. Which statement best describes the difference between == and ===?

Multiple: ☐

// No code Reference provided

1. == compares value; === compares reference
2. == compares value; === compares value and type
3. Both compare value and type
4. == compares type; === compares value

X

✓

X

X



Question 52. what is output

Multiple: ☐

```
var x = 1;  
function test() {  
  console.log(x);  
  var x = 2;  
}  
test();
```

1. 1
2. 2
3. undefined
4. ReferenceError

X

X

✓

X



Question 1. What will this output?

Multiple: ☐

```
console.log(typeof new Map)
```

1. object ☒
2. syntax error ☐
3. invalid data type error ☐
4. None of these ☐



Question 2. What will this output?

Multiple: ☐

```
console.log(Object == {});
```

1. true ☐
2. false ☒
3. undefined ☐
4. Error ☐



Question 3. What will this output?

Multiple: ☐

```
console.log(this === window);
```

1. true ☒
2. false ☐
3. undefined ☐
4. Error ☐



Question 4. What will this output?

Multiple: ☐

```
const obj = {  
  fn: () => console.log(this)  
};  
obj.fn();
```

1. obj ☐
2. window (browser) ☒
3. undefined ☐
4. Error ☐



Question 5. What will this output?

Multiple: ☐

```
const map = new Map();  
map.set(NaN, "value");  
console.log(map.has(NaN));
```

1. true ☒
2. false ☐
3. undefined ☐
4. Error ☐



Question 6. What will this output?

Multiple: ☐

```
const obj = Object.create({ inherited: 10 });  
obj.own = 5;  
console.log("inherited" in obj, obj.hasOwnProperty("inherited"));
```

1. true true ☐
2. true false ☒
3. false true ☐
4. false false ☐



Question 7. What will this output?

Multiple: ☐

```
const obj = { a: undefined };  
console.log("a" in obj, obj.hasOwnProperty("a"));
```

1. false false
2. true false
3. true true
4. false true



Question 8. What will this output?

Multiple: ☐

```
const map = new Map();  
map.set({}, "first");  
const key = {};  
map.set(key, "second");  
console.log(map.size);
```

1. 1
2. 2
3. 0
4. Error



Question 9. What will this output?

Multiple: ☐

```
const obj = { a: 1, b: 2 };  
console.log(Object.entries(obj)[0]);
```

1. ['a',1]
2. ['b',2]
3. ['1','a']
4. Error



Question 10. What will this output?

Multiple: ☐

```
const arr = [{ x: 1 }];  
const shallow = arr.slice();  
shallow[0].x = 999;  
console.log(arr[0].x);
```

1. 1
2. 999
3. undefined
4. Error



Question 11. What will this output?

Multiple: ☐

```
const obj = {};  
console.log(Object.keys(obj).length === 0);
```

1. true
2. false
3. undefined
4. Error



Question 12. What will this output?

Multiple: ☐

```
const obj = { a: 1 };  
const copy = JSON.parse(JSON.stringify(obj));  
console.log(copy === obj);
```

1. true
2. false
3. undefined
4. Error



Question 13. What will this output?

Multiple: ☐

```
const obj = { a: 1, b: 2 };  
console.log(Object.values(obj).includes("1"));
```

1. true
2. false
3. "1"
4. Error

X

✓

X

X



Question 14. What will this output?

Multiple: ☐

```
const arr = [{ a: 1 }, { b: 2 }];  
const shallow = arr.slice();  
shallow[0].a = 99;  
console.log(arr[0].a);
```

1. 1
2. 99
3. undefined
4. Error

X

✓

X

X



Question 15. What will this output?

Multiple: ☐

```
const m = new Map();  
const obj = {};  
m.set(obj, "hello");  
console.log(m.get({}));
```

1. "hello"
2. undefined
3. Error
4. {}

X

✓

X

X



Question 16. What will this output?

Multiple: ☐

```
const obj = { a: 1, b: 2 };  
console.log(Object.hasOwn(obj, "a"));
```

1. true
2. false
3. "a"
4. Error

✓

X

X

X



Question 17. Output?

Multiple: ☐

```
const obj = { a: 1, b: 2 };  
delete obj.a;  
console.log(Object.keys(obj));
```

1. ['a']
2. ['b']
3. ['a','b']
4. []

X

✓

X

X



Question 18. Output?

Multiple: ☐

```
const map = new Map();  
map.set({}, "value1");  
map.set({}, "value2");  
console.log(map.size);
```

1. 1
2. 2
3. 0
4. undefined

X

✓

X

X



Question 19. Consider

Multiple: ☐

```
const obj = { a: 1, b: { c: 2 } };  
const shallow = { ...obj };  
shallow.b.c = 99;  
console.log(obj.b.c);
```

1. 2
2. 99
3. undefined
4. Error

X

✓

X

X



Question 20. Consider

Multiple: ☐

```
const obj = { a: 10, b: 20 };  
console.log("a" in obj);
```

1. true
2. false
3. "a"
4. Error

✓

X

X

X



Question 21. What will this output?

Multiple: ☐

```
const obj = { a: 1, b: 2 };  
console.log(Object.keys(obj));
```

1. ['a', 'b']
2. [1, 2]
3. ['1', '2']
4. ['a1', 'b:2']

✓

X

X

X



Question 22. Which one is faster for frequent add/remove of keys?

Multiple: ☐

// No code Reference provided

1. Object
2. Map
3. Both equal
4. Spread operator

X

✓

X

X



Question 23. Consider:

Multiple: ☐

```
const obj = { a: 1, b: { c: 2 } };  
const copy = JSON.parse(JSON.stringify(obj));  
copy.b.c = 10;  
console.log(obj.b.c);
```

1. 1
2. 2
3. 10
4. undefined

X

✓

X

X



Question 24. Which one is not a valid Map operation?

Multiple: ☐

// No code Reference provided

1. map.delete(key)
2. map.pop()
3. map.has(key)
4. map.set(key, value)

X

✓

X

X



Question 23. Consider:

Multiple: ☐

```
const obj = { a: 1, b: { c: 2 } };  
const copy = JSON.parse(JSON.stringify(obj));  
copy.b.c = 10;  
console.log(obj.b.c);
```

- 1
- 2
- 10
- undefined



Question 24. Which one is not a valid Map operation?

Multiple: ☐

// No code Reference provided

- map.delete(key)
- map.pop()
- map.has(key)
- map.set(key, value)



Question 25. In a shallow copy of an object containing arrays, modifying the array inside the copy will:

Multiple: ☐

// No code Reference provided

- Affect the original
- Not affect the original
- Throw error
- Convert to primitive



Question 26. What does map.get("missingKey") return if the key doesn't exist?

Multiple: ☐

// No code Reference provided

- undefined
- null
- Error
- Empty object



Question 27. Two objects with identical properties are used as keys in a Map. How are they treated?

Multiple: ☐

// No code Reference provided

- Treated as same key
- Treated as different keys
- Causes error
- Converts to string key



Question 28. Which of these methods exists on Map?

Multiple: ☐

// No code Reference provided

- map.keys()
- map.values()
- map.entries()
- All of the above



Question 29. Which one is NOT a correct way to copy an array shallowly?

Multiple: ☐

// No code Reference provided

1. [...arr] ☐
2. arr.slice() ☐
3. Array.from(arr) ☐
4. JSON.parse(JSON.stringify(arr)) ☒



Question 30. How do you loop through all entries in a Map?

Multiple: ☐

// No code Reference provided

1. for (let x in map) ☐
2. forEach((k,v) => ...) ☐
3. for (let [k,v] of map) ☐
4. Both b and c ☒



Question 31. What happens when you shallow copy an object with spread syntax?

Multiple: ☐

// No code Reference provided

1. Primitives are copied by value, objects by reference ☒
2. Everything copied deeply ☐
3. Nothing is copied ☐
4. It crashes ☐



Question 32. What will this output?

Multiple: ☐

```
const m = new Map();  
m.set({}, "A");  
console.log(m.size);
```

1. 0 ☐
2. 1 ☒
3. Error ☐
4. undefined ☐



Question 33. What is the difference between Map and Object?

Multiple: ☐

// No code Reference provided

1. Objects maintain insertion order, Map doesn't ☐
2. Map allows keys of any type, Object doesn't ☒
3. Both only allow strings as keys ☐
4. Map is slower than Object ☐



Question 34. Which method removes a specific key-value pair from a Map?

Multiple: ☐

// No code Reference provided

1. erase(key) ☐
2. delete(key) ☒
3. remove(key) ☐
4. discard(key) ☐



Question 35. If you shallow copy an array of objects, what happens when you modify a nested object?

Multiple: ☐

// No code Reference provided

1. It won't affect the original ☐
2. It will affect the original ☒
3. A new object will be created automatically ☐
4. It throws an error ☐



Question 36. Which of the following can be used as a key in a Map but not in a plain object?

Multiple: ☐

// No code Reference provided

1. Strings ☐
2. Numbers ☐
3. Objects ☒
4. Booleans ☐



Question 37. Which method removes all key-value pairs from a Map?

Multiple: ☐

// No code Reference provided

1. clear() ☒
2. delete() ☐
3. reset() ☐
4. removeAll() ☐



Question 38. What does new Map() create in JavaScript?

Multiple: ☐

// No code Reference provided

1. A regular object ☐
2. An array ☐
3. A collection of key-value pairs ☒
4. A set ☐



Question 39. A shallow copy in JavaScript copies:

Multiple: ☐

// No code Reference provided

1. Only primitive values deeply ☐
2. References of objects/arrays ☒
3. Everything deeply including nested objects ☐
4. Both deep and shallow at the same time ☐



Question 40. How do you check the number of elements in a Map?

Multiple: ☐

// No code Reference provided

1. map.count ☐
2. map.length ☐
3. map.size ☒
4. map.total ☐



Question 41. Which method is used to add a key-value pair to a Map?

Multiple ☐

// No code reference provided

1. append()
2. set()
3. push()
4. .add()



Question 42. Which method deeply compares two objects?

Multiple ☐

// No code reference provided

1. Objects()
2. ===
3. ==
4. none of the above



Question 43. What will be the output?

Multiple ☐

```
let obj = {}  
console.log(obj, typeof(obj));
```

1. undefined
2. [object Object]
3. {}
4. Error



Question 44. What will this log?

Multiple ☐

```
let obj = {a: 1}  
console.log("a" in obj);
```

1. false
2. true
3. undefined
4. Error



Question 45. What will this log?

Multiple ☐

```
let obj = {x: 10}  
let copy = Object.assign({}, obj);  
copy.x = 20;  
console.log(obj, x);
```

1. 10
2. 20
3. undefined
4. Error



Question 46. Which operator checks if a property exists in an object?

Multiple ☐

// No code reference provided

1. is
2. exist
3. in
4. has



Question 47. What will this code output?

Multiple ☐

```
let obj = {name: "Ali", age: 25};  
console.log(obj["name"]);
```

1. undefined
2. Ali
3. name
4. error



Question 48. Which method returns an array of an object's keys?

Multiple ☐

// No code reference provided

1. Object.keys(obj)
2. Object.values(obj)
3. Object.entries(obj)
4. Object.getKeys(obj)

