The Map Function in R: Takeaways

Syntax

- Creating a custom function and using map() to vectorize it ` format_score <- function(score) { fmt_string <- str_replace(score, "%", "") num <- as.numeric(fmt_string)
  return(num) }
  example_scores <- c("19%", "81%", "100%")
  map_result <- map(example_scores, format_score) `
- Using map2() to vectorize a function that takes in two inputs ` first_inputs <- c(1, 2, 3)
  second_inputs <- c(4, 5, 6)
  add_inputs <- function(x, y) { return(x + y) }
  output <- map2(first_inputs, second_inputs, add_inputs) `
- Using the map() and mutate() functions to create a new column in your dataset ` format_score <- function(score) { fmt_string <- str_replace(score, "%", "") num <- as.numeric(fmt_string)
  return(num) }
  scores <- scores %>% mutate(new_writing_score = unlist(map(writing_score, format_score))) `
- Using lists as an input to the map() function ` input_list <- list(c(1, 2), c(3, 4), c(5, 6), c(7, 8), c(9, 10))
  output <- map(input_list, sum) `
- Using group_by() and summarize() together to vectorize a summary function across groups in a dataset

```
avg_score_by_student <- student_scores %>%
      group_by(names) %>%
      summarize(
        avg_writing = mean(new_writing_score)
      )
```

Concepts

- The `purrr` package has a family of functions that can accommodate any number of inputs and data types. Each of these functions work out similarly, so learning one can make learning the others easier.
- We use the `map()` function to vectorize a given function. You can use any function, whether it's one from R itself or a custom function that you've made yourself.
- We use the `map2()` function to vectorize a given function that uses two inputs.
- We can use the `group_by()` and `summarize()` functions together to create powerful analyses. These two work well when a dataset has two or more groups that we would like to compare against each other.