

```
make[1]: Leaving directory '/home/waseemshahzad/xv6-labs-2025'
== Test sleep, no arguments ==
$ make qemu-gdb
sleep, no arguments: OK (3.6s)
== Test sleep, returns ==
$ make qemu-gdb
sleep, returns: OK (0.6s)
== Test sleep, makes syscall ==
$ make qemu-gdb
sleep, makes syscall: OK (1.1s)
== Test sixfive_test ==
$ make qemu-gdb
sixfive_test: OK (0.9s)
== Test sixfive_readme ==
$ make qemu-gdb
sixfive_readme: OK (1.1s)
== Test sixfive_all ==
$ make qemu-gdb
sixfive_all: OK (1.1s)
== Test memdump, examples ==
$ make qemu-gdb
memdump, examples: OK (1.0s)
== Test memdump, format ii, S, p ==
```

```

== Test memdump, format ii, S, p ==
$ make qemu-gdb
memdump, format ii, S, p: OK (0.9s)
== Test find, in current directory ==
$ make qemu-gdb
find, in current directory: OK (1.1s)
      (Old xv6.out.find_curdir failure log removed)
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.0s)
      (Old xv6.out.find_subdir failure log removed)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.3s)
      (Old xv6.out.find_recursive failure log removed)
== Test exec ==
$ make qemu-gdb
exec: OK (0.7s)
      (Old xv6.out.find_exec failure log removed)
== Test exec, multiple args ==
$ make qemu-gdb

```

```

Command Prompt
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$
sixfive_all: OK (1.1s)
== Test memdump, examples ==
$ make qemu-gdb
memdump, examples: OK (1.0s)
== Test memdump, format ii, S, p ==
$ make qemu-gdb
memdump, format ii, S, p: OK (0.9s)
== Test find, in current directory ==
$ make qemu-gdb
find, in current directory: OK (1.1s)
      (Old xv6.out.find_curdir failure log removed)
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.0s)
      (Old xv6.out.find_subdir failure log removed)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.3s)
      (Old xv6.out.find_recursive failure log removed)
== Test exec ==
$ make qemu-gdb
exec: OK (0.7s)
      (Old xv6.out.find_exec failure log removed)
== Test exec, multiple args ==
$ make qemu-gdb
exec, multiple args: OK (1.0s)
      (Old xv6.out.find_exec_args failure log removed)
== Test exec, recursive find ==
$ make qemu-gdb
exec, recursive find: OK (1.5s)
      (Old xv6.out.test_find_sh failure log removed)
== Test time ==
time: OK
Score: 131/131
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$

```

```
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$ memdump
Example 1:
Example 2:
Example 3:
Example 4:
Example 5:
$ echo deadc0de | memdump hhcccc
echo deadc0de | memdump p
$ $ QEMU: Terminated
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$ nano user/sleep.c
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$ make qemu
mv -f fs.img fs.img.bk
mkfs/mkfs fs.img README user/findtest.sh user/sixfive.txt user/_cat user/_echo user/_forktest user/_grep user/_init u
ser/_kill user/_ln user/_ls user/_mkdir user/_rm user/_sh user/_stressfs user/_usertests user/_grind user/_wc user/_z
ombie user/_logstress user/_forphan user/_dorphan user/_hello user/_sixfive user/_sleep user/_memdump
nmeta 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1) blocks 1953 total 2000
ballocc: first 1066 blocks have been allocated
ballocc: write bitmap block at sector 46
qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m 128M -smp 3 -nographic -global virtio-mmio.forc
e-legacy=false -drive file=fs.img,if=none,format=raw,id=x0 -device virtio-blk-device,drive=x0,bus=virtio-mmio-bus.0

xv6 kernel is booting

hart 2 starting
hart 1 starting
init: starting sh
$ sixfive sixfive.txt
5
100
18
6
$

waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$ make zipball
rm -rf *.tex *.dvi *.idx *.aux *.log *.ind *.ilg *.dSYM *.zip *.pcap \
*/*.o */*.d */*.asm */*.sym \
kernel/kernel fs.img \
mkfs/mkfs .gdbinit \
user/usys.S \
user/_cat user/_echo user/_forktest user/_grep user/_init user/_kill user/_ln user/_ls user/_mkdir user/_rm user/_sh
user/_stressfs user/_usertests user/_grind user/_wc user/_zombie user/_logstress user/_forphan user/_dorphan user/_he
llo user/_sixfive user/_sleep user/_find user/_memdump
M Makefile
M user/memdump.c
?? =
?? fs.img.bk
?? user/Makefile
?? user/Myprog.c
?? user/find.c
?? user/find.c.bak
```

```
user/echo.c
user/find.c
user/findtest.sh
user/forktest.c
user/forphan.c
user/grep.c
user/grind.c
user/init.c
user/kill.c
user/ln.c
user/logstress.c
user/lsc.c
user/memdump.c
user/mkdir.c
user/printf.c
user/rm.c
user/sh.c
user/sixfive.c
user/sixfive.txt
user/sleep.c
user/stressfs.c
user/ulib.c
user/umalloc.c
user/user.h
user/user.ld
user/usertests.c
user/usys.pl
user/wc.c
user/zombie.c
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$ ls -lh lab.zip
-rw-r--r-- 1 waseemshahzad waseemshahzad 108K Sep 22 03:39 lab.zip
waseemshahzad@Waseem-Shahzad:~/xv6-labs-2025$
```