

Bash scripting 2

1) Create a bash script to check if a directory is available or not

Created a vi file named else.bash and filled the bash

```
#!/bin/bash
if [ -d /root/waseem/scripts ]
then
    echo "directory exist"
else
    echo "directory does not exist"
fi
```

Pwd

Cat else.bash

We already changed the permission of file using

Chmod 755 else.bash

And ./else.bash to run the script

```
[root@ip-172-31-8-74 scripts]# vi else.bash
[root@ip-172-31-8-74 scripts]# pwd
/root/waseem/scripts
[root@ip-172-31-8-74 scripts]# cat else.bash
#!/bin/bash
if [ -d /root/waseem/scripts ]
then
    echo "directory exist"
else
    echo "directory does not exist"
fi

[root@ip-172-31-8-74 scripts]# ./else.bash
directory exist
[root@ip-172-31-8-74 scripts]# vi else.bash
[root@ip-172-31-8-74 scripts]#
```

So as the directory exist it displayed directory exist

2) Create a bash script to **create multiple files**.

```
#!/bin/bash
touch file1 file2 file3
~
~
```

Created a vi file of create.bash
Touch file1, file2, file3
To create multiple files

```
[root@ip-172-31-8-74 scripts]# vi create.bash
[root@ip-172-31-8-74 scripts]# chmod 755 create.bash
[root@ip-172-31-8-74 scripts]# cat create.bash
#!/bin/bash
touch file1 file2 file3
[root@ip-172-31-8-74 scripts]# ./create.bash
```

Now give permission to file
Chmod 755 to give permission
Cat create.bash for viewing

./create.bash “(for running the bash script)”

```
[root@ip-172-31-8-74 scripts]# ./create.bash
[root@ip-172-31-8-74 scripts]# ls
create.bash else.bash file1 file2 file3
[root@ip-172-31-8-74 scripts]# ll
total 8
-rwxr-xr-x. 1 root root 36 Nov 7 09:52 create.bash
-rwxr-xr-x. 1 root root 121 Nov 7 09:46 else.bash
-rw-r--r--. 1 root root 0 Nov 7 09:53 file1
-rw-r--r--. 1 root root 0 Nov 7 09:53 file2
-rw-r--r--. 1 root root 0 Nov 7 09:53 file3
[root@ip-172-31-8-74 scripts]# vi create.bash
[root@ip-172-31-8-74 scripts]# $
```

File1, file2, file3 three multiple files are created

3) Create a bash script to take a backup of a directory.

```
#!/bin/bash

tar cvf scripts_backups.tar .

echo " Backup completed: scripts_backups.tar"
```

Open vi back.bash file and

Tar cvf script_backups.tar . (Will create a compress backup tar file of present directory)

```
[[root@ip-172-31-8-74 scripts]# vi backup.bash
[[root@ip-172-31-8-74 scripts]# ./backup.bash
./
./else.bash
./file1
./file2
./file3
./create.bash
./scripts_backups.tar
./backup.bash
tar: ./scripts_backups.tar: file is the archive; not dumped
Backup completed: scripts_backups.tar
[[root@ip-172-31-8-74 scripts]# ls
backup.bash  create.bash  else.bash  file1  file2  file3  scripts_backup.tar  scripts_backups.tar
[[root@ip-172-31-8-74 scripts]# cat backup.bash
```

./backup.bash

Ls (we can see backup file of scripts is present scripts_backups.tar)

4) Create a bash script to install Nginx on an EC2 server.

Yum install nginx -y

Systemctl start nginx

Systemctl enable nginx

Echo " nginx installed successfully"

In vi nginx.bash

```
#!/bin/bash
yum install nginx -y
systemctl start nginx
systemctl enable nginx
echo "Nginx Installed Successfully"
```

Chmod 755 nginx.bash will give permissions
./nginx.bash will start running bash scripting

```
Complete!
[root@ip-172-31-8-74 scripts]# vi nginx.bash
[root@ip-172-31-8-74 scripts]# chmod 755 nginx.bash
[root@ip-172-31-8-74 scripts]# ./nginx.bash
Last metadata expiration check: 1:04:06 ago on Fri Nov 7 09:26:11 2025.
Dependencies resolved.

=====
Package                                Architecture                            Version
=====
Installing:
  nginx                                x86_64                                  1:1.28.0-1.amzn2023.0.2
Installing dependencies:
  generic-logos-httpd                 noarch                                  18.0.0-12.amzn2023.0.3
  gperftools-libs                     x86_64                                  2.9.1-1.amzn2023.0.3
  libunwind                           x86_64                                  1.4.0-5.amzn2023.0.3
  nginx-core                          x86_64                                  1:1.28.0-1.amzn2023.0.2
  nginx-filessystem                   noarch                                  1:1.28.0-1.amzn2023.0.2
  nginx-mimetypes                     noarch                                  2.1.49-3.amzn2023.0.3
=====

Transaction Summary
-----
Install 7 Packages

Total download size: 1.1 M
Installed size: 3.7 M
Downloading Packages:
(1/7): generic-logos-httpd-18.0.0-12.amzn2023.0.3.noarch.rpm
(2/7): libunwind-1.4.0-5.amzn2023.0.3.x86_64.rpm
(3/7): gperftools-libs-2.9.1-1.amzn2023.0.3.x86_64.rpm
(4/7): nginx-1.28.0-1.amzn2023.0.2.x86_64.rpm
(5/7): nginx-core-1.28.0-1.amzn2023.0.2.x86_64.rpm
(6/7): nginx-filessystem-1.28.0-1.amzn2023.0.2.noarch.rpm
(7/7): nginx-mimetypes-2.1.49-3.amzn2023.0.3.noarch.rpm
=====
```

⚠ Not Secure 16.171.69.182

Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to nginx.org.
Commercial support is available at nginx.com.

Thank you for using nginx.

5) Create a bash script to install Apache Tomcat on an EC2 server.

Wget command for installing tar file of tomcat address link

Tar -xvf to extract that tar file

Mv for moving the application to opt part

Chomd +x for permission and running

And /opt/tomcat/bin/startup.sh for starting application to run

```
#!/bin/bash
cd /root/waseem/scripts

wget https://d1cdn.apache.org/tomcat/tomcat-9/v9.0.111/bin/apache-tomcat-9.0.111.tar.gz

tar -xvf apache-tomcat-9.0.111.tar.gz

mv apache-tomcat-9.0.111 /opt/tomcat

chmod +x /opt/tomcat/bin/*.sh

/opt/tomcat/bin/startup.sh
```

```
[root@ip-172-31-8-74 scripts]# ./tomcat.bash
--2025-11-07 11:25:59-- https://d1cdn.apache.org/tomcat/tomcat-9/v9.0.111/bin/apache-tomcat-9.0.111.tar.gz
Resolving d1cdn.apache.org (d1cdn.apache.org)... 151.101.2.132, 2a04:4e42::644
Connecting to d1cdn.apache.org (d1cdn.apache.org)|151.101.2.132|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 13037002 (12M) [application/x-gzip]
Saving to: 'apache-tomcat-9.0.111.tar.gz'
```

```
apache-tomcat-9.0.111.tar.gz 100%[=====]
2025-11-07 11:25:59 (290 MB/s) - 'apache-tomcat-9.0.111.tar.gz' saved [13037002/13037002]
```

```
apache-tomcat-9.0.111/conf/
apache-tomcat-9.0.111/conf/catalina.policy
apache-tomcat-9.0.111/conf/catalina.properties
apache-tomcat-9.0.111/conf/context.xml
apache-tomcat-9.0.111/conf/jaspic-providers.xml
apache-tomcat-9.0.111/conf/jaspic-providers.xsd
apache-tomcat-9.0.111/conf/logging.properties
apache-tomcat-9.0.111/conf/server.xml
apache-tomcat-9.0.111/conf/tomcat-users.xml
apache-tomcat-9.0.111/conf/tomcat-users.xsd
apache-tomcat-9.0.111/conf/web.xml
apache-tomcat-9.0.111/bin/
apache-tomcat-9.0.111/lib/
apache-tomcat-9.0.111/logs/
apache-tomcat-9.0.111/temp/
apache-tomcat-9.0.111/webapps/
apache-tomcat-9.0.111/webapps/ROOT/
apache-tomcat-9.0.111/webapps/ROOT/WEB-INF/
apache-tomcat-9.0.111/webapps/docs/
apache-tomcat-9.0.111/webapps/docs/META-INF/
apache-tomcat-9.0.111/webapps/docs/WEB-INF/
apache-tomcat-9.0.111/webapps/docs/WEB-INF/jsp/
apache-tomcat-9.0.111/webapps/docs/annotationapi/
apache-tomcat-9.0.111/webapps/docs/api/
apache-tomcat-9.0.111/webapps/docs/appdev/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/docs/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/src/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/src/mypackage/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/web/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/web/WEB-INF/
apache-tomcat-9.0.111/webapps/docs/appdev/sample/web/images/
apache-tomcat-9.0.111/webapps/docs/architecture/
apache-tomcat-9.0.111/webapps/docs/architecture/requestProcess/
apache-tomcat-9.0.111/webapps/docs/architecture/startup/
apache-tomcat-9.0.111/webapps/docs/config/
apache-tomcat-9.0.111/webapps/docs/elapi/
apache-tomcat-9.0.111/webapps/docs/images/
```

```

apache-tomcat-9.0.111/bin/daemon.sh
apache-tomcat-9.0.111/bin/digest.sh
apache-tomcat-9.0.111/bin/makebase.sh
apache-tomcat-9.0.111/bin/setclasspath.sh
apache-tomcat-9.0.111/bin/shutdown.sh
apache-tomcat-9.0.111/bin/startup.sh
apache-tomcat-9.0.111/bin/tool-wrapper.sh
apache-tomcat-9.0.111/bin/version.sh
Using CATALINA_BASE:   /opt/tomcat
Using CATALINA_HOME:   /opt/tomcat
Using CATALINA_TMPDIR: /opt/tomcat/temp
Using JRE_HOME:        /usr
Using CLASSPATH:       /opt/tomcat/bin/bootstrap.jar:/opt/tomcat/bin/tomcat-juli.jar
Using CATALINA_OPTS:
Tomcat started.
[root@ip-172-31-8-74 scripts]# vi tomcat.bash
[root@ip-172-31-8-74 scripts]#

```

All the scripts are running and tomcat has started

Not Secure
16.171.69.182:8080

Home
Documentation
Configuration
Examples
Wiki
Mailing Lists
Find Help

Apache Tomcat/9.0.111



If you're seeing this, you've successfully installed Tomcat. Congratulations!

Recommended Reading:

- [Security Considerations How-To](#)
- [Manager Application How-To](#)
- [Clustering/Session Replication How-To](#)

Server Status
Manager App
Host Manager

Developer Quick Start

[Tomcat Setup](#)
[Realms & AAA](#)
[Examples](#)
[Servlet Specifications](#)

[First Web Application](#)
[JDBC DataSources](#)
[Tomcat Versions](#)

Managing Tomcat

For security, access to the [manager.webapp](#) is restricted. Users are defined in:

```
$CATALINA_HOME/conf/tomcat-users.xml
```

In Tomcat 9.0 access to the manager application is split between different users. [Read more...](#)

[Release Notes](#)

[Changelog](#)

[Migration Guide](#)

[Security Notices](#)

Documentation

[Tomcat 9.0 Documentation](#)

[Tomcat 9.0 Configuration](#)

[Tomcat Wiki](#)

Find additional important configuration information in:

`$CATALINA_HOME/RUNNING.txt`

Developers may be interested in:

- [Tomcat 9.0 Bug Database](#)
- [Tomcat 9.0 JavaDocs](#)
- [Tomcat 9.0 Git Repository at GitHub](#)

Getting Help

FAQ and Mailing Lists

The following mailing lists are available:

[tomcat-announce](#)
Important announcements, releases, security vulnerability notifications. (Low volume).

- [tomcat-users](#)
User support and discussion
- [taglibs-user](#)
User support and discussion for [Apache Taglibs](#)
- [tomcat-dev](#)
Development mailing list, including commit messages

Other Downloads

- [Tomcat Connectors](#)
- [Tomcat Native](#)
- [Taglibs](#)
- [Deployer](#)

Other Documentation

- [Tomcat Connectors](#)
- [mod_jk Documentation](#)
- [Tomcat Native](#)
- [Deployer](#)

Get Involved

- [Overview](#)
- [Source Repositories](#)
- [Mailing Lists](#)
- [Wiki](#)

Miscellaneous

- [Contact](#)
- [Legal](#)
- [Sponsorship](#)
- [Thanks](#)

Apache Software Foundation

- [Who We Are](#)
- [Heritage](#)
- [Apache Home](#)
- [Resources](#)

6) Create a bash script to **check if the Nginx service is running**, if not running then script should start the service.

```
#!/bin/bash

# Check if nginx is running
if systemctl is-active --quiet nginx
then
    echo "Nginx is already running "
else
    echo "Nginx is NOT running "
    echo "Starting Nginx..."
    sudo systemctl start nginx

    # Check again after starting
    if systemctl is-active --quiet nginx
    then
        echo "Nginx started successfully "
    else
        echo "Failed to start Nginx "
    fi
fi
```

If then script is used for checking the above script of nginx

```
[root@ip-172-31-8-74 scripts]# systemctl stop nginx
[root@ip-172-31-8-74 scripts]# ./if.bash
Nginx is NOT running
Starting Nginx...
Nginx started successfully
[root@ip-172-31-8-74 scripts]#
```

Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to nginx.org.
Commercial support is available at nginx.com.

Thank you for using nginx.

Nginx started again by the script

7) Create a bash script for a **calculator**.

```
#!/bin/bash
# Simple Calculator

echo "Enter first number:"
read a

echo "Enter operator (+ - * /):"
read op

echo "enter second number:"
read b

if [ "$op" = "+" ]
then
    result=$((a + b))
    echo "Answer = $result"

elif [ "$op" = "-" ]
then
    result=$((a - b))
    echo "Answer = $result"

elif [ "$op" = "*" ]
then
    result=$((a * b))
    echo "Answer = $result"

elif [ "$op" = "/" ]
then
    result=$((a / b))
    echo "Answer = $result"

else
    echo "Invalid Operator"
fi
```

~
~
~
~

I have created a calculator where I have addition(+), subtraction(-), multiplication(*), division (/) used then read for us to add which number for A and number for B and line by line executing each .

```
Answer = 0
[root@ip-172-31-8-74 scripts]# vi calculator.bash
[root@ip-172-31-8-74 scripts]# chmod 755 calculator.bash
[root@ip-172-31-8-74 scripts]# ./calculator.bash
Enter first number:
8
Enter operator (+ - * /):
+
enter second number:
12
Answer = 20
[root@ip-172-31-8-74 scripts]#
```

8) Create a bash script to **check if a directory exists**, if not then create a directory.

```
#!/bin/bash
# Script to check directory exists or not

echo "Enter directory name:"
read taskbash

if [ -d "$taskbash" ]
then
    echo "Directory already exists"
else
    echo "Directory does not exist, creating now..."
    mkdir $taskbash
    echo "Directory created successfully"
fi

~
~
```

Read for typing the directory name whether it exists or not .if not then
Mkdir \$taskbash for creating directory

We have run the script ./dir.bash
And the directory is not found so
We created a directory in same shell
We can have a look at ll task bash directory is created

```
[root@ip-172-31-8-74 scripts]# vi dir.bash
[root@ip-172-31-8-74 scripts]# ./dir.bash
Enter directory name:
taskbash
Directory does not exist, creating now...
Directory created successfully
[root@ip-172-31-8-74 scripts]# ll
total 12796
-rw-r--r--. 1 root root 13037002 Oct 10 14:29 apache-tomcat-9.0.111.tar.gz
-rwxr-xr-x. 1 root root    92 Nov  7 10:21 backup.bash
-rwxr-xr-x. 1 root root   525 Nov  7 13:01 calculator.bash
-rwxr-xr-x. 1 root root    36 Nov  7 09:56 create.bash
-rwxr-xr-x. 1 root root   302 Nov  7 13:13 dir.bash
-rwxr-xr-x. 1 root root   121 Nov  7 11:32 else.bash
-rw-r--r--. 1 root root     0 Nov  7 09:53 file1
-rw-r--r--. 1 root root     0 Nov  7 09:53 file2
-rw-r--r--. 1 root root     0 Nov  7 09:53 file3
-rwxr-xr-x. 1 root root   403 Nov  7 11:39 if.bash
-rwxr-xr-x. 1 root root   115 Nov  7 10:30 nginx.bash
-rw-r--r--. 1 root root  10240 Nov  7 10:17 scripts_backup.tar
-rw-r--r--. 1 root root  20480 Nov  7 10:19 scripts_backups.tar
drwxr-xr-x. 2 root root     6 Nov  7 13:14 taskbash
-rwxr-xr-x. 1 root root   262 Nov  7 11:26 tomcat.bash
```

9) Create a bash script to delete the last 3 lines of a file.

```
#!/bin/bash
# Script to delete last 3 lines of a file

echo "Enter file name:"
read file1

# Check if file exists
if [ -e "$file1" ]
then

    head -n -3 "$file1" > temp.txt

    # Move the temp file back to original
    mv temp.txt "$file1"

    echo "Last 3 lines deleted successfully."
else
    echo "File1 does not exist."
fi

~
~
~
~
```

We have checked whether the file exists
And if it exists then used head -3 for deleting first three lines of a file file1
And given permission and run the file

```
[root@ip-172-31-8-74 scripts]# vi file2
[root@ip-172-31-8-74 scripts]# chmod 755 file2
[root@ip-172-31-8-74 scripts]# ./file2
Enter file name:
[file1]
Last 3 lines deleted successfully.
[root@ip-172-31-8-74 scripts]# cat file1
my name is waseem
[root@ip-172-31-8-74 scripts]# vi file2
[root@ip-172-31-8-74 scripts]#
```

As we can see first three lines were removed

10) Bash script to monitor cpu and if it is more than 80% then send email notification.

```
#!/bin/bash
# Monitor CPU usage and send email if greater than 80%

TO="waseem.akram082003@gmail.com"

# Get CPU usage
cpu=$(top -bn1 | grep "Cpu(s)" | awk '{print 100 - $8}')

cpu=${cpu%.*} # Convert decimal to integer

if [ $cpu -gt 80 ]
then
    echo "Warning: High CPU Usage = $cpu%" | mail -s "CPU ALERT" $TO
    echo "High CPU detected. Email sent."
else
    echo "CPU is Normal = $cpu%"
fi
~
```

We have monitored the cpu of gmail and it is less than 80

The cpu is normal =3%

```
[root@ip-172-31-8-74 scripts]# vi cpu.sh
[root@ip-172-31-8-74 scripts]# chmod 755 cpu.sh
[root@ip-172-31-8-74 scripts]# ./cpu.sh
CPU is Normal = 3%
[root@ip-172-31-8-74 scripts]# cat cpu.sh
#!/bin/bash
# Monitor CPU usage and send email if greater than 80%

TO="waseem.akram200308@gmail.com"

# Get CPU usage
cpu=$(top -bn1 | grep "Cpu(s)" | awk '{print 100 - $8}')

cpu=${cpu%.*} # Convert decimal to integer

if [ $cpu -gt 80 ]
then
    echo "Warning: High CPU Usage = $cpu%" | mail -s "CPU ALERT" $TO
    echo "High CPU detected. Email sent."
else
    echo "CPU is Normal = $cpu%"
fi
```

11) Bash script to monitor disk space and if it is more than 80% then send email notification.

```
#!/bin/bash

THRESHOLD=80
EMAIL="waseem.akram200308@gmail.com"

# Get the disk usage of root partition (/)
USAGE=$(df -h / | awk 'NR==2 {print $5}' | sed 's/%//')

if [ $USAGE -gt $THRESHOLD ]; then
    echo "Disk Usage is High: $USAGE%" | mail -s "Disk Alert on Server" $EMAIL
    echo "High Disk usage detected. Email sent."
else
    echo "Disk usage is Normal: $USAGE%"
fi
```

We have disk memory less than 80% then memory usage is normal as output
if it was more than 80% then out put will be high memory usage sends email as memory alert

```
[root@ip-172-31-8-74 scripts]# vi cpu1.sh
[root@ip-172-31-8-74 scripts]# bash cpu1.sh
CPU is normal: 2.9%
[root@ip-172-31-8-74 scripts]# vi cpu2.sh
```

We have disk memory 2.9% in my email so memory usage is normal

12) Bash script to monitor memory and if it is more than 80% then send email notification.

```
#!/bin/bash

THRESHOLD=80
EMAIL="waseem.akram200308@gmail.com"

MEMORY=$(free | grep Mem | awk '{print $3/$2 * 100.0}')
MEMORY_INT=${MEMORY%.*}

if [ $MEMORY_INT -gt $THRESHOLD ]; then
    echo "High Memory Usage: $MEMORY_INT%" | mail -s "Memory Alert on Server" $EMAIL
    echo "High Memory detected. Email sent."
else
    echo "Memory usage is Normal: $MEMORY_INT%"
fi
```

We have the monitor memory 21% which is less than 80%

```
[root@ip-172-31-8-74 scripts]# vi cpu3.sh
[root@ip-172-31-8-74 scripts]# bash cpu3.sh
Memory usage is Normal: 21%
```

Exercise: Crontab Entries

1. April 5th Midnight
2. 5th of Every November, January, June if it is a Thursday
3. At 05 and 27th minutes of 9, 10, 11 hours every day
4. 34 minutes of 9th hour on 15th August
5. Every midnight
6. Every Weekend (Saturday night 11:59 PM)
7. After every reboot

```
# 1) April 5th Midnight
0 0 5 4 * echo "April 5th Midnight Job Ran $(date)" >> /root/cron_logs/april5.log 2>&1

# 2) 5th of November, January, June IF Thursday
0 0 5 11,1,6 4 echo "5th + Thursday Condition Ran $(date)" >> /root/cron_logs/5th_thursday.log 2>&1

# 3) At 05 and 27 minutes of 9, 10, 11 hrs daily
5,27 9,10,11 * * * echo "Time Job Ran $(date)" >> /root/cron_logs/timing.log 2>&1

# 4) 34 minutes of 9th hour on 15th August
34 9 15 8 * echo "Independence Job Ran $(date)" >> /root/cron_logs/aug15.log 2>&1

# 5) Every Midnight
0 0 * * * echo "Midnight Job $(date)" >> /root/cron_logs/midnight.log 2>&1

# 6) Every Saturday 11:59 PM
59 23 * * 6 echo "Weekend Job $(date)" >> /root/cron_logs/weekend.log 2>&1

# 7) After Reboot
@reboot sleep 20; echo "Reboot Job $(date)" >> /root/cron_logs/reboot.log 2>&1

~
~
```

We added a cron test in given path //root

```
# 1) April 5th Midnight
0 0 5 4 * echo "April 5th Midnight Job Ran $(date)" >> /root/cron_logs/april5.log 2>&1

# 2) 5th of November, January, June IF Thursday
0 0 5 11,1,6 4 echo "5th + Thursday Condition Ran $(date)" >> /root/cron_logs/5th_thursday.log 2>&1

# 3) At 05 and 27 minutes of 9, 10, 11 hrs daily
5,27 9,10,11 * * * echo "Time Job Ran $(date)" >> /root/cron_logs/timing.log 2>&1

# 4) 34 minutes of 9th hour on 15th August
34 9 15 8 * echo "Independence Job Ran $(date)" >> /root/cron_logs/aug15.log 2>&1

# 5) Every Midnight
0 0 * * * echo "Midnight Job $(date)" >> /root/cron_logs/midnight.log 2>&1

# 6) Every Saturday 11:59 PM
59 23 * * 6 echo "Weekend Job $(date)" >> /root/cron_logs/weekend.log 2>&1

# 7) After Reboot
@reboot sleep 20; echo "Reboot Job $(date)" >> /root/cron_logs/reboot.log 2>&1

* * * * * echo "Cron Test $(date)" >> /root/cron_logs/cron_test.log 2>&1

~
```

Waited one min an checked cron_test.log file

```
[root@ip-172-31-8-74 cron_logs]# cat /root/cron_logs/cron_test.log  
Cron Test Tue Nov 11 06:41:01 UTC 2025  
[root@ip-172-31-8-74 cron_logs]#
```

```
[root@ip-172-31-8-74 cron_logs]# cat /root/cron_logs/reboot.log  
Reboot Job Tue Nov 11 06:32:41 UTC 2025
```

```
[root@ip-172-31-8-74 cron_logs]# cat /root/cron_logs/cron_test.log  
Cron Test Tue Nov 11 06:41:01 UTC 2025  
Cron Test Tue Nov 11 06:42:01 UTC 2025  
Cron Test Tue Nov 11 06:43:02 UTC 2025  
Cron Test Tue Nov 11 06:44:01 UTC 2025  
Cron Test Tue Nov 11 06:45:01 UTC 2025  
Cron Test Tue Nov 11 06:46:02 UTC 2025  
Cron Test Tue Nov 11 06:47:01 UTC 2025  
[root@ip-172-31-8-74 cron_logs]#
```


