Database Table Dictionary

A Web-Based Tracer and Employment Analytics System for the Alumni Relations and Linkages Office

Central Mindanao University | May 2026

Item	Value
Prepared for	WASHELEY TAN and ELVIN LAR GONZALES
Program	Bachelor of Science in Information Technology
Database verified from	pgsql connection, database cmu_arlo_db
Schema generated at	2026-06-05 20:22:16
Current table count	21

Verification Note
This document was generated from the current Laravel and PostgreSQL database schema. The live database contains 21 documented tables. It does not contain job_applications, queue_jobs, job_batches, or job_matches in the current implementation. Analytics is computed from existing operational tables, especially users and tracer_records; it does not use a separate analytics table.

1. How the Database Works as a Story

The database begins with accounts. Alumni records are stored in the users table, regular administrators are stored in the admins table, and the higher account-control role is stored in the super_admins table. This separation keeps graduate records away from staff accounts and makes the Super Admin role clearer in the system design.

When ARLO imports a CSV file, the imported alumni are stored in users as roster records. They are not treated as fully registered accounts yet. During registration, the alumnus must match the stored name, birthdate, college, graduation year, and optional student number. Once verified, the same record becomes the account used for login and profile completion.

After login, the alumnus can maintain profile information and submit tracer data. The profile remains in users, while detailed tracer answers are stored in tracer_records. This is the main data source for charts, reports, and employment analytics.

For communication, administrators create announcements in announcements, while read tracking is stored in announcement_reads. Direct reminders, warnings, and system messages are stored in notifications. Feedback from alumni is stored in feedback so administrators can review and respond in an organized way.

For employment support, administrators manage published job opportunities in jobs. Alumni can notify ARLO about job opportunities through job_submissions. The current system does not store job applications because alumni do not apply for jobs through the portal.

Finally, system_logs records important actions for accountability. Laravel support tables such as migrations, sessions, cache, cache_locks, password_reset_tokens, and failed_jobs support framework operations such as schema tracking, login sessions, recovery links, temporary storage, and troubleshooting.

2. Current Table Summary

Table	Category	Rows	Main Purpose	Main Users
admin_role	Role assignment	1	Administrator account creation	Super Admin, System
admins	Administrative account	1	Admin login	Administrator, Super Admin
announcement_reads	Read tracking	3	Alumni announcement detail	Alumni, System
announcements	Communication record	118	Admin announcement management	Alumni, Administrator
cache	Laravel support	22	Framework-level caching	System
cache_locks	Laravel support		Framework-level lock management and concurrency protection.	System
failed_jobs	Laravel support		Framework-level troubleshooting for failed queued tasks.	System
feedback	Alumni feedback	4	Alumni feedback form	Alumni, Administrator
job_submissions	Alumni-submitted job opportunity	1	Alumni job opportunity submission	Alumni, Administrator
jobs	Published job opportunity	1	Job browsing page	Alumni, Administrator
migrations	Laravel support	48	Database version control	System
notifications	System notification	2357	Alumni notification page	Alumni, Administrator, System
password_reset_tokens	Account recovery support	1	Forgot password and reset password workflow for alumni	System
permissions	Permission definition	7	Admin route middleware	Super Admin, Administrator
role_permission	Permission assignment	9	Permission middleware	System
roles	Role definition	3	Super Admin account management	Super Admin, Administrator
sessions	Authentication support	2	Login state	System
super_admins	Super Admin account	1	Super Admin login	Super Admin
system_logs	Audit trail	423	Audit log module	Administrator, Super Admin
tracer_records	Tracer and employment data	105	Tracer form	Alumni, Administrator
users	Core alumni record	549	Registration verification	Alumni, Admin, Super Admin

3. Tables Not Present in the Current Database

The following names appeared during design discussion or earlier development stages, but they are not part of the current live schema.

Table Name	Reason
job_applications	Removed from the current implementation because alumni do not apply for jobs through the portal. Jobs are used for browsing and information only.
queue_jobs	Removed because the project now uses sync queue execution instead of storing queued jobs in the database.
job_batches	Removed because Laravel batch queue processing is not used in the current system.
job_matches	Not present in the current database schema.

4. Fields Removed from the Current Schema

The following fields were removed from the ERD because they were obsolete or derived from fields already maintained by the system.

Removed Field	Reason
jobs.salary_min	Removed because the maintained job salary value is the selected salary_range label.
jobs.salary_max	Removed because it was only a derived copy of the salary_range label and was not needed for the current workflow.
jobs.applications_count	Removed with the direct job-application workflow. The current system uses job_submissions for alumni-suggested opportunities.

5. Detailed Table Dictionary

admin_role

Purpose. The admin_role table connects administrator accounts to their assigned roles. It is a pivot table that allows the system to answer which administrator has which role without storing all access rules directly in the admins table.

Where it appears in the system. Administrator account creation, administrator role editing, login access checks, and scoped module access.

How records are created or changed. Created or updated when an administrator account is saved and the selected role is synchronized.

Item	Value
Table category	Role assignment
Current development row count	1
Direct relationships	admin_id -> admins.id; role_id -> roles.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
admin_id	uuid	Yes	PK; FK -> admins.id	Identifier of the administrator connected to this action.

Field	Data Type	Required	Key / Relationship	Purpose in the System
role_id	uuid	Yes	PK; FK -> roles.id	Role assigned to the administrator account.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

admins

Purpose. The admins table stores regular administrator accounts used by ARLO staff. These accounts are separate from alumni records so office personnel do not mix with graduate records. Admins use this table to log in to the operational dashboard where they manage alumni records, job postings, announcements, feedback, reports, analytics, and audit logs.

Where it appears in the system. Admin login, dashboard access, alumni management, jobs, announcements, feedback, analytics, reports, and audit logging.

How records are created or changed. Created and maintained by the Super Admin. Admin actions are linked to this table through related records and system logs.

Item	Value
Table category	Administrative account
Current development row count	1
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
firstname	varchar(255)	No	-	First name of the account holder.
lastname	varchar(255)	No	-	Last name of the account holder.
email	varchar(255)	Yes	Unique	Email address used for contact, login, or account recovery.
password	varchar(255)	Yes	-	Encrypted password used for secure authentication.
phone	varchar(30)	No	-	Contact phone number.
role	varchar(40)	Yes; default: 'admin'	-	Access role used by the application to control permissions.
email_verified_at	timestamp	No	-	Date and time when the email address was verified.
remember_token	varchar(100)	No	-	Token used by Laravel for remember-me authentication.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

announcement_reads

Purpose. The announcement_reads table answers a simple but useful question: has this alumnus already opened this announcement? It supports read/unread indicators so the system can make announcements easier to monitor.

Where it appears in the system. Alumni announcement detail, notification indicators, read/unread status, and announcement engagement monitoring.

How records are created or changed. Created when an alumnus opens or reads an announcement; deleted automatically when the related announcement is deleted.

Item	Value
Table category	Read tracking
Current development row count	3
Direct relationships	announcement_id -> announcements.id; user_id -> users.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	bigint	Yes; default: nextval('announcement_reads_id_seq')	PK	Primary identifier for the record.
announcement_id	uuid	Yes	Unique; FK -> announcements.id	Announcement record that was read by the alumnus.
user_id	uuid	Yes	Unique; FK -> users.id	Identifier of the alumni user connected to this record.
read_at	timestampTz	No	-	Date and time when the notification or announcement was read.
created_at	timestampTz	No	-	Date and time when the record was created.
updated_at	timestampTz	No	-	Date and time when the record was last updated.

announcements

Purpose. The announcements table stores official ARLO updates. It connects the previous Facebook-centered communication process to the web system by allowing administrators to create and publish announcements in one place, with optional Facebook synchronization.

Where it appears in the system. Admin announcement management, alumni announcements, notification generation, Facebook sync, and announcement views.

How records are created or changed. Created and edited by administrators; published to alumni; deleted permanently when the admin chooses Delete.

Item	Value
Table category	Communication record
Current development row count	118
Direct relationships	archived_by -> admins.id; created_by -> admins.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
title	varchar(255)	Yes	-	Display title of the record.
content	text	Yes	-	Main body or message content.
type	varchar(50)	No	-	Classification or category of the record.
priority	varchar(20)	Yes; default: 'Medium'	-	Importance level used to organize or highlight the record.
target_audience	varchar(100)	Yes; default: 'All'	-	Stores the target audience value used by the announcements record.
image_url	text	No	-	URL reference for image.
attachment_url	text	No	-	URL reference for attachment.
event_date	timestampTz	No	-	Date value for event.
event_location	varchar(255)	No	-	Stores the event location value used by the announcements record.
is_published	boolean	Yes; default: false	-	Indicates whether the announcement is visible to alumni.
published_at	timestampTz	No	-	Date and time when the announcement was published.
expires_at	timestampTz	No	-	Date and time related to expires.
views_count	integer	Yes; default: 0	-	Number of times the announcement was viewed.
created_by	uuid	No	FK -> admins.id	Administrator who created the record.
created_at	timestampTz	No; default: CURRENT_TIMESTAMP	-	Date and time when the record was created.
updated_at	timestampTz	No; default: CURRENT_TIMESTAMP	-	Date and time when the record was last updated.
archived_at	timestampTz	No	-	Previous archive timestamp column retained in the schema, although the current delete action removes records directly.
archived_by	uuid	No	FK -> admins.id	Administrator who archived the record before archive behavior was replaced by direct delete.
target_department	varchar(150)	No	-	Stores the target department value used by the announcements record.
target_graduation_year	smallint	No	-	Stores the target graduation year value used by the announcements record.
facebook_post_id	varchar(191)	No	Unique	Facebook post identifier used when syncing with the official page.
facebook_post_url	text	No	-	URL of the related Facebook post.

Field	Data Type	Required	Key / Relationship	Purpose in the System
facebook_last_synced_at	timestampTz	No	-	Date and time related to facebook last synced.

cache

Purpose. The cache table stores temporary system values that Laravel can reuse. It is not a direct alumni feature, but it helps the application avoid repeated work for values that can be safely stored for a short time.

Where it appears in the system. Framework-level caching, temporary lookups, and performance support.

How records are created or changed. Created and cleared automatically by Laravel cache operations.

Item	Value
Table category	Laravel support
Current development row count	22
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
key	varchar(255)	Yes	PK	Cache or lock key used by Laravel.
value	text	Yes	-	Cached value stored by Laravel.
expiration	integer	Yes	-	Unix timestamp indicating when the cache value expires.

cache_locks

Purpose. The cache_locks table prevents two processes from performing the same sensitive cached operation at the same time. It is a support table for safe background or concurrent operations.

Where it appears in the system. Framework-level lock management and concurrency protection.

How records are created or changed. Created temporarily when Laravel obtains a database cache lock; removed when the lock expires or is released.

Item	Value
Table category	Laravel support
Current development row count	
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
key	varchar(255)	Yes	PK	Cache or lock key used by Laravel.
owner	varchar(255)	Yes	-	Owner token of a Laravel cache lock.
expiration	integer	Yes	-	Unix timestamp indicating when the cache value expires.

failed_jobs

Purpose. The failed_jobs table records background jobs that fail. In the current system the queue driver is set to sync and queue_jobs/job_batches were removed, so this table is normally empty unless queued processing is reintroduced later.

Where it appears in the system. Framework-level troubleshooting for failed queued tasks.

How records are created or changed. Receives records only when a queued job fails while a queue worker is being used.

Item	Value
Table category	Laravel support
Current development row count	
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	bigint	Yes; default: nextval('failed_jobs_id_seq')	PK	Primary identifier for the record.
uuid	varchar(255)	Yes	Unique	Stores the uuid value used by the failed_jobs record.
connection	text	Yes	-	Stores the connection value used by the failed_jobs record.
queue	text	Yes	-	Queue name used by Laravel background job support.
payload	text	Yes	-	Serialized technical session or job data used by Laravel.
exception	text	Yes	-	Error details captured when a background job fails.
failed_at	timestamp	Yes; default: CURRENT_TIMESTAMP	-	Date and time when the background job failed.

feedback

Purpose. The feedback table stores alumni concerns, suggestions, and inquiries. It gives ARLO a structured place to receive and review alumni feedback instead of keeping concerns scattered across informal messages.

Where it appears in the system. Alumni feedback form, admin feedback management, response tracking, and dashboard summaries.

How records are created or changed. Created by alumni; reviewed and updated by administrators.

Item	Value
Table category	Alumni feedback

Item	Value
Current development row count	4
Direct relationships	assigned_to -> admins.id; user_id -> users.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
user_id	uuid	No	FK -> users.id	Identifier of the alumni user connected to this record.
subject	varchar(255)	Yes	-	Stores the subject value used by the feedback record.
message	text	Yes	-	Feedback, concern, or inquiry submitted by an alumnus.
type	varchar(50)	No	-	Classification or category of the record.
status	varchar(50)	Yes; default: 'Open'	-	Current workflow state of the record.
priority	varchar(20)	Yes; default: 'Medium'	-	Importance level used to organize or highlight the record.
assigned_to	uuid	No	FK -> admins.id	Stores the assigned to value used by the feedback record.
resolved_at	timestampTz	No	-	Date and time related to resolved.
created_at	timestampTz	No	-	Date and time when the record was created.
updated_at	timestampTz	No	-	Date and time when the record was last updated.

job_submissions

Purpose. The job_submissions table stores job opportunities suggested by alumni. It acts as a review lane: alumni can notify ARLO about an opportunity, and administrators decide whether to approve or reject it. Approved submissions can become published job records.

Where it appears in the system. Alumni job opportunity submission, admin job submission review, approval/rejection notifications, and audit trail.

How records are created or changed. Created by alumni; reviewed by admins; linked to users as submitters and admins as reviewers.

Item	Value
Table category	Alumni-submitted job opportunity
Current development row count	1
Direct relationships	reviewed_by -> admins.id; user_id -> users.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	bigint	Yes; default: nextval('job_submissions_id_seq')	PK	Primary identifier for the record.
user_id	uuid	Yes	FK -> users.id	Identifier of the alumni user connected to this record.
title	varchar(255)	Yes	-	Display title of the record.
company	varchar(255)	Yes	-	Stores the company value used by the job_submissions record.
type	varchar(255)	No	-	Classification or category of the record.
location	varchar(255)	No	-	Stores the location value used by the job_submissions record.
contact_email	varchar(255)	Yes	-	Stores the contact email value used by the job_submissions record.
application_deadline	date	No	-	Stores the application deadline value used by the job_submissions record.
description	text	Yes	-	Explanation, details, or description for the record.
requirements	text	No	-	Stores the requirements value used by the job_submissions record.
status	varchar(255)	Yes; default: 'pending'	-	Current workflow state of the record.
admin_notes	text	No	-	Notes entered by the administrator during review.
reviewed_by	uuid	No	FK -> admins.id	Administrator who reviewed the alumni-submitted job opportunity.
reviewed_at	timestamp	No	-	Date and time when the submitted job opportunity was reviewed.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

jobs

Purpose. The jobs table stores employment opportunities that are visible to alumni. In the current implementation, alumni can browse job postings but do not apply through the system. This keeps the module as an employment information board managed by the office.

Where it appears in the system. Job browsing page, admin job management, dashboard counts, and employment opportunity publication.

How records are created or changed. Created and edited by administrators or produced from approved alumni job submissions; deleted directly from the database when removed.

Item	Value
Table category	Published job opportunity

Item	Value
Current development row count	1
Direct relationships	archived_by -> admins.id; created_by -> admins.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
title	varchar(255)	Yes	-	Display title of the record.
company	varchar(255)	Yes	-	Stores the company value used by the jobs record.
description	text	No	-	Explanation, details, or description for the record.
requirements	text	No	-	Stores the requirements value used by the jobs record.
location	varchar(255)	No	-	Stores the location value used by the jobs record.
type	varchar(50)	No	-	Classification or category of the record.
salary_range	varchar(100)	No	-	Salary range label displayed with the published job posting.
application_deadline	date	No	-	Stores the application deadline value used by the jobs record.
contact_email	varchar(255)	No	-	Stores the contact email value used by the jobs record.
contact_phone	varchar(30)	No	-	Stores the contact phone value used by the jobs record.
is_active	boolean	Yes; default: true	-	Indicates whether the job posting is visible and active.
views_count	integer	Yes; default: 0	-	Number of times the job posting was viewed.
created_by	uuid	No	FK -> admins.id	Administrator who created the record.
created_at	timestamp	No; default: CURRENT_TIMESTAMP	-	Date and time when the record was created.
updated_at	timestamp	No; default: CURRENT_TIMESTAMP	-	Date and time when the record was last updated.
archived_at	timestamp	No	-	Previous archive timestamp column retained in the schema, although the current delete action removes records directly.
archived_by	uuid	No	FK -> admins.id	Administrator who archived the record before archive behavior was replaced by direct delete.

migrations

Purpose. The migrations table is Laravel's memory of database changes. Every time a migration runs, Laravel records it here so the system knows which table changes have already been applied.

Where it appears in the system. Database version control, deployment, migration status checks, and schema maintenance.

How records are created or changed. Updated automatically by Laravel when php artisan migrate is executed.

Item	Value
Table category	Laravel support
Current development row count	48
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	integer	Yes; default: nextval('migrations_id_seq')	PK	Primary identifier for the record.
migration	varchar(255)	Yes	-	Name of a Laravel migration file that has already run.
batch	integer	Yes	-	Migration batch number used by Laravel.

notifications

Purpose. The notifications table is the system's message inbox. It stores notices, reminders, warnings, announcement alerts, and job submission review results for registered alumni. This supports direct system-based communication instead of relying only on Facebook or manual messages.

Where it appears in the system. Alumni notification page, admin warning/reminder/notice buttons, announcement alerts, and job submission results.

How records are created or changed. Created by Laravel notification classes or admin actions; marked read when alumni open or acknowledge them.

Item	Value
Table category	System notification
Current development row count	2357
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
type	varchar(255)	Yes	-	Classification or category of the record.

Field	Data Type	Required	Key / Relationship	Purpose in the System
notifiable_type	varchar(255)	Yes	-	Laravel notification target model type.
notifiable_id	uuid	Yes	-	Identifier of the notification recipient.
data	text	Yes	-	Serialized notification payload shown to the user.
read_at	timestamp	No	-	Date and time when the notification or announcement was read.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

password_reset_tokens

Purpose. The password_reset_tokens table stores temporary reset tokens. It only receives data when a user requests a password reset link. The record is short-lived and is used to confirm that the reset request is valid.

Where it appears in the system. Forgot password and reset password workflow for alumni, admins, and Super Admin accounts.

How records are created or changed. Created when a reset link is requested; replaced by newer reset requests and consumed or expired after password reset.

Item	Value
Table category	Account recovery support
Current development row count	1
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
email	varchar(255)	Yes	PK	Email address used for contact, login, or account recovery.
token	varchar(255)	Yes	-	Secure token used for password reset validation.
created_at	timestamp	No	-	Date and time when the record was created.

permissions

Purpose. The permissions table stores the individual actions that can be granted to administrator roles. These records describe access such as managing alumni, managing jobs, managing announcements, handling feedback, viewing analytics, and viewing audit logs.

Where it appears in the system. Admin route middleware, module access checks, role setup, and Super Admin account-control workflows.

How records are created or changed. Seeded by the RBAC migration and connected to roles through the role_permission table.

Item	Value
Table category	Permission definition
Current development row count	7
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
name	varchar(100)	Yes	Unique	System name used internally by the application.
label	varchar(140)	Yes	-	User-readable label displayed in the system.
guard_name	varchar(40)	Yes; default: 'admin'	-	Authentication guard where the role or permission applies.
description	text	No	-	Explanation, details, or description for the record.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

role_permission

Purpose. The role_permission table connects each role to the permissions it grants. Through this pivot table, the system can check whether an administrator is allowed to open a module or perform an administrative action.

Where it appears in the system. Permission middleware, admin navigation, scoped administrator workflows, and RBAC maintenance.

How records are created or changed. Seeded by the RBAC migration according to the default permission set for each administrator role.

Item	Value
Table category	Permission assignment
Current development row count	9
Direct relationships	permission_id -> permissions.id; role_id -> roles.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
role_id	uuid	Yes	PK; FK -> roles.id	Role that receives the permission.
permission_id	uuid	Yes	PK; FK -> permissions.id	Permission granted to the role.

Field	Data Type	Required	Key / Relationship	Purpose in the System
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

roles

Purpose. The roles table stores the administrator role names used by the role-based access control design. Instead of treating every regular administrator the same way, the system can classify an admin account as Administrator, Alumni Records Manager, or Job Manager.

Where it appears in the system. Super Admin account management, admin login authorization, scoped administrator navigation, and permission checks.

How records are created or changed. Seeded by the RBAC migration and synchronized when the Super Admin creates or updates an administrator account.

Item	Value
Table category	Role definition
Current development row count	3
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
name	varchar(80)	Yes	Unique	System name used internally by the application.
label	varchar(120)	Yes	-	User-readable label displayed in the system.
guard_name	varchar(40)	Yes; default: 'admin'	-	Authentication guard where the role or permission applies.
description	text	No	-	Explanation, details, or description for the record.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

sessions

Purpose. The sessions table supports active logins when the database session driver is used. It stores technical session payloads so the system can remember that a user is already logged in while moving across protected pages.

Where it appears in the system. Login state, protected route access, session management, and logout behavior.

How records are created or changed. Created when a user logs in or starts a session; removed or expired when the session ends.

Item	Value
Table category	Authentication support
Current development row count	2
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	varchar(255)	Yes	PK	Primary identifier for the record.
user_id	uuid	No	-	Identifier of the alumni user connected to this record.
ip_address	varchar(45)	No	-	IP address captured during the action or session.
user_agent	text	No	-	Browser or device information captured during the action or session.
payload	text	Yes	-	Serialized technical session or job data used by Laravel.
last_activity	integer	Yes	-	Stores the last activity value used by the sessions record.

super_admins

Purpose. The super_admins table stores the highest account-control role. It is separated from the admins table because the Super Admin has a different interface and responsibility: managing admin accounts and maintaining alumni accounts, not handling daily operational modules such as announcements or analytics.

Where it appears in the system. Super Admin login, administrator account creation, administrator account editing, role/access control, and alumni account correction.

How records are created or changed. Usually seeded or created by a trusted setup process; used to create, update, or delete admin accounts and recorded in system logs.

Item	Value
Table category	Super Admin account
Current development row count	1
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
firstname	varchar(255)	No	-	First name of the account holder.
lastname	varchar(255)	No	-	Last name of the account holder.

Field	Data Type	Required	Key / Relationship	Purpose in the System
email	varchar(255)	Yes	Unique	Email address used for contact, login, or account recovery.
password	varchar(255)	Yes	-	Encrypted password used for secure authentication.
phone	varchar(30)	No	-	Contact phone number.
email_verified_at	timestamp	No	-	Date and time when the email address was verified.
remember_token	varchar(100)	No	-	Token used by Laravel for remember-me authentication.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.

system_logs

Purpose. The system_logs table is the accountability record of the platform. Important actions such as logins, record changes, admin account changes, announcements, notifications, and deletes are recorded here so the office can trace what happened and who performed the action.

Where it appears in the system. Audit log module, security monitoring, accountability checks, and administrative review.

How records are created or changed. Created automatically by audit logging services whenever important system actions occur.

Item	Value
Table category	Audit trail
Current development row count	423
Direct relationships	admin_id -> admins.id; super_admin_id -> super_admins.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
user_id	uuid	No	-	Identifier of the alumni user connected to this record.
action	varchar(255)	Yes	-	Name of the system action that was recorded.
description	text	No	-	Explanation, details, or description for the record.
ip_address	varchar(45)	No	-	IP address captured during the action or session.
user_agent	text	No	-	Browser or device information captured during the action or session.

Field	Data Type	Required	Key / Relationship	Purpose in the System
created_at	timestampTz	Yes; default: CURRENT_TIMESTAMP	-	Date and time when the record was created.
admin_id	uuid	No	FK -> admins.id	Identifier of the administrator connected to this action.
super_admin_id	uuid	No	FK -> super_admins.id	Identifier of the Super Admin connected to this action.

tracer_records

Purpose. The tracer_records table is where the graduate tracer story becomes measurable. After an alumnus completes tracer forms, the answers are stored here and connected to the alumni account. The analytics dashboard reads this table to summarize employment status, industry distribution, job alignment, satisfaction, salary range, and related graduate outcomes.

Where it appears in the system. Tracer form, employment analytics, report generation, charts, graduate outcome monitoring, and institutional planning.

How records are created or changed. Created or updated when alumni submit tracer information. Administrators read it for monitoring and reporting.

Item	Value
Table category	Tracer and employment data
Current development row count	105
Direct relationships	user_id -> users.id

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
user_id	uuid	Yes	FK -> users.id	Identifier of the alumni user connected to this record.
tracer_date	date	Yes	-	Date when the tracer record was submitted or updated.
is_employed	boolean	No	-	Boolean flag indicating whether employed applies.
employment_type	varchar(50)	No	-	Stores the employment type value used by the tracer_records record.
current_position	varchar(200)	No	-	Stores the current position value used by the tracer_records record.
current_company	varchar(200)	No	-	Stores the current company value used by the tracer_records record.
monthly_income	varchar(100)	No	-	Stores the monthly income value used by the tracer_records record.
industry	varchar(100)	No	-	Stores the industry value used by the tracer_records record.
job_satisfaction	smallint	No	-	Stores the job satisfaction value used by the tracer_records record.

Field	Data Type	Required	Key / Relationship	Purpose in the System
skills_used	text	No	-	Stores the skills used value used by the tracer_records record.
further_education	boolean	Yes; default: false	-	Stores the further education value used by the tracer_records record.
education_level	varchar(100)	No	-	Stores the education level value used by the tracer_records record.
challenges_faced	text	No	-	Stores the challenges faced value used by the tracer_records record.
recommendations	text	No	-	Stores the recommendations value used by the tracer_records record.
contact_permission	boolean	Yes; default: true	-	Stores the contact permission value used by the tracer_records record.
created_at	timestampTz	No	-	Date and time when the record was created.
updated_at	timestampTz	No	-	Date and time when the record was last updated.
curriculum_relevant_to_first_job	boolean	No	-	Stores the curriculum relevant to first job value used by the tracer_records record.
first_job_useful_competencies	json	No	-	Stores the first job useful competencies value used by the tracer_records record.
first_job_useful_competencies_other	varchar(200)	No	-	Stores the first job useful competencies other value used by the tracer_records record.
curriculum_not_relevant_reason	varchar(200)	No	-	Stores the curriculum not relevant reason value used by the tracer_records record.
curriculum_not_relevant_reason_other	varchar(200)	No	-	Stores the curriculum not relevant reason other value used by the tracer_records record.
employed_after_graduation	boolean	No	-	Stores the employed after graduation value used by the tracer_records record.
time_to_first_job	varchar(100)	No	-	Stores the time to first job value used by the tracer_records record.
time_to_first_job_other	varchar(200)	No	-	Stores the time to first job other value used by the tracer_records record.
first_job_related_to_course	varchar(20)	No	-	Stores the first job related to course value used by the tracer_records record.
first_job_finding_method	varchar(150)	No	-	Stores the first job finding method value used by the tracer_records record.
first_job_finding_method_other	varchar(200)	No	-	Stores the first job finding method other value used by the tracer_records record.

Field	Data Type	Required	Key / Relationship	Purpose in the System
first_job_monthly_earnings	varchar(100)	No	-	Stores the first job monthly earnings value used by the tracer_records record.
first_job_duration	varchar(100)	No	-	Stores the first job duration value used by the tracer_records record.
first_job_duration_other	varchar(200)	No	-	Stores the first job duration other value used by the tracer_records record.
presently_employed	varchar(30)	No	-	Stores the presently employed value used by the tracer_records record.
present_employment_status	varchar(100)	No	-	Stores the present employment status value used by the tracer_records record.
direct_supervisor_name	varchar(200)	No	-	Stores the direct supervisor name value used by the tracer_records record.
employer_email	varchar(200)	No	-	Stores the employer email value used by the tracer_records record.
is_first_job_after_college	boolean	No	-	Boolean flag indicating whether first job after college applies.
employment_proof_path	varchar(255)	No	-	Stored file path of the uploaded employment proof document.
job_level	varchar(100)	No	-	Stores the job level value used by the tracer_records record.
job_level_other	varchar(200)	No	-	Stores the job level other value used by the tracer_records record.
present_job_acceptance_reasons	json	No	-	Stores the present job acceptance reasons value used by the tracer_records record.
present_job_acceptance_other	varchar(200)	No	-	Stores the present job acceptance other value used by the tracer_records record.
present_job_monthly_earnings	varchar(100)	No	-	Stores the present job monthly earnings value used by the tracer_records record.
has_employee_awards	boolean	No	-	Stores the has employee awards value used by the tracer_records record.
employee_awards	text	No	-	Stores the employee awards value used by the tracer_records record.
teaching_faculty_enthusiastic	smallint	No	-	Stores the teaching faculty enthusiastic value used by the tracer_records record.
teaching_concepts_clear	smallint	No	-	Stores the teaching concepts clear value used by the tracer_records record.
teaching_faculty_knowledgeable	smallint	No	-	Stores the teaching faculty knowledgeable value used by the tracer_records record.

Field	Data Type	Required	Key / Relationship	Purpose in the System
teaching_commitment	smallint	No	-	Stores the teaching commitment value used by the tracer_records record.
degree_program_quality	smallint	No	-	Stores the degree program quality value used by the tracer_records record.
has_curriculum_suggestions	boolean	No	-	Stores the has curriculum suggestions value used by the tracer_records record.
curriculum_suggestions	text	No	-	Stores the curriculum suggestions value used by the tracer_records record.
has_employability_suggestions	boolean	No	-	Stores the has employability suggestions value used by the tracer_records record.
employability_suggestions	text	No	-	Stores the employability suggestions value used by the tracer_records record.
facilities_satisfaction	varchar(50)	No	-	Stores the facilities satisfaction value used by the tracer_records record.
has_facility_suggestions	boolean	No	-	Stores the has facility suggestions value used by the tracer_records record.
facility_suggestions	text	No	-	Stores the facility suggestions value used by the tracer_records record.
overall_recommend_institution	smallint	No	-	Stores the overall recommend institution value used by the tracer_records record.
overall_objectives_met	smallint	No	-	Stores the overall objectives met value used by the tracer_records record.
overall_university_experience	smallint	No	-	Stores the overall university experience value used by the tracer_records record.
employment_proof_disk	varchar(50)	No	-	Stores the employment proof disk value used by the tracer_records record.
employment_proof_original_name	varchar(255)	No	-	Stores the employment proof original name value used by the tracer_records record.
employment_proof_mime_type	varchar(120)	No	-	Stores the employment proof mime type value used by the tracer_records record.
employment_proof_size_bytes	bigint	No	-	Stores the employment proof size bytes value used by the tracer_records record.
employment_proof_uploaded_at	timestamp	No	-	Date and time related to employment proof uploaded.
tracer_number	varchar(20)	No	Unique	Human-readable tracer reference number used in reports.

Field	Data Type	Required	Key / Relationship	Purpose in the System
employment_proof_status	varchar(20)	No	-	Review status of the uploaded employment proof.
employment_proof_reviewed_by_guard	varchar(30)	No	-	Authentication guard of the reviewer who evaluated the employment proof.
employment_proof_reviewed_by_id	uuid	No	-	Identifier of the reviewer who evaluated the employment proof.
employment_proof_reviewed_at	timestamp	No	-	Date and time related to employment proof reviewed.
employment_proof_rejection_note	text	No	-	Reason recorded when an employment proof upload is rejected.

users

Purpose. The users table is the center of the alumni side of the system. It stores both CSV-imported alumni roster records and alumni accounts that already completed registration. When an alumnus signs up, the system checks the submitted name, birthdate, college, graduation year, and optional student number against this table. After registration, the same record becomes the alumni account used for login, profile management, notifications, tracer submission, and analytics.

Where it appears in the system. Registration verification, alumni login, alumni directory, profile management, tracer analytics, notifications, and CSV batch import.

How records are created or changed. Created by CSV import or manual/admin entry; completed by alumni registration; updated by alumni profile forms, admin maintenance, and super admin account correction.

Item	Value
Table category	Core alumni record
Current development row count	549
Direct relationships	No direct foreign key from this table in the current schema.

Field	Data Type	Required	Key / Relationship	Purpose in the System
id	uuid	Yes	PK	Primary identifier for the record.
firstname	varchar(100)	Yes	-	First name of the account holder.
lastname	varchar(100)	Yes	-	Last name of the account holder.
email	varchar(255)	Yes	Unique	Email address used for contact, login, or account recovery.
email_verified_at	timestamp	No	-	Date and time when the email address was verified.
password	varchar(255)	Yes	-	Encrypted password used for secure authentication.
phone	varchar(20)	No	-	Contact phone number.
department	varchar(100)	No	-	College or department graduated from.

Field	Data Type	Required	Key / Relationship	Purpose in the System
degree	varchar(200)	No	-	Degree or program completed by the alumnus.
year_graduated	integer	No	-	Graduation year used for filtering, reports, and verification.
employed_after_grad	varchar(10)	No	-	Stores the employed after grad value used by the users record.
industry	varchar(100)	No	-	Stores the industry value used by the users record.
current_position	varchar(200)	No	-	Stores the current position value used by the users record.
company	varchar(200)	No	-	Stores the company value used by the users record.
location	varchar(200)	No	-	Stores the location value used by the users record.
salary_range	varchar(50)	No	-	Stores the salary range value used by the users record.
linkedin_profile	varchar(500)	No	-	Stores the linkedin profile value used by the users record.
skills	text	No	-	Stores the skills value used by the users record.
achievements	text	No	-	Stores the achievements value used by the users record.
is_admin	boolean	Yes; default: false	-	Boolean flag indicating whether admin applies.
profile_visibility	varchar(20)	Yes; default: 'public_basic'	-	Controls whether selected alumni profile information can be displayed.
remember_token	varchar(100)	No	-	Token used by Laravel for remember-me authentication.
created_at	timestamp	No	-	Date and time when the record was created.
updated_at	timestamp	No	-	Date and time when the record was last updated.
data_privacy_consent	boolean	Yes; default: false	-	Stores whether the alumnus agreed to the system's data privacy consent.
data_privacy_consented_at	timestamp	No	-	Date and time related to data privacy consented.
has_scholarship	boolean	Yes; default: false	-	Stores the has scholarship value used by the users record.
scholarship_name	varchar(255)	No	-	Stores the scholarship name value used by the users record.
scholarship_year_awarded	smallint	No	-	Stores the scholarship year awarded value used by the users record.
scholarship_helped_get_job	boolean	No	-	Stores the scholarship helped get job value used by the users record.

Field	Data Type	Required	Key / Relationship	Purpose in the System
sex	varchar(20)	No	-	Stores the sex value used by the users record.
alumni_idnum	varchar(100)	No	-	Official alumni ID number used for graduate reference and verification.
student_idnum	varchar(100)	No	-	Student ID number used as an optional additional verification field.
middlename	varchar(100)	No	-	Middle name or middle initial of the account holder.
course	varchar(200)	No	-	Stores the course value used by the users record.
major	varchar(200)	No	-	Stores the major value used by the users record.
dt_grad	date	No	-	Exact graduation date when available from the alumni record.
is_batch_imported	boolean	Yes; default: false	-	Marks records imported from the CSV graduate reference file before full account registration.
batch_imported_at	timestampTz	No	-	Date and time when the alumni roster record was imported.
role	varchar(20)	Yes; default: 'alumni'	-	Access role used by the application to control permissions.
birthdate	date	No	-	Birth date used to strengthen alumni registration verification.
civil_status	varchar(30)	No	-	Stores the civil status value used by the users record.
newsletter_opt_in	boolean	Yes; default: true	-	Stores whether the alumnus agreed to receive announcement and newsletter emails.

6. Notes for the Manuscript

If the paper still mentions direct job applications, update that part to match the current implementation: alumni browse job postings and submit job opportunities for review, but they do not apply for jobs inside the portal.

If the ERD is updated, it should show users, admins, and super_admins as separate account tables.

The analytics module should be described as a computed feature that reads from users, tracer_records, jobs, job_submissions, announcements, feedback, notifications, and system_logs, not as a separate analytics table.

The queue_jobs and job_batches tables should not be included in the final ERD because they were removed from the current database.