Features

- Timing belt pulley
- T5mm teeth
- Suitable for 10mm wide belts
- Aluminium construction
- Resistant to corrosion, oils an acids

RS PRO Synchroflex timing Pulleys T5

RS Stock No.: see below table



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO hardwearing and tough pulley with 27 teeth for the secure holding of 10mm Polyurethane timing belts helping maintain the timing of your systems and eliminate the risk of damage caused from slippage.

Constructed from Aluminium with durable Zinc plated Stel flanges for excellent corrosion resistance and protection from moisture, oils and acids.


Suitable for a wide range of applications and commonly used in industrial automation, conveyor systems and vehicle manufacturing.

General Specifications


Application	For 10mm wide belt
Material	Aluminium with Zinc plated Steel Flanges
Belt Pulley type	Timing Belt Pulley

Products Range

RS Article no.	Type	No. of Teeth	dp	De	Df	Dm	F	L	Pilor Bore	No. Flanges
744946	1F	10	15.92	15.05	20	8	15	21	-	2
744952	1F	12	19.10	18.25	23	12	15	21	-	2
744968	1F	14	22.28	21.45	26	14	15	21	6	2
744974	1F	15	23.87	23.05	28	16	15	21	6	2
744980	1F	18	28.65	27.80	33	20	15	21	6	2
744996	1F	27	42.97	42.15	47	30	15	21	8	2
745652	1F	32	50.93	50.10	55	38	15	21	8	2
745668	1F	40	63.66	62.85	67	40	15	21	8	2



EXECUTION 1F



EXECUTION 2

Dimensions

Please note : All dimensions subject to change.
Pulleys may be Bored or Unbored.
If a dimension is critical to your application please contact our sales department for confirmation. for special pulleys or reworked pulleys