Routeur vers Poste D et poste A

```
Router>ping 192.168.10.14

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.10.14, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/2/8 ms

Router>ping 192.168.10.11

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.10.11, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/1 ms
```

PC-E vers le routeur et PC-3

```
C:\>ping 192.168.10.100

Pinging 192.168.10.100 with 32 bytes of data:

Reply from 192.168.10.100: bytes=32 time<1ms TTL=255
Reply from 192.168.10.100: bytes=32 time<1ms TTL=255
Reply from 192.168.10.100: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.10.100:
    Packets: Sent = 3, Received = 3, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

Control-C
^C
C:\>ping 192.168.10.19

Pinging 192.168.10.19 with 32 bytes of data:

Reply from 192.168.10.19: bytes=32 time<1ms TTL=128
Reply from 192.168.10.19: bytes=32 time<1ms TTL=128
```

Ces pings suffisent car ils représentent la