

Coarse-Grained Measurement

Donghun Jung

20 Feb 2026

Department of Physics, Sungkyunkwan University
QuiME Lab, Center for Quantum Technology, Korea
Institute of Science Technology



Schematic of the NV^- electronic structure

Coarse-grained quantum state tomography with optimal POVM construction

η_0, η_1 : the probability of **failing** to detect a signal from the $|0\rangle$ and $|1\rangle$ state.

$$\begin{aligned}\Pi_0 &= \eta_0|0\rangle\langle 0| + \eta_1|1\rangle\langle 1| && \text{no detection} \\ \Pi_1 &= (1 - \eta_0)|0\rangle\langle 0| + (1 - \eta_1)|1\rangle\langle 1| && \text{a detection event}\end{aligned}$$

Extending this framework to N -qubit system, the signal detection probability becomes:

$$M_{\text{CG}} = I^{\otimes N} - \Pi_0^{\otimes N}$$

resulting in two positive semidefinite observable operators $\{M_{\text{CG}}, I^{\otimes N} - M_{\text{CG}}\}$.

By implementing unitary gates $G^k(\hat{\theta})$ via parameterized quantum circuits, an extended set of CG POVM operators, $\Omega^k = G^{k\dagger}(\hat{\theta})M_{\text{CG}}G^k(\hat{\theta})$ can be constructed.

Coarse-grained quantum state tomography with optimal POVM construction

Idea: Uniformly distributed Measurement Operators across Hilbert space.

Uniformness of the set of measurement operators can be represented by von Neumann entropy of Gram matrix

$$S = -\text{Tr}(\Pi' \ln \Pi') = -\sum_i \lambda'_i \ln \lambda'_i$$

where Gram matrix is defined as each element is the inner product of the POVM bases $\Pi_{ij} = \text{Tr} \Omega^i \Omega^j$, and normalized $\Pi' = \Pi / \text{Tr} \Pi$ so that sum of eigenvalues becomes 1.

To maximize von Neumann entropy S , we iteratively update the circuit parameters $\hat{\theta}$. That is, we solved $\arg \max_{\hat{\theta}} S$.

Thank You!

Questions & Discussion