DUPLEX SEAWATER PUMPS / PRODUCT INFORMATION

# Seawater pumping needs a defined materials envelope.

Review duplex pump options against salinity, temperature, flow and pressure. Confirm the complete wetted package and flushing requirements; alloy selection is one part of a reliable seawater installation.

Seawater pumps use advanced materials and loaded sliding surfaces to operate with seawater as the only coolant and lubricant. The Duplex build uses bar-stock Duplex 2205 for all water-contacting components, with no cast parts.



axial piston seawater pump assembly

## Key operating parameters

| Parameter | Published value |
|---|---|
| Max speed | 2,000 rpm |
| Max input power | 1.4 / 1.8 kW (1.88 / 2.41 hp) |
| Max water flow | 0.55 / 0.72 m3/hr (2.42 / 3.17 US gpm) |
| Weight | 2.2 kg (4.85 lb) |
| Standard ports | 3/8 in BSPP |

## Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

# Technical data

| Parameter | Published value |
|---|---|
| Max speed | 2,000 rpm |
| Max input power | 1.4 / 1.8 kW (1.88 / 2.41 hp) |
| Max water flow | 0.55 / 0.72 m3/hr (2.42 / 3.17 US gpm) |
| Weight | 2.2 kg (4.85 lb) |
| Standard ports | 3/8 in BSPP |
| Max speed | 2,200 rpm |
| Max input power | 4.0 / 4.9 / 6.2 kW (5.36 / 6.57 / 8.31 hp) |
| Max water flow | 1.58 / 1.98 / 2.51 m3/hr (6.96 / 8.72 / 11.1 US gpm) |
| Weight | 6 kg (13.2 lb) |
| Standard ports | 3/4 in BSPP |
| Max speed | 2,000 rpm |
| Max input power | 6.9 / 8.9 / 10.4 kW (9.25 / 11.9 / 13.9 hp) |
| Max water flow | 2.76 / 3.6 / 4.2 m3/hr (12.2 / 15.9 / 18.5 US gpm) |
| Weight | 10 kg (22 lb) |
| Standard ports | 3/4 in BSPP |
| Max speed | 2,000 rpm |
| Max input power | 15.2 / 18.7 / 20.8 / 23.8 kW (20.4 / 25.1 / 27.9 / 31.9 hp) |
| Max water flow | 6.1 / 7.5 / 8.4 / 9.6 m3/hr (26.9 / 33 / 37 / 42.3 US gpm) |
| Weight | 19 kg (41.9 lb) |
| Standard ports | 1 in BSPP |
| Max speed | 2,000 rpm |
| Max input power | 40.0 / 53.3 / 66.7 kW (53.6 / 71.5 / 89.4 hp) |
| Max water flow | 16.2 / 21.6 / 27 m3/hr (71.3 / 95.1 / 119 US gpm) |
| Weight | 82 kg (181 lb) |
| Standard ports | 1-1/2 in BSPP |
| Max speed | 2,000 rpm |
| Max input power | 84.8 kW (114 hp) |
| Max water flow | 34.3 m3/hr (151 US gpm) |
| Weight | 82 kg (181 lb) |

| Parameter | Published value |
| --- | --- |
| Standard ports | 2 in BSPP |
| Max speed | 1,250 rpm |
| Max input power | 72.2 / 115.8 kW (96.8 / 155 hp) |
| Max water flow | 29.3 / 46.8 m3/hr (129 / 206 US gpm) |
| Weight | 120 kg (265 lb) |
| Standard ports | 4 in BSPP |