WATER HYDRAULIC MOTORS / PRODUCT INFORMATION

Rotary power begins with starting torque - not just running speed.

Compare water hydraulic motors against breakaway torque, speed range and the load's inertia. Confirm pressure difference, available flow, return conditions and the required stopping or holding arrangement.

Use the performance data and service instructions for the exact model at the intended duty. Efficiency, wear and replacement intervals depend on operating conditions and the selected component construction.



M3 Water Hydraulic Motor

Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

Technical data

Model selector

Product / configuration	Published selection information
M15: water hydraulic rotary power	Configuration-specific: refer to the individual product sheet.
M180: water hydraulic rotary power	Configuration-specific: refer to the individual product sheet.
M3: water hydraulic rotary power	Displacement 3.0 cc/rev (0.183 in³/rev); Max Pressure 160 bar (2,321 psi) continuous
M30: water hydraulic rotary power	Configuration-specific: refer to the individual product sheet.
M6: water hydraulic rotary power	Displacement 6.0 cc/rev (0.366 in³/rev); Max Pressure 160 bar (2,321 psi) continuous
M60: water hydraulic rotary power	Configuration-specific: refer to the individual product sheet.

Specifications and selection data

Model	Max Displacement (cm³/rev)	Min Displacement (cm³/rev)	Max Speed (RPM)	Max Torque (Nm)
M3	3.0 (0.183 in³/rev)	3.0 (0.183 in³/rev)	3000	7.5 (5.53 lbf·ft)
M6	6.0 (0.366 in³/rev)	4.6 (0.281 in³/rev)	3000	15 (11.1 lbf·ft)
M15	15 (0.915 in³/rev)	12 (0.732 in³/rev)	2500	38 (28 lbf·ft)
M30	30 (1.83 in³/rev)	23 (1.4 in³/rev)	2500	75 (55.3 lbf·ft)
M60	60 (3.66 in³/rev)	51 (3.11 in³/rev)	2200	150 (111 lbf·ft)
M180	180 (11 in³/rev)	135 (8.24 in³/rev)	1800	450 (332 lbf·ft)

Model	Max Power (kW)	Efficiency (%)	Weight (kg)	Temp Range
M3	2.4 (3.22 hp)	~90	2.8 (6.17 lb)	2 to 50°C (35.6 to 122 °F)
M6	4.7 (6.3 hp)	~90	3.2 (7.05 lb)	2 to 50°C (35.6 to 122 °F)
M15	10 (13.4 hp)	~90	7.5 (16.5 lb)	2 to 50°C (35.6 to 122 °F)
M30	20 (26.8 hp)	~90	12 (26.5 lb)	2 to 50°C (35.6 to 122 °F)
M60	35 (46.9 hp)	~90	24 (52.9 lb)	2 to 50°C (35.6 to 122 °F)
M180	85 (114 hp)	~90	95 (209 lb)	2 to 50°C (35.6 to 122 °F)

Selection and integration

Confirm current hazardous-area and quality-system documentation for the exact configuration. A supplier programme or quality certificate does not by itself approve the installed equipment for a hazardous area, marine duty, food contact or nuclear service.

Selection and integration

Never connect ports in reverse order. Catastrophic failure will occur.

Selection and integration

Do not use taper fittings under any circumstances.

Drawings and reference visuals

Dimensions, ports and curves are reproduced from the webpage visuals. Use the original drawing units and confirm the current approved drawing before fabrication or installation.

M6 Water Hydraulic Motor



M15 Water Hydraulic Motor

