AXIAL PISTON PUMPS / PRODUCT INFORMATION

Water hydraulic pumps: match delivered flow to useful work.

Choose displacement, speed and inlet arrangement against the required duty point. Review the P-series dimensions and performance data with water quality, drive power and service access in view.

Removing hydraulic oil from this circuit removes that oil inventory from a potential release. Water quality, additives, other machine fluids and local discharge requirements still need review for the application.



P15



P180



P3



P30

Selected models from this product family

Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

Technical data

Model selector

Product / configuration	Published selection information
P15: water hydraulic pumping at the required duty point	Displacements 12/15/19 cc/rev (1.159 in³/rev); Max Pressure 160 bar (2,321 psi) continuous
P180: water hydraulic pumping at the required duty point	Displacements 135/180/225 cc/rev (13.730 in³/rev); Max Pressure 160 bar (2,321 psi) continuous
P3: water hydraulic pumping at the required duty point	Displacement 3.0 cc/rev (fixed); Max Pressure 160 bar (2,321 psi) continuous
P30: water hydraulic pumping at the required duty point	Displacements 23/30/35 cc/rev (2.136 in³/rev); Max Pressure 160 bar (2,321 psi) continuous
P6: water hydraulic pumping at the required duty point	Max Displacement 6.0 cc/rev (0.366 in³/rev); Min Displacement 4.6 cc/rev (0.281 in³/rev)
P60: water hydraulic pumping at the required duty point	Displacements 51/63/70 cc/rev (4.272 in³/rev); Max Pressure 160 bar (2,321 psi) continuous

Specifications and selection data

Model	Max Disp (cc/rev)	Min Disp (cc/rev)	Max RPM Unboosted	Max RPM Boosted
P1	1.2 (0.0732 in³/rev)	0.8 (0.0488 in³/rev)	2000	,
P3	3.0 (0.183 in³/rev)	3.0 (0.183 in³/rev)	1800	2000
P6	6.0 (0.366 in³/rev)	4.6 (0.281 in³/rev)	1800	2000
P15	19.0 (1.16 in³/rev)	12.0 (0.732 in³/rev)	1800	2000
P30	35.0 (2.14 in³/rev)	23.0 (1.4 in³/rev)	1800	2000
P60	70.3 (4.29 in³/rev)	51.0 (3.11 in³/rev)	1800	2000
P180	225.0 (13.7 in³/rev)	135.0 (8.24 in³/rev)	,	2000

Model	Max Power (kW)	Max Flow (l/min)	Max Pressure (bar)	Weight (kg)
P1	0.55 (0.738 hp)	2.4 (0.634 US gpm)	160 (2,321 psi)	1.5 (3.31 lb)
P3	1.75 (2.35 hp)	6.0 (1.59 US gpm)	160 (2,321 psi)	1.9 (4.19 lb)
P6	3.8 (5.1 hp)	12 (3.17 US gpm)	160 (2,321 psi)	2.2 (4.85 lb)
P15	11 (14.8 hp)	37.2 (9.83 US gpm)	160 (2,321 psi)	6 (13.2 lb)
P30	19.5 (26.1 hp)	66 (17.4 US gpm)	160 (2,321 psi)	10 (22 lb)
P60	42 (56.3 hp)	146 (38.6 US gpm)	160 (2,321 psi)	19 (41.9 lb)
P180	114 (153 hp)	430 (114 US gpm)	160 (2,321 psi)	82 (181 lb)

Model	Temp Range
P1	2 to 90°C (35.6 to 194 °F)
P3	2 to 50°C (35.6 to 122 °F)
P6	2 to 50°C (35.6 to 122 °F)
P15	2 to 50°C (35.6 to 122 °F)
P30	2 to 50°C (35.6 to 122 °F)
P60	2 to 50°C (35.6 to 122 °F)
P180	2 to 50°C (35.6 to 122 °F)

Selection and integration

Variable displacement available on P60 and P180 only. Boost above 2000 RPM available on request. Antifreeze option available for below-freezing conditions. P180 unboosted RPM not rated; boosted operation required.