DUPLEX SEAWATER PUMPS / PRODUCT INFORMATION

Seawater pumping needs a defined materials envelope.

Review duplex pump options against salinity, temperature, flow and pressure. Confirm the complete wetted package and flushing requirements; alloy selection is one part of a reliable seawater installation.

Seawater pumps use advanced materials and loaded sliding surfaces to operate with seawater as the only coolant and lubricant. The Duplex build uses bar-stock Duplex 2205 for all water-contacting components, with no cast parts.



axial piston seawater pump assembly

Key operating parameters

Parameter	Published value
Max speed	2,000 rpm
Max input power	1.4 / 1.8 kW (1.88 / 2.41 hp)
Max water flow	0.55 / 0.72 m3/hr (2.42 / 3.17 US gpm)
Weight	2.2 kg (4.85 lb)
Standard ports	3/8 in BSPP

Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

Technical data

Parameter	Published value
Max speed	2,000 rpm
Max input power	1.4 / 1.8 kW (1.88 / 2.41 hp)
Max water flow	0.55 / 0.72 m3/hr (2.42 / 3.17 US gpm)
Weight	2.2 kg (4.85 lb)
Standard ports	3/8 in BSPP
Max speed	2,200 rpm
Max input power	4.0 / 4.9 / 6.2 kW (5.36 / 6.57 / 8.31 hp)
Max water flow	1.58 / 1.98 / 2.51 m3/hr (6.96 / 8.72 / 11.1 US gpm)
Weight	6 kg (13.2 lb)
Standard ports	3/4 in BSPP
Max speed	2,000 rpm
Max input power	6.9 / 8.9 / 10.4 kW (9.25 / 11.9 / 13.9 hp)
Max water flow	2.76 / 3.6 / 4.2 m3/hr (12.2 / 15.9 / 18.5 US gpm)
Weight	10 kg (22 lb)
Standard ports	3/4 in BSPP
Max speed	2,000 rpm
Max input power	15.2 / 18.7 / 20.8 / 23.8 kW (20.4 / 25.1 / 27.9 / 31.9 hp)
Max water flow	6.1 / 7.5 / 8.4 / 9.6 m3/hr (26.9 / 33 / 37 / 42.3 US gpm)
Weight	19 kg (41.9 lb)
Standard ports	1 in BSPP
Max speed	2,000 rpm
Max input power	40.0 / 53.3 / 66.7 kW (53.6 / 71.5 / 89.4 hp)
Max water flow	16.2 / 21.6 / 27 m3/hr (71.3 / 95.1 / 119 US gpm)
Weight	82 kg (181 lb)
Standard ports	1-1/2 in BSPP
Max speed	2,000 rpm
Max input power	84.8 kW (114 hp)
Max water flow	34.3 m3/hr (151 US gpm)
Weight	82 kg (181 lb)

Parameter	Published value
Standard ports	2 in BSPP
Max speed	1,250 rpm
Max input power	72.2 / 115.8 kW (96.8 / 155 hp)
Max water flow	29.3 / 46.8 m3/hr (129 / 206 US gpm)
Weight	120 kg (265 lb)
Standard ports	4 in BSPP