***WATERQUEST SOLUTIONS | SELECTION CLARIFICATION***

# Water hydraulic power units: selection basis

Revision 2026-10-27. Read this page before the accompanying catalogue extracts.

### *Configure the whole package*

Select the pump, drive, reservoir, filtration, valves and accessories around the required operating duty. P1 HPU configurations are listed to 100 bar (1,450 psi); P3, P6 and P15 configurations are listed to 160 bar (2,321 psi). These limits are subject to the supplied configuration.

### *Confirm Canadian electrical requirements*

Provide actual voltage, phase, frequency, available current, enclosure location and control requirements. The existing 400 V / 240 V catalogue options are not confirmation of a Canadian electrical supply or installation approval. Agree the motor, panel, protection and applicable approval evidence in the quotation.

### *Select materials for the water*

Confirm every wetted part, seal and fitting for the fluid chemistry, salinity and temperature. Do not assume that stainless construction or an oil-free hydraulic circuit establishes seawater suitability or a complete-package certification.

### *Agree supply and support*

Record included and excluded work, drawings, commissioning, acceptance criteria, delivery, warranty and service/spares arrangements in the written quotation. A reservoir or component approval does not establish approval of a complete HPU.

The following two pages retain the existing configuration tables as reference data. Obtain current, approved project drawings and selection records before ordering.

Sources: Current WaterQuest HPU configuration tables and website selection requirements.

bruce@waterquestsolutions.com | waterquestsolutions.com

# Technical data

## Your HPU, configured for the job

| Pump range | P1, P3, P6 and P15. P30, P60 and P180 on request. |
|---|---|
| Pressure | P1: up to 100 bar (1,450 psi). P3, P6 and P15: up to 160 bar (2,321 psi). |
| Reservoir | 5, 25, 55 or 90 L (1.32, 6.60, 14.5 or 23.8 US gal). Size matched to the pump and duty. |
| Filtration | Return filter with gauge or pressure switch; incoming-water filter and auto-fill options. |
| Valve package | C01-C07 configurations: relief, check, unloading and manifold options. |
| Accessories | Hand pump, pressure and level gauges, heat exchanger, fan cooler and tank return. |

## Configuration and ordering data

| Pump Series | cc/rev | 10 bar (145 psi) | 40 bar (580 psi) | 80 bar (1,160 psi) |
|---|---|---|---|---|
| P1 | 0.8 to 1.2 | 1.1 l/min (0.291 US gpm) 0.12 kW (0.161 hp) | 0.9 l/min (0.238 US gpm) 0.12 kW (0.161 hp) | 0.7 l/min (0.185 US gpm) 0.18 kW (0.241 hp) |
| P3 | 3.0 | 4.5 l/min (1.19 US gpm) 0.25 kW (0.335 hp) | 4.2 l/min (1.11 US gpm) 0.37 kW (0.496 hp) | 4.0 l/min (1.06 US gpm) 0.75 kW (1.01 hp) |
| P6 | 4.6 to 6.0 | 8.8 l/min (2.32 US gpm) 0.37 kW (0.496 hp) | 8.2 l/min (2.17 US gpm) 1.1 kW (1.48 hp) | 7.5 l/min (1.98 US gpm) 1.5 kW (2.01 hp) |
| P15 | 12.0 to 19.0 | 28.0 l/min (7.4 US gpm) 0.55 kW (0.738 hp) | 26.8 l/min (7.08 US gpm) 2.2 kW (2.95 hp) | 25.1 l/min (6.63 US gpm) 5.5 kW (7.38 hp) |

| Pump Series | 100 bar (1,450 psi) | 120 bar (1,740 psi) | 160 bar (2,321 psi) |
|---|---|---|---|
| P1 | 0.6 l/min (0.159 US gpm) 0.25 kW (0.335 hp) | - | - |
| P3 | 3.9 l/min (1.03 US gpm) 1.1 kW (1.48 hp) | 3.8 l/min (1 US gpm) 1.1 kW (1.48 hp) | 3.5 l/min (0.925 US gpm) 1.5 kW (2.01 hp) |
| P6 | 7.2 l/min (1.9 US gpm) 2.2 kW (2.95 hp) | 6.8 l/min (1.8 US gpm) 2.2 kW (2.95 hp) | 6.1 l/min (1.61 US gpm) 3.0 kW (4.02 hp) |
| P15 | 24.3 l/min (6.42 US gpm) 5.5 kW (7.38 hp) | 23.5 l/min (6.21 US gpm) 7.5 kW (10.1 hp) | 21.8 l/min (5.76 US gpm) 11 kW (14.8 hp) |

## Configuration and ordering data

| Pump | Code | Volume | A mm | B mm | C mm |
|---|---|---|---|---|---|
| P1 | S05 | 5L (1.32 US gal) | 120 (4.72 in) | 220 (8.66 in) | 300 (11.8 in) |
| P3 | S25 | 25L (6.6 US gal) | 220 (8.66 in) | 300 (11.8 in) | 870 (34.3 in) |
| P6 | S25 / S55 | 25 to 55L (6.6 to 14.5 US gal) | 220 to 350 | 300 to 550 | 870 to 1050 |
| P15 | S55 / S90 | 55 to 90L (14.5 to 23.8 US gal) | 350 (13.8 in) | 550 (21.7 in) | 1050 to 1350 |