Hydraulic Power Units for Water

Compact. Stainless. Built for clean power. 316L stainless steel, carbon-reinforced PEEK wear surfaces, 100% oil-free operation on tap or seawater. WaterQuest Solutions Pick a Pack configurator lets you build your HPU in five steps from pump to accessories.

Spill cleanup, regulatory fines, and remediation costs escalate quickly. Leaks and spills can add clean-up, remediation and reporting costs to an oil-driven power pack.

Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

Technical data

Your HPU, configured for the job

Pump range	P1, P3, P6 and P15. P30, P60 and P180 on request.
Pressure	P1: up to 100 bar (1,450 psi). P3, P6 and P15: up to 160 bar (2,321 psi).
Reservoir	5, 25, 55 or 90 L (1.32, 6.60, 14.5 or 23.8 US gal). Size matched to the pump and duty.
Filtration	Return filter with gauge or pressure switch; incoming-water filter and auto-fill options.
Valve package	C01-C07 configurations: relief, check, unloading and manifold options.
Accessories	Hand pump, pressure and level gauges, heat exchanger, fan cooler and tank return.

Configuration and ordering data

Pump Series	cc/rev	10 bar (145 psi)	40 bar (580 psi)	80 bar (1,160 psi)
P1	0.8 to 1.2	1.1 l/min (0.291 US gpm) 0.12 kW (0.161 hp)	0.9 l/min (0.238 US gpm) 0.12 kW (0.161 hp)	0.7 l/min (0.185 US gpm) 0.18 kW (0.241 hp)
P3	3.0	4.5 l/min (1.19 US gpm) 0.25 kW (0.335 hp)	4.2 l/min (1.11 US gpm) 0.37 kW (0.496 hp)	4.0 l/min (1.06 US gpm) 0.75 kW (1.01 hp)
P6	4.6 to 6.0	8.8 l/min (2.32 US gpm) 0.37 kW (0.496 hp)	8.2 l/min (2.17 US gpm) 1.1 kW (1.48 hp)	7.5 l/min (1.98 US gpm) 1.5 kW (2.01 hp)
P15	12.0 to 19.0	28.0 l/min (7.4 US gpm) 0.55 kW (0.738 hp)	26.8 l/min (7.08 US gpm) 2.2 kW (2.95 hp)	25.1 l/min (6.63 US gpm) 5.5 kW (7.38 hp)

Pump Series	100 bar (1,450 psi)	120 bar (1,740 psi)	160 bar (2,321 psi)
P1	0.6 l/min (0.159 US gpm) 0.25 kW (0.335 hp)	-	-
P3	3.9 l/min (1.03 US gpm) 1.1 kW (1.48 hp)	3.8 l/min (1 US gpm) 1.1 kW (1.48 hp)	3.5 l/min (0.925 US gpm) 1.5 kW (2.01 hp)
P6	7.2 l/min (1.9 US gpm) 2.2 kW (2.95 hp)	6.8 l/min (1.8 US gpm) 2.2 kW (2.95 hp)	6.1 l/min (1.61 US gpm) 3.0 kW (4.02 hp)
P15	24.3 l/min (6.42 US gpm) 5.5 kW (7.38 hp)	23.5 l/min (6.21 US gpm) 7.5 kW (10.1 hp)	21.8 l/min (5.76 US gpm) 11 kW (14.8 hp)

Configuration and ordering data

Pump	Code	Volume	A mm	B mm	C mm
P1	S05	5L (1.32 US gal)	120 (4.72 in)	220 (8.66 in)	300 (11.8 in)
P3	S25	25L (6.6 US gal)	220 (8.66 in)	300 (11.8 in)	870 (34.3 in)
P6	S25 / S55	25 to 55L (6.6 to 14.5 US gal)	220 to 350	300 to 550	870 to 1050
P15	S55 / S90	55 to 90L (14.5 to 23.8 US gal)	350 (13.8 in)	550 (21.7 in)	1050 to 1350