P1 | Axial-piston pump

Compact, water-lubricated axial-piston technology for a defined operating duty.

P1 supplies pressurised water to hydraulic actuators or a process. Select delivered flow at the working pressure, then match displacement, speed, drive power and inlet supply.

Published parameter	P1 range rating
Maximum displacement (cm³/rev)	1.2
Minimum displacement (cm³/rev)	0.8
Maximum speed, unboosted (rpm)	2000
Maximum speed, boosted (rpm)	Not listed
Maximum input power (kW)	0.55
Maximum water flow (L/min)	2.4
Maximum continuous pressure (bar)	160
Mass (kg)	1.5
Maximum temperature (°C)	90
Minimum temperature (°C)	2

Nominal ordering displacements: 0.8 / 1.2 cm³/rev. Nominal options and range-table limits are different source entries; use the selected configuration.

Design & environmental advantages

Multiple pistons smooth the delivery of power. Water lubricates the working surfaces, removing hydraulic oil from this circuit. Standard stainless construction and selectable internal materials support fluid-specific selection.

Efficiency & selection

Match component size to useful work. Read the supplied efficiency curve at pressure and speed. Avoid sustained relief flow and excessive throttling; these convert useful hydraulic power into heat.

Installation and procurement

Specify flow, pressure, speed, fluid chemistry, inlet supply, rotation, seal type, shaft coupling and mounting. No induced radial or axial shaft load. Nominal 10 µm / 25 µm absolute filtration, beta10 ≥ 75, is listed in the pump catalogue. Variable versions are listed for P60 and P180 only.

P1 pressure varies by configuration: the range table lists 160 bar, while the dimensional page shows PC100 models. The standard HPU uses a 100 bar limit. Use the ordered rating. The 90 °C range-table maximum requires configuration review; standard guidance above 50 °C is conditional.



Connect the selected design

Two-port pumps need flooded, positive inlet pressure and cannot lift water. Three-port boosted units separate the feed and case drain. Specify that arrangement in the order.

Reference conversions: 160 bar = 2,321 psi; 1 L/min = 0.264172 US gpm; 1 kg = 2.20462 lb.


Family photograph; configuration varies.

Janus Axial Piston Water Pump - V.01.25 (3).pdf, pp. 2-4. Website product context checked 17 Oct 2026.


P1 | Performance curves

Read displacement, speed and pressure together. Published curve data are preserved.


Output flow (L/min)




Input power (kW)



Input torque (N·m)



Overall efficiency (%)



Apply the curves to the duty

P1 pressure varies by configuration: the range table lists 160 bar, while the dimensional page shows PC100 models. The standard HPU uses a 100 bar limit. Use the ordered rating. The 90 °C range-table maximum requires configuration review; standard guidance above 50 °C is conditional.


1 L/min = 0.264172 US gpm; 1 bar = 14.5038 psi; 1 kW = 1.34102 hp; 1 N·m = 0.737562 lbf·ft.

Janus Axial Piston Water Pump - V.01.25 (3).pdf, p. 6.

P1 | Dimensions & connections


Manufacturer technical reference | dimensions govern; reproduction is not to scale.

PC100-0.8WMS & PC100-1.2WMS



M4 Mounting studs supplied

PC100-0.8W & PC100-1.2W



M4 Mounting studs supplied

Port threads and flange classes are connection designations, not converted diameters or operating-pressure ratings. Select the exact configuration shown on the approved order drawing.