Flow Control Valve


Selection data & performance | Manufacturer technical reference.

Manufactured from 316 stainless steel and special engineering polymer selected for their corrosion resistance and resilience to flow erosion. Designed for operation on tap water to EU directive 98/83/EC without additive.

SPECIFICATION		
	DN3	DN6
Operating Pressure Range	0.1 to 200 bar	0.1 to 200 bar
Maximum Cv Value in flow control direction	0.02	0.62
Feed Gallery Diameter	3mm	6mm
Porting	1/4" BSP (Parallel)	1/4" BSP (Parallel)
Construction Materials	A.I.S.I 316/Polymer	A.I.S.I 316/Polymer
Number of turns Fully open to fully closed	4	4
Media	Water	Water



Dimensions




Dimensions in mm


Rotation of the control wheel opens the flow to a series of helical ports resulting in a very precise control throughout its range. Using materials with a high resistance to flow erosion and a design that ensures the aggressive high pressure jets do not affect the long term setting of the valve.

The valve is supplied with an externally adjusted thumb wheel for operator control without the need for tools. Also fitted with a tamper proof locking screw; when locked, the wheel can be rotated but the setting will not be affected.

Free Flow Characteristics DN3



Free Flow Characteristics DN6



ORDERING CODES	DN3	DN6
Flow Control Valve	204AXXW	204BXXW


Identify the metered direction and free-return direction. Flow depends on differential pressure; adjustment-turn curves apply to the stated test pressure. Water service removes hydraulic oil from the fluid circuit. Minimise unnecessary pressure loss; request configuration-specific approval evidence.

Flow Control Valve V.01.25.pdf, p. 1. Manufacturer labels and dimensions retained.


Flow Control Valve

Dimensions, connections & configuration | Manufacturer technical reference.

204AXXW Restricted Flow output in relation to turns of the collar 160 bar inlet pressure



204BXXW Restricted Flow output in relation to turns of the collar 160 bar inlet pressure



The Water Hydraulics Co. Ltd.
Alexandra House, English Street, Hull, East Yorkshire, HU3 2DJ, United Kingdom.
Tel: +44 (0)1482 595000, E-Mail: sales@waterhydraulics.co.uk.
England Website: www.waterhydraulics.co.uk
Whilst every endeavour has been made to ensure accuracy, this publication cannot be considered to represent part of any contract, whether expressed or implied. The publishers reserve the right to amend specification at their discretion.

V01.25

bsi ISO 9001 Quality Management Systems CERTIFIED
FM 87247

Identify the metered direction and free-return direction. Flow depends on differential pressure; adjustment-turn curves apply to the stated test pressure. Water service removes hydraulic oil from the fluid circuit. Minimise unnecessary pressure loss; request configuration-specific approval evidence.

Flow Control Valve V.01.25.pdf, p. 2. Manufacturer labels and dimensions retained.