# Hose Burst Valve

Selection data & performance | Manufacturer technical reference.

Manufactured from 316 stainless steel and special engineering polymer selected for their corrosion resistance and resilience to flow erosion. Designed for operation on tap water to EU directive 98/83/EC without additive.


| SPECIFICATION | | |
|---|---|---|
| | DN3 | DN6 |
| Operating Pressure Range | 0.1 to 200 bar | 0.1 to 200 bar |
| Reverse Flow Adjustment L/min | 1 to 5 | 5-10 |
| Max Flow rate L/min | 30 | 50 |
| Maximum Cv Value in flow control direction | 0.02 | 0.62 |
| Feed Gallery Diameter | 6mm | 6mm |
| Porting | 1/4" BSP (Parallel) | 1/4" BSP (Parallel) |
| Construction Materials | A.I.S.I 316/Polymer | A.I.S.I 316/Polymer |
| Media | Water | Water |



The hose burst valves allows free flow in both directions under normal operating conditions, however in the event of a hose burst the surge in flow from 'B' to 'A' the valve will immediately stop the flow locking pressure in 'B' . The valve can be reset by reversing the flow when the hose has been replaced. Reaction flow rate should be set to 1.5 x maximum system flow rate.


The valve is supplied with an internally adjusted spring. This can be set by TWHC to the flow required.

## Dimensions






Dimensions in mm

## Free Flow Characteristics DN3




## Free Flow Characteristics DN6




| ORDERING CODES | DN3 | DN6 |
|---|---|---|
|  Hose Burst Valve | 591-001 | 591-007 |

The Water Hydraulics Co. Ltd.

Alexandra House, English Street, Hull, East Yorkshire, HU3 2DJ, United Kingdom.

Tel: +44 (0)1482 595000, E-Mail: sales@waterhydraulics.co.uk.

England Website: www.waterhydraulics.co.uk

Whilst every endeavour has been made to ensure accuracy, this publication cannot be considered to represent part of any contract, whether expressed or implied. The publishers reserve the right to amend specification at their discretion.

V01.25

bsi ISO 9001 Quality Management Systems CERTIFIED

FM 87247

Match trip flow to normal motion, transients and the protected load. Verify reset, leakage and response within the complete machine circuit. Water service removes hydraulic oil from the fluid circuit. Minimise unnecessary pressure loss; request configuration-specific approval evidence.

Hose Burst Valve V.01.25.pdf, p. 1. Manufacturer labels and dimensions retained.