Valve Ordering Code

Selection data & performance | Manufacturer technical reference.



PRESSURE RATING	
*	(Bar)
1	<30
2	Up to 160
3	>60* (*Relief Valve Only)
4	25-100* (*Relief Valve Only)

MOUNTING	
*	
.....	Stand Alone
M	Janus Manifold
C	CETOP-3

VALVE TYPE	
*	
01	4/2
02	4/3 Closed Centre
03	3/2 Spring to P Closed
04	Priority Flow Control
05	Relief (Inline)
06	4/3 Closed P
07	Pressure Control (Janus)
08	3/2 Spring to P Open
09	Pressure Reducing
10	Check
11	PO Check Single Port 3:1
12	4/3 Open Centre
13	PO Check Double Port 3:1
14	4/3 P to A B at centre
15	Flow Divider
16	Pressure Compensated Flow Control
17	Solenoid Operated Un-Loader
18	- - - -
19	PO Check Single Port 9:1
20	- - - -
21	2/2 Normally Open
22	PO Check Double Port 9:1
23	Electronic Flow Control
24	- - - -
25	Electronic Pressure Control
26	2/2 Normally Closed
XX	Assembly

PORT ORIFICE	
*	
A	3
B	6
C	9
D	12
E	16
F	25
G	38

ACTUATION / RETURN	
*	
A	Solenoid 12VDC (No Card)
B	Solenoid 24VDC (Card Required)
C	Solenoid 48VDC (Card Required)
D	Detent
E	- - - -
F	Air Pilot
G	Manual
H	Flow Controlled
J	Water Pilot
K	- - - -
L	Oil Pilot
M	- - - -
N	24VDC Proportional
O	24VDC (No Card)
P	48VDC (No Card)
R	Stepper Motor Control
S	Spring* (*Return Only)
X	Pressure

FLUID	
*	
O	Other
S	Sea Water
T	Tech. Water
W	Tap Water

Example:
A Valve with a system operating pressure of 140 Bar, 4/3 Closed P, 6mm Ports, Manifold Mounted, 24V DC Solenoid actuated spring return for tap water.

(Note: Janus Control Valves stating (Card Req'd) require an actuation card as additional item. (Please refer to actuation card data sheet)

Ordering Code = 2 M 0 6 B B S W

The Water Hydraulics Co. Ltd.
Alexandra House, English Street, Hull, East Yorkshire, HU3 2DJ, United Kingdom.
Tel: +44 (0)1482 595000, E-Mail: sales@waterhydraulics.co.uk.
England Website: www.waterhydraulics.co.uk

Whilst every endeavour has been made to ensure accuracy, this publication cannot be considered to represent part of any contract, whether expressed or implied. The publishers reserve the right to amend specification at their discretion.

V01.25

bsi ISO 9001 Quality Management Systems CERTIFIED
FM 87247

Use the code guide with the selected valve specification. Confirm every code segment, fluid, seal, actuation and port configuration in the supplier quotation. Water service removes hydraulic oil from the fluid circuit. Minimise unnecessary pressure loss; request configuration-specific approval evidence.

Valve Ordering Code V.01.25.pdf, p. 1. Manufacturer labels and dimensions retained.