APPLICATION BRIEF · HYDRO

Hydroelectric gates and powerhouse valves

Put clean-water actuation beside the reservoir and tailrace.

Water-actuated gates and valves can remove an oil source from a drainage or waterway exposure path. Choose a bounded mechanism and define the actual operating and protective duties before selecting equipment.

Typical duties to assess

Gate and stoplog actuation · Trash-rack rake mechanisms · Powerhouse unwatering and dewatering valves · Cooling-water and service-water isolation

Equipment and project scope

Select water-service pumps, cylinders or motors, control valves and a power unit around the duty. The quotation defines equipment, interfaces, documentation and integration responsibilities.

What to establish

Send valve size and pressure class, gate or linkage loads, required movement time, fail position, standby interval and available utilities. Pressure transients, load holding and site acceptance remain project design responsibilities.

Evidence and boundaries

WaterQuest’s stainless, cylinder-operated gate is shown in a workshop demonstration. The separate supplied motor-driven hydraulic schematic illustrates another gate drive arrangement; it is not the as-built circuit for the cylinder gate.

Start with the duty

Send the asset, operating problem, location, required timing and available drawings. We will assess the equipment scope and the evidence needed for a quotation.

Proposed applications are not customer installations or approvals. Confirm ratings and documentation for the selected equipment and project.