POWER CENTRE REVERSE OSMOSIS / PRODUCT INFORMATION

Recover brine energy. Measure the complete RO duty.

Explore Power Centre configurations that combine feed pumping and energy recovery. Compare them at the project's feed chemistry, pressure, recovery and production rate, with auxiliary electrical loads included.

The pump supplies RO feed pressure while the energy-recovery function uses pressure available in the concentrate stream. Confirm both flow paths, recovery ratio and pressure conditions. Auxiliary pumping may still be required for the complete arrangement.



PC1000



PC250



PC300



PC500

Selected models from this product family

Selection basis

Match the selected configuration to the working water, pressure, flow, temperature and duty. Maximum ratings and separate curve points do not establish one simultaneous operating point. Confirm installation and supplied configuration with WaterQuest Solutions.

Technical data

Model selector

Product / configuration	Published selection information
PC1000: feed pumping and brine energy recovery	Configuration Dual axial piston pumps + integrated energy recovery motor; Housing, shaft and pistons Duplex stainless steel
PC250: feed pumping and brine energy recovery	Configuration Axial piston pump + integrated energy recovery motor; Housing, shaft and pistons Duplex stainless steel
PC300: feed pumping and brine energy recovery	Configuration Axial piston pump + integrated energy recovery motor; Housing, shaft and pistons Duplex stainless steel
PC500: feed pumping and brine energy recovery	Configuration Axial piston pump + integrated energy recovery motor; Housing, shaft and pistons Duplex stainless steel

Application and specification

Compare input at the same product-water rate, feed conditions and membrane duty. State whether pretreatment, booster pumps and other auxiliaries are included. Reference production and recovery curves are useful selection inputs, not guaranteed plant output.

Review feed and brine chemistry, cleaning agents and flushing procedure against the selected materials and seals. Include pressure protection, instrumentation and service access. Confirm the operating envelope for the exact Power Centre configuration.

Compare specifications, performance curves, installation drawings and configuration options.

Axial piston, product-lubricated. Water-based lubrication throughout. No oil changes.

Converts high-pressure brine exhaust energy directly back to shaft power. No separate unit.

Driven directly by recovered brine energy via shaft coupling. No separate motor needed.