INDEX

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

Page numbers with (f) refer to figures: those with (t) refer to tables.

A

abrasion, 210; bank, 643, 645; coefficients, 212(f); quantification, 211–212; rivers, application to, 212–213; selective sorting, 223–224
abutment protection. *see also* riprap protection for abutments; scour at abutments: alternatives for, 573–574; failure mechanisms, 568–569; guide banks, 569–570, 569(f), 570(f); shape of abutment, 569
accelerated (human-induced) deposition, 11
accelerated erosion: agricultural activities, 5; causes, 7; dams and river regulation, 6–7; forest activities, 5; mining activities, 6; roads, railways, bridges, levees, 5–6, 6(f); urbanization, 5; warfare and population migration, 7
accuracy, defined, 719, 1089
Ackers-White extended with Proffitt-Sutherland relation, 201–202
Ackers-White relation, 126–127
active-bed channels: example, 490(t); slope and depth, 489–490; width determination, 488–489
active-layer composition, 1090(f)
active-layer concept: bed and near bed processes, 703, 703(f); bed elevation during transport, 183; diagram, 184(f), 703(f); entrainment formulation, 185–186; generalizations, 185; Hirano formulation, 183–184; system closure for sediment processes, 709–711; thickness and interfacial exchange fractions, 184–185
active sediment-transport processes: advection, 971–972; bioturbation-induced transport, 972–974; deposition or erosion, 971; dune formation, 971
active-stratum approach, 704–705, 704(f), 709–711
ADCP (Acoustic Doppler Current Profiler): flow velocities measured with, 293, 295, 722; Leavenworth Bend, Missouri River, 736, 738–740; special considerations regarding, 719
adjustment factor, 387–391, 522(f), 1089
advection, 971–972
aggradation: bridge site selection, 548, 556; defined, 876, 1085; induced by dams, 172; long-term, total scour, 506
aggregation: concentration, 264–265; fine-grained sediment transport, 261–266; floc strength, 263–264; floc transport, 261–262, 261(f); fractal depression, 263; order, 262–263, 263(t); settling velocity, 266–267; shear stress, 264–265; transport modes, 265–266; turbulence, 264–265
AGNPS (Agricultural NonPoint Source pollution model), 840, 841, 850–851, 852
agricultural activities, 5
Agricultural Runoff Management (ARM) model, 848
Agricultural Stabilization and Conservation Service (ASCS), 667
air temperatures, 614(f), 615, 617, 618, 624–625
algebraic stress models, 793–794
algorithm, 591, 910, 1089
alluvial-channels. *see also* alluvial streams: classification, 377(t); hydraulic and geomechanical impacts, combined, 645; hydraulic impacts, 635–640; ice effects, 635, 640–645
alluvial deposit, defined, 1089
alluvial fan flooding, 900; before and after comparison, 914(f); background, 901–902; boulder deposit, 898(f); characteristics, 903(t); current developments, 903–904; early developments, 902–903; hydraulic processes, 904(t)
alluvial fans, 12; bridge site selection, 549; characteristics, 903(t); examples, 870(f); geomorphic map, 871(f); inundation, 917(f)
alluvial reach, 470, 635, 1089
alluvial streams, 33(f), 367, 476, 1089, 1096
alluvium, 58, 220, 402, 863, 877, 1089
alternate bars, 81, 82(f), 84–85, 362(f), 1089, 1090(f)
American sedimentation law: "act of God" defense, 950–952; court decisions, trend-setting, 937, 939–940; defenses, 946; forensic geology, 952; future directions, 952–954; Manual 54, 937–939; natural hazards, 940–946; Project Impact, 954–955; public liability, 940–946; recent developments, 954–956; sovereign immunity, 946–948; statutes of limitations, 948; stream *vs.* downstream legal issues, 949–950; taking laws, 940–946, 949; tort laws, 949; tort theories, hazard mitigation measures based on, 948–949; trends in, recent, 939
anabranching, 636–637
Anaconda copper mine, 235(f)
analytical model, defined, 1089
analytical methods, 489
Annualized Agricultural NonPoint Source model (AnnAGNPS), 840, 841, 842–844(t), 850–851

anomaly, defined, 1089
ANSWERS, 840, 850, 851, 852; ANSWERS-continuous, 840, 841, 850
antidunes, 81, 82(f), 83
arbitrarily sloping bed, 59–60
Argos Modeling System, 699
armor (dark grains): coarse static, 169(f); layer, 165, 216, 551, 1089
armoring measures, 165(f), 216, 550, 550(f), 552(t), 1089
Ashida-Michiue relation, 195
Assessment of Structural Flood-Control Measures on Alluvial Fans (HEC), 907
auxiliary relations, 711–712. *see also* system closure
avalanches, 9, 22, 891, 897
average end concept, 1090
avulsion: defined, 878, 1090; hydraulic impacts of river ice, 632; riparian rights gained or lost by, 938–939

B

backfilling, 876
backwater curve, 125, 135, 1090
backwater profile, 1090
Bagnoldean formulation, 66
bag samplers, 328
bank erosion: conceptual models, 408–410; defined, 876; empirical methods, 415; equilibrium approaches, 411–414
bankfast-ice: frazil-ice, 616(f); loading, 615, 615(f), 642–643, 642(f)
bank-full discharge, 364–365; *vs.* bank-full depth, 180(f); frequencies, 365(t); stage-discharge diagram, 178(f)
bank-full flow, 121–123, 122–123(f)
bank mechanics: advance, 406–407; basal endpoint control, 404–405; erosion, 400–401; erosion, resistance to, 401; extremal hypotheses, 422; geofluvial approaches, 422–423; retreat *vs.* near-bank velocity, 415(f); seepage effects, 406; stability, mass failure, 401–404; vegetation effects, 405–406
bank migration, 443, 649, 1090
bank protection, 549–553; armoring measures, 550, 550(f), 552(t); artificial riprap, 550; bendway weirs, 553; broken concrete, 550; cable-tied blocks, 550; concrete-grouted riprap, 551; concrete pavement, 551; flow-retarding measures, 553; gabions, 551; groins, 553, 553(f), 554(t); grout-filled bags, 550; grout-filled mats, 551; hardpoints, 553; Iowa vanes, 553; overview, 549–550; precast blocks, 550; Reno mattresses, 551; rock riprap and broken concrete, 550; used tires, 550–551; vegetation, 551, 553
bank sediment reservoir, 1090
basaltic rocks, 34
base test, 655
BASINS, 848, 851
bathymetric survey, 591–592
bay, defined, 533
bechevnik, 643, 644(f)
bed and near-bed processes: active-layer and active-stratum approach, 703–705; bed load-layer and total-load approach, 701–703; overview, 701
bed-elevation changes, 696(t), 698(t), 700
bed forms, 77, 1090. *see also* flow resistance; alternate bars, 81, 82(f), 84–85; antidunes, 81, 82(f), 83; characteristics, 96(f); charts, 89–92(f); classification, 88–89(f), 93(f); criteria diagram, 87(f); dimensionless characterization, 85–94; discriminators, 86(f); dunes, 81–83, 82(f); equilibrium predictions, 94–97; geometry types, 93; knowledge in, 78–81; progression, 85; ripples, 81, 83–84; river stage effects, 97–99; transition zone, 93(f); types, 82(f); undermining, 558
bed-layer, 178, 238, 629, 1090
bed load: be-material-load equations, 1079–1083(t); box-and-whisker plots, 1076(f); defined, 8, 1090; discharge, 121, 308, 344–345, 1090, 1099; field data on, 633; functions, 74(f)
bed load-layer approach, 701–703, 709
bed load material equations, 1079–1082(t); data issues, 1074–1076, 1074(f), 1075–1076(f); overview, 1073–1074; sediment supply issues, 1076–1077; summary, 1083(t); technical issues, 1077–1078, 1083
bed load samplers, 338; calibrations, 341–342; discharge measurements, 344–345; Helley-Smith, 1074–1075(f); manually operated portable, 339–341, 341(f); pit and trough, 342–343; summary, 343–344; types, 339–344; vortex tube, 343
bed load transport, 66. *see also* bed-material load in sand-bed streams, dimensionless relations for; analysis, 67–68; defined, 68–69; rate and flow changes, 339(f); rates measurements, 1074–1075(f); relations, 70–74; sediment mass (Exner equation), 69–70; two-dimensional, 74–77
bed load transport in mixtures, relations for hiding: Ackers-White extended with Proffitt-Sutherland, 201–202; Ashida-Michiue, 195; Einstein, 195; Parker, surface-based, 196–197; Parker-Klingeman-McLean, 195–196; Powell-Reid-Laronne, 200–201; Tsujimoto, 197–198; Wilcock-Crowe, 199–200; Wilcock-Kenworthy, 198–199; Wu-Wang-Jia, 200
bed load transport of mixtures: analysis, 186–187; equal-threshold limiting cases, size independence and, 190; field data comparisons, 208–209; hiding functions, 189–190; mobile armor, 219–221; sample applications, 202–204; shear stress and flow parameters calculation, 193–195; significant, onset, 187–188; similarity hypothesis, 188–189; substrate-based formulation, 190; surface-based formulation, 186, 191, 196–197; surface-based *vs.* substrate-based, 208; threshold of motion and hiding, 191–193; variability, patchiness, and partial transport, 204–208
bed-material load, 8; estimating, 1073–1083; predictors, grain-size-specific bulk, 232–233; sediment transport loads, 8–9, 60–63
bed-material load in sand-bed streams, dimensionless relations for. *see also* Brownlie relation; Engelund-Hansen relation: Ackers-White, 126–127; form, 123–124; Karim-Kennedy, 127–128; Molinas-Wu, 128–129; other, 129; Yang, 127
bed-material measurement techniques: bias sampling methods, 311–313; sample collection and analysis, 310–311; sample size and accuracy, 313–319; sediment-sampling issues, 309–310
bedrock, 476, 860, 1001, 1090
bed-sediment transport: control volume, 1090; field data, 633–634; laboratory data, 632–633
bed-slope, incipient motion and: arbitrarily sloping bed, 59–60; granular sediment, 55–57; side slopes, 57–59
bed-sorting, defined, 1100
bendway weirs (stream barbs), 451, 523, 553, 1038, 1101
berming, 876–877
best management practices (BMPs), 840, 851–852
bias, 204, 1091
bioaccumulation, 962
biomagnification, 962

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

Boguchwal-Southard diagram, 86, 86(f)
Bonnefille-Pernecker diagram, 88, 88(f), 89(f)
bottomset evolution, 133–134; linked-one dimensional model, 139–141
boundary conditions, 108–109, 655, 668, 717, 1091
boundary effect, 1091
boundary roughness, 468, 620, 653, 1049, 1091
Boussinesq approximation, 691, 724, 767
Boussinesq Eddy-viscosity model. *See* Eddy-viscosity model
box-and-whisker plots, 1076(f)
braided meandering, 441(f), 877, 878
braided river deposits, 12, 12(f)
Brandywine Creek, 415
Bridge-Bennett model, 55
bridge-scour evaluation, 505. *see also* HEC-18 pier scour equation; pier foundations (complex), scour for; scour at abutments; analysis, 534–535; bed material movement, critical, 510–511; clear-water scour, 507; computer models, 530; general scour, 508–510; hydraulic variables, 536–539; Jain-Fisher's equation, 523–524; live-bed scour, 507; local scour, 511–512; long-term changes, 507–508; Melville's equation, 524–525; pier debris, 523; pier scour equations, 525; pier scour holes, 525; stream instability, 530–531; tidal processes, 533; tidal waterways, 531–533; total scour, 506–507
bridge-scour prevention, 543; abutment protection, 568–574; countermeasures, 544–545(t); distribution, 546(t); environmental considerations, 574; general scour and contraction scour, 549–557 (*see also* bridge site selection); piers, 557–568
bridge-scour processes: abutments, 546–547; piers, 543, 546; river morphology and channel contraction, 547–549
bridge site selection. *see also* bank protection: aggradation, 548, 556; alluvial fans, 549; bank protection, 549–550; bend scour, 556–557; catchment influences, 549; channel curvature, 549; channel lining, 555; channel widening, 555–556; check dams, 555; confluence scour, 556–557; contraction scour, 553, 555; debris, 557; degradation, 553, 555; ice jams, 557; relief bridges, 555–556; river training works, 549; sediment-wave effects, 553, 555; submerged Iowa vanes, 553; thalweg effects, 553, 555; waterway areas, 549
BRI-STARS model, 417
broad-level classification criteria, 378(t)
Brownlie relation: gradually varied flow, 126; hydraulic resistance, 126; normal flow, 126; sediment transport, 125–126
bulking factor, 605

C

cable-and-reel samplers, 325–328
cable-tied blocks, 550, 563, 564(t)
Cache Creek, 6
calibration, 667–668. *see also* hydraulic calibration; parameters, 670, 733
California, isoerodent map, 833(f)
California Bank and Shore Protection (CBSP) Manual, 1050–1051
Canadian River, 587
cantilever failure, 405(f)
Canton Dam, 587
capture, 875
Cartesian tensor notation, 815–817
CASC2D, 840, 841, 849, 851, 852
Castle Creek channel profile, 929(f)
Catalyst-Old River Hydroelectric Limited Partnership d.b.a. Louisiana Hydroelectric Limited Partnership, 722
catchment influences on bridge site selection, 549
CCHEBank model, 417
CCHE3D, 417
CCHE2D, 700
central processing unit (CPU), 684, 699–700
Cerro Grande River, 886(f), 914(f); channel morphological response, 915; conclusions, 916–917; flood description, 913; mudflow and debris-flow modeling, 915–916; 1999 flood hydrograph, 913–915; rainfall analysis, 913; simulation results, 916
Chang-Davis abutment scour, 527–528
Chang-Davis abutment scour equation, 527–528
channel(s): anabranching, 636; avulsions, 636; bed slope-drainage area, 480(f); bed slope *vs.* bank-full discharge, 180(f); classifications, 376(f); confluences, 638; curvature, 549; cutoffs, 636–637; degradation, 172(f); erosion, 675(t); geometry, 362(f); morphology, 6(f); narrowing by floodplain formation, 389(f); parameters, 124(f); pattern classifications, 376(f); simulation, 809(f); types, 861(t); widening, 555–556
channel design: active-bed, 487–488; alignment and geometric detail, 490–491; for restoration projects, 485–486; threshold, 486–487
channel evolution and processes: channel stability diagram, 410–411; incised, 408–410; sequence *vs.* channel stability parameters, 410(f)
channel-floodplain connectivity, river restoration design: confinement, longitudinal variation in, 490; reconnection issues, 490
channel-forming discharge: bank-full discharge, 364–365; effective discharge, 365–367; overview, 367; representations, 470(t)
channel lining (paving), 555
channel stability, 445. *see also* meander/meandering; dominant wavelength, 447–448; finite-amplitude meanders, 448; flow and stability relations, 449–450; perturbation stability analyses, 446–447; prediction uncertainties, 448–449; regime theories, 446; strategy, 451; submerged vanes, 452–454; technologies, 451–452
Channel Stability Assessment for Flood Control Projects (Engineering Manual 1110-2-1418), 907
Chaubert-Chauvin diagram, 87–88, 88(f), 89(f)
check dams, 555
Cheng formula, 73–74
Chezy coefficient, 28, 33
ch3d hydrodynamic module, 721–722, 723, 738, 740
CH3D-SED, 700, 701, 723, 726–727, 733, 735
Churchill's curve, 595–596, 596(f)
Churchill's sedimentation index, 596
civil law rule, 938
Civil Rights Act of 1871, 941
clay, 728(f), 1091(t)
Clear Creek, 998(f)
clear-water abutment scour, 528
coastal processes, defined, 533
colloids, 970
Colorado River, 2, 2(f), 138, 173, 1071(f)
Colorado State University (CSU) equations, 512, 513, 515
comprehensive fracture mechanics (CFM), 1028

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

Comprehensive Scour Model (CSM), 1026, 1028
computational analysis, 668
computational hydrograph, 1092
computational modeling, 668. *see also* sedimentation processes, computational modeling; channel cross sections, 675, 679, 679(t); channel geometry, 675; defined, 668; longitudinal profiles, 675; measured bed profile, 675; model data, 672–673; sediment delivery, 674–675, 675(t); sediment transport formula, 673–675
conceptual model, 408–411, 1092
concrete: bridge site selection, 550–551; broken, 550; check dam, 555(f); grouted riprap, 551, 563, 566; pavement, 551
confirmation, defined, 1092
confluence scour, 556–557
Conservation Technology Information Center, 599–600
consistency, defined, 1092
consolidation, 272–275, 1092
contaminant processes in sediments, 959; active sediment-transport, 967–970; chlorinated organic compounds, 962; conventional pollutants, 960–961; dredging, 452, 977–979; engineering management, 974–979; heavy metals, 961; passive sediment fate, 965–967; pesticides, 962; polycyclic aromatics, 962; release and exposure pathways, 962–968; sediment bed fate and transport mechanics, 969–974; sediment processes in sediment environments, 961(t); in situ capping, 975–977; water-side mass transfer process, 968–969
contour surveying, 591, 592(f)
contraction scour. *see also* bank protection: aggradation, 556; bend and confluence scour, 556–557; bridge waterway area, 549; debris and ice jams, 557; degradation, contraction scour, thalweg effects, or sediment-wave effects, 554–556; equations, 508; river training works, 549; site selection, 549
control point, 1092, 1092(f)
convergence, 106, 712, 815, 1092
conversion of units, 1103–1105
conveyance, 361, 1092
Coralville Reservoir, 746–755, 748, 749–750(f), 750(f), 751–754(f), 751–755(f)
Corps of Engineers CTH, 295
Coulcomb friction, 45, 47
cover layer, defined, 1092
cover-management factor, 835–837
CREAMS, 841, 848
critical depth, 902, 1092
critical flow, 1092
critical shear velocity: grain diameter, 53(f); streamwise bed slope effects, 57(f)
crossing, 360
cross-section, defined, 1093
Cruickshank-Maza Flow Resistance Predictor diagram, 97, 98(f)
CUR Manual, 1050
cutoffs, 636–637, 877–878

D

dam removal, 607–608. *see also* Marmot Dam, removal of (simulation); modeling efforts, numerical, 995–996; pre-dam-removal longitudinal profile, 999; reservoir sediment erosion, 997–998; sediment-transport equations, 998–999; sediment transport following, 1000–1019; upstream and downstream reaches, coupled modeling of, 996–997
Danish Hydraulic Institute, 844
Darcy-Weisbach friction factor, 85, 85(f)
data types and resolution: definitions, 667–668; equilibrium and nonequilibrium channels, 429–430; field, 719–720; fluvial, 593–594, 1083–1084; geometric, 656–658; hydraulic calibration, 668–669; hydrologic, 664–665; model development, 656; movable-bed unsteady-state test, 669–670; operating rules, 665; prototype history, 656; sediment, 658–664; sources of data, 665, 667
DDD (dichlorodiphenyldichoroethane), 962
DDT (dichlorodiphenyltrichloroethane), 962
debris-flows. *see also* mudflows, debris-flows and mud-floods, mechanics of; mudflows and debris-flows, mathematical modeling of: bridge site selection, 556; defined, 890–892, 894; physical properties of, 986(t)
default size-fraction distribution, 732(t)
degradation, 506, 553, 556, 875, 1093; bridge site selection, 549, 555; channel, 172(f); defined, 876; long-term, 505, 531; riprap protection at piers, 562–563; river corridor, 464(t)
delivery ratios, sediment, 839–840, 840(t)
delta progradation, 136–137, 137(f), 226
deltas, 133–134, 404, 595, 1093
density. *see also* turbid density currents (turbid currents): current, 603–604, 1093; profile, instantaneous, 273(f); of reservoir sediment deposition, 597–598, 597(t), 598(t); size distribution and size density scale, 37–38(f); stone, riprap design and, 1039
denudation and retreat, 875
deposition. *See* sediment deposition
deposits. *See* sediment deposits
depth-averaged equations, 691–692
depth-averaged model, 817(f)
depth-discharge computation: bad load, 121; bank-full, 121–122; overview, 119, 121; sediment, 121
depth of flow, defined, 1093
design discharge: bank-full, 472–473; channel-forming, 473; drainage area-flow duration curve, 473; effective, 470–474; range of, 473–474; regional duration curve, 473; specific return intervals, 473; ungauged sites, 473
Des Moines River, 755
deterministic model, defined, 1093
diffusion, 291–292
diffusivity and the turbulent Schmidt number, 772–774
digitize/digitization, 1093
dikes, 451–452
dimensionless number, defined, 1093
discretization, 177, 815, 1093
dissolved organic matter (DOM), 970
dissolved oxygen concentration profiles, 986(f)
distorted model, defined, 1093
distortion, defined, 1093
distributaries, defined, 1093
dominant discharge, 364–365, 1093
downfilling, 876
Down's channel classifications, 379(f)
downstream fining: *vs.* abrasion, 223–224; in laboratory channel, 225(f); laboratory studies, 224–225; numerical models, 226–227; tectonics and base level variation, 226
draft depth, 1093
drainage basin, 172, 355, 869, 870, 1093
drainage network development, 878

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

drawdown: characteristics of, 601–602, 601(f); rule curve, 603; seasonal, 602–603
dredging: contaminated sediments, 452, 977–979; hydraulic, 604–605; material handling, 978–979; overdredging, 978, 1097; residual sediment contamination, 978; resuspension of contaminants, 978; *vs.* sediment-pass through, 583(f); technologies, 977
drop, 1093
dune flow, 795(f)
dunes, 81–83, 82(f)
dynamic impulsion (DI), 1028
dynamic model, 1094, defined
Dynamic Watershed Simulation Model (DWSM), 840, 844, 849–850
dynamism, 463, 482–483

E

earthflows, 891
ebb/ebb tide, 533
echosound bottom profile, 78(f)
ecological disaster, man-induced, 13(f)
Eddy-viscosity model: constant, 774–775; deficiencies of, 788; diffusivity and the turbulent Schmidt number, 772–774; equilibrium and mixing-length models, 781; k–ω model, 788–790; Mellor-Yamada length-scale equation, 790; mixing-length models, 775–776, 778–780; momentum, molecular transport of, 771; one-equation model, 780–782; RNG model, 789–790; sophisticated models, 790–794; specifications, 774; stably stratified-flow analogy, 776–778; turbulent kinetic energy, equation for, 780–781; two-equation model, 782–784, 787
edge failure, 558
effective discharge, 365–367, 470(f)
effective (grain) size, 1040, 1094
Einstein, Hans Albert, 66, 70–71
Einstein integrals, 115(f)
Einstein partition, 100–101
Einstein relation, 195
empirical equations, 368–369(t)
empirical models, 1021, 1094
Engelund-Fredsøe partition, 73, 102
Engelund-Hansen relation: gradually varied flow, 125; hydraulic resistance, 125; normal flow, 125; sediment transport, 125
engineering geomorphology, approaches to. *see also* geomorphic hazards: direct, 861–863; indirect, 863–865; systems, 865–873
engineering geomorphology, systems approach to, 865; direct approach, 866–869; indirect approach, 869–873
engineering treatment projects, 16
entrainment: active-layer concept, 183; bank materials, 419; defined, 1094; fluid mud, 283, 289–290; formulation, 185–186; rate against Richardson number, 282(f); relation of Tsujimoto, surface-based, 197–198; sand-bed rivers, suspension-dominated, 229–230; suspended bed-material load, 116–119
Environmental Protection Agency (EPA), 599, 848, 851
equal-discharge-increment (EDI), 330–331, 332
equal-width-increment (EWI), 331–332
equations. *see also* bed load material equations; flow in mobile boundary channels, equations for; HEC-18 pier scour equation; Reynolds-averaged equations; scour equations: basic, 690; Chang-Davis abutment scour, 527–528; depth-averaged, 691–692, 909; empirical, 368–369(t); Exner equation, 69–70; governing, in meandering flow bed topography, 443–445; Mellor-Yamada length-scale, 790; morphodynamics of rivers, 129–131; one-equation model, 780–782; Reynolds-averaged Navier-Stokes equations, 690–691; rheological, 909–910; St. Venant, 10, 213–214, 391, 650, 669; sediment-transport, 998–999; summary of, 1083(t); turbulent kinetic energy, 780–781; two-equation model, 782–784, 787
equilibrium: bank erosion, 408–411; bed forms, 94–97; depth, 1085, 1090; Eddy-viscosity model, 780; load, 1090; near-bed sediment concentration, 116–119; nonequilibrium channels, 429–430; passive sediment fate and transport processes, 969–971; river width adjustment, 428; in wide channel, 109–110
Erodibility Index Method (EIM): erodibility index, 1025–1026, 1026(t); scour assessment, 1026, 1027(t), 1028(t); stream power, 1024–1025
erosion. *see also* accelerated erosion; wave-induced erosion: defined, 1094; engineering works, 8; fluid mud entrainment, 283; geologic or natural, 4; mass, 282–283; modes, 275; overview, 4; rate constant, 281–282; rates and quantities, 7–8; sedimentation delivery, 587; shear strength, 276–280; streambank, 387 (*see also* river width adjustment); surface, 275–278
EROSion model, 840
erosion rate: *vs.* bed shear stress for mixtures, 276(f); constant *vs.* bed shear strength, 281(f); *vs.* excess shear stress, 276(f); *vs.* meander bends, 363(f); surf zone functions, 288(f)
estuary, 533
Exner equation, 10, 69–70
explicit scheme, 1094, 1095
extension, 875

F

falling jet module, 1028–1030
fall velocity, 41–43, 42(f), 1094
fan-delta, 143(f)
FAST2D, 700, 701
FAST3D, 700, 701
Federal Emergency Management Agency (FEMA), 889, 900–902, 905, 954–955
Federal Highway Administration, 512
Federal Interagency Sedimentation Project BL-84, 341(f)
feldspar, 34
Fernandez-Luque-van Beek formula, 73
FHWA manual design of riprap revetment, 1051
final conditions, survey data for, 655
fine-grained sediment transport, 253. *see also* erosion; aggregation, 261–266; applications, 293; deposition under flow, 270–272; diffusion, 291–292; gelling, 274–275; sediment characterization, 254–259; sediment transport processes, 259–261; settling and consolidation, 272–275; settling velocity, 266–270
finite-difference methods, 694–695
finite element method, defined, 1094
fixed-bed model, defined, 1094
FLESCOT, 700, 701
floating material, 61, 62

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

flocculation, 254(t), 272(f), 278(f)
floc strength, aggregation and, 263–264
floc transport, aggregation and, 261–262, 261(f)
floes, 617
flood/flood tide, 533
floodplain, 232–234, 233(f), 234(f)
flood protection levees, 7
flood routing, defined, 1094
floods, 892
flow: aligned with piles, 518(f); around a circular bridge pier, 811(f), 812(t); in a bend, 806(t); in a channel reach and fixed ice cover, 636(f); competence, 51; discharge rating curve, 122–123(f); distribution, 669; duration curve, 473, 1094; field, around consecutive vanes, 453(f); measurements and predictions of, 809(f); open-water, 638(f); over bed forms, 797(t); retarding measures, 553; routing models, 416(t); in sedimentation tanks, 800(t); sediment modeling, 676–678(f); stability relations, 449–450, 449(f); structures at a rectangular pier, 547(f); through non-emergent vegetation, 802(f); between two parallel plates, 985(f)
flow and bed topography in meanders: governing equations and sample solution, 443–445; simulation of, 445
flow in mobile boundary channels, equations for: allocation of scour and fill, 652–653; bankline migration, 653–654; channel width, 653; continuity, 650; diffusion, 651–652; energy, 650; planform migration, 653–654; sediment transport, 650–651
flow resistance. *see also* shear stress partitions; stage-discharge relations: channel, 27–29; diagrams, 103–104(f); equivalent roughness of bed forms, 33–34; fixed-bed (skin or grain) roughness, 29–31; form drag and skin friction, 99–100; movable flat-bed roughness, 32
flow velocity: concentration profiles, 284(f); law of the wall, 24–25; velocity-defect and log-wake laws, 25–27
fluidization, 261
fluid mud generation experiments in flumes, 290(t)
FLUVIAL-12 model, 415, 422
fluvial data: sediment, 1083–1084; sediment rating curves, 593–594; turbidity measurements, 594
fluvial geomorphology: channel classification, 375–379; channel evolution models, 379–381; channel-forming discharge, 364–367; channel instability, 371, 372; channel morphology, 359–363; channel narrowing, 389(f); channel stability, 371; channel widening, 388(f); closure, 382; complexity of, 357; defined, 355; dynamic system, 356–357; fluvial system, 355–356; geomorphic assessment, 381–382; local instability, 372–373; relationships in rivers, 367–371; scale and, 358–359; sediment transport, 363–364; system stability and instability, 373–375; thresholds of, 357; time, 358
fluvial hydraulics in bank mechanics: cross-sectional shape, 392–398; hydrodynamics, 415–417; interactions, 422–423; longitudinal changes, 398–399; near-bank zones, 399–400
Food and Agricultural Organization (FAO), 5
foreset evolution, 133–134; linked-one dimensional model of, 139–141
forest activities, 5
fractal depression, 261
frazil ice, 616–618, 617(f), 618(f)
free overfall jet plunging, 1030(f)
free-surface elevations, 724(t), 738(t), 740(t)
freeze-up jam, 618(f)
frequency, defined, 1094
Froude number, 92, 182(f), 1094
full sediment balance, 581
fuse plug: core, 1059, 1059(f); lateral erosion process, 1060(f); prototype gradation curves, 1063(f); test, 1062–1064, 1063–1064(f), 1065(f)

G

gabions, 551, 563, 565(t)
García-Parker sediment entrainment function, 118, 118(f)
gauging station, 334, 748, 862, 1094
gelling, 274–275
General Land Office (GLO), 861–862
general scour, 508–510, 549–557
geological control, defined, 1094
geological erosion, 3(f)
geologic (natural) deposition, 11
geology, defined, 1094
geometric data: cross-sectional layout and spacing, 656–657; hydraulic roughness, 657–658
geometric similarity, 1057
geomorphic hazards: drainage network, 875; identification of, 873, 874; piedmont and coastal plains, 878; river, 876–878; slope, 875–876; variables affecting, 874–875(t)
geomorphology. *see also* fluvial geomorphology: defined, 355
glacial till profile plot, 296(f)
GLEAMS, 841, 848
glossary, 1089–1101
gouging of banks, 643–645, 644(f)
Government Performance and Results Act (GPRA), 955
gradation: of bed sediment reservoir, 658–659; curves, 1040(f), 1063(f), 1095(f); defined, 1094; model calibration, 668; on point bar, 664, 664(f); of riprap, 559, 561(f), 1040, 1040(t); types, 1040(t)
grade scale, sediment, 36(t)
grain shape factor, defined, 1097
grain-size distributions: annual bed load, 222(f); bed samples, 177–178; definitions and continuous formulations, 175–176; densities, 45(f), 171(f), 176(f); discretization, 177; fifty-stone grid samples, 319(f); grain mobility number and grain size, 46, 94(f); numerical modeling, 213, 216; reaches plot, range and number of, 178(f); scale, 37–38(f), 37–39; sediment deposits, 1008(f); sediment load, 662(t); sediment transport sensitivity, 665(f)
granite, 34
granular flows, 895
graphical user interfaces (GUIs), 10–11
gravel, defined, 1091(t), 1095
gravel and sediment mixtures, transport of. *see also* active-layer concept; bed load transport of mixtures: abrasion, 210–213; in bed loads, fraction of, 203(f); distributions, 203(f); downstream fining, 223–227; engineering relevance, 171–175; equal mobility, hypothesis of, 221; field data, 209–210; fluvial phenomena associated with, 165–171; geometric mean size and, 203(f); gravel-bed and sand-bed streams, dimensionless bank-full relations, 178–183; mobile armor, 219–221; numerical modeling, 213–216; planform sorting, 227–228; static armor, 216–219; suspension-dominated sand-bed rivers, 229–237; tracers, 237; vertical sorting, 238–239
gravel-bed streams, 63
gravelometer, 310, 310(f), 311, 313

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

gravitational sediment flows, 892
gravity, 35(t)
grid, 714, 1095
groins/groin fields, 553, 553(f), 554(t)
gross erosion, 839
grout-filled bags, 550–551, 563, 566(t)
grout-filled mats, 551, 563
GSTARS model, 417, 419, 422
gauge stations, 588(t)
guide banks, 555–556, 569(f)
gullies: erosion, 2(f), 837–839; in floodplains, 374(f)

H

habitat structures: design of, 491, 492(t); migratory barrier removal (fish passage), 491, 493; river restoration design, 491; spawning gravel, 491, 493
handheld and hand-line samplers, 323, 325, 326(f)
hardpoints, 553
Hawaii, isoerodent map of, 835(f)
headcutting: development, 997, 998(f); severe erosion, 7, 7(f)
headgate, 655
HEC-1 hydrologic model, 914, 915(f), 916–917
HEC-6, 294, 508, 602, 652, 680(t), 758, 996, 997
HEC-18 pier scour equation, 513. *see also* pier foundations (complex), scour for; correction factor for very large piers, 514; Mueller (1996) K_4 correction coefficient, 514; multiple columns skewed to flow, 521–523; pressure flow scour, 523
Helley-Smith bed load samplers, 1074–1075(f)
heuristic model, 1095
hexachlorbenzene, 962
hiding function plot, 192(f), 202(f)
high sediment: concentration flows, 893(t); concentration turbidity currents, 13(f)
Hirano formulation, 183–184
historic flows, defined, 1095
horizontal collars, 568, 568(f)
hybrid model, 1095
hydraulic calibration: fixed bed steady and unsteady-state, 668–669; hydraulic and sediment calibration, 669–670; movable-bed, steady-state, 669–670; movable-boundary, unsteady-state, 669
hydraulic depth, 1095
Hydraulic Design of Flood Control Channels (Engineering Manual 1110-2-1601), 906–907, 1051–1052
hydraulic dredging, 604–605
hydraulic flushing, 605–607, 606(f)
hydraulic geometry formulas, 370(t)
hydraulic impacts and geomechanic impacts, 644(f)
hydraulic impacts of river ice, 635; avulsions, 636–637; channel anabranching, 636–637; channel confluences, 638; cover influence on thalweg alignment, 638–639, 638(f), 639(f); cutoffs, 636–637; ice-cover influence, 636; jam-collapse surges, 639
hydraulic loading: for bank protection, 1042–1043; below energy dissipators, 1043; classifications of, 1042(t); descriptors of channel type and bend severity, 1041; parameters, 1041, 1042(t); from propeller jets, 1043; for steep slopes and river closures, 1043; from waves, 1043–1044
hydraulic model, 722, 1095
hydraulic radius, 126, 1095
hydraulics, defined, 1095
hydraulic sorting, defined, 1100
hydraulic variables, determination of: computer programs for, 539; for constricted waterways, 538–539; design flows, 536–537; for unconstricted waterways, 537–538
hydrodynamic boundary conditions, 749(f)
hydrodynamic modeling, 488, 690, 756; coordinate transformations for finite-difference methods, 694–695; depth-averaged equations, 691–692; hydrostatic pressure assumption, 691, 693; introduction and scope, 690; Reynolds-averaged Navier-Stokes equations, 690–691; solution techniques and applicability, 693–694; turbulence closure models, 692–693, 695
hydrodynamic-process formulations: basic equations, 690; depth-averaged equations, 691–692; hydrostatic-pressure simplification, 691; Reynolds-averaged Navier-Stokes equations, 690–691; turbulence closure problem, 692–693
hydrograph: computational, 1092(f); defined, 1095; 1999 flood, estimated, 913–914; prediction, 602–603, 603(f)
hydrographic track lines, 592(f)
Hydrological Simulation Program—Fortran (HSPF), 848, 850
hydrologic data: boundary condition changes over time, 665; main stream water inflows, 664; trailwater elevation, 665; tributaries, 664–665; water temperature, 665
Hydrologic Engineering Center (HEC). *see also* HEC-18 pier scour equation: *Assessment of Structural Flood-Control Measures on Alluvial Fans,* 907; HEC-1 hydrologic model, 914, 915(f), 916–917; HEC-6 numerical model, 294, 508, 602, 652, 680(t), 758, 996, 997; numerical models, 495
Hydrologic Simulation Program (HSP), 848
hydrology, defined, 1095
hydrostatic pressure assumption: ch3d hydrodynamic module, 738, 740; role of, 693; streamline curvature, 700; three-dimensional models for reservoir sedimentation, 686–691, 755, 756–757
hyperconcentrated flow: defined, 885–887, 891–892; rheology of, 892–895; streamflows, 894, 895
hypothetical stability assessment, 484(t)

I

ice-cover effects, 613–614, 614(f). *see also* hydraulic impacts of river ice; river-ice effects on alluvial channel morphology; effects on secondary currents, 623(f); flow distribution, 619–623; ice-cover breakup, 623–625; ice-cover effects on sediment transport by flow, 627–628; on a meandering channel, 640(f); open-water proportions, 621(f); sediment transport by ice, 627–635; sinuous-braided channel, 637(f); transverse bed slope, 624(f)
ice-cover effects on sediment transport by flow: bed-sediment transport, 632–633; constriction scour and local scour at bridge piers, 634–635; flow resistance, 630–631; local scour beneath ice jams, 634; overview, 627–628; parameters, 628–629; sediment movement and bed forms, 629–630; water-temperature effects, 629
ice formation: bankfast ice, 616, 616(f); frazil ice, 616–618(f), 617(f), 618(f); skim ice, 616
ice jams, 557, 625(f), 634
ice model, defined, 1095
Ikeda-Coleman-Iwagaki analysis, 46, 48, 48(f), 53
Illinois State Water Survey (ISWS), 844
impeded removal, 404

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

implicit scheme, 851, 1094
impoundment, 1001, 1095
inactive layer, 1095
in-bed flow pressure variations, 973(f)
in-channel and overbank flow diagram, 214(f)
in-channel habitat structures, 492(t)
incipient motion, 480–481, 483, 1052, 1095; stability checks, 481(t)
incised channel evolution model (ICEM), 380(f), 409(f), 864, 864(f)
ineffective flow, 1095
inflowing sediment, size and concentration of: bed gradation on point bar, 664; concentrations, 660; grain size classes, 660; transport theory, 661–664; from tributaries, 660–661, 664
initialization, model, 655, 715–717
in situ capping of contaminated sediment, 975–977
instantaneous samplers, 321–322
Institute of Hydrology (U.K.), 844
International Erosion Control Association, 600
Iowa vanes: installation of, 453(f); as a pier-scour countermeasure, 567–568, 567(f); submerged, 553
island and bar formation and shift, 877
isoerodent maps, 830–831; of California, 833(f); of Hawaii, 835(f); of Oregon, 834(f); of U.S. (western), 832(f); of Washington, 834(f)
isokinetic samplers, 322–323, 324(t)

J

Jacalitos Creek, 6
Jain-Fisher's equation, 523–524
jam-collapse surges, 639
jet turbulence intensity: based on outlet structure, 1030(t); polynomial coefficients and, 1031(t)
joint alternate number, 1027(t)
jointed rock, 1033(f)
joint roughness number, 1027(t)
joint set number, 1022(t)
June 2000 event. *See* Leavenworth Bend, Missouri River

K

Kankakee River, 43, 43(f), 44
kaolinite, 78, 254
Karim-Kennedy relation, 127–128
KINematic runoff, 840
kinematic similarity, 1057
kinematic-wave approach to debris-flow routing: depth-averaged equations of motion, 909; kinematic wave approximation, 910–911; model application, 911; rheological equations, 909–910
KINEROS model, 840, 844, 849–850
Knapp-Vlugter criterion, 62
knickpoints, 876, 876(f)
k–ω model, 788–790

L

Lagrangian models, 71, 769–770
Laguna Dam, 2
lake and reservoir sedimentation, morphodynamics of: delta formation, 133–134, 133–134(f); detrainment and sediment trap efficiency, muddy pond formation in reservoir, 144–146, 144(f), 145(f), 146(f); linked one-dimensional model of topset, foreset, bottomset evolution, 139–141, 141–142(f); linked quasi-dimensional model of topset, foreset, bottomset evolution, 141, 143–144, 143(f), 144(f); numerical modeling of, parameters used in, 136(t); plunging of muddy turbidity current, 138–139, 138(f); topset and foreset, fluvial deposition of formation, 134–138, 135(f), 136(f), 136(t), 137(f)
Lake Erie, 288
Lake Francis Case, 582(f)
Lake Mead, 133, 133(f)
Lake Ontario, 288
landslides, 170(f), 887–888, 892–893, 893(f), 895
Lane's balance, 372(f)
Lara-Pemberton method, 598(t)
lateral turbulence intensity, 809(f)
lateral velocity, 807(f)
Leavenworth Bend, Missouri River: background, 735; boundary and initial conditions, October 1999 event, 736–737, 737(t); field data campaigns, 736; flow computations, 738(t), 740; layout of, 735(f); measured and computed free-surface elevations, June 2000 event, 740(t); measured and computed free-surface elevations, October 1999 event, 738(t); model calibration, June 2000 event, 740; model calibration, October 1999 event, 737–740, 738(t), 739(f); model construction, 736; model to study proposed habitat restoration measures, 743–746, 744(f), 745(f), 746(f); sediment computations, 740–743, 742(f), 743(f)
left overbank. *see* overbank
Leopold scour chains, 237(f)
limestone, 34
linear elastic fracture mechanics (LEFM), 1032
linear model, 1069, 1095
linear scale, 37–38(f)
linked-one dimensional model of topset, foreset, bottomset evolution, 139–141
liquefaction, 261
Lischtvan-Levediev diagram, 55–56, 56(f)
Little Salmon Creek, 17
littoral drift, 532
live-bed abutment scour, 527–528
local agencies, 667
local inflow and outflow point, 1095
local scour. *see also* piers, local scour at: bridge-scour evaluation, 511–512; ice jams, 634; sedimentation processes, computational modeling of, 646; tidal waterways, calculations for, 529; total scour and, 503
location-for-condition evaluation (LCE), 867–868
location for time substitution (LTS) technique, 863, 867
logarithmic law: critical stress for flow over a granular bed, 46–47; *vs.* power laws for velocity, 27(f); velocity distribution, 775
log scale, 37–38(f)
Loíza reservoir, 603(f)
longitudinal staggered discharges, 751(f), 753(f)
Loowit Creek channel profiles, 928(f)

M

Mad River, 172
Madsen-Jimenez formula, 41–42, 73, 106
magnetite, 34
Mahatta River, 16(f)

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

main stem: defined, 1096, 1096(f); downstream fining, 172; water inflows, 664
Manning's *n:* with flow discharge, 98(f), 489(f), 1096; Manning-Strickler form of, 28, 29
Manual 54, 937–939
Maple Gulch Dam, 998(f)
Mapocho River, 28
Marmot Dam, removal of (simulation): background gravel and sand transport rates, 1009; channel gradient and width, 1005; discharge data and hydrologic scenarios, 1005–1006; discussion, 1018–1019; grain-size distribution of reservoir sediment, 1008, 1008(f); grain-size distribution of the channel-bed surface layer, 1006–1008, 1007(f); input data, 1005–1009; model results, 1009; project background, 1000–1002, 1000(f), 1001(f); reference runs of numerical models, 1010–1012, 1011–1012(f); Sandy River, effects on, 1001–1002, 1002(t); Sandy River channel slope, 1006; sediment-transport models developed for, 1002–1005; sensitivity tests, 1016–1018; single-season dam removal and minimal sediment excavation, 1012–1016, 1013–1016(f), 1017(f); water year series selected for use in, 1007(t); zero process, 1009
Marmot Reservoir, 1003, 1008–1009, 1008(f), 1010(f), 1016
mass failure, 876
mass strength number for rock, 1026(t)
mass-transfer coefficient, 987–989
mathematical modeling: Bridge-Bennett model for entrainment and transport, 55; defined, 1096; of mudflows and debris-flows, 909–917
Matilija dam, 608(f)
mean annual discharge, 412, 413(f)
mean channel velocities, 483(t)
meander bend, 361–363; active surface-layer thickness, 184; average annual erosion rate *versus r/w,* 363(f); bank erosion, 87(f), 871–872; competing transverse effects, 75; flow and transport processes, numerical models for computing, 399–400, 400(f); radius-of-curvature-to-width ratio, 362
meander/meandering. *see also* channel stability: amplitude, 361; braided, 441(f), 877, 878; criteria, 441; evolution, simulation of, 450–451; finite-amplitude, 448; flow and bed topography, 443–445; growth and shift, 877, 877(f); migration, 442–443; path length, 361; planform, 441–442; point bar, 361, 361(f), 406–407, 871–873; process, 439–441, 441(f); river, 13(f), 871–873; straight and braided to meandering (Cd1 and Cd3), 878; straight and meandering to braided (Cd2 and Cd6), 878; stream, 359, 361, 406–407, 530, 1096; wavelength, 361
mean velocity, defined, 1096
Mellor-Yamada length-scale equation, 790
Melville's equation, 524–525
mesh, 36, 551
Meyer-Peter-Muller formula, 72
middle bar, 361, 361(f)
migration: meander, 442–443; planform and bankline, 653–654; rates, lateral and down-valley, 449(t)
MIKE SHE (European Hydrological System model), 840, 841, 849, 851, 852, 857
mining activities, 12, 13(f); accelerated erosion, 6, 6(f); sedimentation due to, 12, 13(f); undermining bed forms, 558; wash load of river systems, 61
Minnesota River, 35, 235(f)
Mississippi River, 95, 732(t), 1068(f), 1070(f). *see also* Old River Control Complex (ORCC), Mississippi River
Missouri River, 79, 95, 99, 582(f), 616(f), 735(f), 737(t), 1069(f). *see also* Leavenworth Bend, Missouri River
mitigation. *See* sedimentation hazards
mixing-layer concept, 703
mixing-length models, 775–776, 778–780, 782; limitations of, 778–780
MOBED2 two-dimensional mobile-bed program
mobile-bed modeling, multidimensional. *see also* Leavenworth Bend, Missouri River: bed-sediment initial condition, 731–733, 732(t); calibrated model, use of, 735; calibration parameters, 733; CH3D modeling system, 721–722; complexity of, 683–684; computer resources, limitations of, 684; Coralville Reservoir, 746–755, 749–750(f), 751–754(f); field data campaign and model construction, 722–723, 736; flow computations, 737, 737(t); habitat restoration measures, 743–746; hydrodynamic boundary and initial conditions, 723; hydrodynamic model calibration and verification, 724–726, 724(t); June 2000 event, 740, 742(t); mobile-bed program, 746–747; model calibration and verification, 733–735, 737–740; model construction, 736; model sediment size classes, 726, 727(t); necessity of, 683; October 1999 event, 737–740, 738(f), 738(t), 739(f); Old River Control Complex (ORCC), 720–721, 721(f); Red Rock Reservoir, 755, 757(f); Saylorville Reservoir, 755, 756(f); sediment boundary conditions, 726–727; sediment computations, 740–743, 742(f); suspended-sediment conditions, 727–731, 728–730(f)
mobile-bed numerical solution considerations: choice of numerical method, 713–714; grid-generation and adaptive-grid issues, 714; numerical coupling and uncoupling, 712–713
mobile-bed processes, conceptual models of, 699–701
model calibration: defined, 655; definitions, 667–668; fixed bed, steady-state hydraulic calibration, 668–669; fixed bed, unsteady-state hydraulic calibration, 669; movable-bed, steady-state hydraulic and sediment calibration, 669–670, 670(f); movable-boundary, unsteady-state sediment calibration, 670
model capability requirements, 685(t)
modeling systems, 10–11. *see also* hydrodynamic-process formulations; mobile-bed modeling, multidimensional; ADCP techniques, 719; for bed and near-bed processes, 701–705; bed-surface material initial conditions, 716; capability requirements, 685–687, 685(t); critical assessment of, art and future perspectives and, 755–759; field data for construction of, 714–720; finite-difference methods, 694–695; hydrodynamic boundary conditions, 717; hydrostatic pressure assumption, 693; initialization of model, 715–717; limits of, 654–655; long-term bed evolution in response to changes, 688–689; mobile-bed numerical solution considerations, 712–714; mobile-bed processes, 699–701; mobile-bed dynamics around structures, 688; mobile-bed model calibration and verification, 716–717; overview, 695, 699–701; reservoir sedimentation, 685; reviewed models, list of, 416(f), 418(t), 420(f); river-bend dynamics and training works, 687–688; sediment-exchange processes, 707–708; settling basins, 687; simplifications used in, 700; solution techniques and applicability of, 693–694; sorbed contaminant fate and transport, 689–690; subsurface strata initial conditions, 716–717; suspended-material processes, 705–706; suspended-sediment initial conditions, 715–716; system closure and auxiliary relations, 708–712; turbulence closure models, 695
Molinas-Wu relation, 128–129
momentum, molecular transport of, 771
momentum-diffusion model, 413(f)

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

M1 curve, 134
morphodynamics. *see also* lake and reservoir sedimentation, morphodynamics of; sediment transport: defined, 70; of rivers, equations governing, 129–131
Mount Fubilian, 13(f)
Mount St. Helens, 23; chronology of, 923–927; conclusions, 934–936; eruption, after effects of, 925(f), 926(f); sediment sources, 930–933; sediment yield, 933–934; watershed recovery, 927–930
moveable bed, defined, 1096
M2 curve, 134
mud balls, armored, 8, 9(f)
mud definition and rheology: coefficient values, 259(t); fine-grained sediment transport, 255(t); parameters, 259(t); properties, 258(t)
muddy pond: detrainment and sediment trap efficiency, 144–146, 144(f), 145(f), 146(f); reservoir set up, 144(f)
mud-floods. *see also* mudflows, debris-flows and mud-floods, mechanics of: defined, 890, 893; examples, 891(f)
mudflows, debris-flows and mud-floods, mechanics of: dimensionless rheological model, 899–900; hyperconcentrated flow, defined, 885–887; hyperconcentrated sediment flows, rheology of, 892–895; main classification criteria, 887–896, 893(t)
mudflows, defined, 890, 893
mudflows and debris-flows, mathematical modeling of: Cerro Grande River, simulation of mudflows and debris-flows in, 913–917; kinematic-wave approach, 909–913; mathematical modeling of
muds, coefficient values, 259(t)
multivertical sampling, 330

N

National Weather Service (NWS), 667; DWOPER model, 849
naturalization, defined, 462(t)
Natural Resources Conservation Service, 595
Navier-Stokes Equations, 690–691
near-bank zones, 393, 400, 419
Nelson-Smith partition, 101–102
neural network models, 594–595
Newton-Raphson method, 747
Nielsen formula, 73
Niger River, 60, 61(f), 226, 233
Nikuradse sand-roughened pipe experiments, 29–33, 30(f), 31(t), 53, 119
Nile River, 61, 344, 866–867
Ningerum Flats, 171(f)
Niño-García formula, 66–68, 71–74
node, defined, 1096
nonengineering treatment techniques, 16–17, 16(f)
nonequilibrium channels, 429–430, 429(t)
nonlinear κ-ε models, 399, 791–792, 792(f)
non-point-source model (NPSM), 848
Nonpoint Source Runoff (NPS) model, 848
numerical experiments, 66, 295
numerical modeling. *see also* numerical width adjustment models; one-dimensional models; three-dimensional models: of lake and reservoir sedimentation, parameters used in, 136(t); one-dimensional, 1000, 1019; overview, 10–11; sediment transport mechanics and dune morphology research, 97; two-dimensional, 903, 909, 915
numerical modeling of bed level variation with sorting: elements of, 213–214; examples using grain-size distributions, 215–216; field applications to engineering problems, 214–215, 214(f)
numerical scheme, 841, 851
numerical stability, 719, 737
numerical width adjustment models: cohesive and noncohesive-bank stability analyses, 419, 420(t), 421; equilibrium and nonequilibrium channels, 429–430, 429(t); extremal hypotheses, 422; field testing, 424, 426(f); fluvial entrainment of bank materials, 419; fluvial hydraulics and bank mechanics, 422–423; fluvial hydraulics and hydrodynamics, 415, 416(t), 417; geofluvial, 422–423, 429(t); homogenous and heterogeneous bank structures, 421; laboratory data, tests with, 423–424, 425(f); longitudinal extent of mass failure, 421–422; numerical models, testing and application of, 419–420; overview, 415, 416(t); retreat and advance processes, 419; riverbank mechanics, 419–422; sediment transport and continuity, 417, 418(t), 419; summary of, 424(t); testing and application of, 423–424; width adjustment problems, approaching, 426–427
n-values, 654, 669, 916

O

Oak Creek: bed material samples, size distribution of, 43, 44, 44(f), 193(t), 195–197, 207–208, 207(f); ratio of unit bed load transport rate q_i/F_i *versus* grain size D_i, 207; substrate-based relation of Parker et al., 195–197; total bed load transport rate q_T * *versus* Shields stress τ^*_{50}, 207–208, 207(f); Values of γ, 193(t)
Oaklimiter Creek, 408, 409(f), 410(f)
observed debris flows, physical properties of, 896(t)
October 1999 event. *See* Leavenworth Bend, Missouri River
Ohio River, 405, 865–866, 1044, 1044(f)
OK Tedi Mine, 13(f), 171(f), 174(f)
Old River Control Complex (ORCC), Mississippi River: background, 720–721, 721(f); bed-sediment initial conditions, 731–733; calibrated model, use of, 735; Ch3D modeling system, 721–722, 723; field data campaign and model construction, 722–723; free-surface elevations, computed and measured, 724(t); hydrodynamic boundary and initial conditions, 723; hydrodynamic model calibration and verification, 723–726, 725–726(f); hydroelectric power plant (HPP), 723, 726, 733; model calibration and verification, 733–735; model sediment size classes, 726; physical calibration parameters, 733; sediment boundary conditions, 726–727; size classes for, 727(t); size-fraction distributions, 732(t); suspended-sediment initial conditions, 727, 728–730(f), 731; Tarbert Landing, 722–723, 724, 727, 733, 735; Union Point, 722–723, 724, 726, 727, 731, 733, 734
1D flow-routing methods, 415, 417
one-dimensional models. *see also* Marmot Dam, removal of (simulation): allocation of scour and fill, 652; channel cross sections, locating, 758; flow through an expansion or contraction, 656; limitations of, 996; linked, of topset, fireset, bottomset evolution, 139–141; long-term bed evolution in response to changes, 688–689; measurements of time-varying stages and discharges, 720; reservoir sedimentation, 686; settling basins, 687; volumetric analyses, 687

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

one-equation model, 780–782. *see also* Eddy-viscosity model
open-channel flow diagram, 81, 118, 146, 321, 1111
operating rule (policy), 665, 1097
ordinary stream flows, 894, 895
Oreti River, 555, 555(f)
organic-rich sediments, shear strength parameters for, 279, 279(t)
Orinoco River, 62–63
oscillatory flow, 803–804, 803(f), 804(t)
overbank, 234–236, 637, 643, 1097
overdredging, 978, 1097
oxygen concentration profiles, 464, 465, 986(f)

P

Padma River, 97, 98(f)
Paintal formula, 72–73
Palo Verde Dam, 2
pans, 616–618, 617(f), 618(f)
Paraguay River, 83
parameters: calibration, 670, 733; channel, 124(f); defined, 1097; hydraulic loading, 1041, 1042(t); ice-cover effects, 628–629; lake and reservoir sedimentation, numerical modeling, 136(t); sequence *vs.* channel stability, 410(f); shear stress and flow, bed load transport in mixtures, 193–195
Paraná River, 77, 77(f), 78(f), 83, 95, 96(f), 99
Parker formula, 73. *see also* Shields-Parker's River sedimentation diagram
Parker-Klingeman-McLean relation, 195–196
Parker relation, surface-based, 196–197
partial sediment balance, 581
particle shape factor, defined, 1097
particle size, defined, 1097
passive sediment fate and transport processes: adsorption and desorption equilibrium, 969–970; chemical reaction and biodegradation, 970–971; molecular diffusion, 969
pass-through: characteristics of, 601–602; hydrograph prediction, 602–603, 603(f); rule curve, 603; seasonal drawdown, 602; turbid density currents, routing of, 603–604, 604(f)
pattern change, 877
PCBs (polychlorinated biphenyls), 960, 962, 968, 971, 978
peak shear stress, 405, 1042(f)
permeability, defined, 1097
perturbation stability analyses, 446–447
phasing, defined, 1097
physical models. *See* sediment transport scaling for physical models
pier foundations (complex), scour for. *see also* HEC-18 pier scour equation: components method of analysis and, superposition of, 516, 516(f); depth scour, determining, 515–516; overview, 514–515; pier stem scour depth, determination of, 516–517, 517(f); pile cap (footing) scour depth component, determination of, 517–519, 518(f), 519(f); pile group scour depth component, determination of, 519–523, 520(f), 521–522(f)
piers, local scour at. *see also* bridge-scour evaluation; pier foundations (complex), scour for: countermeasures for local scour at, 557–568 (*see also* bridge-scour prevention; riprap protection at piers); debris on, scour depths with, 523; local scour at, 512–513, 512–513(f); nose shape, 515(t); scour depth in a sand-bed stream, 507(f); scour equations, other, 525; scour holes, top width of, 525; scour ratio, 517, 517(f), 521; shapes, 514(f)
pit and trough samplers, 342–343
plane slip failure, Culmann analysis for, 402–403, 403(f)
planform: bankline migration, 653–654; channel, 375; defined, 1097; meander, 441–442, 442(f); metamorphosis, 373; sorting, 227–228, 228(f)
plan test, 671
plunge point, 138(f)
plunge pool module, 1030–1031, 1031(t)
plunging: free overfall jet, 1030(f); of turbid density currents, 138–144, 138(f)
point bar: bed gradation on, 664, 664(f); defined, 1097; in meandering river, development, 871–873; in meandering stream, 361, 406–407
point-integrated sampling, 333
polycyclic aromatic hydrocarbon (PAHs) compounds, 960, 962, 966, 968, 970
pool-riffle sequences, 360, 360(f)
population migrations, 7
pore pressure: channel widening, 548; determining, 256; fluidization, 261; landslides, 888; loose riprap, drainage advantages of, 551; positive, 401, 404; slaking, 401
Powder River, 390, 407, 412, 413(f)
Powell-Reid-Laronne relation, 200–201
precast blocks, 550
Precipitation-Runoff Modeling System (PRMS), 840–841, 848, 849–852
preservation, defined, 461, 462
probabilistic models and methods, 70–71, 1052, 1077, 1097
prototype, defined, 1097
pumping samplers, automatic. *See* sampling methods, automatic
pyroclastic flows, 892

Q

$Q_{1.5}$ discharge, 588, 588(t)
quartz, 34, 35
quasi-2D method, 417, 419
quasi-steady flow, 144(f), 145
quasi-steady-state model, defined, 1097
quasi-three-dimensional model, 699, 755–757

R

radius of curvature, 362
rainfall-runoff erosivity factor, 830–831
rating curves, 122–123(f), 593–594
reasonable use rule, 938
Red Lake River, evolution of, 450, 451(f)
Red Rock Reservoir, 755, 757(f)
regime formulas, 369(t)
regression analysis, 116(t)
rehabilitation: activities, 494; defined, 462(t); planning, 357
rejuvenation, 875
relative ground structure number, 1025, 1026, 1028(t)
relative shearwave velocity, 258(f)
relief bridges, 555–556
Reno mattresses, 550, 551, 563, 565(t)
REServoir CONservation (RESCON) approach, 584
reservoirs, sedimentation delivery to. *See* sediment yield; sediment yield, quantifying

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

reservoir sedimentation: numerical modeling, parameters used in, 136(t); one dimensional model, 686; sediment transport, 133–146; three-dimensional models and hydrostatic pressure assumption, 686–691, 755, 756–757
reservoir sedimentation rates: capacity-history curves, 582; reservoir half-life, 581; reservoir life, 581, 582(f); worldwide, 580–581, 581(t)
reservoir sediment deposition. *see also* lake and reservoir sedimentation, morphodynamics of: bulk density of, 597–598, 597(t), 598(t); Churchill's curve, 595–596, 596(f); Churchill's sedimentation index, 596; consolidation of sediment over time, 598, 598(t); depositional geometry, 596–597; patterns of sedimentation, prediction of, 598; trapping and releasing efficiency, 595–596; turbid density currents, 597
reservoir sediment management. *see also* reservoir sediment deposition; reservoir sediment management; sediment-routing strategies: control strategies, 598–599; dam removal, 607–608; delivery of sediment, 587–590; hydraulic dredging, 604–605; hydraulic flushing, 605–607, 606(f); impacts, 585–587, 585(t), 586(f); large storage volume, provision of, 600; rates, 580–582; sediment focusing, 607; sustainability and economic analysis, 582–585; yield reduction, 599–600
reservoir survey, estimating sediment yield by: bathymetric survey, 591–592, 592(f); deposit thickness over event horizons, 592–593; overview, 590–591
resistance ratio for an ice-covered flow, 632(f)
restoration: activities, 463; channel design, 485–486; defined, 462; objectives, 464, 465; problems, 466, 466(t); vegetation used in, 495
restoration of function movement, 17
revetments, 451. *see also* riprap revetments
Reynolds-averaged equations: auxiliary (boundary conditions), 770–771; general flow equations, 766–768; Navier-Stokes equations, 690–691; overview, 766; for sediment model, 768–769
Reynolds number, defined, 1098
rheology. *see also* mud definition and rheology: dimensionless rheological model, 899–900; equations, 909–910; of hyperconcentrated flow, 892–895
Rhine River, 95, 340
Richardson et al. abutment scour equation, 530
Richardson-Trivino abutment scour equation, 529–530
right overbank, 234–236, 637, 643, 1097
rigid-bottle samplers, 323
Rio Calicanto plateaus, 2(f)
Rio Grande, 97, 98(f), 99, 105, 320, 586, 863, 1072
Rio Maule, 12(f)
Rio Paraná dunes, 77
RIPA model, 417
riparian rights, 938–939
ripples, 82(f), 83–84
riprap, environmental requirements for: ecological impacts, 1046; overview, 1045–1046; reduced riprap protection, lower bank only, 1046; vegetation in revetments, 1046
riprap, geotechnical requirements for: filter objectives, 1044–1045; geotextile filters, 1045; mineral filters, 1045; seepage effects, 1044, 1045(f)
riprap design. *see also* riprap structure types: advantages and disadvantages of, 1037; factors, 1037; objective and scope of, 1037
riprap protection at piers: construction and maintenance, 1053–1054; degradation, tolerance to, 562–563; design of riprap and, 554; failure mechanisms, 557–558, 558(f); filters, 562; gradation, 559, 561(f); lateral extent, 559, 561; layer thickness, 651; overview, 557; placement level, 561–562, 562(f); size, 558–559, 559(t)
riprap protection at piers, alternatives to: cable-tied blocks, 563, 564(t); concrete apron and grouted riprap, 563, 566; design, 558, 559(f); gabions, 563, 565(t); grout-filled bags and mats, 563, 566(t); horizontal collars, 568, 568(f); Iowa vanes, 567–568, 567(f); overview, 557–558, 558(f); Reno mattresses, 563, 565(t); sacrificial riprap, 566–567, 567(f)
riprap protection for abutments: filter requirements, 573; overview, 570–571; rock protection, extent of, 572–573, 573(f); size of riprap, 571–572, 572(t); thickness of riprap, 573
riprap revetments: adjacent to hydraulic structures, 1038; bank, 1037–1038; protection on lower bank, 1038(f); scour and protection at ends and tops, 1048; thickness, 1040–1041; toe scour along bank revetments, 1046–1047, 1047(f); toe scour protection requirements, 1047–1048, 1048(f); vegetation in, 1046
riprap size requirements: characteristic size and gradation effects, 1050; forces on riprap, 1048–1049, 1049(f); maximum force, design for, 1049; stability, velocity profile and turbulence, 1049
riprap sizing methods: California Bank and Shore Protection (CBSP) Manual, 1050–1051; Corps of Engineers Manual—Hydraulic Design of Flood Control Channels, 1051–1052; CUR Manual, 1050; FHWA manual-design, 1051; field data-based, 1052; flow competence and, 51; hydraulic structures (riprap around), 1053; overview, 1050; probabilistic methods, 1052; propeller jets, 1053; river closures, 1053; safety factor methods, 1051; stability of, ice and debris effects on, 1053; for steep slopes, 1052–1053; Wallingford Design Manual for River and Channel Revetments, 1051; waves, 1053; waves and currents combined, 1053
riprap stone, physical characteristics of: durability, 1039–1040; gradation, 1040, 1040(f); revetment thickness, 1040–1041; rock-type sources, 1039; roughness, 1041; shape and porosity, 1039; stone density, 1039; testing and sampling, 1039
riprap structure types. *see also* hydraulic loading: adjacent to hydraulic structures, 1038; bank revetments, 1037–1038; bed protection, 1039; bendway weirs, 1038; dikes, 1038; factors, 1037; river closure structures, 1039; steep chutes and channels, 1038–1039; toe protection and launchable stone, 1038; wave protection, 1038
riverbank mechanics. *see also* fluvial hydraulics in bank mechanics: cohesive and noncohesive-bank stability analyses, 419–421, 420(t); fluvial entrainment of bank materials, 419; homogenous and heterogeneous bank structures, 421; longitudinal extent of mass failure, 421–422; retreat and advance processes, 419
river corridor degradation, 464(t)
River Hydraulics (Engineering Manual 1110-2-1416), 907
river-ice effects on alluvial channel morphology. *see also* hydraulic impacts of river ice: bankfast-ice loading of banks, 642–643, 642(f); combined hydraulic and geomechanical impacts, 645; freeze-thaw influences on riverbank strength, 640–642; gouging and abrasion of banks, 643–645, 644(f); overview, 635, 640, 641(f); riverbanks, impacts on, 640–645; strength, reduction of, 642; thalweg sinuosity, 639(f)
river metamorphosis, 878

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

river restoration design. *see also* channel design: of backwater protection, 494; of channel bottom habitats, 493–494, 494(t); of channel-floodplain connectivity, 493; of habitat structures, 491–493, 492(t); overview, 485
river training works, 549
river width adjustment, 422. *see also* bank erosion; bank mechanics; fluvial hydraulics in bank mechanics; numerical width adjustment models; cause and effect, influence of scale and, 391; channel evolution, conceptual models of, 408–411, 410(f), 427; empirical methods based on field observations, 415, 415(f); engineering or river management solution, 428; equilibrium approaches, 411–415, 412(f), 413(f); equilibrium morphology, assessment of, 427; field data collection, 426–427; geomorphic context of, 387–391, 388(f), 389–390(f); model prediction, 428; model validation, 427; numerical models, 415–419, 416(t), 418(t); problem identification, 426, 427(f); retreat and advance processes, 419
RNG model, 789–790
rock joints: closed-ended, 1031; open-ended, 1031, 1034, 1034(f); pressure fluctuations, 1022, 1022(f)
rock mass module, 1031–1035, 1032(f), 1033(f), 1034(f), 1034(t)
rock scour: combined application methods, 1024; Comprehensive Scour Model (CSM), 1026, 1028; Erodibility Index Method (EIM), 1024–1026; falling jet module, 1028–1030, 1030(f); mechanisms, 1023–1024, 1023(f); overview of, 1021–1022; plunge pool module, 1030–1031, 1031(t); rock mass module, 1031–1035, 1032(f), 1033(f), 1034(t); water, erosive capacity of, 1022–1023, 1022(f)
roundoff error, defined, 1098
Rouse-Vanoni-Ippen suspended sediment distribution, flow stratification effects, inclusion of, 111–112, 112(f)
routing, defined, 1098
runoff, defined, 1098
Russian River, 16(f)

S

sacrificial riprap, 566–567, 567(f)
Saeltzer Dam, 998, 998(f)
St. Anthony Falls Laboratory (SAFL), 64, 71
St. Venant equations, 10, 213–214, 391, 650, 669
saltation, 66–67
sampling methods, automatic: activation, 336; installation and use criteria, 334–335; overview, 333–334, 334; placement and orientation, 335–336, 335–536, 336(f), 536(f)
sampling methods, manual: bag, 328; cable-and-reel, 325–328; EDI method, 330–331, 332; EWI method, 331–332; handheld and handline, 323, 325; instantaneous, 321–322; isokinetic, 322–323, 324(f); multivertical, 330; overview, 328; point-integrated, 333; rigid-bottle, 323; single-vertical, 328–330; transit rates, 332–333; transit rates for suspended-sediment, 332–333
sand: size classification scale, 1091(t); transport rates, 1009
sand-bed rivers, suspension-dominated: downstream fining, 233–234, 234(f); entrainment and near-bed concentration, grain-size specific relations, 231–232; fine sediment deposition, flushing from gravel, 236–237; floodplain deposition, grain-size-specific formulations, 234–236, 235(f); grain-size-specific bulk predictors, 232–233; Rouse-Vanoni approach for grain-size-specific suspended load, 229–231; sorting in, 229
sand-bed streams. *see also* bed-material load in sand-bed streams, dimensionless relations for: flow resistance, 99, 103–107; *vs.* gravel-bed streams, 65
Sandy River. *see* Marmot Dam, removal of (simulation)
San Francisco sediment, orders of, 261(t)
saturation: defined, 1098; landslides, 895
Saylorville Reservoir, 755, 756(f)
scale: defined, 1098; effect, 1096; fluvial geomorphology, 358–359; influence of, 391; laws, 1096; sediment grade, 36(t); size classification of sediment particles, 1091(f); time (in turbulent sediment transport), 765; watershed, 842–848(t)
scale effect, 1098
Schmidt number, 772–774
Schumm and Rosgen channel classifications, 376
scour. *see also* local scour, total scour, bridge-scour: bend, 556–557; confluence, 556–557; general, 508; local, 511–512(f), 5011–512 (*see also* pier foundations (complex), scour for; piers, local scour at); total, 506–507
scour at abutments: Chang-Davis abutment scour equation, 527–528; design for scour, 526–527; overview, 525–526, 526(f); Richardson et al. abutment scour equation, 530; Richardson-Trivino abutment scour equation, 529–530; shape, 526, 527(f); site conditions, 526; skew adjustment of, 526, 527(f); Sturm abutment scour equation, 528–529
scour equations: Colorado State University (CSU), 512, 513, 515; contraction, 508; Jain-Fisher's equation, 523–524; Melville's equation, 524–525; other, 525; Richardson et al. abutment scour equation, 530; Richardson-Trivino abutment scour equation, 529–530; Sturm abutment scour equation, 528–529
secondary currents (flow): defined, 1098; ice-cover influence on, 623
second-moment closure, 793–794
sediment, defined, 8, 1098
sedimentation, defined, 1098
Sedimentation Committee of the Hydraulics Division of ASCE, 1
sedimentation engineering: global aspects and changing roles in, 1–3; scope of, 3–4; state of, general observations on, 3
Sedimentation Engineering Manuals, 1, 21, 907, 1051–1052, 1110–1111
sedimentation hazards, 881–883. *see also* alluvial fan flooding; geomorphic hazards; mud flows and debris-flows, mathematical modeling of; bank protection works, 907; crib barriers, 907; debris barriers, 908; debris basins, 908; dikes, 908–909; diversions and bypasses, 908; flood control channels, 908; floodwalls, 908–909; general approach to, 906; guidance, 906–907; hazard assessment and mitigation design procedures, currently accepted, 905; hazard mapping and avoidance, 905; history and magnitude of, 887–889; levees, 908; overview, 885–887, 886(f); retention basins, 908; sediment control structures, 908; sediment retention structures, 908; sediment traps, 908; small dam operations, 908; state-of-the-science procedures, 905
Sedimentation Investigations of Rivers and Reservoirs (Engineering Manual 1110-2-4000), 907
sedimentation problems, management and treatment of: engineering treatment and, 15–16; fish habitat and environmental issues, 17; identification and definition of, 15; nonengineering treatment and, 16–17

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

sedimentation processes, computational modeling. *see also* data types and resolution; flow in mobile boundary channels, equations for: base test, 670–671; boundary conditions for, 655; computational and physical model studies, similarity between, 654–656; example application, 672–679, 675(t), 676–678(f); local scour and deposition, 650; model applicability, examples to illustrate, 671–672; overview of, 649–650; *vs.* physical model, 654–656; plan test, 671; results, interpretation of, 671
sediment characterization tests, 254–255, 255(t). *see also* mud definition and rheology
sediment cycle, 22–23
sediment data: bed gradation on a point bar, 664, 664(f); gradation of bed sediment reservoir, 658–659, 659(f); grain size classes, 660, 662(t); inflowing sediment concentrations, 660, 660(f), 661(f); sampling concepts, 659–660; sediment data set, criteria for, 320–321; sediment inflow from tributaries, 664; size and properties of bed sediment reservoir, 658; test for sufficiency, 660; transport theory, calculating with, 661–664; variability of samples, 660
sediment delivery ratios, 839–840, 840(t)
sediment deposition. *see also* reservoir sediment deposition: accelerated (human-induced), 11; causes of, 11–14; environmental and habitat effects of, 14; geologic (natural), 11; rates and quantities, estimation of, 7–8, 14
sediment deposits: debris flow, 11–12; intermediate and lowland river deposits, 12, 12(f); in lakes and reservoirs, 12–14; river, 11–12, 12(f); sand, for single season dam removal, 1012–1013(f); thickness over event horizons, 592–593
sediment-discharge, defined, 1097. *see also* sediment load
sediment discharge, estimating, 1063. *see also* bed load material equations; fluvial-sediment data, collection of, 1083–1089; suspended-sediment concentration interpolation method, 1067–1069, 1068(f); transport-curve method, 1069–1070(f), 1069–1073, 1071(f), 1072(f), 1073(t)
sediment-exchange processes: introduction, 707; near-bed concentration, imposition of, 707; near-bed sediment exchange, imposition of, 707
sediment finer, defined, 12
sediment focusing, 599, 607
sediment grade scale, 36(t)
sediment-laden open-channel flow, 61, 62(f)
sediment load. *see also* depth-discharge computation; suspended bed-material load: classification, 60, 60(t), 61(f); field data on bed-sediment load, 633; rating curves, 593; Rouse-Vanoni approach for grain-size-specific suspended load, 229–231; spatial modeling, 595; suspended, 601; turbidity measurements, 594
sedimentological scale, 37–38(f)
sediment oxygen demand (SOD): developed flow concepts, 989–990; diffusive sublayer thickness, 984–987, 984(f), 985(f), 986(f), 987(f); mass-transfer coefficient, 987–989, 989(f); overview, 983–984
sediment properties: fall velocity, 41–43, 42(f); model laboratory sediments, 35; porosity, 39–40, 40(f); rock types, 34; shape, 40–41, 40(f); size, 35–37, 36(t); size distribution, 37–38(f), 37–39; size distribution *vs.* stream morphology, 43–44, 43–44(f), 45(f); specific gravity, 34–35, 35(t)
sediment-routing models, 418(t)
sediment-routing strategies. *see also* pass-through: offstream reservoir for sediment bypass, 600–601, 600(f); onstream reservoir for sediment bypass, 601; turbidity density currents, routing of, 603–604, 604(f)
sediment studies plan, preparation of: data collection, 468; data inventory, 468; other elements, 468–469, 469(t); overview, 466–468, 467(f); problem areas, identification of potential, 468; stability assessment, 468; study area, boundary of, 468
sediment transport. *see also* bed forms; bed load transport; gravel and sediment mixtures, transport of; suspended bed-material load; threshold conditions for sediment transport: bed material load and wash load, modes of, 60–63, 64(f); continuity and, 417, 418(t), 419; Engelund-Hansen relation for bed-material load in sand-bed streams, 125; equations, summary of, 1083(t); by ice, 625–627, 626(f) (*see also* ice-cover effects on sediment transport by flow); modeling and, 10–11; modes of, 8–9, 60–63; sediment load classification, 60, 60(t), 61(f); Shields-Parker river sedimentation diagram, 63–65, 64(f), 65(f)
sediment transport, fluid mechanics and hydraulics for: bed forms, equivalent roughness of, 33–34, 33(f), 34(f); channel flow resistance, relations for, 27–29; fixed-bed (skin or grain) roughness, 29–31, 30(f), 31(t); flow velocity distribution, law of the wall, 24–25; flow velocity distribution, velocity-defect and log-wake laws, 25–27, 26(f); movable flat-bed roughness, 32
sediment transport and hydraulic variables, relationships between: incipient motion, 480–483, 481(t), 482(f), 483(t); sediment budgets, 484; silt and clay beds, 483–484, 483(f); slope-drainage area relations, 479–480; stream power, 480, 480(f)
sediment transport measurements. *see also* bed load samplers; bed-material measurement techniques; suspended-sediment samplers: overview, 307; sediment-sampling equipment, history of development of, 308–309; techniques, 9–10; terminology, 307–308, 308(f)
sediment-transport mechanics, 9; dune morphology and, 97; related phenomena, 9, 21–22
sediment-transport processes. *see also* active sediment-transport processes; passive sediment fate and transport processes: concentration profile, 259–260, 259(f); unit transport processes, 260–261
sediment transport scaling for physical models: cohesive sediment, structural modeling of, 1059–1060(f); dimensionless unit sediment discharge, 1059, 1061; model-prototype comparison, 1062–1064, 1063(f), 1064(f), 1065(f); nomenclature, 1064; overview, 1057; settling velocity adjustment, 1061–1062, 1062(f); similitude, 1057–1058; similitude deficiency of Froude scaling, 1058; tractive stress, 1058–1059, 1058(f)
sediment trapping: continuous, 581, 582(f); trap efficiency, 144(f), 595–596, 1101
sediment-water interface, 955(f)
sediment-wave effects, 553, 555
sediment yield. *see also* model calibration; watershed sediment yield: *vs.* drainage area, 589, 589(f), 590(f); erosion, 587; $Q_{1.5}$ discharge, 588, 588(t); reduction, 599–600; spatial variation, 587–588, 588(f); temporal variation, 588–590, 589(f), 590(f)
sediment yield, quantifying: from fluvial data, 593–594; neural network models for, 594–595; reservoir survey for, 590–593; spatial modeling for, 595
SEDIMONT, 587
settling and consolidation, 272–274
settling basins, 687

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

settling velocity. *see also* fall velocity: aggregation, 266–267; concentration and, 267–270; other effects on, 270; settling flux variation and, 267(f)
shallow-water (long-wave) model, 82
shape factor, defined, 1097
shear failure, 558
shear force, 820
shear intensity, 865
shear strength to solid volume fraction, 277(t)
shear stress, 194, 1099; aggregation, fine-grained sediment transport, 264–265; boundary, calculation of, 193–195; for cohesive materials, 454(f); diagram, 264(f); distribution, 397(f); distribution sketch and bed slope, 398(f)
shear stress partitions: Einstein partition, 100–101; Engelund-Fredsøe partition, 102; Nelson-Smith partition, 101–102
shear velocity, 776(t), 1099
Shields curve, defined, 1099
Shields diagram, 48–51, 49(f), 50(f)
Shields parameter, 48, 414, 485
Shields-Parker's River sedimentation diagram, 63–65, 64(f), 65(f)
Shields velocity, defined, 1099
shock-capturing formulation, 135(f)
shock-fitting formulation, 136, 137(f), 140–141(f), 144(f), 145(f)
shorefast ice erosion, 642(f)
shoreline recession, 297(f)
side slopes, threshold condition on, 57–59
sieve diameter, 42, 311, 1099
silt, 483–484, 728(f), 1091(f)
siltation, 13(f), 309, 827, 939
Silver Bow Creek, 235(f)
similarity plots, 189(f)
similarity (similitude), 652, 1057, 1099
Simons and Richardson diagram, 86–87, 86(f), 87(f)
simulate, defined, 1099
Simulated Water Erosion (SIMWE) model, 841
simulation, 445, 687, 913–917, 1099
simulation model, 844
single-stage samplers, 336–338
single-vertical sampling, 328–330
sinking material, 61, 62
sinuosity, 361–362
size-class fraction distribution, 742(t)
size distribution and size density scale, 37–38(f)
skewed flow, 520(f)
skim ice, 615
slaking, 401
slope bed, granular sediment on a, 55
slope-discharge relationships, 441(f)
slope dissection, 875–876
slope length and steepness factor, 833–835
slope slide, particle located on a, 58(f)
slurry flows, 893
slush, 616
socioeconomic lifelines, 888
SOGREAH, 844
Soil and Water Assessment Tool (SWAT), 840, 848, 850–851
Soil and Water Conservation Society, 599
Soil Conservation Service (SCS), 667
soil creep, 891
soil erodibility factor, 831–833
soil loss equation, 829–830
soil loss tolerance, 829
solifluction, 891
sophisticated models, 786–790, 790–794; nonlinear κ-ε models, 791–792; second-moment closure and algebraic stress models, 792–794; two-phase, 790–791
Soquel Creek, 16(f)
sorbed contaminant fate and transport, 689–690
sorting, defined, 1100
specific recurrence interval discharge, 365
specific weight computation by Lara-Pemberton method, 598(t)
split flow, 1100(f)
stability analysis, 448(f)
stability assessment for stream restoration, 474; bank stability, 484; channel classification, 477–479; hydraulic geometry relationship, 479; lane relations, 476–477; qualitative, 475; sediment transport and hydraulic variables, relationships between, 479–484; selection of, 484–485
stability checks for stream restoration: of bed and bank stability, 494–495; sediment budget analysis, 495–496
stability numbers *vs.* observed shore stability, 287(t)
stable channel, 1100
stable channel design chart, 489(f)
stably stratified-flow analogy, 776–778, 778
stage, defined, 1100
stage-discharge relations, 103; Brownlie & Cruickshank-Maza method, 106–107; Einstein-Barbarossa method, 103–104; Engelund-Hansen method, 104–105; Karim-Kennedy method, 107; other, 107; Wright-Parker method, 105–106
standard solid viscoelastic model, 257(f)
standard step method, 415, 417, 1100
Stanford Watershed Model (SWM), 848
state agencies, 667
static armour: from equilibrium bed conditions, 218(f); *vs.* experimental data, 217(f)
steady state model, defined, 1097, 1100
steady uniform sediment-laden flows, 779(f)
steep chutes and channels, 1038–1039
step-pool topography, side view of, 167(f), 228(f)
stochastic model, 70–71, 1052, 1077, 1097
stone, launched, 1048(f)
stone cells on bed surfaces, 216(f)
storm surge, 533
straight meandering, 878
straight trapezoidal cross section, 396(f)
strain rate, 256(f)
stratification and sorting, 239(f)
stratification correction, 291(t)
stratum control volumes, 704–705, 704(f), 709–711
streambank erosion, defined, 1098. *see also* river width adjustment
stream discharge, 366, 593, 1100
streamflows, 891
stream gauge, 656, 1100
stream gauge, defined, 1100
stream power: sinuosity variations and, 868(f); stability criteria, 480(f)
stream profile, defined, 1100
stream reach classifications, 494(t)

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

stream restoration: definitions, 461–462; discharge, 469–474; implementation and construction, 496; monitoring and postconstruction adjustment, 496–497; projects, 17, 17(f), 467(f); river dynamism, 463; sediment studies plan, preparation of, 466–469; stability assessment, 474–485; stability checks, 494–496
stream restoration, role of sedimentation engineering in. *see also* river restoration design: bed material size distribution, 474; engineer and, as part of a team, 463–464; habitat assessment, setting objectives and, 464–465; habitat restoration objectives, specific, 465; large scale projects, opportunities offered by, 465; monitoring and postconstruction adjustment, 496–497; objectives, setting, 464; project scale and, effects of objectives on, 465; risk evaluation, 466; sedimentation analysis, scope of, 465–466
stream segment, defined, 1100
streamwise velocity profiles, 114(f)
structure channel, 732(t)
Sturm abutment scour equation, 528–529
sturzstroms, 892
subcritical flow, 1100
submerged Iowa vanes, 453, 553
submodel domain, 744(f)
subsampling equipment, 338
sub-surface layer, 1090
summation convention, 816–817
supercritical flow, 83, 140, 1100
supplies and interests, definitions, 938
support practice factor, 837, 837(t)
surface armoring, contrasts in, 165(f)
surface-based relation of Parker plot, 196–197, 197(f)
surface grain-size distribution: pebble counts by stillwater sciences and, 1007(f); in the Sandy River, 1006(f)
suspended bed-material load: depth-discharge and sediment load computation, example of, 119–122 (*see also* depth-discharge computation); eddy diffusivity (Prandtl analogy), form of, 110–111; equilibrium, in wide channel, 109–110; equilibrium near-bed sediment concentration, 116–119; mass conservation of, 107–108; Rouse-Vanoni-Ippen suspended sediment distribution, 111–114; sediment advection-diffusion equation, boundary conditions for, 108–109; sediment entrainment, functions for, 116–119; vertically averaged concentrations, 114–116
suspended-material processes: sediment mixtures, formulations for, 706; three-dimensional formulation, 705–706; two-dimensional (depth-averaged) formulation, 706
suspended medium sand, computed and measured, 728(f)
suspended-sediment samplers, 326(f), 327(f). *see also* suspended bed-material load; boundary conditions, 749(f); concentrations, 739(f), 742(f), 749(f), 751(f); concentrations following dam removal, simulated, 1015(f); distribution, 112(f); fluxes, 296(f); loads, estimations of annual, 1073(t)
suspended silt and clay concentration, 481(f)
suspended very fine sand, 728(f), 729(f)
suspension concentration during a neap tide, 269(f)
sustainability: economic analysis and, 582–584, 583(f); regulatory and legal aspects, 584–585; RESCON approach, 584
SUTRENCH-2D, 699, 700, 701
SUTRENCH-3D, 699, 700, 701
SWRRB, 848
system closure: active-layer and active-stratum approach, 709–711; auxiliary relations, considerations, 711–712; bed load-layer approach, 709; introduction, 708–709; total-load approach, 709; two-dimensional models, 711
system instability: basin-wide factors, 375; downstream factors, 373–374; upstream factors, 374–375

T

TABS-2, 699
tactical dredging, 604–605
tailgate, 655
tailwater elevation, 665
Taiwanese River, 555(f)
Tanaguarena, 913
Tanaguarena (f), 886
Tanana River, 622(f)
Tarawera River, 78
TELEMAC-3D, 700
tensors, 815–816
thalweg: alignment, 639–640, 640(f), 641(f); defined, 1100; effects, 553, 555; sinuosity and channel variations, 640(f)
thalweg alignment, 638–639, 638(f), 639(f)
thalweg effects, 553, 555
thalweg sinuosity, 639(f)
theoretical model, 48
3D hydrodynamic model, 417
three-dimensional models: computer resources, limitations of, 684, 686; contaminant-sediment capability, 758; field data for model construction, 715; long-term bed evolution in response to changes, 688–689; river-bend dynamics and training works, 687; settling basins, 687; structured *vs.* unstructured grids., 755
Three Gorges Reservoir profile, 601(f)
three-point bars, 1098(f)
threshold channel, river restoration design of: example of, 487; refinements, 487; step-by-step approach, 487; velocity and tractive force, allowable, 487; when to use, 486–487
threshold conditions for sediment transport. *see also* bed-slope, incipient motion and: critical stress for flow over granular bed, 46–48; Lischtvan-Lebediev diagram for sediments for maximum permissible flow velocity, 55; Shields diagram, 48–51; submerged angle of response, 45; Wiberg-Smith diagram for heterogeneous sediments, 52–55; Yalin-Karahan diagram, 51–52
tidal amplitude, 533
tidal cycle, 533
tidal inlets, 533, 536(f)
tidal model, 717
tidal passage, 533
tidal period, 533
tidal prism, 533
tidal processes: defined, 533
tidal range, 533
tidal terms, principle, 535(f)
tidal waterways: crossings, types of, 534(f); definition, 533
tidal waterways, scour calculations for: contraction scour, 532–533; design discharge, 532; local scour, 533; long-term degradation, 532
tides, 533
Tinau River, 11, 11(f)

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

topographic variability, 206(f)
topset evolution: fluvial deposition, 134–137; linked-one dimensional model of, 139–141; linked-quasi-two-dimensional model of, 141–143
top width, defined, 525, 1101
total-load approach, 709
total maximum daily load (TMDL), 840
total scour: aggradation and degradation, long-term, 506; general scour (bridge-scour evaluation), 506–507; lateral shifting of a stream, 507; local scour, 503, 507
total sediment load, 8, 61(f), 308(f)
Toutle River channel profiles, 926(f)
toxic sediments on a floodplain, 235(f)
tracers as function relative to grain size, 237(f)
tractive force, 413–414, 428
transect, defined, 1101
transient flow and dam site following dam removal, 997(f)
transport capacity, 651, 654, 1101
transport modes, aggregation and, 265–266
transverse bed slopes, 445(f)
trap efficiency, 595–596, 1101; of a reservoir, 144(f)
trapezoidal channels, 393(f), 394(f), 395(f)
tributaries: defined, 1100; hydrologic data, 664–665; sediment inflow from, 660–661, 664; uncontaminated, healthy, 235(f)
truncation error, defined, 1101
Tsujimoto relation, 197–198
tsunami, 533
turbid density currents (turbid currents): morphodynamics of, equations governing, 131–133; overview, 597; plunging of, 137–139; rivers and, 129; routing of, 603–604, 606(f)
turbulence, aggregation and, 264–265
turbulence models. *see also* Eddy-viscosity model: aim and scope of modeling, 766; applications of, 794–812; auxiliary, boundary conditions and, 770–771, 784–794; Cartesian tensor notation, 815–817; choice models, considerations in assessment of, 812–815; closure, 695; defined, 1101; erodible-bed modeling, bed load transport and, 786–788; free-surface conditions, 788; other types of, 815; particulate flows, turbulence in, 763–766; problems in sediment transport, length and time scales in, 765; Reynolds-averaged equations, 766–771; sediment equation, boundary conditions and, 785–786; spatially averaged models, 817–820; turbulent flows, qualitative features of, 764–766
turbulent kinetic energy, equation for, 780–781
two-dimensional bed load transport, 75(f)
two-dimensional fan-delta, 143(f)
two-dimensional model, 141–143, 711
two-equation model: equation for ε, 782–783; k–ε model and closure constants, 783–784, 788–789
two-phase models, 790–791

U

U.K. Institute of Hydrology, 844
uniform flow, general resistance diagram for, 1058(f)
unimpeded removal, 404–405
U.S. Army Corps of Engineers: Unsteady flow through a full NETwork of open channels (UNET) model, 849
U.S. Geological Survey (USGS), 665, 667, 848, 955
U.S. Water Resources Council (WRC), 887
U.S. Weather Service, Extended Streamflow Prediction (ESP) program, 848
U.S. Environmental Protection Agency (USEPA), Better Assessment Science Integrating Point and Nonpoint Sources (BASINS), 848, 851
unit longitudinal staggered discharges, 751(f)
units of measurement, 321
unit transport processes, 260–261, 261(f)
Universal Soil Loss Equation (USLE), 587
unsteady-state model, 1101
upland river deposits, 11–12
upland soil erosion: cover-management factor, 835–837; rainfall-runoff erosivity factor, 830–831; slope length and steepness factor, 833–835; soil erodibility factor, 831–833; soil loss equation, 829–830; soil loss tolerance, 829; support practice factor, 837, 837(t)
urbanization and accelerated erosion, 5
U.S. Army Corps of Engineers, 667; HEC-6 model, 996, 997; Hydraulic Design of Flood Control Channels, 1051–1052
USDA allowable-velocity charts, 481(f)
USDA-ARS National Sedimentation Laboratory (NSL), 841
USDA-ARS North Central Soil Conservation Research Laboratory, 841
used tires, 550–551

V

valley filling, 875
vane shear strength and soil consistency, 277(t)
Vanoni, Vito A., 1108(f), 1109(f), 1110(f); career of, 1107; as hydraulic researcher, 1108–1110; personal life, 1111; retirement honors, 1111; as river hydraulics consultant, 1111; *Sedimentation Engineering Manuals,* 1, 21, 1110–1111; sedimentation research, overview of, 1112–1113; as structural engineer, 1108; suspended sediment transport research, 1111–1112; youth of, on farm, 1107–1108
Van Rijn formula, 73
Varnes' classification, 891
vectors, 815–816
vegetation: bank mechanic effects, 405–406; bridge site selection, 551, 553; restoration, 495; in revetments, 1046
velocity: boundary sheer stress and, 392(f); depth on exposed footing and, 519(f); for movement of bed material, critical, 510–511
Venezuela, 886(f)
verification, 668, 714–720, 1101
vertical mass diffusive flux, 292(f)
vertical momentum equation, 684, 686, 690, 756, 818
viscous length scale, 987(f)
Voigt viscoelastic model, 257(f)
volumetric samples and clay samples, 312(f)
vortex tube bed load samplers, 343, 343(f)

W

Walker River, 13(f)
warfare, 7
wash load, 8, 60–63, 1077, 1101
water column, defined, 1101
Water Erosion Prediction Project (WEPP), 587, 841

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.

water floods, 892
watershed management, literature on, 599–600
watershed models: algorithms and efficiencies, 851; curve number and empirical equations, 850–851; defined, 1100; diffusive wave equation used by CASC2D and MIKE SHE, 849; flow-governing equations, basic, 848–849; kinematic wave equations used by DWSM, KINEROS, and PRMS, 849–850; long-term continuous, 842–844(t), 851; review of, 841, 848; sediment yield predictions using, 852–854; storage-based equations, 850; storm-event, 845–848(t), 851–852
watershed sediment yield. *see also* upland soil erosion: gross erosion, 839–840; gully erosion, 837–839; sediment delivery ratios, 839–840, 840(t); soil erosion and sedimentation processes, 828–829; stream bed and bank erosion, 839; water erosion, factors affecting, 829
water-surface profiles, 669
water temperature, 665
waterway areas, 549
waterway openings, 533
Waterways Experiment Station, Vicksburg, Miss, 722
water year series selected for use in simulation, 1007(t), 1008(t)
wave-induced erosion: by breaking waves, 288, 288(t); concave and convex profile configurations, 286, 286(t); fluid mud entrainment by waves, 289–291, 290(t); nearshore zone, 284–286, 284(f); by nonbreaking waves, 288–289, 289(t); profile stability factor, 286–288, 287(t)
wavelets, 81
wave model, 909, 912
wave period, 533
weir, 451, 523, 553, 1038, 1101
wetted perimeter, 361
width adjustment models. *See* numerical width adjustment models
width-depth ratio, 361
Wilcock-Crowe relation, 199–200
Wilcock-Kenworthy relation, 198–199
Wilson formula, 72
winnowing failure, 558
Wu-Wang-Jia relation, 200

Y

Yalin formula, 72
Yang relation, 127
Yangtze River profile, 601(f)

Z

Zingg classification scale, 40, 40(f)

Downloaded from ascelibrary.org by VPI & SU on 01/12/23. Copyright ASCE. For personal use only; all rights reserved.