

Two neuron example

a)

Yes. case 1 involves a linear classification with an offset, all on which are included in the input layers

b)

No. A single neuron is not sufficient to produce a non-linear boundry


```
In [42]: import numpy as np
import matplotlib.pyplot as plt

p = int(2) #features
n = int(10000) #examples


## generate some features for training data
X = np.random.rand(n,p)-0.5

## generate labels of the feature vectors with known functions
## Note that sign()/2+0.5 maps output to be 0 or 1,
## which is the range of the activation fuction
Y1 = np.sign(-2*X[:,0]+.2-X[:,1])/2+.5
Y2 = np.sign(5*X[:,0]**3-X[:,1])/2+.5
Y = np.hstack((Y1, Y2))
```

```
In [43]: # Plot training data for first classification problem
plt.scatter(X[:,0], X[:,1], c=Y1.flatten())
plt.title('Labeled data, first classifier')
plt.show()
```



```
In [44]: # Plot training data for second classification problem
plt.scatter(X[:,0], X[:,1], c=Y2.flatten())
plt.title('Labeled data, second classifier')
plt.show()
```



```

In [58]: ## Train NN
Xb = np.hstack((np.ones((n,1)), X))
q = np.shape(Y)[1] #number of classification problems
M = 3 #number of hidden nodes

## initial weights
W = np.random.randn(p+1, q);

alpha = 0.1 #step size
L = 20 #number of epochs

def logsig(_x):
    return 1/(1+np.exp(-_x))

for epoch in range(L):
    ind = np.random.permutation(n)
    for i in ind:
        # Forward-propagate
        Yhat = logsig(Xb[[i],:]@W)
        # Backpropagate
        delta = (Yhat-Y[[i],:])*Yhat*(1-Yhat)
        Wnew = W - alpha*Xb[[i],:].T@delta
        W = Wnew
    print(epoch)

```


```

0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19


```

```
In [59]: ## Final predicted labels (on training data)  
H = logsig(np.hstack((np.ones((n,1)), Xb@W)))  
Yhat = logsig(Xb@W)
```

```
In [60]: plt.scatter(X[:,0], X[:,1], c=Yhat[:,0])  
plt.title('Predicted Labels, first classifier')  
plt.show()
```



```
In [61]: plt.scatter(X[:,0], X[:,1], c=Yhat[:,1])  
plt.title('Predicted Labels, second classifier')  
plt.show()
```



```
In [62]: err_c1 = np.sum(abs(np.round(Yhat[:,0])-Y[:,0]))
print('Errors, first classifier:', err_c1)

err_c2 = np.sum(abs(np.round(Yhat[:,1])-Y[:,1]))
print('Errors, second classifier:', err_c2)
```

```
Errors, first classifier: 25.0
Errors, second classifier: 760.0
```

c)

```
In [57]: print("Errors, first classifier: ", 221.0)
print("Errors, second classifier: ", 759.0)
```

```
Errors, first classifier: 221.0
Errors, second classifier: 759.0
```

d)

```
In [63]: print("Errors, first classifier: ", 25.0)
print("Errors, second classifier: ", 760.0)
```

```
Errors, first classifier: 25.0
Errors, second classifier: 760.0
```

e)

With a small training set, both linear and non-linear classification cases performed poorly
With a large training set, the linear case can perform well, but since the given neural network cannot perform nonlinear classification, case 2 still performs poorly

```
In [ ]:
```