

Q3

a

```
In [7]: import numpy as np
        from sklearn import mixture
        import math
```

```
In [38]: def EM(xs, K, n):
        # initialization
        l = len(xs)
        mus = np.array([-2, 2])
        pis = np.array([.5, .5])
        sigmas = np.array([[1], [1]])
        r = np.zeros(l)
        for _ in range(n):
            # E-Step
            for i in range(l):
                if abs(xs[i] - mus[0]) >= abs(xs[i] - mus[1]):
                    r[i] = 0
                else:
                    r[i] = 1
            # M-Step
            mus[0] = np.mean(xs[r == 0])
            mus[1] = np.mean(xs[r == 1])
            sigmas[0] = 1/np.count_nonzero(r) * np.add(xs[r == 0], -mus[0])
            sigmas[1] = 1/(l-np.count_nonzero(r)) * np.add(xs[r == 1], -mus[1])
            pis = np.array([np.count_nonzero(r)/l, (l-np.count_nonzero(r))/l])
            print("=====")
            print("mu = ", mus)
            print("sigma = ", sigmas)
            print("pi = ", pis)
            print("=====")
```

```
In [40]: D = np.array([-9, -8, -7, 5, 7, 9])
        EM(D, 2, 10)
```

```
=====
mu = [ 7 -8]
sigma = [[2]
         [0]]
```

```
pi = [0.5 0.5]
=====
=====
mu = [-8 7]
sigma = [[0]
[2]]
pi = [0.5 0.5]
=====
=====
mu = [ 7 -8]
sigma = [[2]
[0]]
pi = [0.5 0.5]
=====
=====
mu = [-8 7]
sigma = [[0]
[2]]
pi = [0.5 0.5]
=====
=====
mu = [ 7 -8]
sigma = [[2]
[0]]
pi = [0.5 0.5]
=====
=====
mu = [-8 7]
sigma = [[0]
[2]]
pi = [0.5 0.5]
=====
=====
mu = [ 7 -8]
sigma = [[2]
[0]]
pi = [0.5 0.5]
=====
=====
mu = [-8 7]
sigma = [[0]
[2]]
pi = [0.5 0.5]
=====
=====
mu = [ 7 -8]
sigma = [[2]
[0]]
pi = [0.5 0.5]
=====
=====
```

```
=====
mu = [-8  7]
sigma = [[0]
         [2]]
pi = [0.5 0.5]
=====
```

b

For the given outputs above, after 1 iteration, we have $p(x) = .5 * N(-8, 0) + .5 * N(7, 2)$

c

we see that solution does not converge as it continues to oscillate

In []: