Changelog

Français : ../fr/changelog.md

Format inspired by “Keep a Changelog”; semantic versioning.

[3.0.0] — unreleased (branch `release/3.0.0`)

Major version: functions follow each business’s plan, invoices shared by Nhill Business and Nhill POS, full export, data deletion at the end of the contract, tools to set up a virtual private server, new website and 3.0 legal documents. **Four migrations (0012 to 0015)**. 2.x applications are asked to update.

Plans and rights

- Catalogue of functions and limits; values per plan editable in Nhill Console; plan conditions (trial, grace period, reminders, automatic renewal with express agreement, fallback plan); assignment rules (migration 0012).
- Effective rights = role permissions reduced to the plan’s functions, checked by the server on every route and on indirect data (lists, dashboard, payments, stock movements, log, notifications); limits protected against concurrent access.
- Applications: menus, tabs, buttons and settings hidden when the plan does not include them; rights reloaded as soon as they change.
- Access computed by the database from the dates: full, read-only (consultation and export), none.

Documents and till

- One model for every sales document, in A4 or as a 58 or 80 mm receipt, used by Nhill Business and Nhill POS (same numbering, notices and rounding); configurable notices (migration 0013).
- Nhill POS: invoice in the name of an identified customer from the till; quantity-to-return field without a truncated label.
- Android: PDFs and exports open in another application or are shared (file provider, `content://`); “Share” button on a document.
- Dashboard: indicator titles on two lines on narrow screens.

Data

- Full export by the account holder (ZIP archive: JSON, CSV, attachments, manifest with SHA-256 fingerprints), whatever the subscription state.
- **Erasure of a business** 90 days after the end of its access, from Nhill Console (superadministrator, trade name to type; earlier only at the customer’s request); paid subscription orders archived for 10 years (migration 0014).
- Retention: sent messages deleted after 30 days, ended sessions after 90 days.
- 36 currencies (ISO 4217) and countries (ISO 3166-1) shared by the server and the applications.
- Searches: `%` and `_` taken literally (migration 0015).

Server and operations

- No API address compiled into the applications: the address is entered and checked at first use, and can be changed in the settings.
- A server refuses a database migrated by a newer version; the first administrator’s token can be reissued until the first access is completed.

- `NH_SUPPORT_EMAIL`: support address in the signature of automatic e-mails.
- `deploy/vps` kit for a Hostinger virtual private server in France: installation, firewall, encrypted backups, trial restore, monitoring every 5 minutes, update with a way back; 12-check acceptance test passed on a fresh machine in continuous integration.
- Client: HTTP/1.1 only (HTTP/2 advisories of Qt 6.5.3).

Website, documents, contacts

- Official contacts: `nhill.online`, `info@nhill.online`, `support@nhill.online`; publisher Nhill Solution, Kinshasa.
- New FR/EN marketing website, real 3.0 screenshots, social sharing image, live domain check (`check_live.py`).
- 3.0.0 legal documents (FR/EN) without fields to fill; compliance matrix between the website and the application; 3.0.0 security audit.
- Legal document 20: consent to use a name, testimonial or image; privacy policy, register and retention completed (field prospecting, testimonials).
- Documentation per component (Nhill Business, Nhill POS, Nhill Console, server, database) in French and English; API (203 endpoints) and database (71 tables) references generated from the code and checked by CI; 0.1–2.x documents archived in `docs/archive/`.
- Sales file: message templates with declared fields, trackers delivered empty (no fictitious row), visuals rebuilt with 3.0 screenshots for the 30-day trial.
- APK: third-party notices included (`assets/THIRD-PARTY-NOTICES.txt`).
- CI: waits for the Xvfb socket for screenshots; Android Keystore test robust to the emulator's activity manager restarting.

[2.1.0] — unreleased (branch `release/2.1.0`)

Two requested fixes: the remembered session on Windows and Android, and recovery of a forgotten password. **One migration (0011)**, four endpoints added to API `v1` (none changed), 2.0 clients accepted.

Remembered session ("Remember me")

- "Remember me" box at sign-in (Nhill Business, Nhill POS) and a "This device" setting in Settings › My account; unticked by default.
- Only the refresh token is kept, never the password, by QtKeychain: Windows Credential Manager, Android Keystore, Secret Service/KWallet on Linux. Without secure storage the session is not remembered and a message says so: no plain-text fallback. "Sign out" and unticking erase the entry.
- Windows: QtKeychain 0.17.0 built from its official source (verified commit) by `packaging/windows/build-qtkeychain.ps1`, **linked statically**; `CredReadW` / `CredWriteW` / `CredDeleteW` imports checked; licence notice installed with each application (`THIRD-PARTY-NOTICES.txt`).
- Android: static QtKeychain 0.17.0 (`packaging/android/build-qtkeychain-android.sh`, `KEYCHAIN_PREFIX`); presence of the Keystore code checked in the APK.
- Real test `tests/keychain` (write then read back in a second process, sign-out, nothing stored without the box): Credential Manager in Windows CI, Android 11 emulator, gnome-keyring on Linux.

Forgotten password

- **Employee**: the establishment administrator gives a temporary password (Settings › Team › "Reset the password"); 12 characters, shown once, valid 72 h; change required at the next sign-in; sessions closed; notice e-mailed to the member. Limited to members of the administrator's establishment, not oneself, not the owner, not an account active in another establishment.

- **Owner, administrator** (and account of several establishments): “Forgot your password?” e-mails an 8-digit code (20 min, 5 attempts, single use); the same answer whether the address exists or not; an employee receives the instruction to contact their administrator; all sessions are closed after the reset.
- Rate limits per address, per IP address and per administrator; activity log without password or code; codes hashed (HMAC-SHA-256) and erased from the outbox after sending.
- **Real e-mail delivery**: `smtp` transport (libcurl, TLS required, relay password in a file); `log` and `disabled` remain available.
- Platform settings: `password_reset_minutes`, `password_reset_max_attempts`, `temporary_password_hours`.
- Tests: 16 server tests (including a fake local SMTP relay).

Other

- E-mail templates completed (signature, subscription reminder bodies).
- Version 2.1.0 (Android version code 20100).

[2.0.0] — 2026-10-26

Major release: interface redesign, new password rule, industrialised builds and packages, marketing website, bilingual documentation and legal and commercial files. **API `v1` and the database schema (migrations 0001–0010) are unchanged**: no migration, 0.1.x clients accepted.

Security and accounts

- **Passwords: at least 8 characters** on every path (business creation, invitation, change, first console sign-in). One rule in `common/` (`kMinPasswordLength`), applied by the applications before sending and by the server.
- Console: the 14-character requirement is removed; **TOTP is still mandatory**.
- Blocklist extended to 40 entries (including “12345678”, “password”, “azerty123”, “kinshasa”).
- No periodic expiry, no composition rules, no two-factor authentication imposed on businesses.
- Client-side validation added to the console’s first access.
- Server behind a proxy: the client address is the **rightmost** `X-Forwarded-For` entry.

Interface (Nhill Business, POS, Console)

- Windows sized from the available screen (`Theme.fitWidth/fitHeight`), centred, maximised on small screens; minimums bounded by the screen; POS usable from 860×560.
- Tables: minimum width per column, horizontal scrolling, tooltips on truncated text, keyboard navigation.
- Colour tokens revised for WCAG AA contrast (secondary text, field borders ≥ 3:1, disabled states, success green); minimum text sizes 12 and 13 px.
- Buttons: visible focus ring, readable disabled state, tooltips (mandatory on icon buttons).
- Password fields: show/hide button.
- Messages: errors shown 8 s, at most 4, announced to screen readers.
- Scrollable side menu; global search with adaptive width; drop-down lists, calendar and notifications kept inside the window.
- POS: narrow mode (ticket below the grid), `F2` (search) and `F9` (pay) shortcuts, − / + buttons, product names on two lines, “Date / time” column, counted amount required before closing.
- Activity log: labels for till, support and console actions; technical fields hidden; “Point of sale” and “Support” filters.

Build and release

- `scripts/` : `install-deps-linux.sh`, `build-linux.sh`, `build-deb.sh`, `build-windows.sh` (+ `packaging/windows/build-windows.ps1`), `build-android.sh`, `build-docs-pdf.sh`, `build-website.sh`, `verify-build.sh`, `package-release.sh`, `build-all.sh` ; `--dry-run` mode, logs, exit codes, SHA-256 sums.
- **Native** Debian 13 packages (Debian's Qt) in addition to Ubuntu 24.04.
- NSIS Windows installers (one per application, Windows 10/11 64-bit, silent `/S` install).
- GitHub Actions workflows: CI, Linux packages (clean containers + test installation), Windows (MSVC, silent test installation), Android, documentation and website.
- Tests: 2 server tests and 2 `common` tests added (8-character rule, console); standalone test tool `tests/support/minigtest` ; static QML check.

Website and documentation

- Static FR/EN website (24 pages, dependency-free HTML5/CSS3/JavaScript) and form backend (SQLite or dedicated PostgreSQL, insert-only web role, abuse protections, automatic purge).
- FR/EN documentation (user, installation, configuration, developer, build and security guides), technical, UI/UX and security audits, PDFs generated from Markdown.
- Legal file (DRC): sourced research, assumptions register, templates to be validated by a lawyer.
- Commercial file (Kinshasa): sourced market study, pilot programme, 90-day plan, scripts, templates, KPI tracking.

Known limitations

- No password reset (no e-mail sending).
- cpp-httplib 0.14: CVE-2025-46728 and CVE-2025-53629, mitigated by Caddy; upgrade to ≥ 0.23.0 to do.
- Nhill is not invoicing software certified by the DRC tax authority (DGI).
- See the validation report for what was built and tested, and on which machine.

[0.1.0] — 2026-10-26

First release: C++17 / PostgreSQL server (forced RLS), Nhill Business, Nhill POS, Nhill Console (Qt 6), Ubuntu 24.04 `.deb` packages, Supabase database initialised. Details: `docs/archive/rapport-tests.md` , `docs/archive/limites.md` (French).