Nhill — Database reference

Français : ../fr/reference-base-de-donnees.md

Generated by `scripts/docs/gen_db_reference.py` from a PostgreSQL database migrated with the repository's migrations (do not edit by hand; continuous integration checks that it is up to date). Version 3.0.0: 71 tables and 29 functions in the `nhill` schema, 15 migrations.

Principles

- Two roles (`db/bootstrap/00-roles.sql`): `nhill_owner` owns the schema and applies the migrations, it is never used by the API; `nhill_app` is the running server's role: it owns nothing, has no definition (DDL) rights and remains subject to row-level security.
- Business isolation: the business-management tables have row-level security **enabled and forced**; the server sets `app.establishment_id` in each transaction and the policies only show that business's rows. Platform tables are read by the server's queries with only the rights the application role needs (see each table).
- Amounts: `bigint` in minor units with a `char(3)` currency; rates: integer basis points; quantities: `bigint` in thousandths; timestamps `timestamptz` (UTC).
- Migrations: files `db/migrations/NNNN_name.sql`, applied in order by `nhill-server migrate`; each applied migration is recorded with its checksum and a migration modified afterwards is refused; a server refuses a database migrated by a newer version.
- Erasing a business: function `nh_erase_establishment` (table owner, 90 days after access ends; see the console).

Migrations

Migration	Purpose
`0001_platform`	Platform tables: businesses, identity, access, subscriptions
`0002_business`	Business tables; composite foreign keys (business, id) so that a row never points to another business's data
`0003_security`	Row-level security and application-role privileges, with no bypass for platform administrators
`0004_reference_data`	Real reference data: ISO 4217 currencies and initial platform settings
`0005_helpers`	API helper functions (ISO 8601 UTC dates, etc.)
`0006_activity_and_platform_stats`	Activity log per employee; platform statistics limited to aggregates
`0007_local_time`	Each business's local time to date documents, sessions and reports
`0008_console_billing`	Console and billing: prices per duration and currency, plan changes, promo codes, payment providers, support, errors, notifications
`0009_pos`	Nhill POS: tills, cashiers, payment methods, sessions, cash movements, approvals, sales promo codes
`0010_fk_indexes`	Indexes on the foreign keys of frequent queries
`0011_password_recovery`	Forgotten password and temporary password (2.1.0)
`0012_plan_entitlements`	Configurable plans (3.0.0): catalogue of features and limits, values per plan, terms, assignment rules, computed access
`0013_documents`	Sales documents (3.0.0): the business's notices, invoices issued at the till with the same numbering
`0014_establishment_erasure`	Permanent erasure of a business, billing archive, retention clean-ups

Migration	Purpose
`0015_search_patterns`	Searches: `%` and `_` taken literally

Platform and identity

`establishments`

Businesses (customer companies): name, country, main currency, status.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Triggers: `establishments_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`kind`	`text`	yes	—
`trade_name`	`text`	yes	—
`legal_name`	`text`	—	—
`country_code`	`character(2)`	yes	—
`city`	`text`	—	—
`address`	`text`	—	—
`sector`	`text`	—	—
`preferred_language`	`text`	yes	`'fr'::text`
`main_currency`	`character(3)`	yes	—
`email`	`text`	—	—
`phone`	`text`	—	—
`website`	`text`	—	—
`vat_registered`	`boolean`	yes	`false`
`compliance_profile_code`	`text`	yes	—
`logo_object_id`	`uuid`	—	—
`status`	`text`	yes	`'active'::text`
`status_reason`	`text`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`
`timezone`	`text`	yes	`'UTC'::text`

Constraints: `FOREIGN KEY (main_currency) REFERENCES nhill.currencies(code)`; `PRIMARY KEY (id)`; 6 `CHECK` constraint(s)

`establishment_identifiers`

A business's legal identifiers according to the country profile.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: DELETE, INSERT, SELECT

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`kind`	`text`	yes	—
`country_code`	`character(2)`	yes	—
`value`	`text`	yes	—
`normalized_value`	`text`	yes	—

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (establishment_id, kind)`; `UNIQUE (country_code, kind, normalized_value)`; 1 `CHECK` constraint(s)

`establishment_settings`

A business's document settings (language, terms, rounding, notices).

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `establishment_settings_tenant`

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`allow_negative_stock`	`boolean`	yes	`false`
`tax_rounding`	`text`	yes	`'per_line'::text`
`default_payment_terms_days`	`integer`	yes	`0`
`document_language`	`text`	yes	`'fr'::text`
`invoice_footer`	`text`	yes	`''::text`
`payment_instructions`	`text`	yes	`''::text`
`updated_at`	`timestamp with time zone`	yes	`now()`
`document_mentions`	`text`	yes	`''::text`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (establishment_id)`; 4 `CHECK` constraint(s)

`establishment_codes`

Business codes: HMAC fingerprint for checking, encrypted copy for display to the owner.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—

Column	Type	Not null	Default
code_hmac	bytea	yes	—
code_cipher	bytea	yes	—
code_nonce	bytea	yes	—
status	text	yes	—
created_at	timestamp with time zone	yes	now()
expires_at	timestamp with time zone	yes	—
ended_at	timestamp with time zone	—	—
ended_reason	text	—	—
created_by_type	text	yes	—
created_by	uuid	—	—

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (code_hmac); 3 CHECK constraint(s)

users

User accounts (Argon2id password hash).

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE
- Triggers: users_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
email	text	yes	—
password_hash	text	yes	—
full_name	text	yes	—
phone	text	—	—
preferred_language	text	yes	'fr'::text
status	text	yes	'active'::text
password_changed_at	timestamp with time zone	yes	now()
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()
must_change_password	boolean	yes	false
temporary_password_expires_at	timestamp with time zone	—	—

Constraints: PRIMARY KEY (id); UNIQUE (email); 4 CHECK constraint(s)

memberships

A user's membership of a business, with their role.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)

- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`user_id`	`uuid`	yes	—
`role`	`text`	yes	—
`status`	`text`	yes	`'active'::text`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (user_id) REFERENCES nhill.users(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, user_id)`; 2 `CHECK` constraint(s)

`invitations`

Pending invitations (activation code stored as a hash).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`email`	`text`	yes	—
`role`	`text`	yes	—
`activation_hash`	`bytea`	yes	—
`expires_at`	`timestamp with time zone`	yes	—
`accepted_at`	`timestamp with time zone`	—	—
`revoked_at`	`timestamp with time zone`	—	—
`created_by`	`uuid`	yes	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (created_by) REFERENCES nhill.users(id)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; 2 `CHECK` constraint(s)

`join_tickets`

Short-lived tickets issued after a business code check.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`ticket_hash`	`bytea`	yes	—
`establishment_id`	`uuid`	yes	—

Column	Type	Not null	Default
expires_at	timestamp with time zone	yes	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (ticket_hash)

attachment_requests

Requests to join an existing company.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
requester_name	text	yes	—
requester_email	text	yes	—
requester_phone	text	—	—
message	text	—	—
status	text	yes	'open'::text
resolution_note	text	—	—
resolved_by	uuid	—	—
resolved_at	timestamp with time zone	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id); PRIMARY KEY (id); 1 CHECK constraint(s)

sessions

Application sessions (hashes of access and refresh tokens).

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
user_id	uuid	yes	—
establishment_id	uuid	yes	—
access_hash	bytea	yes	—
access_expires_at	timestamp with time zone	yes	—
refresh_hash	bytea	yes	—
previous_refresh_hash	bytea	—	—

Column	Type	Not null	Default
refresh_expires_at	timestamp with time zone	yes	—
created_at	timestamp with time zone	yes	now()
last_seen_at	timestamp with time zone	yes	now()
revoked_at	timestamp with time zone	—	—
revoke_reason	text	—	—
user_agent	text	—	—
ip	text	—	—

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; FOREIGN KEY (user_id) REFERENCES nhill.users(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (access_hash); UNIQUE (refresh_hash)

password_resets

Reset codes and password-change tickets (hashes).

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
user_id	uuid	yes	—
purpose	text	yes	—
secret_hash	bytea	yes	—
expires_at	timestamp with time zone	yes	—
attempts	integer	yes	0
used_at	timestamp with time zone	—	—
revoked_at	timestamp with time zone	—	—
ip	text	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (user_id) REFERENCES nhill.users(id) ON DELETE CASCADE; PRIMARY KEY (id); 2 CHECK constraint(s)

auth_throttle

Rate-limiting counters shared by the server instances.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE

Column	Type	Not null	Default
bucket	text	yes	—
window_start	timestamp with time zone	yes	—

Column	Type	Not null	Default
hits	integer	yes	0

Constraints: PRIMARY KEY (bucket, window_start)

trial_registry

HMAC fingerprints of identifiers that already had a trial; survives the business's erasure.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
fingerprint	bytea	yes	—
establishment_id	uuid	—	—
created_at	timestamp with time zone	yes	now()

Constraints: PRIMARY KEY (fingerprint)

compliance_profiles

Loaded country profiles (identifiers, taxes, notices, numbering), versioned.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
code	text	yes	—
version	integer	yes	—
country_code	character(2)	—	—
definition	jsonb	yes	—
content_sha256	text	yes	—
validation_note	text	yes	''::text
loaded_at	timestamp with time zone	yes	now()

Constraints: PRIMARY KEY (code, version); 2 CHECK constraint(s)

currencies

ISO 4217 currencies and number of decimals.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
code	character(3)	yes	—
minor_units	smallint	yes	—
name_fr	text	yes	—

Column	Type	Not null	Default
name_en	text	yes	—
active	boolean	yes	true

Constraints: PRIMARY KEY (code); 2 CHECK constraint(s)

notifications

Notifications for users.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
user_id	uuid	—	—
kind	text	yes	—
params	jsonb	yes	'{}'::jsonb
created_at	timestamp with time zone	yes	now()
read_at	timestamp with time zone	—	—

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; FOREIGN KEY (user_id) REFERENCES nhill.users(id) ON DELETE CASCADE; PRIMARY KEY (id)

email_outbox

Queue of automatic e-mails; sent or failed messages deleted after 30 days.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
to_address	text	yes	—
template	text	yes	—
language	text	yes	'fr'::text
params	jsonb	yes	'{}'::jsonb
status	text	yes	'pending'::text
attempts	integer	yes	0
last_error	text	—	—
created_at	timestamp with time zone	yes	now()
sent_at	timestamp with time zone	—	—

Constraints: PRIMARY KEY (id); 1 CHECK constraint(s)

`schema_migrations`

Applied migrations and their checksum (a modified migration is refused).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: SELECT

Column	Type	Not null	Default
`version`	`text`	yes	—
`checksum`	`text`	yes	—
`applied_at`	`timestamp with time zone`	yes	`now()`

Constraints: `PRIMARY KEY (version)`

Plans, rights and subscriptions

`plans`

Plans: audience, tier, terms (trial, grace, reminders, renewal, fallback plan).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Triggers: `plans_legacy_to_entitlements`, `plans_main_price`, `plans_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`code`	`text`	yes	—
`name_fr`	`text`	yes	—
`name_en`	`text`	yes	—
`description_fr`	`text`	yes	`''::text`
`description_en`	`text`	yes	`''::text`
`billing_period`	`text`	yes	—
`price_minor`	`bigint`	yes	—
`currency`	`character(3)`	yes	—
`tax_rate_bp`	`integer`	yes	`0`
`max_users`	`integer`	—	—
`audience`	`text`	yes	`'any'::text`
`features`	`jsonb`	yes	`'{}'::jsonb`
`active`	`boolean`	yes	`true`
`sort_order`	`integer`	yes	`0`
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`
`tier`	`integer`	yes	`0`

Column	Type	Not null	Default
max_registers	integer	—	—
max_warehouses	integer	—	—
kind	text	yes	'paid'::text
visibility	text	yes	'public'::text
self_service	boolean	yes	true
auto_renew_allowed	boolean	yes	true
grace_days	integer	—	—
reminder_days	integer[]	—	—
trial_days	integer	—	—
expiry_fallback_plan_id	uuid	—	—
archived_at	timestamp with time zone	—	—

Constraints: FOREIGN KEY (currency) REFERENCES nhill.currencies(code); FOREIGN KEY (expiry_fallback_plan_id) REFERENCES nhill.plans(id); PRIMARY KEY (id); UNIQUE (code); 14 CHECK constraint(s)

plan_prices

A plan's prices per duration (1 to 36 months) and currency.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE
- Triggers: plan_prices_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
plan_id	uuid	yes	—
duration_months	integer	yes	—
currency	character(3)	yes	—
price_minor	bigint	yes	—
active	boolean	yes	true
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (currency) REFERENCES nhill.currencies(code); FOREIGN KEY (plan_id) REFERENCES nhill.plans(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (plan_id, duration_months, currency); 2 CHECK constraint(s)

plan_capabilities

Catalogue of features and limits, default and trial values, FR/EN labels.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: SELECT

Column	Type	Not null	Default
key	text	yes	—
kind	text	yes	—
label_fr	text	yes	—
label_en	text	yes	—
description_fr	text	yes	''::text
description_en	text	yes	''::text
unit	text	—	—
default_enabled	boolean	—	—
default_limit	integer	—	—
trial_enabled	boolean	—	—
trial_limit	integer	—	—
sort_order	integer	yes	0

Constraints: PRIMARY KEY (key); 5 CHECK constraint(s)

plan_entitlements

Each feature's or limit's value for a plan.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE
- Triggers: plan_entitlements_check, plan_entitlements_legacy

Column	Type	Not null	Default
plan_id	uuid	yes	—
key	text	yes	—
enabled	boolean	—	—
limit_value	integer	—	—
updated_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (key) REFERENCES nhill.plan_capabilities(key); FOREIGN KEY (plan_id) REFERENCES nhill.plans(id) ON DELETE CASCADE; PRIMARY KEY (plan_id, key); 1 CHECK constraint(s)

plan_assignment_rules

Rules assigning a plan when a business is created (trial or grant).

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE
- Triggers: plan_assignment_rules_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
priority	integer	yes	100

Column	Type	Not null	Default
active	boolean	yes	true
audience	text	yes	'any'::text
country_code	character(2)	—	—
plan_id	uuid	yes	—
mode	text	yes	—
duration_days	integer	—	—
description	text	yes	''::text
created_by	uuid	—	—
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (created_by) REFERENCES nhill.admin_users(id); FOREIGN KEY (plan_id) REFERENCES nhill.plans(id); PRIMARY KEY (id); 6 CHECK constraint(s)

subscriptions

Each business's subscription: plan, period, status, access dates.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE
- Triggers: subscriptions_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
plan_id	uuid	—	—
pending_plan_id	uuid	—	—
status	text	yes	—
is_trial	boolean	yes	false
period_start	timestamp with time zone	yes	—
period_end	timestamp with time zone	yes	—
grace_until	timestamp with time zone	—	—
reminder_sent_for	timestamp with time zone	—	—
auto_renew_consent_at	timestamp with time zone	—	—
canceled_at	timestamp with time zone	—	—
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()
price_id	uuid	—	—
pending_price_id	uuid	—	—
pending_from	timestamp with time zone	—	—

Column	Type	Not null	Default
`failed_payments`	`integer`	yes	`0`
`last_failure_at`	`timestamp with time zone`	—	—
`open_ended`	`boolean`	yes	`false`
`suspension_reason`	`text`	—	—
`assignment_rule_id`	`uuid`	—	—

Constraints: `FOREIGN KEY (assignment_rule_id) REFERENCES nhill.plan_assignment_rules(id) ON DELETE SET NULL`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (pending_plan_id) REFERENCES nhill.plans(id)`; `FOREIGN KEY (pending_price_id) REFERENCES nhill.plan_prices(id)`; `FOREIGN KEY (plan_id) REFERENCES nhill.plans(id)`; `FOREIGN KEY (price_id) REFERENCES nhill.plan_prices(id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id)`; 4 `CHECK` constraint(s)

`subscription_events`

History of subscription changes.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`subscription_id`	`uuid`	yes	—
`establishment_id`	`uuid`	yes	—
`kind`	`text`	yes	—
`from_status`	`text`	—	—
`to_status`	`text`	—	—
`period_start`	`timestamp with time zone`	—	—
`period_end`	`timestamp with time zone`	—	—
`details`	`jsonb`	yes	`'{}'::jsonb`
`actor_type`	`text`	yes	—
`actor_id`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (subscription_id) REFERENCES nhill.subscriptions(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; 1 `CHECK` constraint(s)

`subscription_reminders`

Due-date reminders already sent (no duplicates).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT

Column	Type	Not null	Default
`subscription_id`	`uuid`	yes	—

Column	Type	Not null	Default
`period_end`	`timestamp with time zone`	yes	—
`days_before`	`integer`	yes	—
`sent_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (subscription_id) REFERENCES nhill.subscriptions(id) ON DELETE CASCADE`; `PRIMARY KEY (subscription_id, period_end, days_before)`; 1 `CHECK` constraint(s)

`subscription_orders`

Subscription orders and their payment.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`plan_id`	`uuid`	yes	—
`amount_minor`	`bigint`	yes	—
`currency`	`character(3)`	yes	—
`status`	`text`	yes	`'pending'::text`
`provider`	`text`	—	—
`provider_reference`	`text`	—	—
`created_by`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`paid_at`	`timestamp with time zone`	—	—
`kind`	`text`	yes	`'renewal'::text`
`price_id`	`uuid`	—	—
`duration_months`	`integer`	—	—
`subtotal_minor`	`bigint`	—	—
`discount_minor`	`bigint`	yes	`0`
`credit_minor`	`bigint`	yes	`0`
`tax_minor`	`bigint`	yes	`0`
`promo_code_id`	`uuid`	—	—
`provider_id`	`uuid`	—	—
`provider_session`	`text`	—	—
`checkout_url`	`text`	—	—
`expires_at`	`timestamp with time zone`	—	—
`failure_reason`	`text`	—	—

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (plan_id) REFERENCES nhill.plans(id)`; `FOREIGN KEY (price_id) REFERENCES nhill.plan_prices(id)`; `FOREIGN KEY (promo_code_id) REFERENCES nhill.promo_codes(id)`; `FOREIGN KEY (provider_id) REFERENCES nhill.payment_providers(id)`; `PRIMARY KEY (id)`; `UNIQUE (provider, provider_reference)`; 6 `CHECK` constraint(s)

`promo_codes`

Subscription promo codes.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Triggers: `promo_codes_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`code`	`text`	yes	—
`description`	`text`	yes	`''::text`
`discount_kind`	`text`	yes	—
`percent_bp`	`integer`	—	—
`amount_minor`	`bigint`	—	—
`currency`	`character(3)`	—	—
`valid_from`	`timestamp with time zone`	yes	`now()`
`valid_until`	`timestamp with time zone`	—	—
`max_redemptions`	`integer`	—	—
`max_per_establishment`	`integer`	yes	`1`
`plan_ids`	`uuid[]`	—	—
`min_duration_months`	`integer`	—	—
`new_customers_only`	`boolean`	yes	`false`
`audience`	`text`	yes	`'any'::text`
`active`	`boolean`	yes	`true`
`created_by`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (created_by) REFERENCES nhill.admin_users(id)`; `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `PRIMARY KEY (id)`; `UNIQUE (code)`; 10 `CHECK` constraint(s)

`promo_redemptions`

Uses of subscription promo codes.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
promo_code_id	uuid	yes	—
establishment_id	uuid	yes	—
order_id	uuid	yes	—
status	text	yes	'reserved'::text
discount_minor	bigint	yes	—
currency	character(3)	yes	—
created_at	timestamp with time zone	yes	now()
settled_at	timestamp with time zone	—	—

Constraints: FOREIGN KEY (currency) REFERENCES nhill.currencies(code); FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; FOREIGN KEY (order_id) REFERENCES nhill.subscription_orders(id) ON DELETE CASCADE; FOREIGN KEY (promo_code_id) REFERENCES nhill.promo_codes(id); PRIMARY KEY (id); UNIQUE (order_id); 2 CHECK constraint(s)

payment_providers

Configured payment providers (encrypted secrets).

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE
- Triggers: payment_providers_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
code	text	yes	—
kind	text	yes	—
display_name	text	yes	—
environment	text	yes	'test'::text
enabled	boolean	yes	false
currencies	character(3)[]	yes	'{}'::bpchar[]
settings	jsonb	yes	'{}'::jsonb
secret_cipher	bytea	—	—
secret_nonce	bytea	—	—
secret_fields	text[]	yes	'{}'::text[]
sort_order	integer	yes	0
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()
updated_by	uuid	—	—

Constraints: `FOREIGN KEY (updated_by) REFERENCES nhill.admin_users(id)`; `PRIMARY KEY (id)`; `UNIQUE (code)`; 5 `CHECK` constraint(s)

`payment_webhook_events`

Notifications received from providers (deduplication).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`provider`	`text`	yes	—
`event_id`	`text`	yes	—
`received_at`	`timestamp with time zone`	yes	`now()`
`payload`	`jsonb`	yes	—
`processed_at`	`timestamp with time zone`	—	—
`outcome`	`text`	—	—

Constraints: `PRIMARY KEY (id)`; `UNIQUE (provider, event_id)`

`billing_archive`

Paid or refunded orders of an erased business, kept 10 years.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: SELECT

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`establishment_id`	`uuid`	yes	—
`trade_name`	`text`	yes	—
`legal_name`	`text`	—	—
`country_code`	`character(2)`	—	—
`order_id`	`uuid`	yes	—
`plan_code`	`text`	—	—
`kind`	`text`	—	—
`duration_months`	`integer`	—	—
`subtotal_minor`	`bigint`	—	—
`discount_minor`	`bigint`	—	—
`tax_minor`	`bigint`	—	—
`amount_minor`	`bigint`	yes	—
`currency`	`character(3)`	yes	—
`status`	`text`	yes	—

Column	Type	Not null	Default
`provider`	`text`	—	—
`provider_reference`	`text`	—	—
`created_at`	`timestamp with time zone`	yes	—
`paid_at`	`timestamp with time zone`	—	—
`archived_at`	`timestamp with time zone`	yes	`now()`
`keep_until`	`date`	yes	—

Constraints: `PRIMARY KEY (id)`; `UNIQUE (order_id)`

Business management (businesses' data)

`tax_rates`

A business's tax rates (the rate never changes).

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `tax_rates_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`code`	`text`	yes	—
`label`	`text`	yes	—
`rate_bp`	`integer`	yes	—
`kind`	`text`	yes	`'standard'::text`
`is_default`	`boolean`	yes	`false`
`active`	`boolean`	yes	`true`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, code)`; `UNIQUE (establishment_id, id)`; 3 `CHECK` constraint(s)

`product_categories`

Product categories.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `product_categories_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—

Column	Type	Not null	Default
`name`	`text`	yes	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 1 `CHECK` constraint(s)

`products`

Products and services: price, tax, unit, barcode, alert threshold.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `products_tenant`
- Triggers: `products_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`kind`	`text`	yes	`'good'::text`
`sku`	`text`	yes	—
`barcode`	`text`	—	—
`name`	`text`	yes	—
`description`	`text`	yes	`''::text`
`category_id`	`uuid`	—	—
`unit`	`text`	yes	`'unit'::text`
`currency`	`character(3)`	yes	—
`purchase_price_minor`	`bigint`	yes	`0`
`sale_price_minor`	`bigint`	yes	`0`
`tax_rate_id`	`uuid`	—	—
`track_stock`	`boolean`	yes	`true`
`reorder_level_milli`	`bigint`	yes	`0`
`active`	`boolean`	yes	`true`
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, category_id) REFERENCES nhill.product_categories(establishment_id, id)`; `FOREIGN KEY (establishment_id, tax_rate_id) REFERENCES nhill.tax_rates(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; `UNIQUE (establishment_id, sku)`; 9 `CHECK` constraint(s)

`parties`

Customers and suppliers.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `parties_tenant`
- Triggers: `parties_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`is_customer`	`boolean`	yes	`false`
`is_supplier`	`boolean`	yes	`false`
`kind`	`text`	yes	`'company'::text`
`name`	`text`	yes	—
`email`	`text`	—	—
`phone`	`text`	—	—
`address`	`text`	yes	`''::text`
`city`	`text`	yes	`''::text`
`country_code`	`character(2)`	—	—
`tax_ids`	`jsonb`	yes	`'{}'::jsonb`
`payment_terms_days`	`integer`	yes	`0`
`notes`	`text`	yes	`''::text`
`active`	`boolean`	yes	`true`
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 4 `CHECK` constraint(s)

`warehouses`

Warehouses; the default warehouse is the main one.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `warehouses_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`name`	`text`	yes	—
`is_default`	`boolean`	yes	`false`

Column	Type	Not null	Default
`active`	`boolean`	yes	`true`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`

`stock_levels`

Quantity in stock per product and warehouse.

- Row-level security: enabled and forced
- `nhill_app` rights: SELECT
- Policies: `stock_levels_tenant`

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`product_id`	`uuid`	yes	—
`warehouse_id`	`uuid`	yes	—
`quantity_milli`	`bigint`	yes	`0`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id, product_id) REFERENCES nhill.products(establishment_id, id)`; `FOREIGN KEY (establishment_id, warehouse_id) REFERENCES nhill.warehouses(establishment_id, id)`; `PRIMARY KEY (establishment_id, product_id, warehouse_id)`

`stock_movements`

Stock movements, with their author and origin.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT
- Policies: `stock_movements_tenant`
- Triggers: `stock_movements_apply`

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`establishment_id`	`uuid`	yes	—
`product_id`	`uuid`	yes	—
`warehouse_id`	`uuid`	yes	—
`quantity_milli`	`bigint`	yes	—
`kind`	`text`	yes	—
`source_type`	`text`	—	—
`source_id`	`uuid`	—	—
`note`	`text`	yes	`''::text`
`created_by`	`uuid`	—	—

Column	Type	Not null	Default
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id, product_id) REFERENCES nhill.products(establishment_id, id); FOREIGN KEY (establishment_id, warehouse_id) REFERENCES nhill.warehouses(establishment_id, id); PRIMARY KEY (id); 2 CHECK constraint(s)

sales_documents

Sales documents: quotes, orders, invoices, credit notes, till receipts.

- Row-level security: enabled and forced
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE
- Policies: sales_documents_tenant
- Triggers: sales_documents_guard, sales_documents_usage

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
doc_type	text	yes	—
status	text	yes	'draft'::text
number	text	—	—
sequence_value	bigint	—	—
party_id	uuid	yes	—
currency	character(3)	yes	—
language	text	yes	'fr'::text
issue_date	date	yes	nhill.nh_local_today()
due_date	date	—	—
valid_until	date	—	—
main_currency	character(3)	yes	—
fx_rate	numeric(24,10)	—	—
fx_rate_date	date	—	—
fx_rate_source	text	—	—
tax_rounding	text	yes	'per_line'::text
gross_minor	bigint	yes	0
discount_minor	bigint	yes	0
net_minor	bigint	yes	0
tax_minor	bigint	yes	0
total_minor	bigint	yes	0
paid_minor	bigint	yes	0
credited_minor	bigint	yes	0

Column	Type	Not null	Default
`tax_breakdown`	`jsonb`	yes	`'[]'::jsonb`
`notes`	`text`	yes	`''::text`
`terms`	`text`	yes	`''::text`
`related_document_id`	`uuid`	—	—
`restock`	`boolean`	yes	`false`
`seller_snapshot`	`jsonb`	—	—
`buyer_snapshot`	`jsonb`	—	—
`profile_code`	`text`	—	—
`profile_version`	`integer`	—	—
`fiscal_reference`	`jsonb`	—	—
`pdf_sha256`	`text`	—	—
`created_by`	`uuid`	—	—
`issued_by`	`uuid`	—	—
`issued_at`	`timestamp with time zone`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`
`pos_session_id`	`uuid`	—	—

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, party_id) REFERENCES nhill.parties(establishment_id, id)`; `FOREIGN KEY (establishment_id, pos_session_id) REFERENCES nhill.pos_sessions(establishment_id, id)`; `FOREIGN KEY (establishment_id, related_document_id) REFERENCES nhill.sales_documents(establishment_id, id)`; `FOREIGN KEY (main_currency) REFERENCES nhill.currencies(code)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, doc_type, number)`; `UNIQUE (establishment_id, id)`; 10 `CHECK` constraint(s)

`sales_document_lines`

Lines of sales documents.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `sales_document_lines_tenant`
- Triggers: `sales_document_lines_guard`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`document_id`	`uuid`	yes	—
`line_no`	`integer`	yes	—
`product_id`	`uuid`	—	—

Column	Type	Not null	Default
`description`	`text`	yes	—
`quantity_milli`	`bigint`	yes	—
`unit`	`text`	yes	`'unit'::text`
`unit_price_minor`	`bigint`	yes	—
`discount_bp`	`integer`	yes	`0`
`tax_rate_bp`	`integer`	yes	`0`
`tax_code`	`text`	yes	`''::text`
`gross_minor`	`bigint`	yes	—
`discount_minor`	`bigint`	yes	—
`net_minor`	`bigint`	yes	—
`tax_minor`	`bigint`	yes	—
`total_minor`	`bigint`	yes	—

Constraints: `FOREIGN KEY (establishment_id, document_id) REFERENCES nhill.sales_documents(establishment_id, id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, product_id) REFERENCES nhill.products(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (document_id, line_no)`; 6 `CHECK` constraint(s)

`document_status_history`

History of document statuses.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT
- Policies: `document_status_history_tenant`

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`establishment_id`	`uuid`	yes	—
`document_id`	`uuid`	yes	—
`from_status`	`text`	—	—
`to_status`	`text`	yes	—
`actor_id`	`uuid`	—	—
`note`	`text`	yes	`''::text`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id, document_id) REFERENCES nhill.sales_documents(establishment_id, id) ON DELETE CASCADE`; `PRIMARY KEY (id)`

`document_sequences`

Numbering counters per document type and period.

- Row-level security: enabled and forced

- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `document_sequences_tenant`

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`doc_type`	`text`	yes	—
`period_key`	`text`	yes	—
`next_value`	`bigint`	yes	—

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (establishment_id, doc_type, period_key)`; 1 `CHECK` constraint(s)

`purchases`

Supplier purchases.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `purchases_tenant`
- Triggers: `purchases_guard`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`supplier_id`	`uuid`	yes	—
`status`	`text`	yes	`'draft'::text`
`supplier_reference`	`text`	yes	`''::text`
`purchase_date`	`date`	yes	`nhill.nh_local_today()`
`due_date`	`date`	—	—
`currency`	`character(3)`	yes	—
`warehouse_id`	`uuid`	yes	—
`net_minor`	`bigint`	yes	`0`
`tax_minor`	`bigint`	yes	`0`
`total_minor`	`bigint`	yes	`0`
`paid_minor`	`bigint`	yes	`0`
`notes`	`text`	yes	`''::text`
`created_by`	`uuid`	—	—
`received_by`	`uuid`	—	—
`received_at`	`timestamp with time zone`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, supplier_id) REFERENCES nhill.parties(establishment_id, id)`; `FOREIGN KEY (establishment_id, warehouse_id) REFERENCES nhill.warehouses(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 4 `CHECK` constraint(s)

`purchase_lines`

Purchase lines.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `purchase_lines_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`purchase_id`	`uuid`	yes	—
`line_no`	`integer`	yes	—
`product_id`	`uuid`	—	—
`description`	`text`	yes	—
`quantity_milli`	`bigint`	yes	—
`unit_cost_minor`	`bigint`	yes	—
`tax_rate_bp`	`integer`	yes	`0`
`net_minor`	`bigint`	yes	—
`tax_minor`	`bigint`	yes	—
`total_minor`	`bigint`	yes	—

Constraints: `FOREIGN KEY (establishment_id, product_id) REFERENCES nhill.products(establishment_id, id)`; `FOREIGN KEY (establishment_id, purchase_id) REFERENCES nhill.purchases(establishment_id, id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (purchase_id, line_no)`; 4 `CHECK` constraint(s)

`expense_categories`

Expense categories.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `expense_categories_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`name`	`text`	yes	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 1 `CHECK` constraint(s)

`expenses`

Expenses.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `expenses_tenant`
- Triggers: `expenses_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`category_id`	`uuid`	—	—
`supplier_id`	`uuid`	—	—
`description`	`text`	yes	—
`amount_minor`	`bigint`	yes	—
`tax_minor`	`bigint`	yes	`0`
`currency`	`character(3)`	yes	—
`expense_date`	`date`	yes	`nhill.nh_local_today()`
`due_date`	`date`	—	—
`paid_minor`	`bigint`	yes	`0`
`receipt_object_id`	`uuid`	—	—
`created_by`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, category_id) REFERENCES nhill.expense_categories(establishment_id, id)`; `FOREIGN KEY (establishment_id, receipt_object_id) REFERENCES nhill.objects(establishment_id, id)`; `FOREIGN KEY (establishment_id, supplier_id) REFERENCES nhill.parties(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 6 `CHECK` constraint(s)

`payments`

Payments received and made, linked to a document, purchase or expense.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `payments_tenant`
- Triggers: `payments_usage`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`

Column	Type	Not null	Default
establishment_id	uuid	yes	—
direction	text	yes	—
party_id	uuid	—	—
document_id	uuid	—	—
purchase_id	uuid	—	—
expense_id	uuid	—	—
method	text	yes	—
account_id	uuid	—	—
amount_minor	bigint	yes	—
currency	character(3)	yes	—
paid_at	timestamp with time zone	yes	now()
reference	text	yes	''::text
note	text	yes	''::text
created_by	uuid	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (currency) REFERENCES nhill.currencies(code); FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; FOREIGN KEY (establishment_id, account_id) REFERENCES nhill.cash_accounts(establishment_id, id); FOREIGN KEY (establishment_id, document_id) REFERENCES nhill.sales_documents(establishment_id, id); FOREIGN KEY (establishment_id, expense_id) REFERENCES nhill.expenses(establishment_id, id); FOREIGN KEY (establishment_id, party_id) REFERENCES nhill.parties(establishment_id, id); FOREIGN KEY (establishment_id, purchase_id) REFERENCES nhill.purchases(establishment_id, id); PRIMARY KEY (id); UNIQUE (establishment_id, id); 4 CHECK constraint(s)

cash_accounts

Cash and bank accounts.

- Row-level security: enabled and forced
- nhill_app rights: INSERT, SELECT, UPDATE
- Policies: cash_accounts_tenant

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
name	text	yes	—
kind	text	yes	—
currency	character(3)	yes	—
active	boolean	yes	true
created_at	timestamp with time zone	yes	now()

Constraints: `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; 1 `CHECK` constraint(s)

`exchange_rates`

Recorded exchange rates (date and source).

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `exchange_rates_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`from_currency`	`character(3)`	yes	—
`to_currency`	`character(3)`	yes	—
`rate`	`numeric(24,10)`	yes	—
`rate_date`	`date`	yes	—
`source`	`text`	yes	`''::text`
`created_by`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (from_currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (to_currency) REFERENCES nhill.currencies(code)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, from_currency, to_currency, rate_date)`; 2 `CHECK` constraint(s)

`objects`

Stored files: logo, receipts (PDF, PNG, JPEG, 5 MB at most).

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT, UPDATE
- Policies: `objects_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`purpose`	`text`	yes	—
`mime`	`text`	yes	—
`byte_size`	`integer`	yes	—
`sha256`	`text`	yes	—
`width`	`integer`	—	—
`height`	`integer`	—	—
`data`	`bytea`	yes	—

Column	Type	Not null	Default
created_by	uuid	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (establishment_id, id); 3 CHECK constraint(s)

idempotency_keys

Idempotency keys and recorded answers, in the same transaction as the operation.

- Row-level security: enabled and forced
- nhill_app rights: DELETE, INSERT, SELECT, UPDATE
- Policies: idempotency_keys_tenant

Column	Type	Not null	Default
establishment_id	uuid	yes	—
idem_key	text	yes	—
user_id	uuid	—	—
request_hash	bytea	yes	—
status_code	integer	—	—
response_body	text	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (establishment_id, idem_key); 1 CHECK constraint(s)

audit_log

Activity log, append-only.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT

Column	Type	Not null	Default
id	bigint	yes	identity
establishment_id	uuid	—	—
actor_type	text	yes	—
actor_id	uuid	—	—
action	text	yes	—
entity	text	—	—
entity_id	text	—	—
details	jsonb	yes	'{}'::jsonb
ip	text	—	—
created_at	timestamp with time zone	yes	now()

Constraints: `PRIMARY KEY (id)`; 1 `CHECK` constraint(s)

Till (Nhill POS)

`pos_settings`

Till rules: walk-in customer, maximum discount, price override, receipt footer and width.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `pos_settings_tenant`

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`walk_in_party_id`	`uuid`	—	—
`max_discount_bp`	`integer`	yes	`1000`
`allow_price_override`	`boolean`	yes	`false`
`receipt_footer`	`text`	yes	`''::text`
`receipt_width_mm`	`integer`	yes	`80`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, walk_in_party_id) REFERENCES nhill.parties(establishment_id, id)`; `PRIMARY KEY (establishment_id)`; 2 `CHECK` constraint(s)

`pos_registers`

Tills and their warehouse.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `pos_registers_tenant`
- Triggers: `pos_registers_touch`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`code`	`text`	yes	—
`name`	`text`	yes	—
`location`	`text`	yes	`''::text`
`warehouse_id`	`uuid`	yes	—
`active`	`boolean`	yes	`true`
`created_at`	`timestamp with time zone`	yes	`now()`
`updated_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, warehouse_id) REFERENCES nhill.warehouses(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, code)`; `UNIQUE (establishment_id, id)`; 2 `CHECK` constraint(s)

`pos_register_users`

Authorised cashiers per till.

- Row-level security: enabled and forced
- `nhill_app` rights: DELETE, INSERT, SELECT
- Policies: `pos_register_users_tenant`

Column	Type	Not null	Default
`establishment_id`	`uuid`	yes	—
`register_id`	`uuid`	yes	—
`user_id`	`uuid`	yes	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id, register_id) REFERENCES nhill.pos_registers(establishment_id, id) ON DELETE CASCADE`; `FOREIGN KEY (user_id) REFERENCES nhill.users(id) ON DELETE CASCADE`; `PRIMARY KEY (register_id, user_id)`

`pos_payment_methods`

Till payment methods.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `pos_payment_methods_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`code`	`text`	yes	—
`label`	`text`	yes	—
`kind`	`text`	yes	—
`account_id`	`uuid`	—	—
`active`	`boolean`	yes	`true`
`sort_order`	`integer`	yes	`0`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, account_id) REFERENCES nhill.cash_accounts(establishment_id, id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, code)`; `UNIQUE (establishment_id, id)`; 3 `CHECK` constraint(s)

`pos_sessions`

Till sessions: opening, float, closing, count, difference.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT, UPDATE
- Policies: `pos_sessions_tenant`
- Triggers: `pos_sessions_guard`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`register_id`	`uuid`	yes	—
`number`	`integer`	yes	—
`status`	`text`	yes	`'open'::text`
`currency`	`character(3)`	yes	—
`opened_by`	`uuid`	yes	—
`opened_at`	`timestamp with time zone`	yes	`now()`
`opening_float_minor`	`bigint`	yes	`0`
`closed_by`	`uuid`	—	—
`closed_at`	`timestamp with time zone`	—	—
`expected`	`jsonb`	—	—
`counted`	`jsonb`	—	—
`cash_expected_minor`	`bigint`	—	—
`cash_counted_minor`	`bigint`	—	—
`cash_variance_minor`	`bigint`	—	—
`closing_note`	`text`	yes	`''::text`

Constraints: `FOREIGN KEY (closed_by) REFERENCES nhill.users(id)`; `FOREIGN KEY (currency) REFERENCES nhill.currencies(code)`; `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (establishment_id, register_id) REFERENCES nhill.pos_registers(establishment_id, id)`; `FOREIGN KEY (opened_by) REFERENCES nhill.users(id)`; `PRIMARY KEY (id)`; `UNIQUE (establishment_id, id)`; `UNIQUE (register_id, number)`; 4 `CHECK` constraint(s)

`pos_cash_movements`

Cash in and out during a session.

- Row-level security: enabled and forced
- `nhill_app` rights: INSERT, SELECT
- Policies: `pos_cash_movements_tenant`

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`establishment_id`	`uuid`	yes	—
`session_id`	`uuid`	yes	—
`kind`	`text`	yes	—

Column	Type	Not null	Default
amount_minor	bigint	yes	—
reason	text	yes	—
created_by	uuid	yes	—
approved_by	uuid	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (approved_by) REFERENCES nhill.users(id); FOREIGN KEY (created_by) REFERENCES nhill.users(id); FOREIGN KEY (establishment_id, session_id) REFERENCES nhill.pos_sessions(establishment_id, id); PRIMARY KEY (id); 3 CHECK constraint(s)

pos_approvals

Single-use supervisor approvals.

- Row-level security: enabled and forced
- nhill_app rights: INSERT, SELECT, UPDATE
- Policies: pos_approvals_tenant

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
token_hash	bytea	yes	—
action	text	yes	—
approver_id	uuid	yes	—
requested_by	uuid	yes	—
session_id	uuid	—	—
expires_at	timestamp with time zone	yes	—
used_at	timestamp with time zone	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (approver_id) REFERENCES nhill.users(id); FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; FOREIGN KEY (establishment_id, session_id) REFERENCES nhill.pos_sessions(establishment_id, id); FOREIGN KEY (requested_by) REFERENCES nhill.users(id); PRIMARY KEY (id); UNIQUE (token_hash); 1 CHECK constraint(s)

sales_promo_codes

A business's sales promo codes.

- Row-level security: enabled and forced
- nhill_app rights: INSERT, SELECT, UPDATE
- Policies: sales_promo_codes_tenant

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()

Column	Type	Not null	Default
establishment_id	uuid	yes	—
code	text	yes	—
description	text	yes	''::text
percent_bp	integer	yes	—
min_amount_minor	bigint	yes	0
currency	character(3)	—	—
valid_from	timestamp with time zone	yes	now()
valid_until	timestamp with time zone	—	—
max_redemptions	integer	—	—
active	boolean	yes	true
created_by	uuid	—	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (created_by) REFERENCES nhill.users(id); FOREIGN KEY (currency) REFERENCES nhill.currencies(code); FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (establishment_id, code); UNIQUE (establishment_id, id); 5 CHECK constraint(s)

sales_promo_redemptions

Uses of sales promo codes.

- Row-level security: enabled and forced
- nhill_app rights: INSERT, SELECT
- Policies: sales_promo_redemptions_tenant

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
establishment_id	uuid	yes	—
promo_id	uuid	yes	—
document_id	uuid	yes	—
discount_minor	bigint	yes	—
created_at	timestamp with time zone	yes	now()

Constraints: FOREIGN KEY (establishment_id, document_id) REFERENCES nhill.sales_documents(establishment_id, id); FOREIGN KEY (establishment_id, promo_id) REFERENCES nhill.sales_promo_codes(establishment_id, id); PRIMARY KEY (id); UNIQUE (document_id); 1 CHECK constraint(s)

Console and operations

admin_users

Platform administrators (password and TOTP).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`email`	`text`	yes	—
`full_name`	`text`	yes	—
`password_hash`	`text`	—	—
`totp_cipher`	`bytea`	—	—
`totp_nonce`	`bytea`	—	—
`totp_enabled`	`boolean`	yes	`false`
`role`	`text`	yes	—
`status`	`text`	yes	`'pending'::text`
`setup_token_hash`	`bytea`	—	—
`setup_expires_at`	`timestamp with time zone`	—	—
`last_totp_step`	`bigint`	—	—
`last_login_at`	`timestamp with time zone`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `PRIMARY KEY (id)`; `UNIQUE (email)`; 3 `CHECK` constraint(s)

`admin_sessions`

Console sessions.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`admin_id`	`uuid`	yes	—
`token_hash`	`bytea`	yes	—
`expires_at`	`timestamp with time zone`	yes	—
`revoked_at`	`timestamp with time zone`	—	—
`ip`	`text`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (admin_id) REFERENCES nhill.admin_users(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; `UNIQUE (token_hash)`

`admin_notifications`

Console notifications.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)

- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`kind`	`text`	yes	—
`params`	`jsonb`	yes	`'{}'::jsonb`
`establishment_id`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`
`read_at`	`timestamp with time zone`	—	—
`read_by`	`uuid`	—	—

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE`; `FOREIGN KEY (read_by) REFERENCES nhill.admin_users(id)`; `PRIMARY KEY (id)`

`announcements`

Announcements published to businesses.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`uuid`	yes	`gen_random_uuid()`
`kind`	`text`	yes	—
`title_fr`	`text`	yes	—
`title_en`	`text`	yes	—
`body_fr`	`text`	yes	`''::text`
`body_en`	`text`	yes	`''::text`
`starts_at`	`timestamp with time zone`	yes	`now()`
`ends_at`	`timestamp with time zone`	—	—
`min_client_version`	`text`	—	—
`created_by`	`uuid`	—	—
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (created_by) REFERENCES nhill.admin_users(id)`; `PRIMARY KEY (id)`; 1 `CHECK` constraint(s)

`platform_settings`

Platform settings (allowed list).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
key	text	yes	—
value	jsonb	yes	—
description	text	yes	''::text
updated_at	timestamp with time zone	yes	now()
updated_by	uuid	—	—

Constraints: PRIMARY KEY (key)

support_tickets

Support requests.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)
- nhill_app rights: INSERT, SELECT, UPDATE
- Triggers: support_tickets_touch

Column	Type	Not null	Default
id	uuid	yes	gen_random_uuid()
number	bigint	yes	identity
establishment_id	uuid	yes	—
created_by	uuid	—	—
source	text	yes	—
category	text	yes	—
severity	text	yes	'normal'::text
subject	text	yes	—
status	text	yes	'open'::text
app_version	text	—	—
platform	text	—	—
assigned_to	uuid	—	—
created_at	timestamp with time zone	yes	now()
updated_at	timestamp with time zone	yes	now()
last_message_at	timestamp with time zone	yes	now()
resolved_at	timestamp with time zone	—	—

Constraints: FOREIGN KEY (assigned_to) REFERENCES nhill.admin_users(id); FOREIGN KEY (created_by) REFERENCES nhill.users(id); FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE CASCADE; PRIMARY KEY (id); UNIQUE (number); 5 CHECK constraint(s)

support_ticket_messages

Request messages, internal notes included.

- Row-level security: no (platform table, access limited by the nhill_app role's rights)

- `nhill_app` rights: INSERT, SELECT

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`ticket_id`	`uuid`	yes	—
`author_type`	`text`	yes	—
`author_id`	`uuid`	—	—
`body`	`text`	yes	—
`internal`	`boolean`	yes	`false`
`created_at`	`timestamp with time zone`	yes	`now()`

Constraints: `FOREIGN KEY (ticket_id) REFERENCES nhill.support_tickets(id) ON DELETE CASCADE`; `PRIMARY KEY (id)`; 2 `CHECK` constraint(s)

`error_events`

Technical errors grouped by fingerprint.

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: INSERT, SELECT, UPDATE

Column	Type	Not null	Default
`id`	`bigint`	yes	identity
`source`	`text`	yes	—
`level`	`text`	yes	`'error'::text`
`code`	`text`	yes	—
`message`	`text`	yes	—
`fingerprint`	`text`	yes	—
`context`	`jsonb`	yes	`'{}'::jsonb`
`establishment_id`	`uuid`	—	—
`user_id`	`uuid`	—	—
`app_version`	`text`	—	—
`platform`	`text`	—	—
`occurrences`	`integer`	yes	`1`
`first_seen`	`timestamp with time zone`	yes	`now()`
`last_seen`	`timestamp with time zone`	yes	`now()`
`resolved_at`	`timestamp with time zone`	—	—
`resolved_by`	`uuid`	—	—

Constraints: `FOREIGN KEY (establishment_id) REFERENCES nhill.establishments(id) ON DELETE SET NULL`; `FOREIGN KEY (resolved_by) REFERENCES nhill.admin_users(id)`; `PRIMARY KEY (id)`; 4 `CHECK` constraint(s)

`usage_daily`

Daily usage counters per business (counts only, never content).

- Row-level security: no (platform table, access limited by the `nhill_app` role's rights)
- `nhill_app` rights: SELECT

Column	Type	Not null	Default
`day`	`date`	yes	—
`establishment_id`	`uuid`	yes	—
`documents_issued`	`integer`	yes	`0`
`payments_recorded`	`integer`	yes	`0`

Constraints: `PRIMARY KEY (day, establishment_id)`

Functions

Function	Result	Properties	Executable by `nhill_app`
`nh_apply_stock_movement()`	`trigger`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	—
`nh_check_plan_entitlement()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_count_document_issue()`	`trigger`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	—
`nh_count_payment()`	`trigger`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	—
`nh_current_establishment()`	`uuid`	stable, `search_path=nhill, pg_catalog`	yes
`nh_erase_establishment(p_est uuid, p_early boolean)`	`jsonb`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	yes
`nh_erasing(p_est uuid)`	`boolean`	stable, `search_path=nhill, pg_catalog`	yes

Function	Result	Properties	Executable by nhill_app
`nh_establishment_erasure(p_est uuid)`	`TABLE(eligible boolean, reason text, access_ended_at timestamp with time zone, erasable_from timestamp with time zone)`	stable, `search_path=nhill, pg_catalog`	yes
`nh_establishment_usage(p_est uuid)`	`TABLE(users integer, registers integer, warehouses integer, products integer, documents_month integer, storage_bytes bigint)`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	yes
`nh_guard_pos_session()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_guard_purchase()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_guard_sales_document()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_guard_sales_line()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_iso(ts timestamp with time zone)`	`text`	immutable, `search_path=nhill, pg_catalog`	yes
`nh_like_contains(p text)`	`text`	immutable, `search_path=pg_catalog`	yes
`nh_local_date(p_ts timestamp with time zone)`	`date`	stable, `search_path=nhill, pg_catalog`	yes
`nh_local_start(p_day date)`	`timestamp with time zone`	stable, `search_path=nhill, pg_catalog`	yes
`nh_local_today()`	`date`	stable, `search_path=nhill, pg_catalog`	yes
`nh_plan_main_price()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—

Function	Result	Properties	Executable by `nhill_app`
`nh_platform_establishment_counts(p_est uuid)`	`TABLE(products bigint, customers bigint, suppliers bigint, documents bigint, drafts bigint)`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	yes
`nh_platform_establishment_monthly(p_est uuid, p_from date, p_to date)`	`TABLE(month text, currency text, invoices_issued bigint, invoiced_net_minor bigint, invoiced_total_minor bigint, credited_total_minor bigint, payments_in_minor bigint, expenses_minor bigint)`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	yes
`nh_platform_establishment_volumes(p_est uuid, p_from date, p_to date)`	`TABLE(currency text, invoices_issued bigint, invoiced_net_minor bigint, invoiced_total_minor bigint, credit_notes_issued bigint, credited_total_minor bigint, payments_in_count bigint, payments_in_minor bigint, payments_out_minor bigint, expenses_count bigint, expenses_minor bigint, purchases_minor bigint)`	volatile, `SECURITY DEFINER`, `search_path=nhill, pg_catalog`	yes
`nh_setting_int(p_key text, p_default integer)`	`integer`	stable, `search_path=nhill, pg_catalog`	yes

Function	Result	Properties	Executable by `nhill_app`
`nh_subscription_access(p_est uuid)`	`TABLE(access text, reason text, access_until timestamp with time zone, effective_plan_id uuid, is_trial boolean, status text, grace_end timestamp with time zone)`	stable, `search_path=nhill, pg_catalog`	yes
`nh_sync_plan_entitlements_from_legacy()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_sync_plan_legacy_limits()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_touch_updated_at()`	`trigger`	volatile, `search_path=nhill, pg_catalog`	—
`nh_tz(p_est uuid)`	`text`	stable, `search_path=nhill, pg_catalog`	yes
`nh_window(minutes integer)`	`timestamp with time zone`	stable, `search_path=nhill, pg_catalog`	yes

Summary

Domain	Tables
Platform and identity	18
Plans, rights and subscriptions	14
Business management (businesses' data)	21
Till (Nhill POS)	9
Console and operations	9
Total	**71**