

PYNQ Getting Start

(Based On KD240)

AMD

together we advance_

Install Ubuntu on AMD

PYNQ currently only supports ZYNQ Based and Versal series(include KRIA , Alveo).

PYNQ is a framework designed for the Ubuntu environment, so we must first install Ubuntu on the development board.

Install Ubuntu on AMD | Ubuntu



AMD
together we advance_

Setting Up the SD Card Image (Ubuntu)

Follow the instructions in the tool and select the downloaded image to flash onto your microSD card.

Setting up the SD Card Image (xilinx.com)



AMD
together we advance_

Board Setup

- Insert the SD card with the Ubuntu image, and ensure that it is connected to the external network.
- UART is optional, but it is helpful for accelerating development and debugging.





AMD
together we advance_

Board Setup

Power on and communicate with the development board through UART (choose a preferred serial port debugging app.




```
2. COM17 (USB Serial Port (COM
kria login: ubuntu
Password:
You are required to change your password immediately (administrator enforced).
Changing password for ubuntu.
Current password:
New password:
Retype new password:
Welcome to Ubuntu 22.04.3 LTS (GNU/Linux 5.15.0-9002-xilinx-zynqmp aarch64)

 * Documentation:  https://help.ubuntu.com
 * Management:     https://landscape.canonical.com
 * Support:        https://ubuntu.com/advantage

  System information as of Thu Dec 21 05:15:06 UTC 2023

  System load:  0.11962890625     Processes:             122
  Usage of /:   6.2% of 28.21GB   Users logged in:       0
  Memory usage: 10%               IPv4 address for eth0: 10.8.3.232
  Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

1 update can be applied immediately.
To see these additional updates run: apt list --upgradable

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status


The list of available updates is more than a week old.
To check for new updates run: sudo apt update


The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
```


AMD
together we advance_

Install PYNQ

The login username and password are both "ubuntu" After the first login, you will be prompted to change your password.

After logging in, be sure to execute the following command:

```
sudo apt-get update
sudo apt-get upgrade
```

Next, refer to the following URL.

GitHub - Xilinx/Kria-PYNQ: PYNQ support and examples for Kria SOMs

Execute the following command:

```
git clone https://github.com/Xilinx/Kria-PYNQ.git
cd Kria-PYNQ/
sudo bash install.sh -b KD240
```

This process will take approximately one hour.

For non-Kria series development boards, you need to download the corresponding image file or build yourself.

GitHub - Xilinx/sdbuild : PYNQ Image Building

AMD
together we advance_

Connecting to Jupyter Notebook

After a successful installation, you will see the following message.

```
Installing collected packages: tomli, pluggy, iniconfig, exceptiongroup, pytest
Successfully installed exceptiongroup-1.2.0 iniconfig-2.0.0 pluggy-1.3.0 pytest-7.4.3 tomli-2.0.1
PYNQ Installation completed.


To continue with the PYNQ experience, connect to JupyterLab via a web browser using this url: 10.8.3.232:9090/lab or k
ria:9090/lab - The password is xilinx
```

On your computer, enter the provided URL in yellow, e.g., 10.8.3.232:9090/lab, and enter the password "xilinx." You should then see:



AMD
together we advance_

Example Notebooks

PYNQ uses the Jupyter Notebook environment to provide examples and documentation.



AMD
together we advance_

Start with a simple example

Click on the field and press "Run."




```
Player what is your name?  Xilinx
Guess a number between 0 and 10:  5
Sorry Xilinx, your guess of 5 was too LOW.

Guess a number between 0 and 10:  7
Sorry Xilinx, your guess of 7 was too HIGH.

Guess a number between 0 and 10:  6
Excellent work Xilinx, you won, it was 6!

Done
```


AMD
together we advance_

Matplotlib Library

Matplotlib library is already installed by default; there is no need for additional installation.

Plotting Fibonacci numbers

Plotting is done using the matplotlib library

```
%matplotlib inline
import matplotlib.pyplot as plt
from ipywidgets import *

limit = 1000000
fib = generate_fibonacci_list(limit)
plt.plot(fib)
plt.plot(range(len(fib)), fib, 'ro')

plt.show()
```



Contents

Interactive input and output analysis

Input and output interaction can be achieved using Ipython widgets

[9]:
```
%matplotlib inline
import matplotlib.pyplot as plt
from ipywidgets import *

def update(limit, print_output):
    i = generate_fibonacci_list(limit, print_output)
    plt.plot(range(len(i)), i)
    plt.plot(range(len(i)), i, 'ro')
    plt.show()

limit=widgets.IntSlider(min=10,max=1000000,step=1,value=10)
interact(update, limit=limit, print_output=False);
```

limit 10

print_output



Contents

AMD
together we advance_

Ipython.Core.debugger

Uses set_trace to create a breakpoint in your function.

Interactive debug

Uses `set_trace` from the Ipython debugger library

Type 'h' in debug prompt for the debug commands list and 'q' to exit

```
from IPython.core.debugger import set_trace

def debug_fibonacci_list(limit):
    nums = []
    current, ne_xt = 0, 1

    while current < limit:
        if current > 1000:
            set_trace()
        current, ne_xt = ne_xt, ne_xt + current
        nums.append(current)

    print(f'The fibonacci numbers below the number {limit} are:\n{nums[:-1]}')


debug_fibonacci_list(10000)
```

```
> /tmp/ipykernel_5302/1122840259.py(10)debug_fibonacci_list()
      8         if current > 1000:
      9             set_trace()
---> 10         current, ne_xt = ne_xt, ne_xt + current
     11         nums.append(current)
     12
```

```
ipdb>  h

Documented commands (type help <topic>):
========================================
EOF     commands   enable    ll        pp       s                until
a       condition  exit      longlist  psource  skip_hidden      up
alias   cont       h         n         q        skip_predicates  w
args    context    help      next      quit     source           whatis
b       continue   ignore    p         r        step             where
break   d          interact  pdef      restart  tbreak
bt      debug      j         pdoc      return   u
c       disable    jump      pfile     retval   unalias
cl      display    l         pinfo     run      undisplay
clear   down       list      pinfo2    rv       unt

Miscellaneous help topics:
==========================
exec  pdb

ipdb>
```

Contents

AMD
together we advance_

Ipython.Core.Display

Audio Playback & Add Video

Render SVG images

`SVG` image is rendered in a code cell using Ipython display library.

```
from IPython.display import SVG
SVG(filename='images/python.svg')
```

```
<IPython.core.display.SVG object>
```

Contents

Audio Playback

`IPython.display.Audio` lets you play audio directly in the notebook

```
import numpy as np
from IPython.display import Audio
framerate = 44100
t = np.linspace(0,5,framerate*5)
data = np.sin(2*np.pi*220*t**2)
Audio(data,rate=framerate)
```

Add Video

`IPython.display.YouTubeVideo` lets you play Youtube video directly in the notebook. Library support is available to play Vimeo and local videos as well

```
from IPython.display import YouTubeVideo
YouTubeVideo('dFlDRhvM4L0')
```

Video Link with image display

AMD
together we advance_

Ipython.Core.Display

Add webpages as Interactive Frames



AMD
together we advance_

Notebooks are not just for Python

Access to linux shell commands

System Information ¶

```
!cat /proc/cpuinfo
```

```
processor       : 0
model name      : ARMv7 Processor rev 0 (v7l)
BogoMIPS        : 650.00
Features        : half thumb fastmult vfp edsp neon vfpv3 tls vfpd32
CPU implementer : 0x41
CPU architecture: 7
CPU variant     : 0x3
CPU part        : 0xc09
CPU revision    : 0

processor       : 1
model name      : ARMv7 Processor rev 0 (v7l)
BogoMIPS        : 650.00
Features        : half thumb fastmult vfp edsp neon vfpv3 tls vfpd32
CPU implementer : 0x41
CPU architecture: 7
CPU variant     : 0x3
CPU part        : 0xc09
CPU revision    : 0

Hardware        : Xilinx Zynq Platform
Revision        : 0003
Serial          : 0000000000000000
```

Verify Linux Version

```
!cat /etc/os-release | grep VERSION
```

```
VERSION="16.04 LTS (Xenial Xerus)"
VERSION_ID="16.04"
```

CPU speed calculation made by the Linux kernel

```
!head -5 /proc/cpuinfo | grep "BogoMIPS"
```

```
BogoMIPS        : 650.00
```

Available DRAM ¶

```
!cat /proc/meminfo | grep 'Mem*'
```

```
MemTotal:         507892 kB
MemFree:          101684 kB
MemAvailable:     357020 kB
```

Network connection

```
!ifconfig
```

```
eth0      Link encap:Ethernet  HWaddr 00:18:3e:02:6d:cb
          inet addr:172.19.73.161  Bcast:172.19.75.255  Mask:255.255.252.0
          inet6 addr: fe80::218:3eff:fe02:6dcb/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:22262 errors:0 dropped:0 overruns:0 frame:0
          TX packets:9274 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:3972408 (3.9 MB)  TX bytes:11258468 (11.2 MB)
          Interrupt:27 Base address:0xb000

eth0:1    Link encap:Ethernet  HWaddr 00:18:3e:02:6d:cb
          inet addr:192.168.2.99  Bcast:192.168.2.255  Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          Interrupt:27 Base address:0xb000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:4558 errors:0 dropped:0 overruns:0 frame:0
          TX packets:4558 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1
          RX bytes:3876932 (3.8 MB)  TX bytes:3876932 (3.8 MB)
```


AMD
together we advance_

Magic

IPython has a set of predefined ‘magic functions’ that you can call with a command line style syntax.

To learn more about the IPython magics, simple type %magic in a separate cell.

Below is a list of available magics.

```
%lsmagic
```





AMD
together we advance_

Magic Function Example

Coding other languages

If you want to, you can combine code from multiple kernels into one notebook.

Just use IPython Magics with the name of your kernel at the start of each cell that you want to use that Kernel for:

%%bash
%%HTML
%%python2
%%python3
%%ruby
%%perl

```
%%bash

factorial()
{
    if [ "$1" -gt "1" ]
    then
        i=`expr $1 - 1`
        j=`factorial $i`
        k=`expr $1 \* $j`
        echo $k
    else
        echo 1
    fi
}

input=5
val=$(factorial $input)
echo "Factorial of $input is : "$val
```

```
Factorial of 5 is : 120
```

Time the sorting on an unsorted list

A list of 100000 random numbers is sorted and stored in a variable 'L'

```
import random

L = [random.random() for _ in range(100000)]
%time L.sort()
```

```
CPU times: user 112 ms, sys: 0 ns, total: 112 ms
Wall time: 112 ms
```

Time the sorting of a pre-sorted list

The list 'L' which was sorted in previous cell is re-sorted to observe execution time, it is much less as expected

```
%time L.sort()
```

```
CPU times: user 50.2 ms, sys: 3.57 ms, total: 53.7 ms
Wall time: 53.9 ms
```

Contents

AMD
together we advance_

APPENDIX: Code Flow



AMD
together we advance_

Start with a simple example

10. 點開 kd240_notebooks，再點開 run_face_detection.ipynb，可以發現會去呼叫 faceDetection.py，並且在 faceDetection.py 中會再去呼叫 utils.py，可以點選圖中黃色撥放鍵逐一執行程式



AMD
together we advance_

KD240 Face Detect

11. 最後可以發現結果會顯示在畫面上，並且可以自己抓圖片來做測試

[4]:
```
# read image
image = cv2.imread("face.JPG")
faces = faceDetection.run(image)
# draw rectangle
image = cv2.cvtColor(image, cv2.COLOR_BGR2RGB)
for i, (left, top, right, bottom) in enumerate(faces):
    cv2.rectangle( image, (int(left), int(top)), (int(right), int(bottom)), (0, 255, 0), 3)
```

改這行換要測試的圖片

[5]:
```
plt.subplot(1, 1, 1)
plt.imshow(image)
```

[5]:
```
<matplotlib.image.AxesImage at 0xffff569bb730>
```



AMD
together we advance_


AMD