

AFL Premise Cable - Competitor Cross Reference

PROPERTY	AFL	PRYSMIAN	PANDUIT	COMMSCOPE	MOLEX	BELDEN
PRODUCT FAMILY	TVBQ	DESKWAVE	OPTI-CORE FL RANGE	TeraSPEED	AFOIR	GUMT
MECHANICAL CHARACTERISTICS						
Diameter (mm):						
2f	5.2	Not Stated	Not Stated	3.9	Not Stated	5.4
4f	5.4	4.8	5.3	4.65	Not Stated	5.4
6f	5.8	4.8	5.3	5.15	4.8	5.9
8f	6.3	5.4	5.8	5.5	Not Stated	5.9
12f	6.4	6.2	6.6	6.1	6.2	7.6
24f	8.1	8.8	8.8	7.9	15	9.6
Weight (kg/km):						
2f	28	NA	NA	13.2	NA	25
4f	30	20	25	21	NA	26
6f	34	22	32	25	22	30
8f	41	26	41	28.6	NA	32
12f	43	33	53	34.7	33	45
24f	63	61	60	50.4	185	65
Tensile (N):						
2f - 12f (Install)	1000	600	660	667(4f,2f)	1320	400(2-8f) / 450(12f)
24f (Install)	1300	1100	1320	1335	1320	650
Crush (N):						
2f - 12f (Short term)	1000	500	1000	1000	1000	500
24f (Short term)	1000	500	1000	1000	1000	500
Impact (J):						
2f - 12f	5	1	Not Stated	5.88	Not Stated	Not Stated
24f	5	1	Not Stated	5.88	Not Stated	Not Stated
Cable Bend:						
Cable Bend Radius (No Load)	10 x OD	10 x OD	10 x OD	10 x OD (2 - 24f) 9.3x OD (8f)	10 x OD	10 x OD
Cable Bend Radius (Under Load)	20 x OD	20 x OD	20 x OD	15 x OD (2 - 24f) 14XOD (8f)	15 x OD	20 x OD
ENVIRONMENTAL CHARACTERISTICS						
Temperature range °C:						
Operating temperature	-10 to +70	-10 to +70	-20 to +70	-20 to +70 (4f,24f) -20 to +60 (2f,6f,8f,12f)	-20 to +70	-30 to +70
OTHER CONSIDERATIONS						
Halogen Free	Yes	Yes	Not Stated	Not Stated	Yes	Yes
ACMA compliance	Yes	Yes	Not Stated	Not Stated	Yes	Not Stated
RoHS Compliant	Yes	Not Stated	Yes	Yes	Yes	Not Stated
Outer sheath colour	Any colour within Std. 13 colours (Ref. EIA/TIA 598D)	Black as Std.	Black	?	Black	?
Made in Australia	Y	?	N	N	N	N

