



AFL ADSS FIBER OPTIC CABLE ELECTRIC FIELD QUESTIONNAIRE

Please complete the form below to evaluate the electrical stress on the ADSS cable.

Requested by:

Tower Type:

Phase-to-Phase System Voltage [kV]:

The cable will be installed in the following environment (check all that apply):

High Pollution

Coastal (< 15 miles from coast)

High Humidity (> 75% annual average)

Low Rainfall (< 75 days/year rain)

"Over-insulated" Electrical Environment

None of the above

Phase Conductors:

Number of phases:

Conductor type (bird name, gauge, etc.):

Conductor diameter [unit]:

Number of conductors per phase (bundled):

Smallest distance between two adjacent conductors in the phase bundle (if bundled):

Overhead Ground Wire:

Number of ground wires:

Type of ground wires (bird name, gauge, OPGW design, etc.):

Ground wire diameter [unit]:

List the Conductor, Ground Wire, and ADSS Coordinates:

X = Horizontal distance from vertical center line of tower (+ or -)

Y = Vertical height from terrain at attachment point

Phase	X-Position		Y-Position		Units
GW #1					
GW #2					
ADSS					

Please provide tower drawing on a separate page if available. Alternatively to the chart above, the manual graph can be completed to the right.