

Terrestrial Loose Tube Cables - Part Number Overview

L	M	H	6	1	D	P	B	0	4	8	B	E
1	2	3	4	5	6	7	8	9	10	11	12	13
1. Product Family						7. Tube Size		9, 10 & 11. Fibre Count			12 & 13. Jacket Colour	
L = LOOSE TUBE N = NON-METALLIC ARMOUR R = FRP FLAT ROD ARMOUR U = MICROCORE						P = 2MM (MAX. 12F/TUBE) F = 2.3MM (MAX. 24F/TUBE) L = 2.7MM (MAX. 24F/TUBE) E = 3.2MM (MAX. 24F/TUBE) J = 3.2MM HS1 (MAX. 12F/TUBE) NOTE: ALL MULTI-MODE FIBRE TYPES HAVE A MAX. FIBRE PER TUBE OF 12F.		006 = 6F 048 = 48F 144 = 144F 288 = 288F 624 = 624F* *MAX FIBRE COUNT AT PRESENT			BE = BLUE GY = GREY WE = WHITE RD = RED BK = BLACK YW = YELLOW OTHERS ON SPECIAL REQUEST	
2. Fibres Per Tube						5 & 6. Fibre Type		8. Construction Variation				
K = 6 FIBRES PER TUBE P = 8 FIBRES PER TUBE M = 12 FIBRES PER TUBE T = 24 FIBRES PER TUBE Q = AXIAL TUBE (STD STRENGTH) L = AXIAL TUBE (LIGHT STRENGTH)						1D = SM G.652.D 1E = SM PREMIUM LOW LOSS G.652.D 1F = SM BEND INSENSITIVE G.657.A1 53 = OM3 55 = OM4 62 = OM1 D6 = SM G.652.D + OM1 D3 = SM G.652.D + OM3 D5 = SM G.652.D + OM4 OTHERS ON REQUEST		A = STANDARD A = NON-ARMoured CABLES WITH BLACK (BK) PE OUTER JACKET A = NYLON ONLY (MICROCORE) B = ALL NMA CABLES WITH OUTER PE JACKET B = ANY PE COLOURED SACRIFICIAL JACKETED CABLES (OTHER THAN BLACK) M = LSZH OUTER JACKET F = ADDITIONAL OUTER NYLON JACKET D = ADDITIONAL THIN PE OUTER JACKET (MICROCORE) L = MDPE NOTE: USE 'A' WHEN NO CONSTRUCTION VARIATION OR ADDITIONAL SHEATHS APPLY, EG. WITH B, C, D, E.				
3. Cable Construction (Use with No.8 Construction Variation)						4. Core Structure						
B = LSZH C = PE D = PE/NYLON E = NYLON F = NYLON/PE H = PE/NYLON/SACRIFICIAL JACKET J = PE/NYLON (HS1) K = PE/NYLON/PE (HS1) N = NYLON/THIN PE (MICROCORE)						1 = 1 AXIAL TUBE (NO CSM) 6 = 6 TUBES AROUND CSM 8 = 8 TUBES AROUND CSM C = 12 TUBES AROUND CSM A = 10 TUBES AROUND CSM I = 18 TUBES AROUND CSM (DUAL LAYER) O = 24 TUBES AROUND CSM (DUAL LAYER) Q = 26 TUBES AROUND CSM (DUAL LAYER) CSM = CENTRAL STRENGTH MEMBER						